



25-Ball UltraThin Fine Pitch Ball Grid Array (FE) - 3x3 mm Body [UFBGA]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



25-Ball UltraThin Fine Pitch Ball Grid Array (FE) - 3x3 mm Body [UFBGA]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>




Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Terminals	N	25		
Pitch	e	0.50 BSC		
Overall Height	A	0.51	0.61	0.71
Standoff	A1	0.18	0.23	0.28
Mold Thickness	A2	0.22	0.25	0.28
Substrate Thickness	A3	0.13 REF		
Overall Length	D	3.00 BSC		
Overall Terminal Spacing	D1	2.00 BSC		
Overall Width	E	3.00 BSC		
Overall Terminal Spacing	E1	2.00 BSC		
Terminal Diameter	b	0.25	0.30	0.35

Notes:

- Pin 1 visual index feature may vary, but must be located within the hatched area.
- Dimensioning and tolerancing per ASME Y14.5M
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
REF: Reference Dimension, usually without tolerance, for information purposes only.

25-Ball UltraThin Fine Pitch Ball Grid Array (FE) - 3x3 mm Body [UFBGA]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



RECOMMENDED LAND PATTERN

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Contact Pitch	E	0.50 BSC		
Overall Contact Pad Spacing	C1		2.00	
Overall Contact Pad Spacing	C2		2.00	
Contact Pad Width (X25)	X1			0.25
Contact Pad to Contact Pad	G	0.25		

Notes:

1. Dimensioning and tolerancing per ASME Y14.5M

BSC: Basic Dimension. Theoretically exact value shown without tolerances.