



59-Ball Thin Fine-Pitch Ball Grid Array Package (KVX) - 8x8x1.2 mm Body [TFBGA]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



59-Ball Thin Fine-Pitch Ball Grid Array Package (KVX) - 8x8x1.2 mm Body [TFBGA]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>




Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Terminals	N	59		
Pitch	e	0.65 BSC		
Overall Height	A	–	–	1.20
Ball Height	A1	0.22	–	0.32
Mold Thickness	M	0.53 REF		
Substrate Thickness	S	0.26 REF		
Overall Length	D	8.00 BSC		
Ball Array Length	D2	6.50 BSC		
Overall Width	E	8.00 BSC		
Ball Array Width	E2	6.50 BSC		
Ball Diameter	b	0.32	0.35	0.42

Notes:

1. Terminal A1 visual index feature may vary, but must be located within the hatched area.
2. Dimensioning and tolerancing per ASME Y14.5M
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
REF: Reference Dimension, usually without tolerance, for information purposes only.

59-Ball Thin Fine-Pitch Ball Grid Array Package (KVX) - 8x8x1.2 mm Body [TFBGA]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



RECOMMENDED LAND PATTERN

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Contact Pitch	E	0.65 BSC		
Contact Pad Spacing	C1	6.50 BSC		
Contact Pad Spacing	C2	6.50 BSC		
Contact Pad Width (Xnn)	X			0.35
Contact Pad to Contact Pad (Xnn)	G	0.30		

Notes:

- Dimensioning and tolerancing per ASME Y14.5M
BSC: Basic Dimension. Theoretically exact value shown without tolerances.