



16-Ball Thin Fine-Pitch Ball Grid Array Package (2PW) - 4x4x1.2 mm Body [TFBGA]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



16-Ball Thin Fine-Pitch Ball Grid Array Package (2PW) - 4x4x1.2 mm Body [TFBGA]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>




Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Terminals	N	16		
Pitch	e	1.00 BSC		
Overall Height	A	1.00	1.096	1.20
Ball Height	A1	0.27	0.32	0.37
Mold Thickness	M	0.53 REF		
Substrate Thickness	S	0.246 REF		
Overall Length	D	4.00 BSC		
Ball Array Length	D2	3.00 BSC		
Overall Width	E	4.00 BSC		
Ball Array Width	E2	3.00 BSC		
Ball Diameter	b	0.38	0.43	0.48

Notes:

- Pin 1 visual index feature may vary, but must be located within the hatched area.
- Dimensioning and tolerancing per ASME Y14.5M
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
REF: Reference Dimension, usually without tolerance, for information purposes only.

16-Ball Thin Fine-Pitch Ball Grid Array Package (2PW) - 4x4x1.2 mm Body [TFBGA]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



RECOMMENDED LAND PATTERN

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Contact Pitch	E	1.00 BSC		
Contact Pad Spacing	C1	3.00 BSC		
Contact Pad Spacing	C2	3.00 BSC		
Contact Pad Width (Xnn)	X			0.40
Contact Pad to Contact Pad (Xnn)	G	0.60		

Notes:

1. Dimensioning and tolerancing per ASME Y14.5M

BSC: Basic Dimension. Theoretically exact value shown without tolerances.