



28-Lead Very Thin Mold Interconnect Substrate Package (2SW) - 6x6x0.89 mm Body [VMIS] With 3.7 mm Exposed Pad and Stepped Wettable Flanks

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



28-Lead Very Thin Mold Interconnect Substrate Package (2SW) - 6x6x0.89 mm Body [VMIS]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>




Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Terminals	N	28		
Pitch	e	0.65 BSC		
Overall Height	A	0.79	0.84	0.89
Standoff	A1	0.00	0.02	0.05
Terminal Thickness	A3	0.20 REF		
Overall Length	D	6.00 BSC		
Exposed Pad Length	D2	3.60	3.70	3.80
Overall Width	E	6.00 BSC		
Exposed Pad Width	E2	3.60	3.70	3.80
Terminal Width	b	0.25	0.30	0.35
Terminal Length	L	0.30	0.40	0.50
Corner Anchor	L1	0.40 REF		
Package Edge to Corner Anchor	K	0.20 REF		
Wettable Flank Step Cut Length	D3	0.10 REF		
Wettable Flank Step Cut Height	A4	0.05 REF		

Notes:

1. Pin 1 visual index feature may vary, but must be located within the hatched area.
2. Package is saw singulated
3. Dimensioning and tolerancing per ASME Y14.5M
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
REF: Reference Dimension, usually without tolerance, for information purposes only.

28-Lead Very Thin Mold Interconnect Substrate Package (2SW) - 6x6x0.89 mm Body [VMIS] With 3.7 mm Exposed Pad and Stepped Wettable Flanks

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



RECOMMENDED LAND PATTERN

Dimension	Units	MILLIMETERS		
		MIN	NOM	MAX
Contact Pitch	E	0.65 BSC		
Center Pad Width	X2			3.80
Center Pad Length	Y2			3.80
Center Pad Length	CH			0.25
Contact Pad Spacing	C1		5.90	
Contact Pad Spacing	C2		5.90	
Contact Pad Width (Xnn)	X1			0.35
Contact Pad Length (Xnn)	Y1			0.85
Contact Pad to Center Pad (Xnn)	G1	0.63		
Contact Pad to Contact Pad (Xnn)	G2	0.30		
Thermal Via Diameter	V		0.30	
Thermal Via Pitch	EV		1.00	

Notes:

- Dimensioning and tolerancing per ASME Y14.5M
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
- For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process