



8-Lead Very Thin Plastic Dual Flat, No Lead Package (3PW) - 3x3x1.0 mm Body [VDFN] **With Multiple Exposed Pad and Stepped Wettable Flanks**

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



8-Lead Very Thin Plastic Dual Flat, No Lead Package (3PW) - 3x3x1.0 mm Body [VDFN] With Multiple Exposed Pad and Stepped Wettable Flanks

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>




		Units	MILLIMETERS		
Dimension Limits			MIN	NOM	MAX
Number of Terminals	N		8		
Pitch	e		0.65 BSC		
Overall Height	A		0.80	0.90	1.00
Standoff	A1		0.00	0.02	0.05
Terminal Thickness	A3		0.20 REF		
Overall Length	D		3.00 BSC		
Exposed Pad Length	D2		0.35	0.45	0.55
Overall Width	E		3.00 BSC		
Exposed Pad Width	E2		0.20	0.30	0.40
Index Corner Chamfer	CH		0.15 REF		
Terminal Width	b		0.25	0.30	0.35
Terminal Length	L		0.35	0.45	0.55
Terminal-to-Exposed-Pad	K		0.65 REF		
Wettable Flank Step Cut Length	D3		0.035	0.060	0.085
Wettable Flank Step Cut Height	A4		0.10	-	0.19

Notes:

- Pin 1 visual index feature may vary, but must be located within the hatched area.
- Package is saw singulated
- Dimensioning and tolerancing per ASME Y14.5M
 - BSC: Basic Dimension. Theoretically exact value shown without tolerances.
 - REF: Reference Dimension, usually without tolerance, for information purposes only.

8-Lead Very Thin Plastic Dual Flat, No Lead Package (3PW) - 3x3x1.0 mm Body [VDFN] With Multiple Exposed Pad and Stepped Wettable Flanks

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



RECOMMENDED LAND PATTERN

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Contact Pitch	E	0.65 BSC		
Center Pad Width (X4)	X2			0.55
Center Pad Length (X4)	Y2			0.35
Contact Pad Spacing	C		2.80	
Contact Pad Width (X8)	X1			0.35
Contact Pad Length (X8)	Y1			0.90
Contact Pad to Center Pad (X8)	G1	0.50		
Contact Pad to Contact Pad (X6)	G2	0.30		
Center Pad to Center Pad	G3	0.43		
Center Pad to Center Pad	G4	0.21		

Notes:

- Dimensioning and tolerancing per ASME Y14.5M
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
- For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process

Microchip Technology Drawing C04-2568 Rev B