



**10-Lead Super-Thin Dual Flatpack No-Lead Package (K9A) - 2x2x0.4 mm Body [X2DFN]
With Pullback Leads; Micrel Legacy Package UTMLF22D-10L**

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



10-Lead Super-Thin Dual Flatpack No-Lead Package (K9A) - 2x2x0.4 mm Body [X2DFN] With Pullback Leads; Micrel Legacy Package UTMLF22D-10L

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>




		Units	MILLIMETERS		
Dimension Limits			MIN	NOM	MAX
Number of Terminals	N		10		
Pitch	e		0.40 BSC		
Overall Height	A		–	–	0.40
Standoff	A1		0.00	–	0.01
Overall Length	D		2.00 BSC		
Exposed Pad Length	D2		1.37	1.40	1.43
Overall Width	E		2.00 BSC		
Exposed Pad Width	E2		1.07	1.10	1.13
Terminal Width	b		0.17	0.20	0.23
Terminal Length	L		0.17	0.20	0.23
Terminal Pullback	L1		0.0752 REF		
Terminal-to-Exposed-Pad	K		0.175 REF		

Notes:

- Pin 1 visual index feature may vary, but must be located within the hatched area.
- Package is saw singulated
- Dimensioning and tolerancing per ASME Y14.5M
 - BSC: Basic Dimension. Theoretically exact value shown without tolerances.
 - REF: Reference Dimension, in parentheses, usually without tolerance, for information purposes only.

10-Lead Super-Thin Dual Flatpack No-Lead Package (K9A) - 2x2x0.4 mm Body [X2DFN] With Pullback Leads; Micrel Legacy Package UTMLF22D-10L

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



RECOMMENDED LAND PATTERN

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Contact Pitch	E	0.40 BSC		
Center Pad Width	X2			1.35
Center Pad Length	Y2			1.10
Contact Pad Spacing	C		1.75	
Contact Pad Width (X10)	X1			0.20
Contact Pad Length (X10)	Y1			0.30
Contact Pad to Center Pad (X10)	G1	0.18		
Contact Pad to Contact Pad (X8)	G2	0.20		
Thermal Via Diameter	V		0.30	
Thermal Via Pitch	EV		1.00	

Notes:

- Dimensioning and tolerancing per ASME Y14.5M
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
- For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process