



**84-Lead Very Thin Plastic Quad Flat, No Lead (PYA) - 7x7x1.0 mm Body [VQFN]
With Dual Terminal Rows; Micrel Legacy Package QFN77-84LD-PL-1**

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



**84-Lead Very Thin Plastic Quad Flat, No Lead (PYA) - 7x7x1.0 mm Body [VQFN]
With Dual Terminal Rows; Micrel Legacy Package QFN77-84LD-PL-1**

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>




		Units	MILLIMETERS		
Dimension Limits			MIN	NOM	MAX
Number of Terminals	N		84		
Pitch	e		0.50 BSC		
Inner Row Terminal Spacing	e1		5.50 BSC		
Outer Row Terminal Spacing	e2		6.50 BSC		
Overall Height	A		0.80	0.90	1.00
Standoff	A1		0.00	—	0.10
Overall Length	D		7.00 BSC		
Exposed Pad Length	D2		3.40	3.50	3.60
Overall Width	E		7.00 BSC		
Exposed Pad Width	E2		3.40	3.50	3.60
Terminal Width	b		0.25	0.30	0.35
Terminal Length	L		0.25	0.30	0.35

Notes:

- Pin 1 visual index feature may vary, but must be located within the hatched area.
- Package is saw singulated
- Dimensioning and tolerancing per ASME Y14.5M
 - BSC: Basic Dimension. Theoretically exact value shown without tolerances.
 - REF: Reference Dimension, usually without tolerance, for information purposes only.

**84-Lead Very Thin Plastic Quad Flat, No Lead (PYA) - 7x7x1.0 mm Body [VQFN]
With Dual Terminal Rows; Micrel Legacy Package QFN77-84LD-PL-1**

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



RECOMMENDED LAND PATTERN

	Units	MILLIMETERS		
		MIN	NOM	MAX
Contact Pitch	E	0.50 BSC		
Center Pad Width	X2			3.50
Center Pad Length	Y2			3.50
Outer Contact Pad Spacing	C1		6.50	
Outer Contact Pad Spacing	C2		6.50	
Inner Contact Pad Spacing	C3		5.50	
Inner Contact Pad Spacing	C4		5.50	
Contact Pad Diameter	X1			0.30
Contact Pad to Center Pad	G1	0.85		
Contact Pad to Contact Pad	G2	0.20		
Thermal Via Diameter	V		0.33	
Thermal Via Pitch	EV		1.20	

Notes:

- Dimensioning and tolerancing per ASME Y14.5M
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
- For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process

Microchip Technology Drawing C04-3271 Rev A