



324-Ball Low Profile Fine Pitch Land Grid Array (AUB) - 15x15x1.4mm Body [LFBGA] Atmel Legacy Global Package Code CVM

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



324-Ball Low Profile Fine Pitch Land Grid Array (AUB) - 15x15x1.4mm Body [LFBGA] Atmel Legacy Global Package Code CVM

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>




Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Terminals	N	324		
Pitch	e	0.80 BSC		
Overall Height	A	-	-	1.40
Ball Height	A1	0.16	0.21	0.26
Molded Package Thickness	A2	1.02	1.06	1.10
Mold Cap Thickness	A3	0.70 REF		
Overall Length	D	15.00 BSC		
Overall Width	E	15.00 BSC		
Terminal Diameter	b	0.25	0.30	0.35

Notes:

- Pin 1 visual index feature may vary, but must be located within the hatched area.
- Dimensioning and tolerancing per ASME Y14.5M
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
REF: Reference Dimension, usually without tolerance, for information purposes only.

324-Ball Low Profile Fine Pitch Land Grid Array (AUB) - 15x15x1.4mm Body [LFBGA] Atmel Legacy Global Package Code CVM

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



RECOMMENDED LAND PATTERN

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Contact Pitch	E	0.80 BSC		
Contact Pad Spacing	C1		13.60	
Contact Pad Spacing	C2		13.60	
Contact Pad Width (X20)	X1			0.25


Notes:

- Dimensioning and tolerancing per ASME Y14.5M
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
- For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process

Microchip Technology Drawing C04-23130-AUB Rev A


324-Ball Low Profile Fine Pitch Land Grid Array (AVB) - 15x15x1.4mm Body [LFBGA] Atmel Legacy Global Package Code CVM

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



324-Ball Low Profile Fine Pitch Land Grid Array (AVB) - 15x15x1.4mm Body [LFBGA] Atmel Legacy Global Package Code CVM

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>




Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Terminals	N	324		
Pitch	e	0.80 BSC		
Overall Height	A	-	-	1.40
Ball Height	A1	0.16	0.21	0.26
Molded Package Thickness	A2	1.02	1.06	1.10
Mold Cap Thickness	A3	0.70 REF		
Overall Length	D	15.00 BSC		
Overall Width	E	15.00 BSC		
Terminal Diameter	b	0.25	0.30	0.35

Notes:

- Pin 1 visual index feature may vary, but must be located within the hatched area.
- Dimensioning and tolerancing per ASME Y14.5M
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
REF: Reference Dimension, usually without tolerance, for information purposes only.

324-Ball Low Profile Fine Pitch Land Grid Array (AVB) - 15x15x1.4mm Body [LFBGA] Atmel Legacy Global Package Code CVM

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



RECOMMENDED LAND PATTERN

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Contact Pitch	E	0.80 BSC		
Contact Pad Spacing	C1		13.60	
Contact Pad Spacing	C2		13.60	
Contact Pad Width (X20)	X1			0.25

Notes:

- Dimensioning and tolerancing per ASME Y14.5M
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
- For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process

Microchip Technology Drawing C04-23130-AVB Rev A