



240-Ball Thin Fine-Pitch Ball Grid Array (4PB) - 11x11x1.217 mm Body [TFBGA]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



240-Ball Thin Fine-Pitch Ball Grid Array (4PB) - 11x11x1.217 mm Body [TFBGA]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>




Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Terminals	N	240		
Pitch	e	0.65 BSC		
Overall Height	A	–	–	1.217
Ball Height	A1	0.18	0.297	–
Mold Thickness	M	0.51	0.56	0.61
Overall Length	D	11.00 BSC		
Ball Array Length	D2	9.75 BSC		
Overall Width	E	11.00 BSC		
Ball Array Width	E2	9.75 BSC		
Ball Diameter	b	0.30	0.35	0.40

Notes:

- Pin 1 visual index feature may vary, but must be located within the hatched area.
- Dimensioning and tolerancing per ASME Y14.5M
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
REF: Reference Dimension, usually without tolerance, for information purposes only.

240-Ball Thin Fine-Pitch Ball Grid Array (4PB) - 11x11x1.217 mm Body [TFBGA]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



RECOMMENDED LAND PATTERN

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Contact Pitch	E	0.65 BSC		
Contact Pad Spacing	C1	9.75 BSC		
Contact Pad Spacing	C2	9.75 BSC		
Contact Pad Diameter	X			0.35
Contact Pad to Contact Pad	G	0.30		

Notes:

1. Dimensioning and tolerancing per ASME Y14.5M

BSC: Basic Dimension. Theoretically exact value shown without tolerances.

Microchip Technology Drawing C04-23532 Rev C