


**44-Lead Very Thin Plastic Quad Flat, No Lead Package (TXB) - 7x7 mm Body [VQFN]
With 5.2 x 5.2 mm Exposed Pad and Stepped Wettable Flanks – Atmel Legacy ZCQ**


Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



Microchip Technology Drawing C04-21550 Rev A Sheet 1 of 2

**44-Lead Very Thin Plastic Quad Flat, No Lead Package (TXB) - 7x7 mm Body [VQFN]
With 5.2 x 5.2 mm Exposed Pad and Stepped Wettable Flanks – Atmel Legacy ZCQ**

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>




		Units	MILLIMETERS		
Dimension Limits			MIN	NOM	MAX
Number of Terminals	N		44		
Pitch	e		0.50 BSC		
Overall Height	A		0.80	0.85	0.90
Standoff	A1		0.00	0.035	0.05
Terminal Thickness	A3		0.203 REF		
Overall Length	D		7.00 BSC		
Exposed Pad Length	D2		5.10	5.20	5.30
Overall Width	E		7.00 BSC		
Exposed Pad Width	E2		5.10	5.20	5.30
Terminal Width	b		0.18	0.23	0.28
Terminal Length	L		0.50	0.55	0.60
Terminal-to-Exposed-Pad	K		0.20	-	-
Wettable Flank Step	A4		0.10	0.13	0.15
Wettable Flank Step	E3		-	-	0.04

Notes:

- Pin 1 visual index feature may vary, but must be located within the hatched area.
- Package is saw singulated
- Dimensioning and tolerancing per ASME Y14.5M
 - BSC: Basic Dimension. Theoretically exact value shown without tolerances.
 - REF: Reference Dimension, usually without tolerance, for information purposes only.

**44-Lead Very Thin Plastic Quad Flat, No Lead Package (TXB) - 7x7 mm Body [VQFN]
With 5.2 x 5.2 mm Exposed Pad and Stepped Wettable Flanks – Atmel Legacy ZCQ**

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



RECOMMENDED LAND PATTERN

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Contact Pitch	E	0.50 BSC		
Optional Center Pad Width	X2			5.30
Optional Center Pad Length	Y2			5.30
Corner Chamfer	CH		0.25	
Contact Pad Spacing	C1		6.70	
Contact Pad Spacing	C2		6.70	
Contact Pad Width (X44)	X1			0.25
Contact Pad Length (X44)	Y1			1.00
Contact Pad to Center Pad (X44)	G1	0.20		
Contact Pad to Contact Pad (X40)	G2	0.25		
Thermal Via Diameter	V		0.30	
Thermal Via Pitch	EV		1.00	

Notes:

- Dimensioning and tolerancing per ASME Y14.5M
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
- For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process

Microchip Technology Drawing C04-23550 Rev A