



780-Ball Plastic Ball Grid Array Package (AUC) - 29x29x2.21 mm Body [BGA]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



780-Ball Plastic Ball Grid Array Package (AUC) - 29x29x2.21 mm Body [BGA]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>




		Units	MILLIMETERS		
Dimension Limits			MIN	NOM	MAX
Number of Terminals	N		780		
Pitch	e		1.00 BSC		
Overall Height	A		1.65	1.93	2.21
Ball Height	A1		0.40	0.50	0.64
Substrate Thickness	A2		0.58 REF		
Package Thickness	A3		1.28	1.43	1.61
Overall Length	D		29.00 BSC		
Chip Length	D1		7.46 REF		
Ball Array Length	D2		27.00 BSC		
Overall Width	E		29.00 BSC		
Chip Width	E1		7.23 REF		
Ball Array Width	E2		27.00 BSC		
Ball Diameter	b		0.50	0.64	0.70

Notes:

- Pin 1 visual index feature may vary, but must be located within the hatched area.
- Package is saw singulated
- Dimensioning and tolerancing per ASME Y14.5M
 - BSC: Basic Dimension. Theoretically exact value shown without tolerances.
 - REF: Reference Dimension, usually without tolerance, for information purposes only.

780-Ball Plastic Ball Grid Array Package (AUC) - 29x29x2.21 mm Body [BGA]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



RECOMMENDED LAND PATTERN

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Contact Pitch	E	1.00 BSC		
Contact Pad Spacing	C1	27.00 BSC		
Contact Pad Spacing	C2	27.00 BSC		
Contact Pad Diameter	X1			0.55
Contact Pad to Contact Pad (Xnn)	G	0.45		

Notes:

1. Dimensioning and tolerancing per ASME Y14.5M

BSC: Basic Dimension. Theoretically exact value shown without tolerances.

Microchip Technology Drawing C04-25772 Rev A