

SynapseRAG-MCP

Install

```
pip install -r requirements.txt
```

Start the Dashboard

Local mode — full dashboard, reads `config/settings.yaml`, no masking:

```
python scripts/start_dashboard.py
```

Ingest Files

```
python scripts/ingest.py --path pdfs/  
python scripts/ingest.py --path pdfs/example.pdf  
python scripts/ingest.py --path pdfs/ --collection my_docs  
python scripts/ingest.py --path pdfs/ --force
```

Query

```
python scripts/query.py --query "your question"  
python scripts/query.py --query "your question" --top-k 5 --collection  
my_docs  
python scripts/query.py --query "your question" --verbose
```

Evaluate

```
python scripts/evaluate.py
```

Run Tests

```
pytest  
pytest -m unit
```

Deployment (Streamlit Community Cloud)

Public mode serves the same dashboard with additional Start (sign-in) and Session pages: per-browser-session workspace isolation, a one-hour data TTL, and masking of local paths and secrets for guest visitors (administrators see unmasked data).

```
streamlit run streamlit_app.py
```

1. Push this repository to GitHub and create an app on share.streamlit.io with entrypoint `streamlit_app.py`.
2. Configure the app's Settings → Secrets:

```
ADMIN_PASSWORD = "change-me-to-a-long-random-string"
OWNER_LLM_PROVIDER = "openai"
OWNER_LLM_MODEL = "example-model-name"
OWNER_LLM_BASE_URL = "https://api.example-llm.com/v1"
OWNER_LLM_API_KEY = "sk-example-fake-key-000000"

# Optional: real embedding model for admin sessions (guests always use
# free local hashing)
OWNER_EMBEDDING_PROVIDER = "openai"
OWNER_EMBEDDING_MODEL = "BAAI/bge-m3"
OWNER_EMBEDDING_BASE_URL = "https://api.siliconflow.cn/v1"
OWNER_EMBEDDING_API_KEY = "sk-example-fake-key-000000"
OWNER_EMBEDDING_DIMENSIONS = "1024"
```

3. Set a spending limit in your LLM provider's dashboard — the built-in owner quota (30 calls/hour, 200/day) resets when the process restarts.
4. Guest visitors start a session and add their own LLM key on the Settings page (held in memory only); retrieval works without one.

`.streamlit/secrets.toml` is git-ignored; never commit real credentials.