


MT Summer Term 2021 Ex8: A Bluffer's Guide to NNs

1. In your own words, please describe supervised machine learning. Think about data, descriptive features, labels to be predicted, finding a function that describes the data, models, model bias, parameters, error functions, what is adjusted by learning, how learning is driven by the error, how learning tries to minimise error, overfitting/underfitting the data, generalising to new unseen data, training test and development data etc. Use an example, if you find this useful.

2. Given the following AN:



where $x_1 = 0.9$, $x_2 = -0.3$, $x_3 = 1.2$, $x_4 = 0.1$ and $w_1 = 0.5$, $w_2 = 0.8$, $w_3 = -1.1$, $w_4 = 0.2$, please compute

$$z = \sum_{i=1}^4 x_i w_i$$

$$a = \text{sigmoid}(z)$$

3. Please write the input in (2) above as a column vector \mathbf{x} . What is the transpose \mathbf{x}^T of \mathbf{x} ? Please write the weights in (2) above as a column vector \mathbf{w} . What is the transpose \mathbf{w}^T of \mathbf{w} ?



4. Vectorise the AN in (2) above: please express the same AN as in (2) above in terms of an input column vector \mathbf{x} and a weight column vector \mathbf{w} (with the same values as in (2) above) in terms of an inner product between the vectors and an element-wise application of the sigmoid to the result of the inner product. Please do this once with \mathbf{w} followed by \mathbf{x} , and once the other way around. (Make sure you remember how to place the transpose to make this work).

5. Please complete the definition of the sigmoid below


$$\text{sigmoid}(z) = \dots$$

and draw the sigmoid function in a coordinate system where $z \in [-5, 5]$ and $\text{sigmoid}(z) \in [-0.5, 1.5]$. What are $\text{sigmoid}(0)$, $\text{sigmoid}(-4)$ and $\text{sigmoid}(4)$?

6. Please work out the inner product between the following two matrices:

$$\begin{pmatrix} 1 & 2 \\ 3 & 4 \end{pmatrix} \begin{pmatrix} 5 & 6 \\ 7 & 8 \end{pmatrix} =$$

7. Given the following simple FFNN, please compute the activations (the outputs) of the two ANs in layer 2. Please assume that layer 1 ANs are just input neurons (“sensors”) without activation functions, and that layer 2 ANs have sigmoid activation functions.




8. Please vectorise the simple FFNN in (7) above: define an input column vector \mathbf{I} and a weight matrix \mathbf{W} such that output column vector $\mathbf{O} = \text{sigmoid}(\mathbf{W} \cdot \mathbf{I})$, where “ \cdot ” is the inner product, and \mathbf{I} and \mathbf{O} are column vectors.

9. Can you do the same thing as in (8) above) but where $\mathbf{O} = \text{sigmoid}(\mathbf{I} \cdot \mathbf{W}^T)$, where “ \cdot ” is the inner product, and \mathbf{I} and \mathbf{O} are row vectors. (Please make sure you adapt \mathbf{W} from (8) above in the right way for this to work).



10. Why do we vectorise ANs and ANNs?

11. Given the following FFNN



with

$$I = \begin{pmatrix} 0.9 \\ 0.1 \\ 0.8 \end{pmatrix} \quad W_{\text{input_hidden}} = \begin{pmatrix} 0.9 & 0.3 & 0.4 \\ 0.2 & 0.8 & 0.2 \\ 0.1 & 0.5 & 0.6 \end{pmatrix} \quad W_{\text{hidden_output}} = \begin{pmatrix} 0.3 & 0.7 & 0.5 \\ 0.6 & 0.5 & 0.2 \\ 0.8 & 0.1 & 0.9 \end{pmatrix}$$

please work out :

$$X_{\text{hidden}} = W_{\text{input_hidden}} \cdot I \quad O_{\text{hidden}} = \text{sigmoid}(X_{\text{hidden}}) \quad X_{\text{output}} = W_{\text{hidden_output}} \cdot O_{\text{hidden}}$$

and:

$$O_{\text{output}} = \text{sigmoid}(X_{\text{output}})$$