







Pressure Series

1712

Certified for:

Sound insulation 44 dB



Fire resistance:
30 min. (EPDM standard gasket)
60 min. (optional silicon gasket)



Insulation from smoke 2,16 m3 / h / m - 25 Pa



Usage cycles 200.000 cycles

Protects from:


















Standard measurements (mm)	430	530	630	730	830	930	1030	1130	1230	1330	1430	1530	1630	1730	1830	Longer lengths on
Max shortening (mm)	120	100	100	100	100	100	100	100	100	100	150	150	150	150	150	request

FASTENING SYSTEMS -

أنظمة التثبيت

Remove and screw

إزالة والمسمار





MAIN APPLICATIONS -التطبيقات الرئيسية





Wood door باب خشب

PVC doors

CO1712083	عازل باب0,83م*3 سم مخفي ايطالي
CO1712093	عازل باب0.93م*3 سم مخفي ايطالي
CO1712103	عازل باب 1م*3 سم مخفي ايطالي
CO1712113	عازل باب 1.13م*3 سم مخفي ايطالي
CO1712123	عازل باب 1،23م*3 سم مخفي ايطالي
CO1712153	عازل باب 1.53م*3 سم مخفي ايطالي

Basic Series

422 mini

Certified for:



Sound insulation 42 dB



Fire resistance: 30 min. (EPDM stand



Insulation from smoke 2,03 m3 / h / m - 25 Pa



Usage cycles 200.000 cycles

Protects from:






Water





Not an obstacle for disabled persons لا يشكل عائقا للأشخاص ذوي الإعاقة







	Standard measurements (mm)							
Max shortening (mm)								

330	430	530	530	630	730	830	930	1030	1130	1230	1330
130	130	200	200	200	200	200	200	200	200	200	200

MAIN APPLICATIONS -

التطبيقات الرئيسية


FASTENING SYSTEMS

أنظمة التثبيت



OPTIONAL





CO422M103

عازل باب1م*2 سم مخفي ايطالي

