

Mybaitis 系列课程

时间: 2017/11/14

作者:袁毅雄


邮箱: 896778954@qq.com

目录

Mybaitis 系列课程.....	1
目录.....	1
定位.....	2
MyBatis 是什么.....	2
ORM 定义	3
对象关系映射.....	3
Hibernate 是全自动化的 ORM	3
Ibatis/Mybaitis 相比之下是一个半自动化的 ORM	3
MyBatis CURD	3
连接数据库.....	3
使用 MyBatis 实现添加功能.....	4
使用 MyBatis 实现删除功能.....	8
使用 MyBatis 实现修改功能.....	10
使用 MyBatis 实现查询一个.....	12
使用 MyBatis 实现查询列表.....	13
使用 MyBatis 实现条件查询.....	14
使用 MyBatis 实现动态条件查询.....	15
使用 MyBatis 实现动态条件分页查询.....	17
核心配置 mybatis.cfg.xml	19
插件使用.....	19
别名.....	20
属性文件配置.....	21
使用 generator-core 自动化 SQL	21
导入 mybatis-generator-core-1.3.2.jar	21
配置 generatorConfig.xml.....	21
加载 generatorConfig.xml 生成 mybaitis 各种配置	23
生成后的类结构.....	23
开发示例.....	24
多对一/一对一 MyBatis 解决方案	25
GradeModel.java.....	25
StudentModel.java	27
StudentModelMapper.java	36

StudentModelMapper.xml	37
TestQuery.java	39
一对多/多对多 MyBatis 解决方案	39
StudentModel.java	39
GradeModel.java	47
GradeModelMapper.java	50
GradeModelMapper.xml	51
TestQuery.java	53

定位



MyBatis 是什么

MyBatis 是一款优秀的持久层框架，它支持定制化 SQL、存储过程以及高级映射。MyBatis 避免了几乎所有的 JDBC 代码和手动设置参数以及获取结果集。MyBatis 可以使用简单的 XML 或注解来配置和映射原生信息，将接口和 Java 的 POJOs(Plain Old Java Objects,普通的 Java 对象)映射成数据库中的记录。

ORM 定义

对象关系映射

Hibernate 是全自动化的 **ORM**

lbatis/Mybaits 相比之下是一个半自动化的 **ORM**

MyBatis CURD

连接数据库

mybatis-config.xml

```
<?xml version="1.0" encoding="UTF-8" ?>
<!DOCTYPE configuration
  PUBLIC "-//mybatis.org//DTD Config 3.0//EN"
  "http://mybatis.org/dtd/mybatis-3-config.dtd">
<configuration>
  <environments default="development">
    <environment id="development">
      <transactionManager type="JDBC" />
      <dataSource type="POOLED">
        <property name="driver" value="com.mysql.jdbc.Driver" />
        <property name="url" value="jdbc:mysql://localhost:3306/school" />
        <property name="username" value="root" />
        <property name="password" value="root" />
      </dataSource>
    </environment>
  </environments>
</configuration>
```

TestConnection.java

```
String resource = "mybatis-config.xml";
InputStream inputStream = Resources.getResourceAsStream(resource);
```

```
SqlSessionFactory sqlSessionFactory = new SqlSessionFactoryBuilder().build(inputStream);

//开启数据库链接
SqlSession sqlSession=sqlSessionFactory.openSession();

System.out.println("use curd");

//关闭数据库链接
sqlSession.close();
System.out.println("over");
```

使用 MyBatis 实现添加功能

StudentModel.java

```
package online.qsx.model;

public class StudentModel {
    private int id;
    private String name;
    private int age;

    public int getId() {
        return id;
    }

    public void setId(int id) {
        this.id = id;
    }

    public String getName() {
        return name;
    }

    public void setName(String name) {
        this.name = name;
    }

    public int getAge() {
        return age;
    }
}
```

```

    public void setAge(int age) {
        this.age = age;
    }

    public StudentModel(int id, String name, int age) {
        super();
        this.id = id;
        this.name = name;
        this.age = age;
    }

    public StudentModel(String name, int age) {
        super();
        this.name = name;
        this.age = age;
    }

    public StudentModel(int id) {
        super();
        this.id = id;
    }

    public StudentModel() {
        super();
    }

    @Override
    public String toString() {
        return "StudentModel [id=" + id + ", name=" + name + ", age=" +
age + "]\n";
    }
}

```

StudentMapper.java

```

package online.qsx.mapper;

import java.util.List;
import java.util.Map;

```

```

import online.qsx.model.StudentModel;

public interface StudentMapper {
    /**
     * 添加
     * @param student
     * @return
     */
    int save(StudentModel student);
}

```

StudentMapper.xml

```

<?xml version="1.0" encoding="UTF-8" ?>
<!DOCTYPE mapper
  PUBLIC "-//mybatis.org//DTD Mapper 3.0//EN"
  "http://mybatis.org/dtd/mybatis-3-mapper.dtd">
<mapper namespace="online.qsx.mapper.StudentMapper">

    <insert id="save" parameterType="online.qsx.model.StudentModel">
        insert into tb_student(name,age)
        values(#{name},#{age})
    </insert>

</mapper>

```

mybatis-config.xml

```

<?xml version="1.0" encoding="UTF-8" ?>
<!DOCTYPE configuration
  PUBLIC "-//mybatis.org//DTD Config 3.0//EN"
  "http://mybatis.org/dtd/mybatis-3-config.dtd">
<configuration>

    <environments default="development">
        <environment id="development">
            <transactionManager type="JDBC" />
            <dataSource type="POOLED">
                <property name="driver" value="com.mysql.jdbc.Driver" />
            </dataSource>
        </environment>
    </environments>

```

```

        <property name="url"
value="jdbc:mysql://localhost:3306/school" />
        <property name="username" value="root" />
        <property name="password" value="root" />
    </dataSource>
</environment>
</environments>

<mappers>
    <mapper resource="online/qsx/mapper/StudentMapper.xml" />
</mappers>

</configuration>

```

TestCURD.java

```

package online.qsx.test;

import java.io.IOException;
import java.io.InputStream;
import java.util.HashMap;
import java.util.List;
import java.util.Map;

import org.apache.ibatis.io.Resources;
import org.apache.ibatis.session.SqlSession;
import org.apache.ibatis.session.SqlSessionFactory;
import org.apache.ibatis.session.SqlSessionFactoryBuilder;

import online.qsx.mapper.StudentMapper;
import online.qsx.model.StudentModel;

public class TestCURD {
    public static void main(String[] args) throws IOException {
        new TestCURD().save ();
        System.out.println("over");
    }

    SqlSession sqlSession = null;
    StudentMapper studentMapper = null;

```

```

    public void init() throws IOException {
        String resource = "mybatis-config.xml";
        InputStream inputStream = Resources.getResourceAsStream(resource);
        SqlSessionFactory sqlSessionFactory = new
        SqlSessionFactoryBuilder().build(inputStream);
        // 开启数据库链接
        sqlSession = sqlSessionFactory.openSession();

        // 获取 StudentMapper 接口的实现
        studentMapper = sqlSession.getMapper(StudentMapper.class);
    }

    public void destroy() {
        sqlSession.commit();// 提交事物
        // 关闭数据库链接
        sqlSession.close();
    }

    public void save() throws IOException {
        init();
        studentMapper.save(new StudentModel("jack_02", 30));
        destroy();
    }
}

```

使用 MyBatis 实现删除功能

StudentMapper.java

```

package online.qsx.mapper;

import java.util.List;
import java.util.Map;

import online.qsx.model.StudentModel;

public interface StudentMapper {
    /**

```



```
* 删除
* @param id
* @return
*/
int remove(int id);
}
```

StudentMapper.xml

```
<?xml version="1.0" encoding="UTF-8" ?>
<!DOCTYPE mapper
PUBLIC "-//mybatis.org//DTD Mapper 3.0//EN"
"http://mybatis.org/dtd/mybatis-3-mapper.dtd">
<mapper namespace="online.qsx.mapper.StudentMapper">
  <delete id="remove" parameterType="_int">
    delete from tb_student
    where
      id=#{id}
  </delete>
</mapper>
```

TestCURD.java

```
package online.qsx.test;

import java.io.IOException;
import java.io.InputStream;
import java.util.HashMap;
import java.util.List;
import java.util.Map;

import org.apache.ibatis.io.Resources;
import org.apache.ibatis.session.SqlSession;
import org.apache.ibatis.session.SqlSessionFactory;
import org.apache.ibatis.session.SqlSessionFactoryBuilder;

import online.qsx.mapper.StudentMapper;
import online.qsx.model.StudentModel;

public class TestCURD {
```

```

    public static void main(String[] args) throws IOException {
        new TestCURD().remove ();
        System.out.println("over");
    }

    SqlSession sqlSession = null;
    StudentMapper studentMapper = null;

    public void init() throws IOException {
        String resource = "mybatis-config.xml";
        InputStream inputStream = Resources.getResourceAsStream(resource);
        SqlSessionFactory sqlSessionFactory = new
        SqlSessionFactoryBuilder().build(inputStream);
        // 开启数据库链接
        sqlSession = sqlSessionFactory.openSession();

        // 获取 StudentMapper 接口的实现
        studentMapper = sqlSession.getMapper(StudentMapper.class);
    }

    public void destroy() {
        sqlSession.commit();// 提交事物
        // 关闭数据库链接
        sqlSession.close();
    }

    public void remove() throws IOException {
        init();
        studentMapper.remove(1);
        destroy();
    }
}

```

使用 MyBatis 实现修改功能

StudentMapper.java

```

package online.qsx.mapper;

import java.util.List;

```

```
import java.util.Map;

import online.qsx.model.StudentModel;

public interface StudentMapper {

    /**
     * 修改
     * @param student
     * @return
     */
    int edit(StudentModel student);
}
```

StudentMapper.xml

```
<?xml version="1.0" encoding="UTF-8" ?>
<!DOCTYPE mapper
  PUBLIC "-//mybatis.org//DTD Mapper 3.0//EN"
  "http://mybatis.org/dtd/mybatis-3-mapper.dtd">
<mapper namespace="online.qsx.mapper.StudentMapper">
  <update id="edit" parameterType="online.qsx.model.StudentModel">
    update
      tb_student
    set
      name=#{name},
      age=#{age}
    where
      id=#{id}
  </update>
</mapper>
```

TestCURD.java

```
public void edit() throws IOException {
    init();
    studentMapper.edit(new StudentModel(3, "arvin_003", 22));
    destroy();
}
```

使用 MyBatis 实现查询一个

StudentMapper.java

```
package online.qsx.mapper;

import java.util.List;
import java.util.Map;

import online.qsx.model.StudentModel;

public interface StudentMapper {
    /**
     * 查询一个
     * @param id
     * @return
     */
    StudentModel findObject(int id);
}
```

StudentMapper.xml

```
<?xml version="1.0" encoding="UTF-8" ?>
<!DOCTYPE mapper
PUBLIC "-//mybatis.org//DTD Mapper 3.0//EN"
"http://mybatis.org/dtd/mybatis-3-mapper.dtd">
<mapper namespace="online.qsx.mapper.StudentMapper">
    <select id="findObject" parameterType="int"
resultType="online.qsx.model.StudentModel">
        select
            id,name,age
        from
            tb_student
        where
            id=#{id}
    </select>
</mapper>
```

TestCURD.java

```
public void findObject() throws IOException {
    init();
    StudentModel studentModel = studentMapper.findObject(3);
    System.out.println(studentModel);
    destroy();
}
```

使用 MyBatis 实现查询列表

StudentMapper.java

```
package online.qsx.mapper;

import java.util.List;
import java.util.Map;

import online.qsx.model.StudentModel;

public interface StudentMapper {
    /**
     * 查询所有
     * @return
     */
    List<StudentModel> findList();
}
```

StudentMapper.xml

```
<?xml version="1.0" encoding="UTF-8" ?>
<!DOCTYPE mapper
PUBLIC "-//mybatis.org//DTD Mapper 3.0//EN"
"http://mybatis.org/dtd/mybatis-3-mapper.dtd">
<mapper namespace="online.qsx.mapper.StudentMapper">
    <select id="findList" resultType="online.qsx.model.StudentModel">
        select
            id,name,age
```

```
        from
            tb_student
    </select>
</mapper>
```

TestCURD.java

```
public void findList() throws IOException {
    init();
    List<StudentModel> list = studentMapper.findList();
    for (StudentModel studentModel : list) {
        System.out.println(studentModel);
    }
    destroy();
}
```

使用 MyBatis 实现条件查询

StudentMapper.java

```
package online.qsx.mapper;

import java.util.List;
import java.util.Map;

import online.qsx.model.StudentModel;

public interface StudentMapper {
    /**
     * 根据参数查询
     * @param student
     * @return
     */
    List<StudentModel> findListByParam(StudentModel student);
}
```

StudentMapper.xml

```
<?xml version="1.0" encoding="UTF-8" ?>
<!DOCTYPE mapper
  PUBLIC "-//mybatis.org//DTD Mapper 3.0//EN"
  "http://mybatis.org/dtd/mybatis-3-mapper.dtd">
<mapper namespace="online.qsx.mapper.StudentMapper">
<select id="findListByParam"
parameterType="online.qsx.model.StudentModel"
resultType="online.qsx.model.StudentModel">
  select
    id,name,age
  from
    tb_student
  where
    name like concat('%',{name},'%')
    and
    age <![CDATA[ < ]]> #{age}
</select>
</mapper>
```

TestCURD.java

```
public void findListByParam() throws IOException {
    init();
    List<StudentModel> list = studentMapper.findListByParam(new StudentModel(0, "2",
31));
    for (StudentModel studentModel : list) {
        System.out.println(studentModel);
    }
    destroy();
}
```

使用 MyBatis 实现动态条件查询

StudentMapper.java

```
package online.qsx.mapper;
```

```

import java.util.List;
import java.util.Map;

import online.qsx.model.StudentModel;

public interface StudentMapper {
    /**
     * 根据参数查询
     * @param student
     * @return
     */
    List<StudentModel> findListByParamDynamic(StudentModel student);
}

```

StudentMapper.xml

```

<?xml version="1.0" encoding="UTF-8" ?>
<!DOCTYPE mapper
PUBLIC "-//mybatis.org//DTD Mapper 3.0//EN"
"http://mybatis.org/dtd/mybatis-3-mapper.dtd">
<mapper namespace="online.qsx.mapper.StudentMapper">
<select id="findListByParamDynamic"
parameterType="online.qsx.model.StudentModel"
resultType="online.qsx.model.StudentModel">
    select
        id,name,age
    from
        tb_student
    <where>
        <if test="name != null">
            and name like concat('%',{name},'%')
        </if>
        <if test="age>0">
            and age <![CDATA[ < ]]> #{age}
        </if>
    </where>
</select>
</mapper>

```


TestCURD.java

```
public void findListByParamDynamic() throws IOException {
    init();
    List<StudentModel> list = studentMapper.findListByParamDynamic(new
StudentModel(0, "2", 30));
    for (StudentModel studentModel : list) {
        System.out.println(studentModel);
    }
    destroy();
}
```

使用 MyBatis 实现动态条件分页查询

StudentMapper.java

```
package online.qsx.mapper;

import java.util.List;
import java.util.Map;

import online.qsx.model.StudentModel;

public interface StudentMapper {
    /**
     * 查询所有
     * @return
     */
    List<StudentModel> findPageList(Map<String, Object> map);
}
```

StudentMapper.xml

```
<?xml version="1.0" encoding="UTF-8" ?>
<!DOCTYPE mapper
PUBLIC "-//mybatis.org//DTD Mapper 3.0//EN"
"http://mybatis.org/dtd/mybatis-3-mapper.dtd">
```

```

<mapper namespace="online.qsx.mapper.StudentMapper">
    <select id="findPageList" parameterType="map"
resultType="online.qsx.model.StudentModel">
        select
            id,name,age
        from
            tb_student
        <where>
            <if test="obj.name != null">
                and name like concat('%',{obj.name},'%')
            </if>
            <if test="obj.age>0">
                and age <![CDATA[ < ]]> #{obj.age}
            </if>
        </where>

        limit #{cross},#{size}
    </select>
</mapper>

```

TestCURD.java

```

public void findPageList() throws IOException {
    init();

    Map<String, Object> map=new HashMap<String, Object>();
    map.put("obj", new StudentModel(0, "2", 31));
    map.put("cross", (2-1)*2);
    map.put("size", 2);

    List<StudentModel> list = studentMapper.findPageList(map);
    for (StudentModel studentModel : list) {
        System.out.println(studentModel);
    }
    destroy();
}

```

核心配置 mybatis.cfg.xml

插件使用

使用 pagehelper 优化分页

导入 pagehelper 的 jar

pagehelper-5.0.0.jar

jsqlparser-0.9.5.jar

配置 mybaits.cfg.xml

```
<plugins>
    <plugin interceptor="com.github.pagehelper.PageInterceptor">
        <!-- 设置数据库类型 Oracle,MySQL,MariaDB,SQLite,Hsqldb,PostgreSQL 六种数据
库 -->
        <property name="helperDialect" value="mysql" />
    </plugin>
</plugins>
```

分页使用示例

```
SqlSession sqlSession = null;
StudentMapper studentMapper = null;

public void init() throws IOException {
    String resource = "mybatis-config.xml";
    InputStream inputStream = Resources.getResourceAsStream(resource);
    SqlSessionFactory sqlSessionFactory = new SqlSessionFactoryBuilder().build(inputStream);
    // 开启数据库链接
    sqlSession = sqlSessionFactory.openSession();

    // 获取StudentMapper接口的实现
    studentMapper = sqlSession.getMapper(StudentMapper.class);
}

public void destroy() {
```

```

        sqlSession.commit();// 提交事物

        // 关闭数据库链接
        sqlSession.close();
    }

    public void testFindAll() throws IOException {
        init();
        PageHelper.startPage(3, 3);//使用分页
        List<StudentModel> list = studentMapper.findAll();
        PageInfo<StudentModel> pageInfo=new PageInfo<>(list);//获取分页信息
        System.out.println(pageInfo.toString());
        for (StudentModel studentModel : list) {
            System.out.println(studentModel);
        }
        destroy();
    }

    public static void main(String[] args) throws IOException {
        new TestQuery().testFindAll();
        System.out.println("over");
    }
}

```

别名

指定加载类为某个名称

```

<!-- 别名 -->
<typeAliases>
    <typeAlias alias="StudentModel" type="online.qsx.model.StudentModel" />
</typeAliases>

```

扫描包

```

<!-- 别名 -->
<typeAliases>
    <package name="online.qsx.model"/>
</typeAliases>

```

属性文件配置

定义 jdbc.properties

```
jdbc.driver=com.mysql.jdbc.Driver
jdbc.url=jdbc:mysql://localhost:3306/school
jdbc.username=root
jdbc.password=root
```

优化数据库连接

```
<!-- 数据库环境 -->
<environments default="development">
  <environment id="development">
    <transactionManager type="JDBC" />
    <dataSource type="POOLED">
      <property name="driver" value="${jdbc.driver}" />
      <property name="url" value="${jdbc.url}" />
      <property name="username" value="${jdbc.username}" />
      <property name="password" value="${jdbc.password}" />
    </dataSource>
  </environment>
</environments>
```

使用 generator-core 自动化 SQL

导入 mybatis-generator-core-1.3.2.jar

配置 generatorConfig.xml

```
<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE generatorConfiguration
  PUBLIC "-//mybatis.org//DTD MyBatis Generator Configuration 1.0//EN"
  "http://mybatis.org/dtd/mybatis-generator-config_1_0.dtd">

<generatorConfiguration>
  <context id="testTables" targetRuntime="MyBatis3">
```

```

<plugin type="org.mybatis.generator.plugins.SerializablePlugin"></plugin>
<plugin type="org.mybatis.generator.plugins.ToStringPlugin" />

<!-- 开启支持内存分页 可生成 支持内存分布的方法及参数 <plugin
type="org.mybatis.generator.plugins.RowBoundsPlugin" /> -->
<!-- generate entity时, 生成hashCode和equals方法 <plugin
type="org.mybatis.generator.plugins.EqualsHashCodePlugin" /> -->
<!-- 此处是将Example改名为Criteria 当然 想改成什么都行~ -->
<plugin type="org.mybatis.generator.plugins.RenameExampleClassPlugin">
    <property name="searchString" value="Example$" />
    <!-- 替换后 <property name="replaceString" value="Criteria" /> -->
    <property name="replaceString" value="Criteria" />
</plugin>

<!-- 数据库连接的信息: 驱动类、连接地址、用户名、密码 -->
<jdbcConnection driverClass="com.mysql.jdbc.Driver"
connectionURL="jdbc:mysql://localhost:3306/school" userId="root" password="root">
</jdbcConnection>
<!-- <jdbcConnection driverClass="oracle.jdbc.OracleDriver"
connectionURL="jdbc:oracle:thin:@127.0.0.1:1521:aaaa"
userId="aaaa" password="aaaa"> </jdbcConnection> -->

<!-- 默认false, 把JDBC DECIMAL 和 NUMERIC 类型解析为 Integer, 为 true时把JDBC DECIMAL
和 NUMERIC 类型解析为java.math.BigDecimal -->
<javaTypeResolver>
    <property name="forceBigDecimals" value="false" />
</javaTypeResolver>

<!-- targetProject:生成PO类的位置 -->
<javaModelGenerator targetPackage="online.qsx.model" targetProject=".\\src">
    <!-- enableSubPackages: 是否让schema作为包的后缀 -->
    <property name="enableSubPackages" value="false" />
    <!-- 从数据库返回的值被清理前后的空格 -->
    <property name="trimStrings" value="true" />
</javaModelGenerator>

<!-- targetProject:mapper映射文件生成的位置 -->
<sqlMapGenerator targetPackage="online.qsx.mapper" targetProject=".\\src">
    <!-- enableSubPackages: 是否让schema作为包的后缀 -->
    <property name="enableSubPackages" value="false" />
</sqlMapGenerator>
<!-- targetPackage: mapper接口生成的位置 -->

```

```

<javaClientGenerator type="XMLMAPPER" targetPackage="online.qsx.mapper"
targetProject=".\\src">
    <!-- enableSubPackages:是否让schema作为包的后缀 -->
    <property name="enableSubPackages" value="true" />
</javaClientGenerator>

<table schema="" tableName="grade" domainObjectName="GradeModel" />

<!--
<table schema="" tableName="student" domainObjectName="StudentModel" />
<table schema="" tableName="subject" domainObjectName="SubjectModel" />
<table schema="" tableName="result" domainObjectName="resultModel" />
-->

</context>
</generatorConfiguration>

```

加载 generatorConfig.xml 生成 mybaits 各种配置

```

List<String> warnings = new ArrayList<String>();
boolean overwrite = true;
File configFile = new File("G:/Java4/MyBatisQuery/src/online/qsx/test/generatorConfig.xml");
ConfigurationParser cp = new ConfigurationParser(warnings);
Configuration config = cp.parseConfiguration(configFile);
DefaultShellCallback callback = new DefaultShellCallback(overwrite);
MyBatisGenerator myBatisGenerator = new MyBatisGenerator(config, callback, warnings);
myBatisGenerator.generate(null);

System.out.println("生成 ok");

```

生成后的类结构

```

v online.qsx.mapper
  > GradeModelMapper.java mapper的接口
  > GradeModelMapper.xml mapper接口对应的映射sql文件
v online.qsx.model
  > GradeModel.java 数据库实体
  > GradeModelCriteria.java 动态Sql所需的条件对象

```

开发示例

```
package online.qsx.test;

import java.io.IOException;
import java.io.InputStream;
import java.util.List;

import org.apache.ibatis.io.Resources;
import org.apache.ibatis.session.SqlSession;
import org.apache.ibatis.session.SqlSessionFactory;
import org.apache.ibatis.session.SqlSessionFactoryBuilder;

import online.qsx.mapper.GradeModelMapper;
import online.qsx.model.GradeModel;
import online.qsx.model.GradeModelCriteria;
import online.qsx.model.GradeModelCriteria.Criteria;

public class TestQuery {
    SqlSession sqlSession = null;
    GradeModelMapper gradeModelMapper;
    public void init() throws IOException {
        String resource = "mybatis-config.xml";
        InputStream inputStream = Resources.getResourceAsStream(resource);
        SqlSessionFactory sqlSessionFactory = new SqlSessionFactoryBuilder().build(inputStream);
        // 开启数据库链接
        sqlSession = sqlSessionFactory.openSession();

        gradeModelMapper=sqlSession.getMapper(GradeModelMapper.class);
    }

    public void destroy() {
        sqlSession.commit();// 提交事物
        // 关闭数据库链接
        sqlSession.close();
    }

    public void test() throws IOException{
        init();

        GradeModelCriteria gradeModelCriteria=new GradeModelCriteria();//条件工具
```



```

Criteria criteria=gradeModelCriteria.createCriteria();//条件对象

criteria.andGradenameLike("%大%");//添加年级条件

criteria.andGradeidGreaterThan(2);//添加年级编号条件

List<GradeModel> list= gradeModelMapper.selectByExample(gradeModelCriteria);//执行查询

for (GradeModel gradeModel : list) {
    System.out.println(gradeModel);
}
destroy();
}

public static void main(String[] args) throws IOException {
    new TestQuery().test();
}
}

```

多对一/一对一 MyBatis 解决方案

GradeModel.java

```

package online.qsx.model;

import java.io.Serializable;
import java.util.List;

public class GradeModel implements Serializable {
    /**
     * This field was generated by MyBatis Generator.
     * This field corresponds to the database column grade.GradeID
     *
     * @mbggenerated Mon Nov 20 15:52:42 CST 2017
     */
    private Integer gradeid;

    /**
     * This field was generated by MyBatis Generator.
     * This field corresponds to the database column grade.GradeName
     *

```

```

    * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
    */
    private String gradename;

    /**
     * This field was generated by MyBatis Generator.
     * This field corresponds to the database table grade
     *
     * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
     */
    private static final long serialVersionUID = 1L;

    /**
     * This method was generated by MyBatis Generator.
     * This method returns the value of the database column grade.GradeID
     *
     * @return the value of grade.GradeID
     *
     * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
     */
    public Integer getGradeid() {
        return gradeid;
    }

    /**
     * This method was generated by MyBatis Generator.
     * This method sets the value of the database column grade.GradeID
     *
     * @param gradeid the value for grade.GradeID
     *
     * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
     */
    public void setGradeid(Integer gradeid) {
        this.gradeid = gradeid;
    }

    /**
     * This method was generated by MyBatis Generator.
     * This method returns the value of the database column grade.GradeName
     *
     * @return the value of grade.GradeName
     *
     * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
     */

```

```

public String getGradename() {
    return gradename;
}

/**
 * This method was generated by MyBatis Generator.
 * This method sets the value of the database column grade.GradeName
 *
 * @param gradename the value for grade.GradeName
 *
 * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
 */
public void setGradename(String gradename) {
    this.gradename = gradename == null ? null : gradename.trim();
}

/**
 * This method was generated by MyBatis Generator.
 * This method corresponds to the database table grade
 *
 * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
 */
@Override
public String toString() {
    StringBuilder sb = new StringBuilder();
    sb.append(getClass().getSimpleName());
    sb.append(" [");
    sb.append("Hash = ").append(hashCode());
    sb.append(", gradeid=").append(gradeid);
    sb.append(", gradename=").append(gradename);
    sb.append(", serialVersionUID=").append(serialVersionUID);
    sb.append("]");
    return sb.toString();
}
}

```

StudentModel.java

```

package online.qsx.model;

import java.io.Serializable;
import java.util.Date;

```

```

public class StudentModel implements Serializable {
    /**
     * This field was generated by MyBatis Generator. This field corresponds to
     * the database column student.StudentNo
     *
     * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
     */
    private Integer studentno;

    /**
     * This field was generated by MyBatis Generator. This field corresponds to
     * the database column student.LoginPwd
     *
     * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
     */
    private String loginpwd;

    /**
     * This field was generated by MyBatis Generator. This field corresponds to
     * the database column student.StudentName
     *
     * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
     */
    private String studentname;

    /**
     * This field was generated by MyBatis Generator. This field corresponds to
     * the database column student.Sex
     *
     * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
     */
    private Boolean sex;

    /**
     * This field was generated by MyBatis Generator. This field corresponds to
     * the database column student.GradeId
     *
     * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
     */
    private Integer gradeid;

    // 特殊属性
    // 多对一/一对一

```

```
private GradeModel gradeModel;

public GradeModel getGradeModel() {
    return gradeModel;
}

public void setGradeModel(GradeModel gradeModel) {
    this.gradeModel = gradeModel;
}

/**
 * This field was generated by MyBatis Generator. This field corresponds to
 * the database column student.Phone
 *
 * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
 */
private String phone;

/**
 * This field was generated by MyBatis Generator. This field corresponds to
 * the database column student.Address
 *
 * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
 */
private String address;

/**
 * This field was generated by MyBatis Generator. This field corresponds to
 * the database column student.BornDate
 *
 * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
 */
private Date borndate;

/**
 * This field was generated by MyBatis Generator. This field corresponds to
 * the database column student.Email
 *
 * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
 */
private String email;

/**
 * This field was generated by MyBatis Generator. This field corresponds to
```

```

    * the database column student.IdentityCard
    *
    * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
    */
    private String identitycard;

    /**
     * This field was generated by MyBatis Generator. This field corresponds to
     * the database table student
     *
     * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
     */
    private static final long serialVersionUID = 1L;

    /**
     * This method was generated by MyBatis Generator. This method returns the
     * value of the database column student.StudentNo
     *
     * @return the value of student.StudentNo
     *
     * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
     */
    public Integer getStudentno() {
        return studentno;
    }

    /**
     * This method was generated by MyBatis Generator. This method sets the
     * value of the database column student.StudentNo
     *
     * @param studentno
     *            the value for student.StudentNo
     *
     * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
     */
    public void setStudentno(Integer studentno) {
        this.studentno = studentno;
    }

    /**
     * This method was generated by MyBatis Generator. This method returns the
     * value of the database column student.LoginPwd
     *
     * @return the value of student.LoginPwd

```

```

*
* @mbgggenerated Mon Nov 20 15:52:42 CST 2017
*/
public String getLoginpwd() {
    return loginpwd;
}

/**
 * This method was generated by MyBatis Generator. This method sets the
 * value of the database column student.LoginPwd
 *
 * @param loginpwd
 *         the value for student.LoginPwd
 *
 * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
 */
public void setLoginpwd(String loginpwd) {
    this.loginpwd = loginpwd == null ? null : loginpwd.trim();
}

/**
 * This method was generated by MyBatis Generator. This method returns the
 * value of the database column student.StudentName
 *
 * @return the value of student.StudentName
 *
 * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
 */
public String getStudentname() {
    return studentname;
}

/**
 * This method was generated by MyBatis Generator. This method sets the
 * value of the database column student.StudentName
 *
 * @param studentname
 *         the value for student.StudentName
 *
 * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
 */
public void setStudentname(String studentname) {
    this.studentname = studentname == null ? null : studentname.trim();
}

```

```
/**
 * This method was generated by MyBatis Generator. This method returns the
 * value of the database column student.Sex
 *
 * @return the value of student.Sex
 *
 * @mbggenerated Mon Nov 20 15:52:42 CST 2017
 */
public Boolean getSex() {
    return sex;
}
```

```
/**
 * This method was generated by MyBatis Generator. This method sets the
 * value of the database column student.Sex
 *
 * @param sex
 *         the value for student.Sex
 *
 * @mbggenerated Mon Nov 20 15:52:42 CST 2017
 */
public void setSex(Boolean sex) {
    this.sex = sex;
}
```

```
/**
 * This method was generated by MyBatis Generator. This method returns the
 * value of the database column student.GradeId
 *
 * @return the value of student.GradeId
 *
 * @mbggenerated Mon Nov 20 15:52:42 CST 2017
 */
public Integer getGradeid() {
    return gradeid;
}
```

```
/**
 * This method was generated by MyBatis Generator. This method sets the
 * value of the database column student.GradeId
 *
 * @param gradeid
 *         the value for student.GradeId

```



```

*
* @mbgggenerated Mon Nov 20 15:52:42 CST 2017
*/
public void setGradeid(Integer gradeid) {
    this.gradeid = gradeid;
}

/**
* This method was generated by MyBatis Generator. This method returns the
* value of the database column student.Phone
*
* @return the value of student.Phone
*
* @mbgggenerated Mon Nov 20 15:52:42 CST 2017
*/
public String getPhone() {
    return phone;
}

/**
* This method was generated by MyBatis Generator. This method sets the
* value of the database column student.Phone
*
* @param phone
*         the value for student.Phone
*
* @mbgggenerated Mon Nov 20 15:52:42 CST 2017
*/
public void setPhone(String phone) {
    this.phone = phone == null ? null : phone.trim();
}

/**
* This method was generated by MyBatis Generator. This method returns the
* value of the database column student.Address
*
* @return the value of student.Address
*
* @mbgggenerated Mon Nov 20 15:52:42 CST 2017
*/
public String getAddress() {
    return address;
}

```

```

/**
 * This method was generated by MyBatis Generator. This method sets the
 * value of the database column student.Address
 *
 * @param address
 *         the value for student.Address
 *
 * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
 */
public void setAddress(String address) {
    this.address = address == null ? null : address.trim();
}

/**
 * This method was generated by MyBatis Generator. This method returns the
 * value of the database column student.BornDate
 *
 * @return the value of student.BornDate
 *
 * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
 */
public Date getBorndate() {
    return borndate;
}

/**
 * This method was generated by MyBatis Generator. This method sets the
 * value of the database column student.BornDate
 *
 * @param borndate
 *         the value for student.BornDate
 *
 * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
 */
public void setBorndate(Date borndate) {
    this.borndate = borndate;
}

/**
 * This method was generated by MyBatis Generator. This method returns the
 * value of the database column student.Email
 *
 * @return the value of student.Email
 *

```

```

* @mbgggenerated Mon Nov 20 15:52:42 CST 2017
*/
public String getEmail() {
    return email;
}

/**
 * This method was generated by MyBatis Generator. This method sets the
 * value of the database column student.Email
 *
 * @param email
 *         the value for student.Email
 *
 * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
 */
public void setEmail(String email) {
    this.email = email == null ? null : email.trim();
}

/**
 * This method was generated by MyBatis Generator. This method returns the
 * value of the database column student.IdentityCard
 *
 * @return the value of student.IdentityCard
 *
 * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
 */
public String getIdentitycard() {
    return identitycard;
}

/**
 * This method was generated by MyBatis Generator. This method sets the
 * value of the database column student.IdentityCard
 *
 * @param identitycard
 *         the value for student.IdentityCard
 *
 * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
 */
public void setIdentitycard(String identitycard) {
    this.identitycard = identitycard == null ? null : identitycard.trim();
}

```

```

/**
 * This method was generated by MyBatis Generator. This method corresponds
 * to the database table student
 *
 * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
 */
@Override
public String toString() {
    StringBuilder sb = new StringBuilder();
    sb.append(getClass().getSimpleName());
    sb.append(" [");
    sb.append("Hash = ").append(hashCode());
    sb.append(", studentno=").append(studentno);
    sb.append(", loginpwd=").append(loginpwd);
    sb.append(", studentname=").append(studentname);
    sb.append(", sex=").append(sex);
    sb.append(", gradeid=").append(gradeid);
    sb.append(", phone=").append(phone);
    sb.append(", address=").append(address);
    sb.append(", borndate=").append(borndate);
    sb.append(", email=").append(email);
    sb.append(", identitycard=").append(identitycard);
    sb.append(", GradeModel=").append(this.getGradeModel().toString());
    sb.append(", serialVersionUID=").append(serialVersionUID);
    sb.append("]");
    return sb.toString();
}
}

```

StudentModelMapper.java

```

package online.qsx.mapper;

import java.util.List;
import online.qsx.model.StudentModel;

public interface StudentModelMapper {
    List<StudentModel> findStudentAndGrade();
}

```

StudentModelMapper.xml

嵌套

```
<?xml version="1.0" encoding="UTF-8" ?>
<!DOCTYPE mapper PUBLIC "-//mybatis.org//DTD Mapper 3.0//EN"
"http://mybatis.org/dtd/mybatis-3-mapper.dtd" >
<mapper namespace="online.qsx.mapper.StudentModelMapper" >
  <resultMap id="StudentModel01" type="online.qsx.model.StudentModel">
    <id property="studentno" column="studentno" />
    <result property="loginpwd" column="loginpwd"/>
    <result property="studentname" column="studentname"/>
    <result property="sex" column="sex"/>
    <result property="phone" column="phone"/>
    <result property="address" column="address"/>
    <result property="email" column="email"/>
    <result property="identitycard" column="identitycard"/>

    <!-- 多对一/一对一 -->
    <association property="gradeModel" javaType="online.qsx.model.GradeModel"
column="s_gid" >
      <id property="gradeid" column="g_id" />
      <result property="gradename" column="gradename"/>
    </association>
  </resultMap>

  <select id="findStudentAndGrade" resultMap="StudentModel01" >
    select
      stu.studentno,
      stu.loginpwd,
      stu.studentname,
      stu.sex,
      stu.gradeid as s_gid,
      stu.phone,
      stu.address,
      stu.borndate,
      stu.email,
      stu.identitycard,

      gra.gradeid as g_id,
      gra.gradename
```

```

        from
            student stu
        inner join grade gra on gra.gradeid=stu.gradeid
    </select>
</mapper>

```

分离 resultMap 相互引用

```

<?xml version="1.0" encoding="UTF-8" ?>
<!DOCTYPE mapper PUBLIC "-//mybatis.org//DTD Mapper 3.0//EN"
"http://mybatis.org/dtd/mybatis-3-mapper.dtd" >
<mapper namespace="online.qsx.mapper.StudentModelMapper" >
    <resultMap id="StudentModel01" type="online.qsx.model.StudentModel">
        <id property="studentno" column="studentno" />
        <result property="loginpwd" column="loginpwd"/>
        <result property="studentname" column="studentname"/>
        <result property="sex" column="sex"/>
        <result property="phone" column="phone"/>
        <result property="address" column="address"/>
        <result property="email" column="email"/>
        <result property="identitycard" column="identitycard"/>

        <!-- 多对一/一对一 -->
        <association property="gradeModel" resultMap="GradeModel01" column="s_gid" />
    </resultMap>

    <resultMap type="online.qsx.model.GradeModel" id="GradeModel01">
        <id property="gradeid" column="g_id" />
        <result property="gradename" column="gradename"/>
    </resultMap>

    <select id="findStudentAndGrade" resultMap="StudentModel01" >
        select
            stu.studentno,
            stu.loginpwd,
            stu.studentname,
            stu.sex,
            stu.gradeid as s_gid,
            stu.phone,
            stu.address,
            stu.borndate,
            stu.email,

```

```

        stu.identitycard,

        gra.gradeid as g_id,
        gra.gradename
    from
        student stu
        inner join grade gra on gra.gradeid=stu.gradeid
</select>
</mapper >

```

TestQuery.java

```

public void find() throws IOException{
    init();
    List<StudentModel> list= studentModelMapper.findStudentAndGrade();
    for (StudentModel studentModel : list) {
        System.out.println(studentModel);
    }
    destroy();
}

```

一对多/多对多 MyBatis 解决方案

StudentModel.java

```

package online.qsx.model;

import java.io.Serializable;
import java.util.Date;

public class StudentModel implements Serializable {
    /**
     * This field was generated by MyBatis Generator.
     * This field corresponds to the database column student.StudentNo
     *
     * @mbggenerated Mon Nov 20 15:52:42 CST 2017
     */
    private Integer studentno;

    /**

```

```
* This field was generated by MyBatis Generator.
* This field corresponds to the database column student.LoginPwd
*
* @mbgggenerated Mon Nov 20 15:52:42 CST 2017
*/
private String loginpwd;

/**
* This field was generated by MyBatis Generator.
* This field corresponds to the database column student.StudentName
*
* @mbgggenerated Mon Nov 20 15:52:42 CST 2017
*/
private String studentname;

/**
* This field was generated by MyBatis Generator.
* This field corresponds to the database column student.Sex
*
* @mbgggenerated Mon Nov 20 15:52:42 CST 2017
*/
private Boolean sex;

/**
* This field was generated by MyBatis Generator.
* This field corresponds to the database column student.GradeId
*
* @mbgggenerated Mon Nov 20 15:52:42 CST 2017
*/
private Integer gradeid;

/**
* This field was generated by MyBatis Generator.
* This field corresponds to the database column student.Phone
*
* @mbgggenerated Mon Nov 20 15:52:42 CST 2017
*/
private String phone;

/**
* This field was generated by MyBatis Generator.
* This field corresponds to the database column student.Address
*
* @mbgggenerated Mon Nov 20 15:52:42 CST 2017
```



```

*/
private String address;

/**
 * This field was generated by MyBatis Generator.
 * This field corresponds to the database column student.BornDate
 *
 * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
 */
private Date borndate;

/**
 * This field was generated by MyBatis Generator.
 * This field corresponds to the database column student.Email
 *
 * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
 */
private String email;

/**
 * This field was generated by MyBatis Generator.
 * This field corresponds to the database column student.IdentityCard
 *
 * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
 */
private String identitycard;

/**
 * This field was generated by MyBatis Generator.
 * This field corresponds to the database table student
 *
 * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
 */
private static final long serialVersionUID = 1L;

/**
 * This method was generated by MyBatis Generator.
 * This method returns the value of the database column student.StudentNo
 *
 * @return the value of student.StudentNo
 *
 * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
 */
public Integer getStudentno() {

```

```

        return studentno;
    }

    /**
     * This method was generated by MyBatis Generator.
     * This method sets the value of the database column student.StudentNo
     *
     * @param studentno the value for student.StudentNo
     *
     * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
     */
    public void setStudentno(Integer studentno) {
        this.studentno = studentno;
    }

    /**
     * This method was generated by MyBatis Generator.
     * This method returns the value of the database column student.LoginPwd
     *
     * @return the value of student.LoginPwd
     *
     * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
     */
    public String getLoginpwd() {
        return loginpwd;
    }

    /**
     * This method was generated by MyBatis Generator.
     * This method sets the value of the database column student.LoginPwd
     *
     * @param loginpwd the value for student.LoginPwd
     *
     * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
     */
    public void setLoginpwd(String loginpwd) {
        this.loginpwd = loginpwd == null ? null : loginpwd.trim();
    }

    /**
     * This method was generated by MyBatis Generator.
     * This method returns the value of the database column student.StudentName
     *
     * @return the value of student.StudentName

```

```

*
* @mbgggenerated Mon Nov 20 15:52:42 CST 2017
*/
public String getStudentname() {
    return studentname;
}

/**
* This method was generated by MyBatis Generator.
* This method sets the value of the database column student.StudentName
*
* @param studentname the value for student.StudentName
*
* @mbgggenerated Mon Nov 20 15:52:42 CST 2017
*/
public void setStudentname(String studentname) {
    this.studentname = studentname == null ? null : studentname.trim();
}

/**
* This method was generated by MyBatis Generator.
* This method returns the value of the database column student.Sex
*
* @return the value of student.Sex
*
* @mbgggenerated Mon Nov 20 15:52:42 CST 2017
*/
public Boolean getSex() {
    return sex;
}

/**
* This method was generated by MyBatis Generator.
* This method sets the value of the database column student.Sex
*
* @param sex the value for student.Sex
*
* @mbgggenerated Mon Nov 20 15:52:42 CST 2017
*/
public void setSex(Boolean sex) {
    this.sex = sex;
}

/**

```

```
* This method was generated by MyBatis Generator.  
* This method returns the value of the database column student.GradeId  
*  
* @return the value of student.GradeId  
*  
* @mbggenerated Mon Nov 20 15:52:42 CST 2017  
*/  
public Integer getGradeid() {  
    return gradeid;  
}
```

```
/**  
* This method was generated by MyBatis Generator.  
* This method sets the value of the database column student.GradeId  
*  
* @param gradeid the value for student.GradeId  
*  
* @mbggenerated Mon Nov 20 15:52:42 CST 2017  
*/  
public void setGradeid(Integer gradeid) {  
    this.gradeid = gradeid;  
}
```

```
/**  
* This method was generated by MyBatis Generator.  
* This method returns the value of the database column student.Phone  
*  
* @return the value of student.Phone  
*  
* @mbggenerated Mon Nov 20 15:52:42 CST 2017  
*/  
public String getPhone() {  
    return phone;  
}
```

```
/**  
* This method was generated by MyBatis Generator.  
* This method sets the value of the database column student.Phone  
*  
* @param phone the value for student.Phone  
*  
* @mbggenerated Mon Nov 20 15:52:42 CST 2017  
*/  
public void setPhone(String phone) {
```

```

        this.phone = phone == null ? null : phone.trim();
    }

    /**
     * This method was generated by MyBatis Generator.
     * This method returns the value of the database column student.Address
     *
     * @return the value of student.Address
     *
     * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
     */
    public String getAddress() {
        return address;
    }

    /**
     * This method was generated by MyBatis Generator.
     * This method sets the value of the database column student.Address
     *
     * @param address the value for student.Address
     *
     * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
     */
    public void setAddress(String address) {
        this.address = address == null ? null : address.trim();
    }

    /**
     * This method was generated by MyBatis Generator.
     * This method returns the value of the database column student.BornDate
     *
     * @return the value of student.BornDate
     *
     * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
     */
    public Date getBorndate() {
        return borndate;
    }

    /**
     * This method was generated by MyBatis Generator.
     * This method sets the value of the database column student.BornDate
     *
     * @param borndate the value for student.BornDate

```

```

*
* @mbgggenerated Mon Nov 20 15:52:42 CST 2017
*/
public void setBorndate(Date borndate) {
    this.borndate = borndate;
}

/**
 * This method was generated by MyBatis Generator.
 * This method returns the value of the database column student.Email
 *
 * @return the value of student.Email
 *
 * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
 */
public String getEmail() {
    return email;
}

/**
 * This method was generated by MyBatis Generator.
 * This method sets the value of the database column student.Email
 *
 * @param email the value for student.Email
 *
 * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
 */
public void setEmail(String email) {
    this.email = email == null ? null : email.trim();
}

/**
 * This method was generated by MyBatis Generator.
 * This method returns the value of the database column student.IdentityCard
 *
 * @return the value of student.IdentityCard
 *
 * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
 */
public String getIdentitycard() {
    return identitycard;
}

/**

```

```

    * This method was generated by MyBatis Generator.
    * This method sets the value of the database column student.IdentityCard
    *
    * @param identitycard the value for student.IdentityCard
    *
    * @mbggenerated Mon Nov 20 15:52:42 CST 2017
    */
    public void setIdentitycard(String identitycard) {
        this.identitycard = identitycard == null ? null : identitycard.trim();
    }

    /**
    * This method was generated by MyBatis Generator.
    * This method corresponds to the database table student
    *
    * @mbggenerated Mon Nov 20 15:52:42 CST 2017
    */
    @Override
    public String toString() {
        StringBuilder sb = new StringBuilder();
        sb.append(getClass().getSimpleName());
        sb.append(" [");
        sb.append("Hash = ").append(hashCode());
        sb.append(", studentno=").append(studentno);
        sb.append(", loginpwd=").append(loginpwd);
        sb.append(", studentname=").append(studentname);
        sb.append(", sex=").append(sex);
        sb.append(", gradeid=").append(gradeid);
        sb.append(", phone=").append(phone);
        sb.append(", address=").append(address);
        sb.append(", borndate=").append(borndate);
        sb.append(", email=").append(email);
        sb.append(", identitycard=").append(identitycard);
        sb.append(", serialVersionUID=").append(serialVersionUID);
        sb.append("]");
        return sb.toString();
    }
}

```

GradeModel.java

```
package online.qsx.model;
```

```
import java.io.Serializable;
import java.util.List;

public class GradeModel implements Serializable {
    /**
     * This field was generated by MyBatis Generator.
     * This field corresponds to the database column grade.GradeID
     *
     * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
     */
    private Integer gradeid;

    /**
     * This field was generated by MyBatis Generator.
     * This field corresponds to the database column grade.GradeName
     *
     * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
     */
    private String gradename;

    //多对多/一对多
    private List<StudentModel> studentModels;

    public List<StudentModel> getStudentModels() {
        return studentModels;
    }

    public void setStudentModels(List<StudentModel> studentModels) {
        this.studentModels = studentModels;
    }

    /**
     * This field was generated by MyBatis Generator.
     * This field corresponds to the database table grade
     *
     * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
     */
    private static final long serialVersionUID = 1L;

    /**
     * This method was generated by MyBatis Generator.
     * This method returns the value of the database column grade.GradeID

```



```

*
* @return the value of grade.GradeID
*
* @mbgggenerated Mon Nov 20 15:52:42 CST 2017
*/
public Integer getGradeid() {
    return gradeid;
}

/**
* This method was generated by MyBatis Generator.
* This method sets the value of the database column grade.GradeID
*
* @param gradeid the value for grade.GradeID
*
* @mbgggenerated Mon Nov 20 15:52:42 CST 2017
*/
public void setGradeid(Integer gradeid) {
    this.gradeid = gradeid;
}

/**
* This method was generated by MyBatis Generator.
* This method returns the value of the database column grade.GradeName
*
* @return the value of grade.GradeName
*
* @mbgggenerated Mon Nov 20 15:52:42 CST 2017
*/
public String getGradename() {
    return gradename;
}

/**
* This method was generated by MyBatis Generator.
* This method sets the value of the database column grade.GradeName
*
* @param gradename the value for grade.GradeName
*
* @mbgggenerated Mon Nov 20 15:52:42 CST 2017
*/
public void setGradename(String gradename) {
    this.gradename = gradename == null ? null : gradename.trim();
}

```

```

/**
 * This method was generated by MyBatis Generator.
 * This method corresponds to the database table grade
 *
 * @mbgggenerated Mon Nov 20 15:52:42 CST 2017
 */
@Override
public String toString() {
    StringBuilder sb = new StringBuilder();
    sb.append(getClass().getSimpleName());
    sb.append(" [");
    sb.append("Hash = ").append(hashCode());
    sb.append(", gradeid=").append(gradeid);
    sb.append(", gradename=").append(gradename);
    sb.append(", studentModels=").append(studentModels.toString());
    sb.append(", serialVersionUID=").append(serialVersionUID);
    sb.append("]");
    return sb.toString();
}
}

```

GradeModelMapper.java

```

package online.qsx.mapper;

import java.util.List;
import online.qsx.model.GradeModel;
import online.qsx.model.GradeModelCriteria;
import org.apache.ibatis.annotations.Param;

public interface GradeModelMapper {

    List<GradeModel> findGradeAndStudent();
}

```

GradeModelMapper.xml

嵌套

```
<?xml version="1.0" encoding="UTF-8" ?>
<!DOCTYPE mapper PUBLIC "-//mybatis.org/DTD Mapper 3.0//EN"
"http://mybatis.org/dtd/mybatis-3-mapper.dtd" >
<mapper namespace="online.qsx.mapper.GradeModelMapper" >
  <resultMap id="GraderMap02" type="online.qsx.model.GradeModel">
    <id property="gradeid" column="g_id" />
    <result property="gradename" column="gradename"/>

    <collection property="studentModels" ofType="online.qsx.model.StudentModel">
      <id property="studentno" column="studentno" />
      <result property="Loginpwd" column="Loginpwd"/>
      <result property="studentname" column="studentname"/>
      <result property="sex" column="sex"/>
      <result property="phone" column="phone"/>
      <result property="address" column="address"/>

      <result property="email" column="email"/>
      <result property="identitycard" column="identitycard"/>
    </collection>
  </resultMap>

  <select id="findGradeAndStudent" resultMap="GraderMap02" >
    select
      stu.studentno,
      stu.loginpwd,
      stu.studentname,
      stu.sex,
      stu.gradeid as s_gid,
      stu.phone,
      stu.address,
      stu.borndate,
      stu.email,
      stu.identitycard,

      gra.gradeid as g_id,
      gra.gradename
```

```

        from
            student stu
        inner join grade gra on gra.gradeid=stu.gradeid
    </select>

</mapper>

```

分离 resultMap 相互引用

```

<?xml version="1.0" encoding="UTF-8" ?>
<!DOCTYPE mapper PUBLIC "-//mybatis.org//DTD Mapper 3.0//EN"
"http://mybatis.org/dtd/mybatis-3-mapper.dtd" >
<mapper namespace="online.qsx.mapper.GradeModelMapper" >
    <resultMap id="GraderMap02" type="online.qsx.model.GradeModel">
        <id property="gradeid" column="g_id" />
        <result property="gradename" column="gradename"/>

        <collection property="studentModels" ofType="online.qsx.model.StudentModel"
resultMap="StudentModel01"></collection>
    </resultMap>

    <resultMap type="online.qsx.model.StudentModel" id="StudentModel01">
        <id property="studentno" column="studentno" />
        <result property="loginpwd" column="loginpwd" />
        <result property="studentname" column="studentname" />
        <result property="sex" column="sex" />
        <result property="phone" column="phone" />
        <result property="address" column="address" />

        <result property="email" column="email" />
        <result property="identitycard" column="identitycard" />
    </resultMap>
    <select id="findGradeAndStudent" resultMap="GraderMap02" >
        select
            stu.studentno,
            stu.loginpwd,
            stu.studentname,
            stu.sex,
            stu.gradeid as s_gid,
            stu.phone,
            stu.address,

```

```
        stu.borndate,
        stu.email,
        stu.identitycard,

        gra.gradeid as g_id,
        gra.gradename
    from

        student stu

        inner join grade gra on gra.gradeid=stu.gradeid
</select>
</mapper>
```

TestQuery.java

```
public void find() throws IOException{
    init();
    List<GradeModel> list= gradeModelMapper.findGradeAndStudent();
    for (GradeModel gradeModel : list) {
        System.out.println(gradeModel);
    }
    destroy();
}
```