

## Key Ideas

---

### Detector model:

data point  $\xrightarrow{\text{a detector with parameters } \{p\}}$  severity  $\xrightarrow{sThld} \{1, 0\}$

First, we use a uniform model to represent how different detectors work.


It is basically a two-step process.

## Key Ideas

### Detector model:

data point  $\xrightarrow{\text{a detector with parameters } \{p\}}$  severity  $\xrightarrow{sThld} \{1, 0\}$

For example



For example, this is our KPI data. The red parts are the anomalies labeled by the operators.


**\*\* Click**

If we apply a detector, historical average for example, to this data, it will generate the anomaly severity for each data point. This detector measure the severity using how many times of the standard deviation each point is away from the average. The higher the severity is, the more anomalous the data point is.

## Key Ideas

### Detector model:

data point  $\xrightarrow{\text{a detector with parameters } \{p\}}$  severity  $\xrightarrow{sThld} \{1, 0\}$




Then, we need to set a severity threshold to decide anomalies.

So, this is a general detector model. Different detectors basically work in these two steps, except that they use different techniques or algorithms to measure the severities.


## Key Ideas

### Detector model:



In Opprentice, we do not let each detector determine the anomaly by itself. Instead, we only use the severity as the anomaly feature.


## Key Ideas



Multiple detectors with different parameters are used simultaneously to extract different anomaly features of the data.

We call a combination of a detector and its specific parameters a configuration.

## Key Ideas



We broadly select 14 detectors and sample some parameters. Finally, we get 133 configurations. In other words, we have 133 anomaly features.