

Evaluate testing data (binary-class) - Lasso

John Doe

2019-01-30

Contents

0. Load Data	1
1. Scores	2
1.1 Scores per Class	2
1.2 Average score	3
2. Important Features	4

Note: The two differences between Lasso and Tree-based methods are:

1. Lasso has its own inherent feature selection process.
2. Lasso's vimp will be based on how many times the feature exist in all runs. Regression coefficients may be presented for binary outcomes


```
## user input
project_home <- "~/EVE/examples"
project_name <- "lasso_binary_outCV_test"
```

0. Load Data

```
## 199 of samples were used
## 100 of full features
## 4 runs, each run contains 3 CVs.
## Labels:
##
##    0    1
## 50 149
```

1. Scores

1.1 Scores per Class




Confusion Matrix

```
## confusion matrix at feature size = 100
## sum across 4 seeds


##           Reference
## Prediction  0    1
##           0 200   4
##           1   0 592
```

1.2 Average score




2. Important Features

distribution across 4 seed x 3 CV




of times a feature is selected by lasso ($\alpha = 0.5$)

summary of model size across 12 runs




number of retained features in one run

Number of times a feature is used




(currently only Lasso has this graph)

Distribution of Feature Coefficient



Top Features



Heatmap of top 20 important features

