

hw2

February 19, 2021

1 Homework 2

```
[1]: %config IPCompleter.use_jedi = False
import numpy as np
from scipy import stats
import matplotlib.pyplot as plt
import cvxpy as cp
import pandas as pd
np.set_printoptions(precision=4)

from pathlib import Path
fig_path = str(Path().absolute())+'/figures/hw2/'
print(fig_path)
```

/home/zpyang/grad_courses/2021_spring/ece595_ml/figures/hw2/

1.1 Exercise 1

```
[2]: data_path = str(Path().absolute())+'/hw2/data/'

male_train_data = pd.read_csv(data_path+'male_train_data.csv')
female_train_data = pd.read_csv(data_path+'female_train_data.csv')
m_bmi = male_train_data['male_bmi']*0.1
m_stature = male_train_data['male_stature_mm']*0.001
f_bmi = female_train_data['female_bmi']*0.1
f_stature = female_train_data['female_stature_mm']*0.001

print('Female BMI: '+str(f_bmi.head(10).values))
print('Female Stature(m): '+str(f_stature.head(10).values))
print('Male BMI: '+str(m_bmi.head(10).values))
print('Male Stature(m): '+str(m_stature.head(10).values))
```

```
Female BMI: [2.82 2.22 2.71 2.81 2.55 2.3  3.56 3.11 2.46 4.3 ]
Female Stature(m): [1.563 1.716 1.484 1.651 1.548 1.665 1.564 1.676 1.69  1.704]
Male BMI: [3.    2.56 2.42 2.74 2.59 2.53 2.27 2.54 3.41 3.34]
Male Stature(m): [1.679 1.586 1.773 1.816 1.809 1.662 1.829 1.686 1.761 1.797]
```

2 Exercise 2

2.1 2a) see hand written part

2.2 2b)

```
[3]: N_male = m_bmi.values.shape[0]
      N_female = f_bmi.values.shape[0]
      N = N_male+N_female

      X = np.block([
          [np.ones(N)],
          [m_bmi.values, f_bmi.values],
          [m_stature.values, f_stature.values],
      ]).T
      y = np.block([np.ones(N_male), -np.ones(N_female)])
      yT = np.array([y]).T

      theta = np.linalg.lstsq(X, y, rcond=None)[0]
      theta
```

```
[3]: array([-10.7018,  -0.1234,   6.6749])
```

2.3 2c)

```
[4]: P = 3
      var = cp.Variable(P)
      objective = cp.Minimize(cp.sum_squares(y-X @ var))
      constraints = []
      prob = cp.Problem(objective=objective, constraints=constraints)
      prob.solve()
      theta = var.value
      theta
```

```
[4]: array([-10.7018,  -0.1234,   6.6749])
```

2.4 2 d) e)

```
[5]: n = 50000
      theta0 = np.zeros(3);
      theta_k = theta0

      A = X.T @ X
      b = X.T @ y
      cost_normal = []
      for k in range(n):
          d_k = -2*A @ theta_k + 2*b
```

```

alpha_k = -0.5 * (d_k.T @ d_k) / (d_k.T @ A @ d_k)
theta_k = theta_k - alpha_k * d_k
cost_normal.append(np.linalg.norm(y - X @ theta_k)**2/N)
cost_normal = np.array(cost_normal)
theta = theta_k
theta

```

[5]: array([-10.7018, -0.1234, 6.6749])


2.5 2 f)

```

[17]: plt.figure()
plt.semilogx(cost_normal, 'o')

```

[17]: [<matplotlib.lines.Line2D at 0x7f88e6964700>]



2.6 2 g)

```

[14]: iterations = 50000
theta0 = np.zeros(3)
A = X.T @ X
b = X.T @ y
beta = 0.9

theta_k = theta0

```

```

d_k0 = np.zeros(3)
cost_momentum = np.zeros(iterations)
for k in range(iterations):
    d_k = -2 * A @ theta_k + 2 * b
    fuck = beta * d_k0 + (1-beta) * d_k

    alpha_k = -0.5 * (d_k.T @ fuck)/(fuck.T @ A @ fuck)
    theta_k = theta_k - alpha_k * fuck
    d_k0 = d_k
    cost_momentum[k] = np.linalg.norm(y - X @ theta_k)**2/N
print(theta_k)

```


```
[-10.7018 -0.1234  6.6749]
```

```

[16]: plt.figure()
      plt.semilogx(cost_momentum, 'o')

```

```
[16]: [<matplotlib.lines.Line2D at 0x7f88e6a8d490>]
```




3 Exercise 3

3.1 3 a)

```
[9]: plt.figure(figsize=(10,7))
# plt.axis('equal')
plt.scatter(m_bmi.values, m_stature.values, color='blue',
            ↪label='male',marker='o', alpha=0.4)
plt.scatter(f_bmi.values, f_stature.values, color='red', label='female',
            ↪marker='.',alpha=0.4)
plt.xlabel('bmi')
plt.ylabel('stature')
x1 = np.hstack([m_bmi.values, f_bmi.values])
x2 = (-theta[0]-theta[1]*x1)/theta[2]
plt.plot(x1,x2, linewidth='5', color='orange', label='Decision boudary',
        ↪alpha=0.8)
plt.legend()
```

[9]: <matplotlib.legend.Legend at 0x7f88e852e9d0>



3.2 3 b)

```
[10]: data_path = str(Path().absolute())+'/hw2/data/'

male_test_data = pd.read_csv(data_path+'male_test_data.csv')
female_test_data = pd.read_csv(data_path+'female_test_data.csv')
m_bmi_t = male_test_data['male_bmi']*0.1
m_stature_t = male_test_data['male_stature_mm']*0.001
f_bmi_t = female_test_data['female_bmi']*0.1
f_stature_t = female_test_data['female_stature_mm']*0.001

N_male_t = m_bmi_t.values.shape[0]
N_female_t = f_bmi_t.values.shape[0]
N_t = N_male_t + N_female_t

X_test_male = np.block([
    [np.ones(N_male_t)],
    [m_bmi_t.values],
    [m_stature_t.values],
]).T

X_test_female = np.block([
    [np.ones(N_female_t)],
    [f_bmi_t.values],
    [f_stature_t.values],
]).T

label_true_m = np.ones(N_male_t)
label_true_f = -np.ones(N_female_t)

label_f = np.sign(X_test_female @ theta)
label_m = np.sign(X_test_male @ theta)

# 3 b) i)
N_false_male = sum(label_f-label_true_f)/2
print(N_false_male)
type1_err_male = N_false_male/N_female_t
print('Type I error:',type1_err_male)

# 3 b) ii)
N_false_female = -sum(label_m - label_true_m)/2
print(N_false_female)
type2_err_male = N_false_female/N_male_t
print('Type II error:',type2_err_male)

# 3 b) iii)
```

```

N_model_male = N_false_male + N_male_t - N_false_female
precision = (N_male_t - N_false_female)/N_model_male
print('Precision:', precision)

recall = (N_male_t - N_false_female)/N_male_t
print('Recall:', recall)

```

```

71.0
Type I error: 0.14171656686626746
90.0
Type II error: 0.17964071856287425
Precision: 0.8526970954356846
Recall: 0.8203592814371258

```

3.3 Exercise 4

3.4 4 a)

```

[11]: lambda = np.arange(0.1, 10, 0.1)

f_theta_l = lambda lamb: np.linalg.inv(X.T @ X + np.eye(3) * lamb) @ X.T @ y
theta_l_vec = [f_theta_l(lamb) for lamb in lambda]
first_term = [np.linalg.norm(X@theta-y)**2 for theta in theta_l_vec]
theta_sqr = [np.linalg.norm(theta)**2 for theta in theta_l_vec]

```

```

[12]: plt.figure()
plt.plot(theta_sqr, first_term)
plt.title('||X*theta-y||^2 vs ||theta||^2')
plt.xlabel('||theta||^2')
plt.ylabel('||X*theta-y||^2')

plt.figure()
plt.plot(lambda, first_term)
plt.title('||X*theta-y||^2 vs lambda')
plt.xlabel('lambda')
plt.ylabel('||X*theta-y||^2')



plt.figure()
plt.plot(lambda, theta_sqr)
plt.title('||theta||^2 vs lambda')
plt.xlabel('lambda')
plt.ylabel('||theta||^2')


```

```

[12]: Text(0, 0.5, '||theta||^2')

```





```
[13]: P = 3
      var = cp.Variable(P)
      objective = cp.Minimize(cp.sum_squares(y-X @ var)+ lambd[0]*cp.sum_squares(var))
      constraints = []
      prob = cp.Problem(objective=objective, constraints=constraints)
      prob.solve()
      theta = var.value
      np.linalg.norm(theta)**2
```

[13]: 155.44352320635605

[]:

[]: