Property Data

Envalior
Imagine the Future

Stanyl® HFX31SW

PA46-GF20 FR(40)

20% Glass Reinforced, High Flow, Halogen free and free of red phosphorous

Print Date: 2023-11-14

Stanyl® HFX31SW is an electro-friendly & halogen-free flame-retarded high heat polyamide that offers an excellent combination of high CTI, flow and weld-line strength. HFX-grades are often used in connectors such as USB type C.

PROPERTIES	TYPICAL DATA	UNIT	TEST METHOD
MECHANICAL PROPERTIES	**DRY / COND**		
Tensile modulus	8200 / -	MPa	ISO 527-1/-2
Stress at break	110 / -	MPa	ISO 527-1/-2
Strain at break	2.6 / -	%	ISO 527-1/-2
Flexural modulus	8000 / -	MPa	ISO 178
Flexural strength	130 / -	MPa	ISO 178
Charpy notched impact strength (+23°C)	5.5 / -	kJ/m²	ISO 179/1eA
THERMAL PROPERTIES	**DRY / COND**		
Melting temperature (10°C/min)	295 / *	°C	ISO 11357-1/-3
Temp. of deflection under load (1.80 MPa)	285 / *	°C	ISO 75-1/-2
Burning Behav. at 3.0 mm nom. thickn.	V-0 / *	class	IEC 60695-11-10
Thickness tested	3 / *	mm	IEC 60695-11-10
UL recognition	Yes / *	-	-
OTHER PROPERTIES	**DRY / COND**		
Density	1470 / -	kg/m³	ISO 1183