



组件 - 塑料

AKV35H3.0, AKV35H3.0LT, S223-KG7

Yellow Card™

Envalior

Flughafenstrasse 101
Dusseldorf, 40474 Germany

UL 档案号: E47960

Akulon: AKV35H3.0, AKV35H3.0LT, S223-KG7

Polyamide 66 (PA66), pellets [contains mechanically recycled content]



可燃性	值	测试方法
UL 阻燃等级		UL 94
0.75 mm, ALL	HB	
1.5 mm, ALL	HB	
3.0 mm, ALL	HB	
可燃性等级		IEC 60695-11-10, -20
0.75 mm, ALL	HB75	
1.5 mm, ALL	HB75	
3.0 mm, ALL	HB40	
电气性能	值	测试方法
相比耐漏电起痕指数(CTI)	PLC 0	UL 746A
体积电阻率	1.0E+11 ohms-cm	ASTM D257 IEC 60093
漏电起痕指数	600 V	IEC 60112
热性能	值	测试方法
RTI Elec		UL 746B
0.75 mm	65.0 °C	
1.5 mm	65.0 °C	
3.0 mm	65.0 °C	
RTI Imp		UL 746B
0.75 mm	65.0 °C	
1.5 mm	65.0 °C	
3.0 mm	65.0 °C	
RTI		UL 746B
0.75 mm	65.0 °C	
1.5 mm	65.0 °C	
3.0 mm	65.0 °C	