



ROTOUN® LLD480Z

产品说明 Description:

LLD480Z 是发泡级LLDPE 改性滚塑颗粒，最高发泡倍率可超 8 倍。起发温度约 150℃，最佳发泡温度约 180℃。

LLD480Z is a foaming grade LLDPE modified rotational molding granule, with a maximum foaming ratio that can exceed 8 times. The starting temperature is approximately 150℃, and the optimal foaming temperature is about 180℃.

- 材料状态Forms: ●已商用：当前有效 Commercial: active
- 供货地区Availability: ●亚洲AS
- 添加剂Additive: ●发泡剂FA
- 性能特点Features: ●易加工Easy Processing
- 应用领域Application: ●填充层Fillingg
- 法规符合Regulations: ●RoHS
- 包装形式Packing: ●20Kg/包装 20Kg / packaging(PP bag with PE Inner)
- 保质期Shelf Life: ●生产之日起一年 1 year from the date of production

数据表 Datasheet	典型值 Typical Values	单位 Unit	测试标准 Test Method
物理性能 Physical Properties			
表观密度Apparent Density	0.117	g/cm ³	GB/T 6343
熔体流动速率 Melt Index (190℃,2.16Kg)	-	g/10min	ISO1133
堆积密度 Bulk Density	-	g/cm ³	ISO60
熔点 Melting Point	127	℃	ISO11357
粉体流动性Dry Flow Rate	-	s/100g	ARM

本数据是该牌号的典型数据，不能作为供货的质量保证指标。
This guide data is typical of the brand product data, and can not be used as indicators of supplier quality assurance.

浙江瑞堂塑料科技有限公司
Zhejiang Rotoun Plastic Technology Corp.