

Homework 7

Zachary Moring

October 24, 2024

Code for this assignment is at: <https://github.com/zpm-bu/cs511-formal-methods/blob/assignments/lean/Homework/hw7.lean>

Exercise 1. Use first-order ground tableaux to show that $\Gamma \models \varphi$ where

$$\Gamma \stackrel{\text{def}}{=} \{ \forall x \forall y \forall z (P(x, y) \wedge P(y, z) \rightarrow P(x, z)), \forall x \forall y (P(x, y) \rightarrow P(y, x)) \}$$

and

$$\varphi \stackrel{\text{def}}{=} \forall x \forall y \forall z (P(x, y) \wedge P(z, y) \rightarrow P(x, z))$$

and P is an arbitrary binary predicate.

$$\begin{array}{c}
\Gamma \cup \{\varphi\} \\
| \\
\forall x \forall y \forall z (P(x, y) \wedge P(y, z) \rightarrow P(x, z)) \\
| \\
\forall y \forall z (P(t, y) \wedge P(y, z) \rightarrow P(t, z)) \\
| \\
\forall z (P(t, u) \wedge P(u, z) \rightarrow P(t, z)) \\
| \\
P(t, u) \wedge P(u, v) \rightarrow P(t, v) \\
| \\
\neg \forall x \forall y \forall z (P(x, y) \wedge P(z, y) \rightarrow P(x, z)) \\
| \\
\neg \forall y \forall z (P(t, y) \wedge P(z, y) \rightarrow P(t, z)) \\
| \\
\neg \forall z P(t, u) \wedge P(z, u) \rightarrow P(t, z) \\
| \\
\neg (P(t, u) \wedge P(v, u) \rightarrow P(t, v)) \\
| \\
P(t, u) \wedge P(v, u) \\
| \\
\neg P(t, v) \\
| \\
P(t, u) \\
| \\
P(v, u) \\
| \\
\forall x \forall y P(x, y) \rightarrow P(y, x) \\
| \\
\forall y P(v, y) \rightarrow P(y, v) \\
| \\
P(v, u) \rightarrow P(u, v) \\
\swarrow \quad \searrow \\
\neg (P(t, u) \wedge P(u, v)) \quad P(t, v) \times \\
\swarrow \quad \searrow \\
\neg P(t, u) \times \quad \neg P(u, v) \\
\swarrow \quad \searrow \\
\neg P(v, u) \times \quad P(u, v) \times
\end{array}$$

Exercise 2. Use first-order ground tableaux to show...

