

Document Title	HSD070IFW1-A Formal Product Specification	Page No.	1 / 24
Document No.	DC140-001646	Revision	1.1

TO :

Date : Aug., 08, 2013

HannStar Product Specification **(Formal)**

Model: HSD070IFW1-A00
(Module)

Note:

1. Please contact HannStar Display Corp. before designing your product based on this module specification.
2. The information contained herein is presented merely to indicate the characteristics and performance of our products. No responsibility is assumed by HannStar for any intellectual property claims or other problems that may result from application based on the module described herein.

Document Title	HSD070IFW1-A Formal Product Specification	Page No.	2 / 24
Document No.	DC140-001646	Revision	1.1

Record of Revisions

Rev.	Date	Sub-Model	Description of change
1.0	May, 07, 2013	A00	Formal Product Specification was first released.
1.1	Aug, 08, 2013	A00	P4. Modify Surface treatment

Document Title	HSD070IFW1-A Formal Product Specification	Page No.	3 / 24
Document No.	DC140-001646	Revision	1.1

Contents

1.0	General description	p.4
2.0	Absolute maximum ratings.....	p.5
3.0	Optical characteristics.....	p.6
4.0	Block diagram	p.10
5.0	Interface pin connection	p.13
6.0	Electrical characteristics	p.15
7.0	Reliability test items	p.20
8.0	Outline dimension	p.21
9.0	Lot mark	p.23
10.0	Package specification	p.24
11.0	General precaution	p.25

Document Title	HSD070IFW1-A Formal Product Specification	Page No.	4 / 24
Document No.	DC140-001646	Revision	1.1

1.0 GENERAL DESCRIPTION

1.1 Introduction

HannStar Display model HSD070IFW1-A is a color active matrix thin film transistor (TFT) liquid crystal display (LCD) that uses amorphous silicon TFT as a switching device. This model is composed of a TFT LCD panel, a driving circuit and a back light system. This TFT LCD has a 7.0 (16:9) inch diagonally measured active display area with WSVGA (1024 horizontal by 600 vertical pixel) resolution.

1.2 Features

- 7 inch (16:9 diagonal) configuration
- 16.7M color by 6 bit+HiFRC R.G.B signal input
- RoHS/ Halogen Free Compliance

1.3 Applications

- Automotive

1.4 TFT LCD General information

Item		Specification	Unit
Outline Dimension		164.9 x 100.0 (typ)	mm
Display area		153.6(H) x 86.64(V)	mm
Number of Pixel		1024 RGB (H) x 600(V)	pixels
Pixel pitch		0.150(H) x 0.1444(V)	mm
Pixel arrangement		RGB Vertical stripe	
Display mode		Normally white	
NTSC		50 (typ.)	%
Surface treatment		AG, with EWV Flim	
Weight		146g (Typ.)	g
Back-light		White LED	
Power Consumption	Logic	0.35 (typ) @ Black pattern 、 Frame rate 60Hz	W
	BL System	2.45 (typ) @ Black pattern w/o LED driver	W

1.5 Mechanical Information

Item		Min.	Typ.	Max.	Unit
Module Size	Horizontal (H)	164.6	164.9	165.2	mm
	Vertical (V)	99.7	100.0	100.3	mm
	Depth (D)	5.4	5.7	6.0	mm
	Depth (with component)			7.3	mm
Weight		—	146	156	—

Document Title	HSD070IFW1-A Formal Product Specification	Page No.	5 / 24
Document No.	DC140-001646	Revision	1.1

2.0 ABSOLUTE MAXIMUM RATINGS

2.1 Electrical Absolute Rating

2.1.1 TFT LCD Module

Item	Symbol	Min.	Max.	Unit	Note
Power supply voltage	V_{DD}	-0.3	5.0	V	
	V_{GH}	-0.3	40.0	V	
	V_{GL}	-20.0	0.3	V	
	AV_{DD}	6.5	13.5	V	
	V_I	-0.3	$V_{DD} + 0.3$	V	
Logic Signal Input Level	V_{DD}	-0.3	5.0	V	

2.1.2 Backlight unit

Item	Symbol	Typ.	Max.	Unit	Note
LED current	I_L	240	-	mA	(1) (2)(3)
LED voltage	V_L	9.6	10.2	V	(1) (2)(3)
LED reverse voltage	V_R	--	5	V	

Note:

- (1) Permanent damage may occur to the LCD module if beyond this specification. Functional operation should be restricted to the conditions described under normal operating conditions.
- (2) $T_a = 25 \pm 2^\circ\text{C}$
- (3) Test Condition: LED current 240 mA. The LED lifetime could be decreased if operating I_L is larger than 240 mA.

2.1.3 Environment Absolute Rating

Item	Symbol	Min.	Max.	Unit	Note
Operating Temperature	T_{opa}	-20	70	$^\circ\text{C}$	
Storage Temperature	T_{stg}	-30	80	$^\circ\text{C}$	

Document Title	HSD070IFW1-A Formal Product Specification	Page No.	6 / 24
Document No.	DC140-001646	Revision	1.1

3.0 OPTICAL CHARACTERISTICS

3.1 Optical specification

Item		Symbol	Condition	Min.	Typ.	Max.	Unit	Note
Contrast		CR	Θ=0 Normal viewing angle	640	800	—		(1)(2)(4)
Response time		Tr		—	4	8	msec	(1)(3)
		Tf		—	12	24		
White luminance (Center)		Y _L		480	600	—	cd/m ²	(1)(4) (I _L =240mA)
Color chromaticity (CIE1931)	Red	R _x		-0.05	0.617 0.353 0.365 0.580 0.148 0.098 0.31 0.33	+0.05		
		R _Y						
	Green	G _x						
		G _Y						
	Blue	B _x						
		B _Y						
	White	W _x						
		W _y						
Viewing angle	Hor.	Θ _L	CR>10	70	80	—		(1)(4)
		Θ _R		70	80	—		
	Ver.	Θ _U		60	70	—		
		Θ _D		70	80	—		
Brightness uniformity		B _{UNI}	Θ=0 (9point)	70	75	—		(5)
View Direction		6 O' clock						(6)

3.2 Measuring Condition


- Measuring surrounding : dark room
- LED current I_L : 240mA
- Ambient temperature : 25±2°C
- 15min. warm-up time.

Document Title	HSD070IFW1-A Formal Product Specification	Page No.	7 / 24
Document No.	DC140-001646	Revision	1.1

3.3 Measuring Equipment

- FPM520 of Westar Display technologies, INC., which utilized SR-3 for Chromaticity and BM-5A for other optical characteristics.
- Measuring spot size : 20 ~ 21 mm

Note (1) Definition of Viewing Angle:




Note (2) Definition of Contrast Ratio (CR) :
measured at the center point of panel


$$CR = \frac{\text{Luminance with all pixels white}}{\text{Luminance with all pixels black}}$$

Document Title	HSD070IFW1-A Formal Product Specification	Page No.	8 / 24
Document No.	DC140-001646	Revision	1.1

Note (3) Definition of Response Time : Sum of T_R and T_F




Note (4) Definition of optical measurement setup



Document Title	HSD070IFW1-A Formal Product Specification	Page No.	9 / 24
Document No.	DC140-001646	Revision	1.1

Note (5) Definition of Average Luminance Uniformity of White (Center)
Definition of brightness uniformity




$$\text{Luminance uniformity} = \frac{(\text{Min Luminance of 9 points})}{(\text{Max Luminance of 9 points})} \times 100\%$$

Note (6) Rubbing Direction (The different Rubbing Direction will cause the different optimal view direction.)


Document Title	HSD070IFW1-A Formal Product Specification	Page No.	10 / 24
Document No.	DC140-001646	Revision	1.1

4.0 BLOCK DIAGRAM

4.1 TFT LCD Module



4.2 Pixel Format



Document Title	HSD0701FW1-A Formal Product Specification	Page No.	11 / 24
Document No.	DC140-001646	Revision	1.1

4.3 Relationship Between Displayed Color and Input

4.3.1 6bit

	Display	MSB LSB R5 R4 R3 R2 R1 R0	M L G5 G4 G3 G2 G1 G0	S S B5 B4 B3 B2 B1 B0	Gray scale level
Basic color	Black	L L L L L L	L L L L L L	L L L L L L	-
	Blue	L L L L L L	L L L L L L	H H H H H H	-
	Green	L L L L L L	H H H H H H	L L L L L L	-
	Light Blue	L L L L L L	H H H H H H	H H H H H H	-
	Red	H H H H H H	L L L L L L	L L L L L L	-
	Purple	H H H H H H	L L L L L L	H H H H H H	-
	Yellow	H H H H H H	H H H H H H	L L L L L L	-
	White	H H H H H H	H H H H H H	H H H H H H	-
Gray scale of Red	Black	L L L L L L	L L L L L L	L L L L L L	L0
	Dark ↕ Light	L L L L L H	L L L L L L	L L L L L L	L1
		L L L L H L	L L L L L L	L L L L L L	L2
		:	:	:	L3...L60
	Light	H H H H L H	L L L L L L	L L L L L L	L61
		H H H H H L	L L L L L L	L L L L L L	L62
	Red	H H H H H H	L L L L L L	L L L L L L	Red L63
Gray scale of Green	Black	L L L L L L	L L L L L L	L L L L L L	L0
	Dark ↕ Light	L L L L L L	L L L L L H	L L L L L L	L1
		L L L L L L	L L L L H L	L L L L L L	L2
		:	:	:	L3...L60
	Light	L L L L L L	H H H H L H	L L L L L L	L61
		L L L L L L	H H H H H L	L L L L L L	L62
	Green	L L L L L L	H H H H H H	L L L L L L	Green L63
Gray scale of Blue	Black	L L L L L L	L L L L L L	L L L L L L	L0
	Dark ↕ Light	L L L L L L	L L L L L L	L L L L L H	L1
		L L L L L L	L L L L L L	L L L L H L	L2
		:	:	:	L3...L60
	Light	L L L L L L	L L L L L L	H H H H L H	L61
		L L L L L L	L L L L L L	H H H H H L	L62
	Blue	L L L L L L	L L L L L L	H H H H H H	Blue L63
Gray scale of White & Black	Black	L L L L L L	L L L L L L	L L L L L L	L0
	Dark ↕ Light	L L L L L H	L L L L L H	L L L L L H	L1
		L L L L H L	L L L L H L	L L L L H L	L2
		:	:	:	L3...L60
	Light	H H H H L H	H H H H L H	H H H H L H	L61
		H H H H H L	H H H H H L	H H H H H L	L62
	White	H H H H H H	H H H H H H	H H H H H H	White L63

Document Title	HSD070IFW1-A Formal Product Specification	Page No.	12 / 24
Document No.	DC140-001646	Revision	1.1

4.3.2 8bit

	Display	MSB R7 R6 R5 R4 R3 R2 R1 R0	LSB G7 G6 G5 G4 G3 G2 G1 G0	MSB B7 B6 B5 B4 B3 B2 B1 B0	Gray scale Level
Basic color	Black	L L L L L L L L	L L L L L L L L	L L L L L L L L	-
	Blue	L L L L L L L L	L L L L L L L L	H H H H H H H H	-
	Green	L L L L L L L L	H H H H H H H H	L L L L L L L L	-
	Light Blue	L L L L L L L L	H H H H H H H H	H H H H H H H H	-
	Red	H H H H H H H H	L L L L L L L L	L L L L L L L L	-
	Purple	H H H H H H H H	L L L L L L L L	H H H H H H H H	-
	Yellow	H H H H H H H H	H H H H H H H H	L L L L L L L L	-
	White	H H H H H H H H	H H H H H H H H	H H H H H H H H	-
Gray scale of Red	Black	L L L L L L L L	L L L L L L L L	L L L L L L L L	L0
	Dark ↑ ↓ Light	L L L L L L L H	L L L L L L L L	L L L L L L L L	L1
		L L L L L L H L	L L L L L L L L	L L L L L L L L	L2
		:	:	:	L3...L251
		H H H H H H L L	L L L L L L L L	L L L L L L L L	L252
	Light	H H H H H H L H	L L L L L L L L	L L L L L L L L	L253
		H H H H H H H L	L L L L L L L L	L L L L L L L L	L254
	Red	H H H H H H H H	L L L L L L L L	L L L L L L L L	Red L255
Gray scale of Green	Black	L L L L L L L L	L L L L L L L L	L L L L L L L L	L0
	Dark ↑ ↓ Light	L L L L L L L L	L L L L L L L H	L L L L L L L L	L1
		L L L L L L L L	L L L L L L H L	L L L L L L L L	L2
		:	:	:	L3...L251
		L L L L L L L L	H H H H H H L L	L L L L L L L L	L252
	Light	L L L L L L L L	H H H H H H L H	L L L L L L L L	L253
		L L L L L L L L	H H H H H H H L	L L L L L L L L	L254
	Green	L L L L L L L L	H H H H H H H H	L L L L L L L L	Green L255
Gray scale of Blue	Black	L L L L L L L L	L L L L L L L L	L L L L L L L L	L0
	Dark ↑ ↓ Light	L L L L L L L L	L L L L L L L L	L L L L L L L H	L1
		L L L L L L L L	L L L L L L L L	L L L L L L H L	L2
		:	:	:	L3...L251
		L L L L L L L L	L L L L L L L L	H H H H H H L L	L252
	Light	L L L L L L L L	L L L L L L L L	H H H H H H L H	L253
		L L L L L L L L	L L L L L L L L	H H H H H H H L	L254
	Blue	L L L L L L L L	L L L L L L L L	H H H H H H H H	Blue L255
Gray scale of White & Black	Black	L L L L L L L L	L L L L L L L L	L L L L L L L L	L0
	Dark ↑ ↓ Light	L L L L L L L H	L L L L L L L H	L L L L L L L H	L1
		L L L L L L H L	L L L L L L H L	L L L L L L H L	L2
		:	:	:	L3...L251
		H H H H H H L L	H H H H H H L L	H H H H H H L L	L252
	Light	H H H H H H L H	H H H H H H L H	H H H H H H L H	L253
		H H H H H H H L	H H H H H H H L	H H H H H H H L	L254
	White	H H H H H H H H	H H H H H H H H	H H H H H H H H	White L255

Document Title	HSD0701FW1-A Formal Product Specification	Page No.	13 / 24
Document No.	DC140-001646	Revision	1.1

5.0 INTERFACE PIN CONNECTION

FPC connector is used for electronics interface. The recommended model is FH12A-40S-0.5SH manufactured by Hirose.

Pin No.	Symbol	I/O	Function	Note
1	VCOM	P	Common Voltage	
2	VDD	P	Power Voltage for digital circuit	
3	VDD	P	Power Voltage for digital circuit	
4	NC	---	No connection	
5	Reset	I	Global reset pin	Note1
6	U/D	I	Vertical inversion	Note2
7	L/R	I	Horizontal inversion	Note2
8	STBYB	I	Standby mode, Normally pulled high STBYB = "1", normal operation STBYB = "0", timing controller, source driver will turn off, all output are High-Z	
9	GND	P	Ground	
10	RXCLKIN-	I	- LVDS differential clock input	
11	RXCLKIN+	I	+ LVDS differential clock input	
12	GND	P	Ground	
13	RXIN0-	I	- LVDS differential data input	
14	RXIN0+	I	+ LVDS differential data input	
15	GND	P	Ground	
16	RXIN1-	I	- LVDS differential data input	
17	RXIN1+	I	+ LVDS differential data input	
18	GND	P	Ground	
19	RXIN2-	I	- LVDS differential data input	
20	RXIN2+	I	+ LVDS differential data input	
21	GND	P	Ground	
22	RXIN3-	I	- LVDS differential data input	
23	RXIN3+	I	+ LVDS differential data input	
24	GND	P	Ground	
25	SELB	I	6bit/8bit mode selection	Note3
26	GND	P	Ground	
27	AVDD	P	Power for Analog Circuit	
28	GND	P	Ground	
29	VGH	P	Gate ON Voltage	
30	NC	---	No connection	
31	NC	---	No connection	
32	VGL	P	Gate off Voltage	
33	GND	P	Ground	
34	NC	---	No connection	

Document Title	HSD070IFW1-A Formal Product Specification	Page No.	14 / 24
Document No.	DC140-001646	Revision	1.1

Pin No.	Symbol	I/O	Function	Note
35	LED-	P	LED Cathode	
36	LED-	P	LED Cathode	
37	NC	---	No connection	
38	NC	---	No connection	
39	LED+	P	LED Anode	
40	LED+	P	LED Anode	

I: input O: Output P: Power

Note1 : Global reset pin: Active low to enter reset mode. Suggest connecting with an RC reset circuit for stability. Normally pull high. (R=10K Ω , C=0.1 μ F)

Note: If RC is not added, users must follow the rule, T2 > 50ms on page 18 item 6.5 power on/off sequence.

Note2 : When L/R="0", set right to left scan direction.

When L/R="1", set left to right scan direction.

When U/D="0", set top to bottom scan direction.

When U/D="1", set bottom to top scan direction.

Note3 : If LVDS input data is 6 bits, SELB must be set to High;

If LVDS input data is 8 bits, SELB must be set to Low.

Document Title	HSD070IFW1-A Formal Product Specification	Page No.	15 / 24
Document No.	DC140-001646	Revision	1.1

6.0 ELECTRICAL CHARACTERISTICS

6.1 TFT LCD Module

Item	Symbol	Min.	Typ.	Max.	Unit	Note
Supply Voltage	VDD	3.0	3.3	3.6	V	
	VGH	17.7	18	18.3	V	
	VGL	-10.3	-10	-9.7	V	
	AVDD	9.2	9.5	9.8	V	
VCOM	VCOMin	1.98	2.38	2.78	V	
Input signal voltage	ViH	0.7 VDD	-	VDD	V	Note (1)
	ViL	0	-	0.3 VDD	V	
Current of power supply	IDD	-	33	-	mA	VDD =3.3V
	IADD	-	18	-	mA	AVDD=9.5V
	IGH	-	0.31	-	mA	VGH=18V
	IGL	-	1.0	-	mA	VGL=-10V


6.2 Switching Characteristics for LVDS Receiver

Item	Symbol	Min.	Typ.	Max.	Unit	Conditions
Differential Input High Threshold	Vth	—	—	100	mV	V _{CM} =1.2V
Differential Input Low Threshold	Vtl	-100	—	—	mV	
Input Current	I _{IN}	-10	—	+10	uA	
Differential input Voltage	V _{ID}	0.1	—	0.6	V	
Common Mode Voltage Offset	V _{CM}	0.7	1.2	1.6	V	

Document Title	HSD070IFW1-A Formal Product Specification	Page No.	16 / 24
Document No.	DC140-001646	Revision	1.1

6.3 Bit LVDS input

6.3.1 6bit LVDS input



6.3.2 8Bit LVDS input

