

# Chapter 17

## Recursion

# What is Recursion?

A **recursive function** is one that solves its task by **calling itself** on smaller pieces of data.

- Similar to recurrence function in mathematics.
- Like iteration -- can be used interchangeably; sometimes recursion results in a simpler solution.

Example: Running sum (  $\sum_{i=1}^n i$  )

## Mathematical Definition:


RunningSum(1) = 1

RunningSum(n) =  
n + RunningSum(n-1)

## Recursive Function:

```
int RunningSum(int n) {  
    if (n == 1)  
        return 1;  
    else  
        return n + RunningSum(n-1);  
}
```

# Executing RunningSum



## High-Level Example: Binary Search

**Given a sorted set of exams, in alphabetical order, find the exam for a particular student.**

- 1. Look at the exam **halfway** through the pile.**
- 2. If it matches the name, we're done;  
if it does not match, then...**
- 3a. If the name is greater (alphabetically), then  
**search the upper half** of the stack.**
- 3b. If the name is less than the halfway point, then  
**search the lower half** of the stack.**


# Binary Search: Pseudocode

**Pseudocode is a way to describe algorithms without completely coding them in C.**

```
FindExam(studentName, start, end)
{
    halfwayPoint = (end + start)/2;
    if (end < start)
        ExamNotFound(); /* exam not in stack */
    else if (studentName == NameOfExam(halfwayPoint))
        ExamFound(halfwayPoint); /* found exam! */
    else if (studentName < NameOfExam(halfwayPoint))
        /* search lower half */
        FindExam(studentName, start, halfwayPoint - 1);
    else /* search upper half */
        FindExam(studentName, halfwayPoint + 1, end);
}
```

## High-Level Example: Towers of Hanoi

**Task:** Move all disks from current post to another post.




### Rules:

- (1) Can only move one disk at a time.
- (2) A larger disk can never be placed on top of a smaller disk.
- (3) May use third post for temporary storage.


# Task Decomposition

**Suppose disks start on Post 1, and target is Post 3.**


**1. Move top  $n-1$  disks to Post 2.**



**2. Move largest disk to Post 3.**



**3. Move  $n-1$  disks from Post 2 to Post 3.**



## Task Decomposition (cont.)

Task 1 is really the **same problem**,  
with fewer disks and a different target post.

- "Move  $n-1$  disks from Post 1 to Post 2."

And Task 3 is also the **same problem**,  
with fewer disks and different starting and target posts.

- "Move  $n-1$  disks from Post 2 to Post 3."

So this is a **recursive** algorithm.

- The terminal case is moving the smallest disk -- can move directly without using third post.
- Number disks from 1 (smallest) to  $n$  (largest).



# Towers of Hanoi: Pseudocode

```
MoveDisk(diskNumber, startPost, endPost, midPost)
{
    if (diskNumber > 1) {
        /* Move top n-1 disks to mid post */
        MoveDisk(diskNumber-1, startPost, midPost, endPost);

        printf("Move disk number %d from %d to %d.\n",
            diskNumber, startPost, endPost);

        /* Move n-1 disks from mid post to end post */
        MoveDisk(diskNumber-1, midPost, endPost, startPost);
    }
    else
        printf("Move disk number 1 from %d to %d.\n",
            startPost, endPost);
}
```

## Detailed Example: Fibonacci Numbers

### Mathematical Definition:

$$f(n) = f(n - 1) + f(n - 2)$$

$$f(1) = 1$$

$$f(0) = 1$$


**In other words, the n-th Fibonacci number is the sum of the previous two Fibonacci numbers.**

## Fibonacci: C Code

```
int Fibonacci(int n)
{
    if ((n == 0) || (n == 1))
        return 1;
    else
        return Fibonacci(n-1) + Fibonacci(n-2);
}
```


# Activation Records

**Whenever Fibonacci is invoked,  
a new activation record is pushed onto the stack.**




## Activation Records (cont.)


Fibonacci(1) returns,  
Fibonacci(2) calls  
Fibonacci(0)



Fibonacci(2) returns,  
Fibonacci(3) calls  
Fibonacci(1)



Fibonacci(3)  
returns



## Tracing the Function Calls

**If we are debugging this program,  
we might want to trace all the calls of Fibonacci.**

- **Note: A trace will also contain the arguments passed into the function.**


**For Fibonacci(3), a trace looks like:**

```
Fibonacci (3)
  Fibonacci (2)
    Fibonacci (1)
      Fibonacci (0)
    Fibonacci (1)
```

**What would trace of Fibonacci(4) look like?**

# Fibonacci: LC-3 Code

## Activation Record



## LC-2 Code (part 1 of 3)

```
Fibonacci  ADD    R6, R6, #-2    ; skip ret val, push ret addr
           STR    R7, R6, #0
           ADD    R6, R6, #-1    ; push dynamic link
           STR    R5, R6, #0
           ADD    R5, R6, #-1    ; set frame pointer
           ADD    R6, R6, #-2    ; space for locals and temps

           LDR    R0, R5, #4     ; load n
           BRz    FIB_BASE      ; check for terminal cases
           ADD    R0, R0, #-1
           BRz    FIB_BASE
```



## LC-3 Code (part 2 of 3)

```
LDR    R0, R5, #4    ; read parameter n
ADD    R0, R0, #-1   ; calculate n-1
ADD    R6, R6, #-1   ; push n-1
STR    R0, R6, #0
JSR    Fibonacci     ; call self
```

```
LDR    R0, R6, #0    ; pop return value
ADD    R6, R6, #1
STR    R0, R5, #-1   ; store in temp
LDR    R0, R5, #4    ; read parameter n
ADD    R0, R0, #-2   ; calculate n-2
ADD    R6, R6, #-1   ; push n-2
STR    R0, R6, #0
JSR    Fibonacci     ; call self
```

## LC-3 Code (part 3 of 3)

```
LDR    R0, R6, #0    ; pop return value
ADD    R6, R6, #1
LDR    R1, R5, #-1   ; read temp
ADD    R0, R0, R1     ; Fibonacci(n-1) + Fibonacci(n-2)
BRnzp  FIB_END       ; all done
```

```
FIB_BASE    AND    R0, R0, #0    ; base case – return 1
            ADD    R0, R0, #1
```

```
FIB_END     STR    R0, R5, #3    ; write return value (R0)
            ADD    R6, R5, #1    ; pop local variables
            LDR    R5, R6, #0    ; pop dynamic link
            ADD    R6, R6, #1
            LDR    R7, R6, #0    ; pop return address
            ADD    R6, R6, #1
            RET
```

## A Final C Example: Printing an Integer

**Recursively converts an unsigned integer as a string of ASCII characters.**

- If integer <10, convert to char and print.
- Else, call self on first (n-1) digits and then print last digit.

```
void IntToAscii(int num) {  
    int prefix, currDigit;  
    if (num < 10)  
        putchar(num + '0'); /* prints single char */  
    else {  
        prefix = num / 10; /* shift right one digit */  
        IntToAscii(prefix); /* print shifted num */  
        /* then print shifted digit */  
        currDigit = num % 10;  
        putchar(currDigit + '0');  
    }  
}
```

## Trace of IntToAscii

**Calling IntToAscii with parameter 12345:**

```
IntToAscii(12345)
  IntToAscii(1234)
    IntToAscii(123)
      IntToAscii(12)
        IntToAscii(1)
          putchar('1')
        putchar('2')
      putchar('3')
    putchar('4')
  putchar('5')
```