

THÈSE DE DOCTORAT

ASYNCHRONOUS DOMAIN DECOMPOSITION METHODS FOR MASSIVELY PARALLEL COMPUTING

PRÉPARÉE ET SOUTENUE PAR
GUILLAUME GBIKPI-BENISSAN

DEVANT LE JURY COMPOSÉ DE

RAPHAËL COUTURIER
FABIENNE JEZEQUEL
PIERRE SPITERI
STÉPHANE VIALLE
FRÉDÉRIC MAGOULÈS

(RAPPORTEUR)
(EXAMINATRICE)
(RAPPORTEUR)
(EXAMINATEUR)
(DIRECTEUR DE THÈSE)



Asynchronous iterative methods

“Possibly the kind of methods which will allow the next generation of parallel machines to attain the expected potential.” *[Frommer and Szyld, 2000]*

Asynchronous iterative methods

“Possibly the kind of methods which will allow the next generation of parallel machines to attain the expected potential.” *[Frommer and Szyld, 2000]*

Parallel processing

- ◆ Speedup limit *[Amdahl, 1967]*

$t(p)$: processing time using p processors

α : serial proportion of the processing (data management)

Asynchronous iterative methods

“Possibly the kind of methods which will allow the next generation of parallel machines to attain the expected potential.” *[Frommer and Szyld, 2000]*

Parallel processing

◆ Speedup limit *[Amdahl, 1967]*

$t(p)$: processing time using p processors

α : serial proportion of the processing (data management)

⇒ Theoretical speedup:

$$s(p, \alpha) = \frac{t(1)}{t(p)} \leq \frac{1}{\alpha + \frac{1-\alpha}{p}}$$

Asynchronous iterative methods

“Possibly the kind of methods which will allow the next generation of parallel machines to attain the expected potential.” *[Frommer and Szyld, 2000]*

Parallel processing


◆ Speedup limit *[Amdahl, 1967]*

$t(p)$: processing time using p processors

α : serial proportion of the processing (data management)

⇒ Theoretical speedup:

$$s(p, \alpha) = \frac{t(1)}{t(p)} \leq \frac{1}{\alpha + \frac{1-\alpha}{p}}$$



Asynchronous iterative methods

“Possibly the kind of methods which will allow the next generation of parallel machines to attain the expected potential.” *[Frommer and Szyld, 2000]*

Parallel processing


◆ Speedup limit *[Amdahl, 1967]*

$t(p)$: processing time using p processors

α : serial proportion of the processing (data management)

⇒ Theoretical speedup:

$$s(p, \alpha) = \frac{t(1)}{t(p)} \leq \frac{1}{\alpha + \frac{1-\alpha}{p}}$$



Minimize α : input/output, pre/post-processing, ..., and *inter-process communication*

Asynchronous iterative methods

“Possibly the kind of methods which will allow the next generation of parallel machines to attain the expected potential.” [Frommer and Szyld, 2000]

Parallel processing


♦ Speedup limit [Amdahl, 1967]

$t(p)$: processing time using p processors

α : serial proportion of the processing (data management)

⇒ Theoretical speedup:

$$s(p, \alpha) = \frac{t(1)}{t(p)} \leq \frac{1}{\alpha + \frac{1-\alpha}{p}}$$



Minimize α : input/output, pre/post-processing, ..., and *inter-process communication*


♦ But also: **load balancing** and *fault-tolerance*

Parallel processing

- ◆ Speedup limit [*Amdahl, 1967*]
- ◆ But also: load balancing and fault-tolerance
- ◆ Numerical simulation

Partial differential equations

$$\delta(u(s, t), s, t) = 0, \quad t \in \mathbb{R}^+, \quad s \in \Omega \subset \mathbb{R}^3$$



Parallel processing



- ◆ Speedup limit [*Amdahl, 1967*]
- ◆ But also: load balancing and fault-tolerance
- ◆ Numerical simulation

Partial differential equations

$$\delta(u(s, t), s, t) = 0, \quad t \in \mathbb{R}^+, \quad s \in \Omega \subset \mathbb{R}^3$$

Time discretization

$$\alpha(u(s, t_{n+1})) = \beta(u(s, t_n))$$



Parallel processing

- ◆ Speedup limit [*Amdahl, 1967*]
- ◆ But also: load balancing and fault-tolerance
- ◆ Numerical simulation

Partial differential equations



$$\delta(u(s, t), s, t) = 0, \quad t \in \mathbb{R}^+, \quad s \in \Omega \subset \mathbb{R}^3$$

Time discretization

$$\alpha(u(s, t_{n+1})) = \beta(u(s, t_n))$$

Space discretization

$$AU_{n+1} = B_n, \quad U_{n+1} \in \mathbb{C}^m$$



Parallel processing

- ◆ Speedup limit [*Amdahl, 1967*]
- ◆ But also: load balancing and fault-tolerance
- ◆ Numerical simulation

Partial differential equations

$$\delta(u(s, t), s, t) = 0, \quad t \in \mathbb{R}^+, \quad s \in \Omega \subset \mathbb{R}^3$$

Sparse system of equations



$$Ax = b, \quad x \in \mathbb{C}^m$$

Time discretization

$$\alpha(u(s, t_{n+1})) = \beta(u(s, t_n))$$

Space discretization

$$AU_{n+1} = B_n, \quad U_{n+1} \in \mathbb{C}^m$$



Parallel processing

- ◆ Speedup limit [*Amdahl, 1967*]
- ◆ But also: load balancing and fault-tolerance
- ◆ Numerical simulation

Partial differential equations

$$\delta(u(s, t), s, t) = 0, \quad t \in \mathbb{R}^+, \quad s \in \Omega \subset \mathbb{R}^3$$

Time discretization

$$\alpha(u(s, t_{n+1})) = \beta(u(s, t_n))$$

Space discretization



$$AU_{n+1} = B_n, \quad U_{n+1} \in \mathbb{C}^m$$

Sparse system of equations

$$Ax = b, \quad x \in \mathbb{C}^m$$

Iterative methods

$$x^{k+1} = f(x^k)$$



Parallel processing

- ◆ Speedup limit [*Amdahl, 1967*]
- ◆ But also: load balancing and fault-tolerance
- ◆ Numerical simulation

Partial differential equations

$$\delta(u(s, t), s, t) = 0, \quad t \in \mathbb{R}^+, \quad s \in \Omega \subset \mathbb{R}^3$$

Time discretization

$$\alpha(u(s, t_{n+1})) = \beta(u(s, t_n))$$

Space discretization

$$AU_{n+1} = B_n, \quad U_{n+1} \in \mathbb{C}^m$$

Sparse system of equations



$$Ax = b, \quad x \in \mathbb{C}^m$$

Iterative methods

$$x^{k+1} = f(x^k)$$

$$x_i^{k+1} = f_i(x^k), \quad \forall i \in \{1, \dots, p\}$$

$$x := \begin{bmatrix} x_1 \\ \vdots \\ x_p \end{bmatrix}, \quad p \leq m$$





Parallel computing

Parallel computing

- ◆ Speedup limit [*Amdahl, 1967*]
- ◆ But also: load balancing and fault-tolerance
- ◆ Numerical simulation

$$\delta(u(s, t), s, t) = 0, \quad t \in [0, T], \quad s \in \Omega$$

- ◆ Domain decomposition methods



Parallel computing




- ◆ Speedup limit [*Amdahl, 1967*]
- ◆ But also: load balancing and fault-tolerance
- ◆ Numerical simulation

$$\delta(u(s, t), s, t) = 0, \quad t \in [0, T], \quad s \in \Omega$$

- ◆ Domain decomposition methods

Different subdomains

$$\Omega^{(1)}, \dots, \Omega^{(p)}$$



Parallel computing

- ◆ Speedup limit [*Amdahl, 1967*]
- ◆ But also: load balancing and fault-tolerance
- ◆ Numerical simulation

$$\delta(u(s, t), s, t) = 0, \quad t \in [0, T], \quad s \in \Omega$$



- ◆ Domain decomposition methods

Different subdomains

$$\Omega^{(1)}, \dots, \Omega^{(p)}$$

Parallel solutions

$$u^{(1)}(s, t_{n+1}), \dots, u^{(p)}(s, t_{n+1})$$



Parallel computing

- ◆ Speedup limit [*Amdahl, 1967*]
- ◆ But also: load balancing and fault-tolerance
- ◆ Numerical simulation

$$\delta(u(s, t), s, t) = 0, \quad t \in [0, T], \quad s \in \Omega$$

- ◆ Domain decomposition methods

Different subdomains

$$\Omega^{(1)}, \dots, \Omega^{(p)}$$



Parallel solutions

$$u^{(1)}(s, t_{n+1}), \dots, u^{(p)}(s, t_{n+1})$$

Consistency across interfaces Γ_j^i ,

$$i, j \in \{1, \dots, p\}$$

$$u^{(i)}(s_{\Gamma_j^i}, t_{n+1}) = u^{(j)}(s_{\Gamma_j^i}, t_{n+1})$$



Parallel computing

- ◆ Speedup limit [Amdahl, 1967]
- ◆ But also: load balancing and fault-tolerance
- ◆ Numerical simulation

$$\delta(u(s, t), s, t) = 0, \quad t \in [0, T], \quad s \in \Omega$$

- ◆ Domain decomposition methods

Different subdomains

$$\Omega^{(1)}, \dots, \Omega^{(p)}$$

Parallel solutions



$$u^{(1)}(s, t_{n+1}), \dots, u^{(p)}(s, t_{n+1})$$

Consistency across interfaces Γ_j^i ,

$$i, j \in \{1, \dots, p\}$$

$$u^{(i)}(s_{\Gamma_j^i}, t_{n+1}) = u^{(j)}(s_{\Gamma_j^i}, t_{n+1})$$

- + parallel input/output
- + parallel pre/post-processing



Parallel computing

- ◆ Speedup limit [Amdahl, 1967]
- ◆ But also: load balancing and fault-tolerance
- ◆ Numerical simulation

$$\delta(u(s, t), s, t) = 0, \quad t \in [0, T], \quad s \in \Omega$$

- ◆ Domain decomposition methods

Different subdomains

$$\Omega^{(1)}, \dots, \Omega^{(p)}$$

Parallel solutions



$$u^{(1)}(s, t_{n+1}), \dots, u^{(p)}(s, t_{n+1})$$

Consistency across interfaces Γ_j^i ,

$$i, j \in \{1, \dots, p\}$$

$$u^{(i)}(s_{\Gamma_j^i}, t_{n+1}) = u^{(j)}(s_{\Gamma_j^i}, t_{n+1})$$

- + parallel input/output
- + parallel pre/post-processing
- + static load balancing



Parallel computing

- ◆ **Speedup limit** [Amdahl, 1967]
- ◆ But also: **load balancing** and fault-tolerance
- ◆ Numerical simulation

$$\delta(u(s, t), s, t) = 0, \quad t \in [0, T], \quad s \in \Omega$$

- ◆ Domain decomposition methods

Different subdomains

$$\Omega^{(1)}, \dots, \Omega^{(p)}$$

Parallel solutions

$$u^{(1)}(s, t_{n+1}), \dots, u^{(p)}(s, t_{n+1})$$

Consistency across interfaces Γ_j^i ,



$$i, j \in \{1, \dots, p\}$$

$$u^{(i)}(s_{\Gamma_j^i}, t_{n+1}) = u^{(j)}(s_{\Gamma_j^i}, t_{n+1})$$

- + parallel input/output
- + parallel pre/post-processing

- + static load balancing

- serial parallel iterations
⇒ blocking inter-process
synchronization



Parallel computing

- ◆ **Speedup limit** [Amdahl, 1967]
- ◆ But also: **load balancing** and **fault-tolerance**
- ◆ Numerical simulation

$$\delta(u(s, t), s, t) = 0, \quad t \in [0, T], \quad s \in \Omega$$

- ◆ Domain decomposition methods

Different subdomains

$$\Omega^{(1)}, \dots, \Omega^{(p)}$$

Parallel solutions

$$u^{(1)}(s, t_{n+1}), \dots, u^{(p)}(s, t_{n+1})$$

Consistency across interfaces Γ_j^i ,

$$i, j \in \{1, \dots, p\}$$



$$u^{(i)}(s_{\Gamma_j^i}, t_{n+1}) = u^{(j)}(s_{\Gamma_j^i}, t_{n+1})$$

- + parallel input/output
- + parallel pre/post-processing

+ static load balancing



- serial parallel iterations
 \Rightarrow blocking inter-process
 synchronization

\Rightarrow – non fault-tolerant





Parallel computing

- ◆ Speedup limit [Amdahl, 1967]
 - ◆ But also: load balancing and fault-tolerance
 - ◆ Numerical simulation
 - ◆ Domain decomposition methods
 - ◆ Asynchronous iterations [Chazan and Miranker, 1969]
- + static load balancing
 - serial parallel iterations
 - non fault-tolerant





Parallel computing

- ◆ Speedup limit [Amdahl, 1967]
 - ◆ But also: load balancing and fault-tolerance
 - ◆ Numerical simulation
 - ◆ Domain decomposition methods
 - ◆ Asynchronous iterations [Chazan and Miranker, 1969]
- + static load balancing
 - serial parallel iterations
 - non fault-tolerant
- + parallel serial iterations
⇒ no speedup limit



Parallel computing

- ◆ Speedup limit [Amdahl, 1967]
 - ◆ But also: load balancing and fault-tolerance
 - ◆ Numerical simulation
 - ◆ Domain decomposition methods
 - ◆ Asynchronous iterations [Chazan and Miranker, 1969]
- + parallel serial iterations
⇒ no speedup limit
 - + non-deterministic inter-process communication ⇒ fault-tolerance
- + static load balancing
 - serial parallel iterations
 - non fault-tolerant



Parallel computing

- ◆ Speedup limit [Amdahl, 1967]

- ◆ But also: load balancing and fault-tolerance

- ◆ Numerical simulation

- ◆ Domain decomposition methods

- ◆ Asynchronous iterations
[Chazan and Miranker, 1969]



- + parallel serial iterations

- ⇒ no speedup limit

- + non-deterministic inter-process
communication ⇒ fault-tolerance



- + dynamic adaptation to unbalanced load

- + static load balancing
- serial parallel iterations
- non fault-tolerant



Parallel computing

- ◆ Speedup limit [Amdahl, 1967]
- ◆ But also: load balancing and fault-tolerance
- ◆ Numerical simulation
- ◆ Domain decomposition methods
- ◆ Asynchronous iterations [Chazan and Miranker, 1969]
 - + static load balancing
 - serial parallel iterations
 - non fault-tolerant
- + parallel serial iterations
⇒ no speedup limit
- + non-deterministic inter-process communication ⇒ fault-tolerance
- + dynamic adaptation to unbalanced load
- low convergence rate



Parallel computing

- ◆ Speedup limit [Amdahl, 1967]
- ◆ But also: load balancing and fault-tolerance
- ◆ Numerical simulation
- ◆ Domain decomposition methods
- ◆ Asynchronous iterations [Chazan and Miranker, 1969]

+ parallel serial iterations
⇒ no speedup limit



+ non-deterministic inter-process
communication ⇒ fault-tolerance

+ dynamic adaptation to unbalanced load

– low convergence rate

- + static load balancing
- serial parallel iterations
- non fault-tolerant

Eventual consistency across
interfaces?
(convergence conditions)



Parallel computing

- ◆ Speedup limit [Amdahl, 1967]
- ◆ But also: load balancing and fault-tolerance
- ◆ Numerical simulation
- ◆ Domain decomposition methods

- ◆ Asynchronous iterations
[Chazan and Miranker, 1969]

+ parallel serial iterations
⇒ no speedup limit

+ non-deterministic inter-process
communication ⇒ fault-tolerance



+ dynamic adaptation to unbalanced load

– low convergence rate

- + static load balancing
- serial parallel iterations
- non fault-tolerant

Eventual consistency across
interfaces?
(convergence conditions)

Consistency reached?
(convergence detection)



01 **ASYNCHRONOUS ITERATIVE METHODS**

02 **SPACE DOMAIN DECOMPOSITION**

03 **TIME DOMAIN DECOMPOSITION**

04 **ASYNCHRONOUS CONVERGENCE DETECTION**

05 **CONCLUSION**

01 ASYNCHRONOUS ITERATIVE METHODS

1 - ASYNCHRONOUS ITERATIVE METHODS

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

1 - ASYNCHRONOUS ITERATIVE METHODS

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Splitting

$$A = M - N$$

Mapping

$$f(x) := M^{-1}Nx + M^{-1}b$$

Fixed-point problem

$$Ax = b \iff x = f(x)$$

1 - ASYNCHRONOUS ITERATIVE METHODS

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Splitting

$$A = M - N$$

Mapping

$$f(x) := M^{-1}Nx + M^{-1}b$$

Fixed-point problem

$$Ax = b \iff x = f(x)$$

Iterative methods \Rightarrow sequence $\{x^k\}_{k \in \mathbb{N}}$:

$$x^{k+1} = f(x^k)$$

Convergence from any initial vector x^0

$$\lim_{k \rightarrow \infty} x^k = x^*, \quad f(x^*) = x^*$$

1 - ASYNCHRONOUS ITERATIVE METHODS

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Splitting

$$A = M - N$$

Mapping

$$f(x) := M^{-1}Nx + M^{-1}b$$

Fixed-point problem

$$Ax = b \iff x = f(x)$$

Iterative methods \Rightarrow sequence $\{x^k\}_{k \in \mathbb{N}}$:

$$x^{k+1} = f(x^k)$$

Convergence from any initial vector x^0

$$\lim_{k \rightarrow \infty} x^k = x^*, \quad f(x^*) = x^*$$

Convergence condition (sufficient and necessary)

$$\rho(M^{-1}N) < 1$$

1 - ASYNCHRONOUS ITERATIVE METHODS

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Splitting

$$A = M - N$$

Mapping

$$f(x) := M^{-1}Nx + M^{-1}b$$

Fixed-point problem

$$Ax = b \iff x = f(x)$$

Iterative methods \Rightarrow sequence $\{x^k\}_{k \in \mathbb{N}}$:

$$x^{k+1} = f(x^k)$$

Convergence from any initial vector x^0

$$\lim_{k \rightarrow \infty} x^k = x^*, \quad f(x^*) = x^*$$

Convergence condition (sufficient and necessary)

$$\rho(M^{-1}N) < 1$$

Parallel computing with p processors, $p \leq n$

$$f(x) = \begin{bmatrix} f_1(x) & \cdots & f_p(x) \end{bmatrix}^T$$

$$x = \begin{bmatrix} x_1 & \cdots & x_p \end{bmatrix}^T$$

1 - ASYNCHRONOUS ITERATIVE METHODS

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Splitting

$$A = M - N$$

Mapping

$$f(x) := M^{-1}Nx + M^{-1}b$$

Fixed-point problem

$$Ax = b \iff x = f(x)$$

Iterative methods \Rightarrow sequence $\{x^k\}_{k \in \mathbb{N}}$:

$$x^{k+1} = f(x^k)$$

Convergence from any initial vector x^0

$$\lim_{k \rightarrow \infty} x^k = x^*, \quad f(x^*) = x^*$$

Convergence condition (sufficient and necessary)

$$\rho(M^{-1}N) < 1$$

Parallel computing with p processors, $p \leq n$

$$f(x) = \begin{bmatrix} f_1(x) & \cdots & f_p(x) \end{bmatrix}^T$$

$$x = \begin{bmatrix} x_1 & \cdots & x_p \end{bmatrix}^T$$

$$x_i^{k+1} = f_i(x_1^k, \dots, x_p^k), \quad \forall i \in \{1, \dots, p\}$$

1 - ASYNCHRONOUS ITERATIVE METHODS

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Splitting

$$A = M - N$$

Mapping

$$f(x) := M^{-1}Nx + M^{-1}b$$

Fixed-point problem

$$Ax = b \iff x = f(x)$$

Iterative methods \Rightarrow sequence $\{x^k\}_{k \in \mathbb{N}}$:

$$x^{k+1} = f(x^k)$$

Convergence from any initial vector x^0

$$\lim_{k \rightarrow \infty} x^k = x^*, \quad f(x^*) = x^*$$

Convergence condition (sufficient and necessary)


$$\rho(M^{-1}N) < 1$$

Parallel computing with p processors, $p \leq n$

$$f(x) = \begin{bmatrix} f_1(x) & \cdots & f_p(x) \end{bmatrix}^T$$

$$x = \begin{bmatrix} x_1 & \cdots & x_p \end{bmatrix}^T$$

$$x_i^{k+1} = f_i(x_1^k, \dots, x_p^k), \quad \forall i \in \{1, \dots, p\}$$



1 - ASYNCHRONOUS ITERATIVE METHODS

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Splitting

$$A = M - N$$

Mapping

$$f(x) := M^{-1}Nx + M^{-1}b$$

Fixed-point problem

$$Ax = b \iff x = f(x)$$

Iterative methods \Rightarrow sequence $\{x^k\}_{k \in \mathbb{N}}$:

$$x^{k+1} = f(x^k)$$

Convergence from any initial vector x^0


$$\lim_{k \rightarrow \infty} x^k = x^*, \quad f(x^*) = x^*$$

Convergence condition (sufficient and necessary)

$$\rho(M^{-1}N) < 1$$

Parallel computing with p processors, $p \leq n$

$$\begin{aligned} f(x) &= \begin{bmatrix} f_1(x) & \cdots & f_p(x) \end{bmatrix}^T \\ x &= \begin{bmatrix} x_1 & \cdots & x_p \end{bmatrix}^T \\ x_i^{k+1} &= f_i(x_1^k, \dots, x_p^k), \quad \forall i \in \{1, \dots, p\} \end{aligned}$$



$$x_1^1 := f_1(x_1^0, x_2^0) \quad x_2^1 := f_2(x_1^0, x_2^0)$$

1 - ASYNCHRONOUS ITERATIVE METHODS

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Splitting

$$A = M - N$$

Mapping

$$f(x) := M^{-1}Nx + M^{-1}b$$

Fixed-point problem

$$Ax = b \iff x = f(x)$$

Iterative methods \Rightarrow sequence $\{x^k\}_{k \in \mathbb{N}}$:

$$x^{k+1} = f(x^k)$$

Convergence from any initial vector x^0

$$\lim_{k \rightarrow \infty} x^k = x^*, \quad f(x^*) = x^*$$

Convergence condition (sufficient and necessary)

$$\rho(M^{-1}N) < 1$$


Parallel computing with p processors, $p \leq n$

$$f(x) = \begin{bmatrix} f_1(x) & \cdots & f_p(x) \end{bmatrix}^T$$

$$x = \begin{bmatrix} x_1 & \cdots & x_p \end{bmatrix}^T$$

$$x_i^{k+1} = f_i(x_1^k, \dots, x_p^k), \quad \forall i \in \{1, \dots, p\}$$

speedup limit



$$x_1^1 := f_1(x_1^0, x_2^0) \quad x_2^1 := f_2(x_1^0, x_2^0)$$

wait

wait

1 - ASYNCHRONOUS ITERATIVE METHODS

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Splitting

$$A = M - N$$

Mapping

$$f(x) := M^{-1}Nx + M^{-1}b$$

Fixed-point problem

$$Ax = b \iff x = f(x)$$

Iterative methods \Rightarrow sequence $\{x^k\}_{k \in \mathbb{N}}$:

$$x^{k+1} = f(x^k)$$

Convergence from any initial vector x^0

$$\lim_{k \rightarrow \infty} x^k = x^*, \quad f(x^*) = x^*$$

Convergence condition (sufficient and necessary)


$$\rho(M^{-1}N) < 1$$

Parallel computing with p processors, $p \leq n$

$$f(x) = \begin{bmatrix} f_1(x) & \cdots & f_p(x) \end{bmatrix}^T$$

$$x = \begin{bmatrix} x_1 & \cdots & x_p \end{bmatrix}^T$$

$$x_i^{k+1} = f_i(x_1^k, \dots, x_p^k), \quad \forall i \in \{1, \dots, p\}$$



$$x_1^1 := f_1(x_1^0, x_2^0) \quad x_2^1 := f_2(x_1^0, x_2^0)$$

wait

wait

$$x_1^2 := f_1(x_1^1, x_2^1) \quad x_2^2 := f_2(x_1^1, x_2^1)$$

1 - ASYNCHRONOUS ITERATIVE METHODS

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Splitting

$$A = M - N$$

Mapping

$$f(x) := M^{-1}Nx + M^{-1}b$$

Fixed-point problem

$$Ax = b \iff x = f(x)$$

Iterative methods \Rightarrow sequence $\{x^k\}_{k \in \mathbb{N}}$:

$$x^{k+1} = f(x^k)$$

Convergence from any initial vector x^0

$$\lim_{k \rightarrow \infty} x^k = x^*, \quad f(x^*) = x^*$$

Convergence condition (sufficient and necessary)


$$\rho(M^{-1}N) < 1$$

Parallel computing with p processors, $p \leq n$

$$f(x) = \begin{bmatrix} f_1(x) & \cdots & f_p(x) \end{bmatrix}^T$$

$$x = \begin{bmatrix} x_1 & \cdots & x_p \end{bmatrix}^T$$

$$x_i^{k+1} = f_i(x_1^k, \dots, x_p^k), \quad \forall i \in \{1, \dots, p\}$$



$$x_1^1 := f_1(x_1^0, x_2^0) \quad x_2^1 := f_2(x_1^0, x_2^0)$$

wait

wait

$$x_1^2 := f_1(x_1^1, x_2^1) \quad x_2^2 := f_2(x_1^1, x_2^1)$$

$$x_1^3 := f_1(x_1^2, x_2^2)$$

wait

1 - ASYNCHRONOUS ITERATIVE METHODS

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Splitting

$$A = M - N$$

Mapping

$$f(x) := M^{-1}Nx + M^{-1}b$$

Fixed-point problem

$$Ax = b \iff x = f(x)$$

Iterative methods \Rightarrow sequence $\{x^k\}_{k \in \mathbb{N}}$:

$$x^{k+1} = f(x^k)$$

Convergence from any initial vector x^0

$$\lim_{k \rightarrow \infty} x^k = x^*, \quad f(x^*) = x^*$$

Convergence condition (sufficient and necessary)

$$\rho(M^{-1}N) < 1$$


Parallel computing with p processors, $p \leq n$

$$f(x) = \begin{bmatrix} f_1(x) & \cdots & f_p(x) \end{bmatrix}^T$$

$$x = \begin{bmatrix} x_1 & \cdots & x_p \end{bmatrix}^T$$

$$x_i^{k+1} = f_i(x_1^k, \dots, x_p^k), \quad \forall i \in \{1, \dots, p\}$$

speedup limit



$$x_1^1 := f_1(x_1^0, x_2^0) \quad x_2^1 := f_2(x_1^0, x_2^0)$$

wait

wait

$$x_1^2 := f_1(x_1^1, x_2^1) \quad x_2^2 := f_2(x_1^1, x_2^1)$$

$$x_1^3 := f_1(x_1^2, x_2^2)$$

wait

wait

$$x_2^3 := f_2(x_1^2, x_2^2)$$

1 - ASYNCHRONOUS ITERATIVE METHODS

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Splitting

$$A = M - N$$

Mapping

$$f(x) := M^{-1}Nx + M^{-1}b$$

Fixed-point problem

$$Ax = b \iff x = f(x)$$

Iterative methods \Rightarrow sequence $\{x^k\}_{k \in \mathbb{N}}$:

$$x^{k+1} = f(x^k)$$

Convergence from any initial vector x^0

$$\lim_{k \rightarrow \infty} x^k = x^*, \quad f(x^*) = x^*$$

Convergence condition (sufficient and necessary)


$$\rho(M^{-1}N) < 1$$

Parallel computing with p processors, $p \leq n$

$$f(x) = \begin{bmatrix} f_1(x) & \cdots & f_p(x) \end{bmatrix}^T$$

$$x = \begin{bmatrix} x_1 & \cdots & x_p \end{bmatrix}^T$$

$$x_i^{k+1} = f_i(x_1^k, \dots, x_p^k), \quad \forall i \in \{1, \dots, p\}$$



$$x_1^1 := f_1(x_1^0, x_2^0) \quad x_2^1 := f_2(x_1^0, x_2^0)$$

wait

wait

$$x_1^2 := f_1(x_1^1, x_2^1) \quad x_2^2 := f_2(x_1^1, x_2^1)$$

$$x_1^3 := f_1(x_1^2, x_2^2)$$

wait

wait


$$x_2^3 := f_2(x_1^2, x_2^2)$$

wait

$$x_2^4 := f_2(x_1^3, x_2^3)$$

1 - ASYNCHRONOUS ITERATIVE METHODS


Asynchronous iterations



Synchronous iterations

$$x_i^{k+1} = f_i(x_1^k, \dots, x_p^k), \quad \forall i \in \{1, \dots, p\}$$

delay \Rightarrow speedup limit



$$x_1^1 := f_1(x_1^0, x_2^0) \quad x_2^1 := f_2(x_1^0, x_2^0)$$

wait

wait

$$x_1^2 := f_1(x_1^1, x_2^1) \quad x_2^2 := f_2(x_1^1, x_2^1)$$

$$x_1^3 := f_1(x_1^2, x_2^2)$$

wait

wait


$$x_2^3 := f_2(x_1^2, x_2^2)$$

wait

$$x_2^4 := f_2(x_1^3, x_2^3)$$

1 - ASYNCHRONOUS ITERATIVE METHODS

Asynchronous iterations




$$x_1^1 := f_1(x_1^0, x_2^0) \quad x_2^1 := f_2(x_1^0, x_2^0)$$

Synchronous iterations

$$x_i^{k+1} = f_i(x_1^k, \dots, x_p^k), \quad \forall i \in \{1, \dots, p\}$$

delay \Rightarrow speedup limit



$$x_1^1 := f_1(x_1^0, x_2^0) \quad x_2^1 := f_2(x_1^0, x_2^0)$$

wait

wait

$$x_1^2 := f_1(x_1^1, x_2^1) \quad x_2^2 := f_2(x_1^1, x_2^1)$$

$$x_1^3 := f_1(x_1^2, x_2^2)$$

wait

wait

$$x_2^3 := f_2(x_1^2, x_2^2)$$


wait

$$x_2^4 := f_2(x_1^3, x_2^3)$$

1 - ASYNCHRONOUS ITERATIVE METHODS

Asynchronous iterations

delay \Rightarrow low convergence rate




$$x_1^1 := f_1(x_1^0, x_2^0) \quad x_2^1 := f_2(x_1^0, x_2^0)$$

$$x_1^2 := f_1(x_1^1, x_2^0) \quad x_2^2 := f_2(x_1^0, x_2^1)$$

Synchronous iterations

$$x_i^{k+1} = f_i(x_1^k, \dots, x_p^k), \quad \forall i \in \{1, \dots, p\}$$

delay \Rightarrow speedup limit



$$x_1^1 := f_1(x_1^0, x_2^0) \quad x_2^1 := f_2(x_1^0, x_2^0)$$

wait

wait

$$x_1^2 := f_1(x_1^1, x_2^1) \quad x_2^2 := f_2(x_1^1, x_2^1)$$

$$x_1^3 := f_1(x_1^2, x_2^2)$$

wait

wait

$$x_2^3 := f_2(x_1^2, x_2^2)$$


wait

$$x_2^4 := f_2(x_1^3, x_2^3)$$

1 - ASYNCHRONOUS ITERATIVE METHODS

Asynchronous iterations

delay \Rightarrow low convergence rate



$$x_1^1 := f_1(x_1^0, x_2^0) \quad x_2^1 := f_2(x_1^0, x_2^0)$$


$$x_1^2 := f_1(x_1^1, x_2^0) \quad x_2^2 := f_2(x_1^0, x_2^1)$$

$$x_2^3 := f_2(x_1^1, x_2^2)$$

Synchronous iterations

$$x_i^{k+1} = f_i(x_1^k, \dots, x_p^k), \quad \forall i \in \{1, \dots, p\}$$

delay \Rightarrow speedup limit



$$x_1^1 := f_1(x_1^0, x_2^0) \quad x_2^1 := f_2(x_1^0, x_2^0)$$

wait

wait

$$x_1^2 := f_1(x_1^1, x_2^1) \quad x_2^2 := f_2(x_1^1, x_2^1)$$

$$x_1^3 := f_1(x_1^2, x_2^2)$$

wait

wait

$$x_2^3 := f_2(x_1^2, x_2^2)$$


wait

$$x_2^4 := f_2(x_1^3, x_2^3)$$

1 - ASYNCHRONOUS ITERATIVE METHODS

Asynchronous iterations

delay \Rightarrow low convergence rate



$$x_1^1 := f_1(x_1^0, x_2^0) \quad x_2^1 := f_2(x_1^0, x_2^0)$$

$$x_1^2 := f_1(x_1^1, x_2^0) \quad x_2^2 := f_2(x_1^0, x_2^1)$$


$$x_1^3 := x_1^2 \quad x_2^3 := f_2(x_1^1, x_2^2)$$

$$x_1^4 := f_1(x_1^3, x_2^2) \quad x_2^4 := f_2(x_1^2, x_2^3)$$

Synchronous iterations

$$x_i^{k+1} = f_i(x_1^k, \dots, x_p^k), \quad \forall i \in \{1, \dots, p\}$$

delay \Rightarrow speedup limit



$$x_1^1 := f_1(x_1^0, x_2^0) \quad x_2^1 := f_2(x_1^0, x_2^0)$$

wait

wait

$$x_1^2 := f_1(x_1^1, x_2^1) \quad x_2^2 := f_2(x_1^1, x_2^1)$$

$$x_1^3 := f_1(x_1^2, x_2^2)$$

wait

wait


$$x_2^3 := f_2(x_1^2, x_2^2)$$

wait

$$x_2^4 := f_2(x_1^3, x_2^3)$$

1 - ASYNCHRONOUS ITERATIVE METHODS

Asynchronous iterations

delay \Rightarrow low convergence rate

$$x_1^1 := f_1(x_1^0, x_2^0) \quad x_2^1 := f_2(x_1^0, x_2^0)$$

$$x_1^2 := f_1(x_1^1, x_2^0) \quad x_2^2 := f_2(x_1^0, x_2^1)$$


$$x_1^3 := x_1^2 \quad x_2^3 := f_2(x_1^1, x_2^2)$$

$$x_1^4 := f_1(x_1^3, x_2^2) \quad x_2^4 := f_2(x_1^2, x_2^3)$$

$$x_1^5 := f_1(x_1^4, x_2^3) \quad x_2^5 := f_2(x_1^2, x_2^4)$$

Synchronous iterations

$$x_i^{k+1} = f_i(x_1^k, \dots, x_p^k), \quad \forall i \in \{1, \dots, p\}$$

delay \Rightarrow speedup limit

$$x_1^1 := f_1(x_1^0, x_2^0) \quad x_2^1 := f_2(x_1^0, x_2^0)$$

wait

wait

$$x_1^2 := f_1(x_1^1, x_2^1) \quad x_2^2 := f_2(x_1^1, x_2^1)$$

$$x_1^3 := f_1(x_1^2, x_2^2)$$

wait

wait

$$x_2^3 := f_2(x_1^2, x_2^2)$$

wait

$$x_2^4 := f_2(x_1^3, x_2^3)$$


1 - ASYNCHRONOUS ITERATIVE METHODS

Asynchronous iterations

$$x_i^{k+1} = f_i(x_1^{\tau_1^i(k)}, \dots, x_p^{\tau_p^i(k)}), \quad \forall i \in P^k$$

$$x_i^{k+1} = x_i^k, \quad \forall i \notin P^k$$

delay \Rightarrow low convergence rate



$$x_1^1 := f_1(x_1^0, x_2^0) \quad x_2^1 := f_2(x_1^0, x_2^0)$$

$$x_1^2 := f_1(x_1^1, x_2^0) \quad x_2^2 := f_2(x_1^0, x_2^1)$$

$$x_1^3 := x_1^2 \quad x_2^3 := f_2(x_1^1, x_2^2)$$

$$x_1^4 := f_1(x_1^3, x_2^2) \quad x_2^4 := f_2(x_1^2, x_2^3)$$


$$x_1^5 := f_1(x_1^4, x_2^3) \quad x_2^5 := f_2(x_1^2, x_2^4)$$

$$P^k \subset \{1, \dots, p\}, \quad \tau_j^i(k) \leq k$$

Synchronous iterations

$$x_i^{k+1} = f_i(x_1^k, \dots, x_p^k), \quad \forall i \in \{1, \dots, p\}$$

delay \Rightarrow speedup limit



$$x_1^1 := f_1(x_1^0, x_2^0) \quad x_2^1 := f_2(x_1^0, x_2^0)$$

wait

wait

$$x_1^2 := f_1(x_1^1, x_2^1) \quad x_2^2 := f_2(x_1^1, x_2^1)$$

$$x_1^3 := f_1(x_1^2, x_2^2)$$

wait

wait

$$x_2^3 := f_2(x_1^2, x_2^2)$$

wait

$$x_2^4 := f_2(x_1^3, x_2^3)$$

1 - ASYNCHRONOUS ITERATIVE METHODS

♦ Linear problems

$$Ax = b \iff M^{-1}Nx + M^{-1}b = x$$

Asynchronous iterations

$$\begin{aligned} x_i^{k+1} &= f_i(x_1^{\tau_1^i(k)}, \dots, x_p^{\tau_p^i(k)}), & \forall i \in P^k \\ x_i^{k+1} &= x_i^k, & \forall i \notin P^k \end{aligned}$$

Synchronous iterations

$$x_i^{k+1} = f_i(x_1^k, \dots, x_p^k), \quad \forall i \in \{1, \dots, p\}$$

Convergence condition (necessary and sufficient)

$$\rho(M^{-1}N) < 1$$

1 - ASYNCHRONOUS ITERATIVE METHODS

♦ Linear problems

$$Ax = b \iff M^{-1}Nx + M^{-1}b = x$$

Asynchronous iterations

$$\begin{aligned} x_i^{k+1} &= f_i(x_1^{\tau_1^i(k)}, \dots, x_p^{\tau_p^i(k)}), & \forall i \in P^k \\ x_i^{k+1} &= x_i^k, & \forall i \notin P^k \end{aligned}$$

Convergence condition (necessary and sufficient)

[Chazan and Miranker, 1969]

$$\rho(|M^{-1}N|) < 1$$

Synchronous iterations

$$x_i^{k+1} = f_i(x_1^k, \dots, x_p^k), \quad \forall i \in \{1, \dots, p\}$$

Convergence condition (necessary and sufficient)

$$\rho(M^{-1}N) < 1$$

1 - ASYNCHRONOUS ITERATIVE METHODS

♦ Linear problems

$$Ax = b \iff M^{-1}Nx + M^{-1}b = x$$

Asynchronous iterations

$$\begin{aligned} x_i^{k+1} &= f_i(x_1^{\tau_1^i(k)}, \dots, x_p^{\tau_p^i(k)}), & \forall i \in P^k \\ x_i^{k+1} &= x_i^k, & \forall i \notin P^k \end{aligned}$$

Convergence condition (necessary and sufficient)

[Chazan and Miranker, 1969]

$$\rho(M^{-1}N) \leq \rho(|M^{-1}N|) < 1$$

Synchronous iterations

$$x_i^{k+1} = f_i(x_1^k, \dots, x_p^k), \quad \forall i \in \{1, \dots, p\}$$

Convergence condition (necessary and sufficient)

$$\rho(M^{-1}N) < 1$$

1 - ASYNCHRONOUS ITERATIVE METHODS

♦ Linear problems

$$Ax = b \iff M^{-1}Nx + M^{-1}b = x$$

Asynchronous iterations

$$\begin{aligned} x_i^{k+1} &= f_i(x_1^{\tau_1^i(k)}, \dots, x_p^{\tau_p^i(k)}), & \forall i \in P^k \\ x_i^{k+1} &= x_i^k, & \forall i \notin P^k \end{aligned}$$

Convergence condition (necessary and sufficient)

[Chazan and Miranker, 1969]

$$\rho(M^{-1}N) \leq \rho(|M^{-1}N|) < 1$$

Synchronous iterations

$$x_i^{k+1} = f_i(x_1^k, \dots, x_p^k), \quad \forall i \in \{1, \dots, p\}$$

Convergence condition (necessary and sufficient)

$$\rho(M^{-1}N) < 1$$

General fixed-point problems

$$f^{(k)}(x, x, \dots, x) = x, \quad \forall k \in \mathbb{N}, \quad f^{(k)} : E^m \mapsto E, \quad m \in \mathbb{N}^*$$

1 - ASYNCHRONOUS ITERATIVE METHODS

♦ Linear problems

$$Ax = b \iff M^{-1}Nx + M^{-1}b = x$$

[Chazan and Miranker, 1969] (necessary and sufficient): $\rho(|M^{-1}N|) < 1$

♦ General fixed-point problems

$$f^{(k)}(x, x, \dots, x) = x, \quad \forall k \in \mathbb{N}, \quad f^{(k)} : E^m \mapsto E, \quad m \in \mathbb{N}^*$$

$$m = 1, \quad f^{(k)} \equiv f, \quad \forall k$$

1 - ASYNCHRONOUS ITERATIVE METHODS

♦ Linear problems

$$Ax = b \iff M^{-1}Nx + M^{-1}b = x$$

[Chazan and Miranker, 1969] (necessary and sufficient): $\rho(|M^{-1}N|) < 1$

♦ General fixed-point problems

$$f^{(k)}(x, x, \dots, x) = x, \quad \forall k \in \mathbb{N}, \quad f^{(k)} : E^m \mapsto E, \quad m \in \mathbb{N}^*$$

$$m = 1, \quad f^{(k)} \equiv f, \quad \forall k$$

[Miellou, 1975] (sufficient)

$$|f(x) - f(y)| \leq T|x - y|$$

$$T \geq 0, \quad \rho(T) < 1, \quad |x| = (|x_1|, \dots, |x_p|)$$

1 - ASYNCHRONOUS ITERATIVE METHODS

♦ Linear problems

$$Ax = b \iff M^{-1}Nx + M^{-1}b = x$$

[Chazan and Miranker, 1969] (necessary and sufficient): $\rho(|M^{-1}N|) < 1$

♦ General fixed-point problems

$$f^{(k)}(x, x, \dots, x) = x, \quad \forall k \in \mathbb{N}, \quad f^{(k)} : E^m \mapsto E, \quad m \in \mathbb{N}^*$$

$$m = 1, \quad f^{(k)} \equiv f, \quad \forall k$$

[Miellou, 1975] (sufficient)

$$|f(x) - f(y)| \leq T|x - y|$$

$$T \geq 0, \quad \rho(T) < 1, \quad |x| = (|x_1|, \dots, |x_p|)$$

[El Tarazi, 1982] (sufficient)

$$\|f(x) - f(y)\|_{\infty}^w \leq \alpha \|x - y\|_{\infty}^w$$

$$w > 0, \quad \alpha < 1, \quad \|x\|_{\infty}^w = \max_i |x_i|/w_i$$

1 - ASYNCHRONOUS ITERATIVE METHODS

♦ Linear problems

$$Ax = b \iff M^{-1}Nx + M^{-1}b = x$$

[Chazan and Miranker, 1969] (necessary and sufficient): $\rho(|M^{-1}N|) < 1$

♦ General fixed-point problems

$$f^{(k)}(x, x, \dots, x) = x, \quad \forall k \in \mathbb{N}, \quad f^{(k)} : E^m \mapsto E, \quad m \in \mathbb{N}^*$$

$$m = 1, \quad f^{(k)} \equiv f, \quad \forall k$$

[Miellou, 1975] (sufficient)

$$|f(x) - f(y)| \leq T|x - y|$$

$$T \geq 0, \quad \rho(T) < 1, \quad |x| = (|x_1|, \dots, |x_p|)$$

[El Tarazi, 1982] (sufficient)

$$\|f(x) - f(y)\|_{\infty}^w \leq \alpha \|x - y\|_{\infty}^w$$

$$w > 0, \quad \alpha < 1, \quad \|x\|_{\infty}^w = \max_i |x_i|/w_i$$

[Bertsekas, 1983] (sufficient)

$$f(S^{(t)}) \subset S^{(t+1)} \subset S^{(t)}$$

$$S^{(t)} = S_1^{(t)} \times \dots \times S_p^{(t)}, \quad \lim_{t \rightarrow \infty} S^{(t)} = \{x^*\}$$

1 - ASYNCHRONOUS ITERATIVE METHODS

♦ Linear problems

$$Ax = b \iff M^{-1}Nx + M^{-1}b = x$$

[Chazan and Miranker, 1969] (necessary and sufficient): $\rho(|M^{-1}N|) < 1$

♦ General fixed-point problems

$$f^{(k)}(x, x, \dots, x) = x, \quad \forall k \in \mathbb{N}, \quad f^{(k)} : E^m \mapsto E, \quad m \in \mathbb{N}^*$$

$$m = 1, \quad f^{(k)} \equiv f, \quad \forall k$$

$$m = 1$$

[Miellou, 1975] (sufficient)

$$|f(x) - f(y)| \leq T|x - y|$$

$$T \geq 0, \quad \rho(T) < 1, \quad |x| = (|x_1|, \dots, |x_p|)$$

[El Tarazi, 1982] (sufficient)

$$\|f(x) - f(y)\|_\infty^w \leq \alpha \|x - y\|_\infty^w$$

$$w > 0, \quad \alpha < 1, \quad \|x\|_\infty^w = \max_i |x_i|/w_i$$

[Bertsekas, 1983] (sufficient)

$$f(S^{(t)}) \subset S^{(t+1)} \subset S^{(t)}$$

$$S^{(t)} = S_1^{(t)} \times \dots \times S_p^{(t)}, \quad \lim_{t \rightarrow \infty} S^{(t)} = \{x^*\}$$

[Frommer and Szyld, 1994] (sufficient)

$$\|f^{(k)}(x) - f^{(k)}(y)\|_\infty^w \leq \alpha \|x - y\|_\infty^w, \quad \forall k$$

$$w > 0, \quad \alpha < 1, \quad \|x\|_\infty^w = \max_i |x_i|/w_i$$

1 - ASYNCHRONOUS ITERATIVE METHODS

◆ Linear problems

$$Ax = b \iff M^{-1}Nx + M^{-1}b = x$$

[Chazan and Miranker, 1969] (necessary and sufficient): $\rho(|M^{-1}N|) < 1$

◆ General fixed-point problems

$$f^{(k)}(x, x, \dots, x) = x, \quad \forall k \in \mathbb{N}, \quad f^{(k)} : E^m \mapsto E, \quad m \in \mathbb{N}^*$$

$$m = 1, \quad f^{(k)} \equiv f, \quad \forall k$$

$$m = 1$$

[Miellou, 1975] (sufficient)

$$|f(x) - f(y)| \leq T|x - y|$$

$$T \geq 0, \quad \rho(T) < 1, \quad |x| = (|x_1|, \dots, |x_p|)$$

[El Tarazi, 1982] (sufficient)

$$\|f(x) - f(y)\|_\infty^w \leq \alpha \|x - y\|_\infty^w$$

$$w > 0, \quad \alpha < 1, \quad \|x\|_\infty^w = \max_i |x_i|/w_i$$

[Bertsekas, 1983] (sufficient)

$$f(S^{(t)}) \subset S^{(t+1)} \subset S^{(t)}$$

$$S^{(t)} = S_1^{(t)} \times \dots \times S_p^{(t)}, \quad \lim_{t \rightarrow \infty} S^{(t)} = \{x^*\}$$

[Frommer and Szyld, 1994] (sufficient)

$$\|f^{(k)}(x) - f^{(k)}(y)\|_\infty^w \leq \alpha \|x - y\|_\infty^w, \quad \forall k$$

$$w > 0, \quad \alpha < 1, \quad \|x\|_\infty^w = \max_i |x_i|/w_i$$

[Frommer and Szyld, 2000] (sufficient)

$$f^{(k)}(S^{(t)}) \subset S^{(t+1)} \subset S^{(t)}, \quad \forall k$$

$$S^{(t)} = S_1^{(t)} \times \dots \times S_p^{(t)}, \quad \lim_{t \rightarrow \infty} S^{(t)} = \{x^*\}$$

1 - ASYNCHRONOUS ITERATIVE METHODS

♦ Linear problems

$$Ax = b \iff M^{-1}Nx + M^{-1}b = x$$

[Chazan and Miranker, 1969] (necessary and sufficient): $\rho(|M^{-1}N|) < 1$

♦ General fixed-point problems

$$f^{(k)}(x, x, \dots, x) = x, \quad \forall k \in \mathbb{N}, \quad f^{(k)} : E^m \mapsto E, \quad m \in \mathbb{N}^*$$

$$m = 1, \quad f^{(k)} \equiv f, \quad \forall k$$

$$m \geq 1, \quad f^{(k)} \equiv f, \quad \forall k$$

[Miellou, 1975] (sufficient): $|\cdot|$ -contraction

[El Tarazi, 1982] (sufficient): $\|\cdot\|_\infty^w$ -contraction

[Bertsekas, 1983] (sufficient): $\{S^{(t)}\}$ -contraction

$$m = 1$$

[Frommer & Szyld, 1994] (sufficient): $\|\cdot\|_\infty^w$ -contraction, $\forall k$

[Frommer & Szyld, 2000] (sufficient): $\{S^{(t)}\}$ -contraction, $\forall k$

1 - ASYNCHRONOUS ITERATIVE METHODS

♦ Linear problems

$$Ax = b \iff M^{-1}Nx + M^{-1}b = x$$

[Chazan and Miranker, 1969] (necessary and sufficient): $\rho(|M^{-1}N|) < 1$

♦ General fixed-point problems

$$f^{(k)}(x, x, \dots, x) = x, \quad \forall k \in \mathbb{N}, \quad f^{(k)} : E^m \mapsto E, \quad m \in \mathbb{N}^*$$

$$m = 1, \quad f^{(k)} \equiv f, \quad \forall k$$

[Miellou, 1975] (sufficient): $|\cdot|$ -contraction

[El Tarazi, 1982] (sufficient): $\|\cdot\|_\infty^w$ -contraction

[Bertsekas, 1983] (sufficient): $\{S^{(t)}\}$ -contraction

$$m = 1$$

[Frommer & Szyld, 1994] (sufficient): $\|\cdot\|_\infty^w$ -contraction, $\forall k$

[Frommer & Szyld, 2000] (sufficient): $\{S^{(t)}\}$ -contraction, $\forall k$

$$m \geq 1, \quad f^{(k)} \equiv f, \quad \forall k$$

$$X := (x^{(1)}, \dots, x^{(m)}), \quad Y := (y^{(1)}, \dots, y^{(m)})$$

[Baudet, 1978] (sufficient)

$$|f(X) - f(Y)| \leq T \max\{|x^{(1)} - y^{(1)}|, \dots, |x^{(m)} - y^{(m)}|\}$$

$$T \geq 0, \quad \rho(T) < 1, \quad (\max\{|x|, |y|\})_i = \max\{|x_i|, |y_i|\}$$

1 - ASYNCHRONOUS ITERATIVE METHODS

◆ Linear problems

$$Ax = b \iff M^{-1}Nx + M^{-1}b = x$$

[Chazan and Miranker, 1969] (necessary and sufficient): $\rho(|M^{-1}N|) < 1$

◆ General fixed-point problems

$$f^{(k)}(x, x, \dots, x) = x, \quad \forall k \in \mathbb{N}, \quad f^{(k)} : E^m \mapsto E, \quad m \in \mathbb{N}^*$$

$$m = 1, \quad f^{(k)} \equiv f, \quad \forall k$$

[Miellou, 1975] (sufficient): $|\cdot|$ -contraction

[El Tarazi, 1982] (sufficient): $\|\cdot\|_\infty^w$ -contraction

[Bertsekas, 1983] (sufficient): $\{S^{(t)}\}$ -contraction

$$m = 1$$

[Frommer & Szyld, 1994] (sufficient): $\|\cdot\|_\infty^w$ -contraction, $\forall k$

[Frommer & Szyld, 2000] (sufficient): $\{S^{(t)}\}$ -contraction, $\forall k$

$$m \geq 1, \quad f^{(k)} \equiv f, \quad \forall k$$

$$X := (x^{(1)}, \dots, x^{(m)}), \quad Y := (y^{(1)}, \dots, y^{(m)})$$

[Baudet, 1978] (sufficient)

$$|f(X) - f(Y)| \leq T \max\{|x^{(1)} - y^{(1)}|, \dots, |x^{(m)} - y^{(m)}|\}$$

$$T \geq 0, \quad \rho(T) < 1, \quad (\max\{|x|, |y|\})_i = \max\{|x_i|, |y_i|\}$$

[El Tarazi, 1982] (sufficient)

$$\|f(X) - x^*\|_\infty^w \leq \alpha \max\{\|x^{(l)} - x^*\|_\infty^w\}_{1 \leq l \leq m}$$

$$w > 0, \quad \alpha < 1, \quad \|x\|_\infty^w = \max_i |x_i|/w_i$$

1 - ASYNCHRONOUS ITERATIVE METHODS

◆ Linear problems

$$Ax = b \iff M^{-1}Nx + M^{-1}b = x$$

[Chazan and Miranker, 1969] (necessary and sufficient): $\rho(|M^{-1}N|) < 1$

◆ General fixed-point problems

$$f^{(k)}(x, x, \dots, x) = x, \quad \forall k \in \mathbb{N}, \quad f^{(k)} : E^m \mapsto E, \quad m \in \mathbb{N}^*$$

$$m = 1, \quad f^{(k)} \equiv f, \quad \forall k$$

[Miellou, 1975] (sufficient): $|\cdot|$ -contraction

[El Tarazi, 1982] (sufficient): $\|\cdot\|_\infty^w$ -contraction

[Bertsekas, 1983] (sufficient): $\{S^{(t)}\}$ -contraction

$$m = 1$$

[Frommer & Szyld, 1994] (sufficient): $\|\cdot\|_\infty^w$ -contraction, $\forall k$

[Frommer & Szyld, 2000] (sufficient): $\{S^{(t)}\}$ -contraction, $\forall k$

$$m \geq 1, \quad f^{(k)} \equiv f, \quad \forall k$$

$$X := (x^{(1)}, \dots, x^{(m)}), \quad Y := (y^{(1)}, \dots, y^{(m)})$$

[Baudet, 1978] (sufficient): $|\cdot|$ -contraction

[El Tarazi, 1982] (sufficient)

$$\|f(X) - x^*\|_\infty^w \leq \alpha \max\{\|x^{(l)} - x^*\|_\infty^w\}_{1 \leq l \leq m}$$

$$w > 0, \quad \alpha < 1, \quad \|x\|_\infty^w = \max_i |x_i|/w_i$$

[Frommer & Szyld, 1998] (sufficient)

$$\|f(x, y) - x^*\|_\infty^w \leq \alpha \max\{\|x - x^*\|_\infty^w, \|y - x^*\|_\infty^w\}$$

$$w > 0, \quad \alpha < 1, \quad \|x\|_\infty^w = \max_i |x_i|/w_i$$

1 - ASYNCHRONOUS ITERATIVE METHODS

◆ Linear problems

$$Ax = b \iff M^{-1}Nx + M^{-1}b = x$$

[Chazan and Miranker, 1969] (necessary and sufficient): $\rho(|M^{-1}N|) < 1$

◆ General fixed-point problems

$$f^{(k)}(x, x, \dots, x) = x, \quad \forall k \in \mathbb{N}, \quad f^{(k)} : E^m \mapsto E, \quad m \in \mathbb{N}^*$$

$$m = 1, \quad f^{(k)} \equiv f, \quad \forall k$$

[Miellou, 1975] (sufficient): $|\cdot|$ -contraction

[El Tarazi, 1982] (sufficient): $\|\cdot\|_\infty^w$ -contraction

[Bertsekas, 1983] (sufficient): $\{S^{(t)}\}$ -contraction

$$m = 1$$

[Frommer & Szyld, 1994] (sufficient): $\|\cdot\|_\infty^w$ -contraction, $\forall k$

[Frommer & Szyld, 2000] (sufficient): $\{S^{(t)}\}$ -contraction, $\forall k$

$$m \geq 1, \quad f^{(k)} \equiv f, \quad \forall k$$

$$X := (x^{(1)}, \dots, x^{(m)}), \quad Y := (y^{(1)}, \dots, y^{(m)})$$

[Baudet, 1978] (sufficient): $|\cdot|$ -contraction

[El Tarazi, 1982] (sufficient)

$$\|f(X) - x^*\|_\infty^w \leq \alpha \max\{\|x^{(l)} - x^*\|_\infty^w\}_{1 \leq l \leq m}$$

$$w > 0, \quad \alpha < 1, \quad \|x\|_\infty^w = \max_i |x_i|/w_i$$

[Frommer & Szyld, 1998] (sufficient) $m = 2$

$$\|f(x, y) - x^*\|_\infty^w \leq \alpha \max\{\|x - x^*\|_\infty^w, \|y - x^*\|_\infty^w\}$$

$$w > 0, \quad \alpha < 1, \quad \|x\|_\infty^w = \max_i |x_i|/w_i$$

1 - ASYNCHRONOUS ITERATIVE METHODS

◆ Linear problems

$$Ax = b \iff M^{-1}Nx + M^{-1}b = x$$

[Chazan and Miranker, 1969] (necessary and sufficient): $\rho(|M^{-1}N|) < 1$

◆ General fixed-point problems

$$f^{(k)}(x, x, \dots, x) = x, \quad \forall k \in \mathbb{N}, \quad f^{(k)} : E^m \mapsto E, \quad m \in \mathbb{N}^*$$

$$m = 1, \quad f^{(k)} \equiv f, \quad \forall k$$

[Miellou, 1975] (sufficient): $|\cdot|$ -contraction

[El Tarazi, 1982] (sufficient): $\|\cdot\|_\infty^w$ -contraction

[Bertsekas, 1983] (sufficient): $\{S^{(t)}\}$ -contraction

$$m = 1$$

[Frommer & Szyld, 1994] (sufficient): $\|\cdot\|_\infty^w$ -contraction, $\forall k$

[Frommer & Szyld, 2000] (sufficient): $\{S^{(t)}\}$ -contraction, $\forall k$

$$m \geq 1, \quad f^{(k)} \equiv f, \quad \forall k$$

[Baudet, 1978] (sufficient): $|\cdot|$ -contraction

$$|f(X) - f(Y)| \leq T \max\{|x^{(1)} - y^{(1)}|, \dots, |x^{(m)} - y^{(m)}|\}$$

$$T \geq 0, \quad \rho(T) < 1, \quad (\max\{|x|, |y|\})_i = \max\{|x_i|, |y_i|\}$$

[El Tarazi, 1982] (sufficient): $\|\cdot\|_\infty^w$ -contraction

$$\|f(X) - x^*\|_\infty^w \leq \alpha \max\{\|x^{(l)} - x^*\|_\infty^w\}_{1 \leq l \leq m}$$

$$w > 0, \quad \alpha < 1, \quad \|x\|_\infty^w = \max_i |x_i|/w_i$$


[Frommer & Szyld, 1998] $m = 2$

02 SPACE DOMAIN DECOMPOSITION

2 - SPACE DOMAIN DECOMPOSITION

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$




2 - SPACE DOMAIN DECOMPOSITION

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Two subdomains

$$\begin{bmatrix} A_{1,1} & O & A_{1,\Gamma} \\ O & A_{2,2} & A_{2,\Gamma} \\ A_{\Gamma,1} & A_{\Gamma,2} & A_{\Gamma,\Gamma}^{(1)} + A_{\Gamma,\Gamma}^{(2)} \end{bmatrix} \begin{bmatrix} x_1 \\ x_2 \\ x_\Gamma \end{bmatrix} = \begin{bmatrix} b_1 \\ b_2 \\ b_\Gamma^{(1)} + b_\Gamma^{(2)} \end{bmatrix}$$



2 - SPACE DOMAIN DECOMPOSITION

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$


Two subdomains

$$\begin{bmatrix} A_{1,1} & O & A_{1,\Gamma} \\ O & A_{2,2} & A_{2,\Gamma} \\ A_{\Gamma,1} & A_{\Gamma,2} & A_{\Gamma,\Gamma}^{(1)} + A_{\Gamma,\Gamma}^{(2)} \end{bmatrix} \begin{bmatrix} x_1 \\ x_2 \\ x_\Gamma \end{bmatrix} = \begin{bmatrix} b_1 \\ b_2 \\ b_\Gamma^{(1)} + b_\Gamma^{(2)} \end{bmatrix}$$

$$A_{1,1}x_1 + A_{1,\Gamma}x_\Gamma = b_1$$

$$A_{2,2}x_2 + A_{2,\Gamma}x_\Gamma = b_2$$

$$A_{\Gamma,1}x_1 + A_{\Gamma,2}x_2 + (A_{\Gamma,\Gamma}^{(1)} + A_{\Gamma,\Gamma}^{(2)})x_\Gamma = b_\Gamma^{(1)} + b_\Gamma^{(2)}$$



2 - SPACE DOMAIN DECOMPOSITION

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Two subdomains

$$\begin{bmatrix} A_{1,1} & O & A_{1,\Gamma} \\ O & A_{2,2} & A_{2,\Gamma} \\ A_{\Gamma,1} & A_{\Gamma,2} & A_{\Gamma,\Gamma}^{(1)} + A_{\Gamma,\Gamma}^{(2)} \end{bmatrix} \begin{bmatrix} x_1 \\ x_2 \\ x_\Gamma \end{bmatrix} = \begin{bmatrix} b_1 \\ b_2 \\ b_\Gamma^{(1)} + b_\Gamma^{(2)} \end{bmatrix}$$


$$A_{1,1}x_1 + A_{1,\Gamma}x_\Gamma = b_1$$

$$A_{2,2}x_2 + A_{2,\Gamma}x_\Gamma = b_2$$

$$A_{\Gamma,1}x_1 + A_{\Gamma,2}x_2 + \left(A_{\Gamma,\Gamma}^{(1)} + A_{\Gamma,\Gamma}^{(2)} \right) x_\Gamma = b_\Gamma^{(1)} + b_\Gamma^{(2)}$$

$$x_2 = A_{2,2}^{-1} (b_2 - A_{2,\Gamma}x_\Gamma)$$

$$A_{\Gamma,1}x_1 + \left(A_{\Gamma,\Gamma}^{(1)} + A_{\Gamma,\Gamma}^{(2)} \right) x_\Gamma = b_\Gamma^{(1)} + b_\Gamma^{(2)} - A_{\Gamma,2}x_2$$



2 - SPACE DOMAIN DECOMPOSITION

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Two subdomains

$$\begin{bmatrix} A_{1,1} & O & A_{1,\Gamma} \\ O & A_{2,2} & A_{2,\Gamma} \\ A_{\Gamma,1} & A_{\Gamma,2} & A_{\Gamma,\Gamma}^{(1)} + A_{\Gamma,\Gamma}^{(2)} \end{bmatrix} \begin{bmatrix} x_1 \\ x_2 \\ x_\Gamma \end{bmatrix} = \begin{bmatrix} b_1 \\ b_2 \\ b_\Gamma^{(1)} + b_\Gamma^{(2)} \end{bmatrix}$$

$$A_{1,1}x_1 + A_{1,\Gamma}x_\Gamma = b_1$$


$$A_{2,2}x_2 + A_{2,\Gamma}x_\Gamma = b_2$$

$$A_{\Gamma,1}x_1 + A_{\Gamma,2}x_2 + \left(A_{\Gamma,\Gamma}^{(1)} + A_{\Gamma,\Gamma}^{(2)} \right) x_\Gamma = b_\Gamma^{(1)} + b_\Gamma^{(2)}$$

$$x_2 = A_{2,2}^{-1} (b_2 - A_{2,\Gamma}x_\Gamma)$$

$$A_{\Gamma,1}x_1 + \left(A_{\Gamma,\Gamma}^{(1)} + A_{\Gamma,\Gamma}^{(2)} \right) x_\Gamma = b_\Gamma^{(1)} + b_\Gamma^{(2)} - A_{\Gamma,2}x_2$$

$$\begin{bmatrix} A_{1,1} & A_{1,\Gamma} \\ A_{\Gamma,1} & A_{\Gamma,\Gamma}^{(1)} + A_{\Gamma,\Gamma}^{(2)} \end{bmatrix} \begin{bmatrix} x_1 \\ x_\Gamma \end{bmatrix} = \begin{bmatrix} b_1 \\ b_\Gamma^{(1)} + b_\Gamma^{(2)} - A_{\Gamma,2}x_2 \end{bmatrix}$$



2 - SPACE DOMAIN DECOMPOSITION


Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Two subdomains

$$\begin{bmatrix} A_{1,1} & A_{1,\Gamma} \\ A_{\Gamma,1} & A_{\Gamma,\Gamma}^{(1)} + A_{\Gamma,\Gamma}^{(2)} \end{bmatrix} \begin{bmatrix} x_1 \\ x_\Gamma \end{bmatrix} = \begin{bmatrix} b_1 \\ b_\Gamma^{(1)} + b_\Gamma^{(2)} - A_{\Gamma,2}x_2 \end{bmatrix}$$

$$\begin{bmatrix} A_{2,2} & A_{2,\Gamma} \\ A_{\Gamma,2} & A_{\Gamma,\Gamma}^{(1)} + A_{\Gamma,\Gamma}^{(2)} \end{bmatrix} \begin{bmatrix} x_2 \\ x_\Gamma \end{bmatrix} = \begin{bmatrix} b_2 \\ b_\Gamma^{(1)} + b_\Gamma^{(2)} - A_{\Gamma,1}x_1 \end{bmatrix}$$



2 - SPACE DOMAIN DECOMPOSITION


Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Two subdomains

$$\begin{bmatrix} A_{1,1} & A_{1,\Gamma} \\ A_{\Gamma,1} & A_{\Gamma,\Gamma}^{(1)} + A_{\Gamma,\Gamma}^{(2)} \end{bmatrix} \begin{bmatrix} x_1 \\ x_\Gamma \end{bmatrix} = \begin{bmatrix} b_1 \\ b_\Gamma^{(1)} + b_\Gamma^{(2)} - A_{\Gamma,2}x_2 \end{bmatrix}$$

$$\begin{bmatrix} A_{2,2} & A_{2,\Gamma} \\ A_{\Gamma,2} & A_{\Gamma,\Gamma}^{(1)} + A_{\Gamma,\Gamma}^{(2)} \end{bmatrix} \begin{bmatrix} x_2 \\ x_\Gamma \end{bmatrix} = \begin{bmatrix} b_2 \\ b_\Gamma^{(1)} + b_\Gamma^{(2)} - A_{\Gamma,1}x_1 \end{bmatrix}$$



2 - SPACE DOMAIN DECOMPOSITION

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Two subdomains




$$\begin{bmatrix} A_{1,1} & A_{1,\Gamma} \\ A_{\Gamma,1} & A_{\Gamma,\Gamma}^{(1)} + A_{\Gamma,\Gamma}^{(2)} \end{bmatrix} \begin{bmatrix} x_1 \\ x_\Gamma \end{bmatrix} = \begin{bmatrix} b_1 \\ b_\Gamma^{(1)} + b_\Gamma^{(2)} - A_{\Gamma,2}x_2 \end{bmatrix}$$

$$\begin{bmatrix} A_{2,2} & A_{2,\Gamma} \\ A_{\Gamma,2} & A_{\Gamma,\Gamma}^{(1)} + A_{\Gamma,\Gamma}^{(2)} \end{bmatrix} \begin{bmatrix} x_2 \\ x_\Gamma \end{bmatrix} = \begin{bmatrix} b_2 \\ b_\Gamma^{(1)} + b_\Gamma^{(2)} - A_{\Gamma,1}x_1 \end{bmatrix}$$

Parallel solutions

$$\begin{bmatrix} A_{1,1} & A_{1,\Gamma} \\ A_{\Gamma,1} & A_{\Gamma,\Gamma}^{(1)} + \Lambda_{\Gamma,\Gamma}^{(1)} \end{bmatrix} \begin{bmatrix} x_1 \\ x_\Gamma^{(1)} \end{bmatrix} = \begin{bmatrix} b_1 \\ b_\Gamma^{(1)} + \lambda_\Gamma^{(1)} \end{bmatrix}$$

$$\begin{bmatrix} A_{2,2} & A_{2,\Gamma} \\ A_{\Gamma,2} & A_{\Gamma,\Gamma}^{(2)} + \Lambda_{\Gamma,\Gamma}^{(2)} \end{bmatrix} \begin{bmatrix} x_2 \\ x_\Gamma^{(2)} \end{bmatrix} = \begin{bmatrix} b_2 \\ b_\Gamma^{(2)} + \lambda_\Gamma^{(2)} \end{bmatrix}$$



2 - SPACE DOMAIN DECOMPOSITION

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Two subdomains

$$\begin{bmatrix} A_{1,1} & A_{1,\Gamma} \\ A_{\Gamma,1} & A_{\Gamma,\Gamma}^{(1)} + A_{\Gamma,\Gamma}^{(2)} \end{bmatrix} \begin{bmatrix} x_1 \\ x_\Gamma \end{bmatrix} = \begin{bmatrix} b_1 \\ b_\Gamma^{(1)} + b_\Gamma^{(2)} - A_{\Gamma,2}x_2 \end{bmatrix}$$

$$\begin{bmatrix} A_{2,2} & A_{2,\Gamma} \\ A_{\Gamma,2} & A_{\Gamma,\Gamma}^{(1)} + A_{\Gamma,\Gamma}^{(2)} \end{bmatrix} \begin{bmatrix} x_2 \\ x_\Gamma \end{bmatrix} = \begin{bmatrix} b_2 \\ b_\Gamma^{(1)} + b_\Gamma^{(2)} - A_{\Gamma,1}x_1 \end{bmatrix}$$

Parallel solutions





$$\begin{bmatrix} A_{1,1} & A_{1,\Gamma} \\ A_{\Gamma,1} & A_{\Gamma,\Gamma}^{(1)} + \Lambda_{\Gamma,\Gamma}^{(1)} \end{bmatrix} \begin{bmatrix} x_1 \\ x_\Gamma^{(1)} \end{bmatrix} = \begin{bmatrix} b_1 \\ b_\Gamma^{(1)} + \lambda_\Gamma^{(1)} \end{bmatrix}$$

$$\begin{bmatrix} A_{2,2} & A_{2,\Gamma} \\ A_{\Gamma,2} & A_{\Gamma,\Gamma}^{(2)} + \Lambda_{\Gamma,\Gamma}^{(2)} \end{bmatrix} \begin{bmatrix} x_2 \\ x_\Gamma^{(2)} \end{bmatrix} = \begin{bmatrix} b_2 \\ b_\Gamma^{(2)} + \lambda_\Gamma^{(2)} \end{bmatrix}$$

Consistency across interface Γ

$$x_\Gamma^{(1)} = x_\Gamma^{(2)}$$

$$\lambda_\Gamma^{(1)} - \Lambda_{\Gamma,\Gamma}^{(1)} x_\Gamma^{(1)} = - \left(\lambda_\Gamma^{(2)} - \Lambda_{\Gamma,\Gamma}^{(2)} x_\Gamma^{(2)} \right)$$



2 - SPACE DOMAIN DECOMPOSITION

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Two subdomains

Parallel solutions




$$\begin{bmatrix} A_{1,1} & A_{1,\Gamma} \\ A_{\Gamma,1} & A_{\Gamma,\Gamma}^{(1)} + \Lambda_{\Gamma,\Gamma}^{(1)} \end{bmatrix} \begin{bmatrix} x_1 \\ x_{\Gamma}^{(1)} \end{bmatrix} = \begin{bmatrix} b_1 \\ b_{\Gamma}^{(1)} + \lambda_{\Gamma}^{(1)} \end{bmatrix}$$

$$\begin{bmatrix} A_{2,2} & A_{2,\Gamma} \\ A_{\Gamma,2} & A_{\Gamma,\Gamma}^{(2)} + \Lambda_{\Gamma,\Gamma}^{(2)} \end{bmatrix} \begin{bmatrix} x_2 \\ x_{\Gamma}^{(2)} \end{bmatrix} = \begin{bmatrix} b_2 \\ b_{\Gamma}^{(2)} + \lambda_{\Gamma}^{(2)} \end{bmatrix}$$

Consistency across interface Γ

$$x_{\Gamma}^{(1)} = x_{\Gamma}^{(2)}$$

$$\lambda_{\Gamma}^{(1)} - \Lambda_{\Gamma,\Gamma}^{(1)} x_{\Gamma}^{(1)} = - \left(\lambda_{\Gamma}^{(2)} - \Lambda_{\Gamma,\Gamma}^{(2)} x_{\Gamma}^{(2)} \right)$$



2 - SPACE DOMAIN DECOMPOSITION

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Two subdomains

Parallel solutions

$$\begin{bmatrix} A_{1,1} & A_{1,\Gamma} \\ A_{\Gamma,1} & A_{\Gamma,\Gamma}^{(1)} + \Lambda_{\Gamma,\Gamma}^{(1)} \end{bmatrix} \begin{bmatrix} x_1 \\ x_{\Gamma}^{(1)} \end{bmatrix} = \begin{bmatrix} b_1 \\ b_{\Gamma}^{(1)} + \lambda_{\Gamma}^{(1)} \end{bmatrix}$$

$$\begin{bmatrix} A_{2,2} & A_{2,\Gamma} \\ A_{\Gamma,2} & A_{\Gamma,\Gamma}^{(2)} + \Lambda_{\Gamma,\Gamma}^{(2)} \end{bmatrix} \begin{bmatrix} x_2 \\ x_{\Gamma}^{(2)} \end{bmatrix} = \begin{bmatrix} b_2 \\ b_{\Gamma}^{(2)} + \lambda_{\Gamma}^{(2)} \end{bmatrix}$$




Consistency across interface Γ

$$x_{\Gamma}^{(1)} = x_{\Gamma}^{(2)}$$

$$\lambda_{\Gamma}^{(1)} - \Lambda_{\Gamma,\Gamma}^{(1)} x_{\Gamma}^{(1)} = - \left(\lambda_{\Gamma}^{(2)} - \Lambda_{\Gamma,\Gamma}^{(2)} x_{\Gamma}^{(2)} \right)$$

$$x_1 = A_{1,1}^{-1} \left(b_1 - A_{1,\Gamma} x_{\Gamma}^{(1)} \right)$$

$$A_{\Gamma,1} x_1 + \left(A_{\Gamma,\Gamma}^{(1)} + \Lambda_{\Gamma,\Gamma}^{(1)} \right) x_{\Gamma}^{(1)} = b_{\Gamma}^{(1)} + \lambda_{\Gamma}^{(1)}$$



2 - SPACE DOMAIN DECOMPOSITION

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Two subdomains

Parallel solutions

$$\begin{bmatrix} A_{1,1} & A_{1,\Gamma} \\ A_{\Gamma,1} & A_{\Gamma,\Gamma}^{(1)} + \Lambda_{\Gamma,\Gamma}^{(1)} \end{bmatrix} \begin{bmatrix} x_1 \\ x_{\Gamma}^{(1)} \end{bmatrix} = \begin{bmatrix} b_1 \\ b_{\Gamma}^{(1)} + \lambda_{\Gamma}^{(1)} \end{bmatrix}$$

$$\begin{bmatrix} A_{2,2} & A_{2,\Gamma} \\ A_{\Gamma,2} & A_{\Gamma,\Gamma}^{(2)} + \Lambda_{\Gamma,\Gamma}^{(2)} \end{bmatrix} \begin{bmatrix} x_2 \\ x_{\Gamma}^{(2)} \end{bmatrix} = \begin{bmatrix} b_2 \\ b_{\Gamma}^{(2)} + \lambda_{\Gamma}^{(2)} \end{bmatrix}$$

Consistency across interface Γ




$$x_{\Gamma}^{(1)} = x_{\Gamma}^{(2)}$$

$$\lambda_{\Gamma}^{(1)} - \Lambda_{\Gamma,\Gamma}^{(1)} x_{\Gamma}^{(1)} = - \left(\lambda_{\Gamma}^{(2)} - \Lambda_{\Gamma,\Gamma}^{(2)} x_{\Gamma}^{(2)} \right)$$

$$x_1 = A_{1,1}^{-1} \left(b_1 - A_{1,\Gamma} x_{\Gamma}^{(1)} \right)$$

$$A_{\Gamma,1} x_1 + \left(A_{\Gamma,\Gamma}^{(1)} + \Lambda_{\Gamma,\Gamma}^{(1)} \right) x_{\Gamma}^{(1)} = b_{\Gamma}^{(1)} + \lambda_{\Gamma}^{(1)}$$

$$\left(A_{\Gamma,\Gamma}^{(1)} - A_{\Gamma,1} A_{1,1}^{-1} A_{1,\Gamma} + \Lambda_{\Gamma,\Gamma}^{(1)} \right) x_{\Gamma}^{(1)} = b_{\Gamma}^{(1)} + \lambda_{\Gamma}^{(1)} - A_{\Gamma,1} A_{1,1}^{-1} b_1$$



2 - SPACE DOMAIN DECOMPOSITION

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Two subdomains

Parallel solutions


$$\left(A_{\Gamma,\Gamma}^{(1)} - A_{\Gamma,1} A_{1,1}^{-1} A_{1,\Gamma} + \Lambda_{\Gamma,\Gamma}^{(1)} \right) x_{\Gamma}^{(1)} = b_{\Gamma}^{(1)} + \lambda_{\Gamma}^{(1)} - A_{\Gamma,1} A_{1,1}^{-1} b_1$$

$$\left(A_{\Gamma,\Gamma}^{(2)} - A_{\Gamma,2} A_{2,2}^{-1} A_{2,\Gamma} + \Lambda_{\Gamma,\Gamma}^{(2)} \right) x_{\Gamma}^{(2)} = b_{\Gamma}^{(2)} + \lambda_{\Gamma}^{(2)} - A_{\Gamma,2} A_{2,2}^{-1} b_2$$

Consistency across interface Γ

$$x_{\Gamma}^{(1)} = x_{\Gamma}^{(2)}$$

$$\lambda_{\Gamma}^{(1)} - \Lambda_{\Gamma,\Gamma}^{(1)} x_{\Gamma}^{(1)} = - \left(\lambda_{\Gamma}^{(2)} - \Lambda_{\Gamma,\Gamma}^{(2)} x_{\Gamma}^{(2)} \right)$$



2 - SPACE DOMAIN DECOMPOSITION

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Two subdomains

Parallel solutions

$$\left(A_{\Gamma,\Gamma}^{(1)} - A_{\Gamma,1} A_{1,1}^{-1} A_{1,\Gamma} + \Lambda_{\Gamma,\Gamma}^{(1)} \right) x_{\Gamma}^{(1)} = b_{\Gamma}^{(1)} + \lambda_{\Gamma}^{(1)} - A_{\Gamma,1} A_{1,1}^{-1} b_1$$

$$\left(A_{\Gamma,\Gamma}^{(2)} - A_{\Gamma,2} A_{2,2}^{-1} A_{2,\Gamma} + \Lambda_{\Gamma,\Gamma}^{(2)} \right) x_{\Gamma}^{(2)} = b_{\Gamma}^{(2)} + \lambda_{\Gamma}^{(2)} - A_{\Gamma,2} A_{2,2}^{-1} b_2$$




$$\left(S_{\Gamma,\Gamma}^{(1)} + \Lambda_{\Gamma,\Gamma}^{(1)} \right) x_{\Gamma}^{(1)} = d_{\Gamma}^{(1)} + \lambda_{\Gamma}^{(1)}$$

$$\left(S_{\Gamma,\Gamma}^{(2)} + \Lambda_{\Gamma,\Gamma}^{(2)} \right) x_{\Gamma}^{(2)} = d_{\Gamma}^{(2)} + \lambda_{\Gamma}^{(2)}$$

Consistency across interface Γ

$$x_{\Gamma}^{(1)} = x_{\Gamma}^{(2)}$$

$$\lambda_{\Gamma}^{(1)} - \Lambda_{\Gamma,\Gamma}^{(1)} x_{\Gamma}^{(1)} = - \left(\lambda_{\Gamma}^{(2)} - \Lambda_{\Gamma,\Gamma}^{(2)} x_{\Gamma}^{(2)} \right)$$



Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Two subdomains

Parallel solutions

$$\left(A_{\Gamma,\Gamma}^{(1)} - A_{\Gamma,1} A_{1,1}^{-1} A_{1,\Gamma} + \Lambda_{\Gamma,\Gamma}^{(1)} \right) x_{\Gamma}^{(1)} = b_{\Gamma}^{(1)} + \lambda_{\Gamma}^{(1)} - A_{\Gamma,1} A_{1,1}^{-1} b_1$$

$$\left(A_{\Gamma,\Gamma}^{(2)} - A_{\Gamma,2} A_{2,2}^{-1} A_{2,\Gamma} + \Lambda_{\Gamma,\Gamma}^{(2)} \right) x_{\Gamma}^{(2)} = b_{\Gamma}^{(2)} + \lambda_{\Gamma}^{(2)} - A_{\Gamma,2} A_{2,2}^{-1} b_2$$

$$\left(S_{\Gamma,\Gamma}^{(1)} + \Lambda_{\Gamma,\Gamma}^{(1)} \right) x_{\Gamma}^{(1)} = d_{\Gamma}^{(1)} + \lambda_{\Gamma}^{(1)}$$

$$\left(S_{\Gamma,\Gamma}^{(2)} + \Lambda_{\Gamma,\Gamma}^{(2)} \right) x_{\Gamma}^{(2)} = d_{\Gamma}^{(2)} + \lambda_{\Gamma}^{(2)}$$


Consistency across interface Γ

$$x_{\Gamma}^{(1)} = x_{\Gamma}^{(2)}$$

$$\lambda_{\Gamma}^{(1)} - \Lambda_{\Gamma,\Gamma}^{(1)} x_{\Gamma}^{(1)} = - \left(\lambda_{\Gamma}^{(2)} - \Lambda_{\Gamma,\Gamma}^{(2)} x_{\Gamma}^{(2)} \right)$$

Primal approach: $\lambda_{\Gamma}^{(i)} = \left(S_{\Gamma,\Gamma}^{(i)} + \Lambda_{\Gamma,\Gamma}^{(i)} \right) x_{\Gamma}^{(i)} - d_{\Gamma}^{(i)}$

Dual approach: $x_{\Gamma}^{(i)} = \left(S_{\Gamma,\Gamma}^{(i)} + \Lambda_{\Gamma,\Gamma}^{(i)} \right)^{-1} \left(d_{\Gamma}^{(i)} + \lambda_{\Gamma}^{(i)} \right)$



2 - SPACE DOMAIN DECOMPOSITION

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Two subdomains

Parallel solutions

$$\left(A_{\Gamma,\Gamma}^{(1)} - A_{\Gamma,1} A_{1,1}^{-1} A_{1,\Gamma} + \Lambda_{\Gamma,\Gamma}^{(1)} \right) x_{\Gamma}^{(1)} = b_{\Gamma}^{(1)} + \lambda_{\Gamma}^{(1)} - A_{\Gamma,1} A_{1,1}^{-1} b_1$$

$$\left(A_{\Gamma,\Gamma}^{(2)} - A_{\Gamma,2} A_{2,2}^{-1} A_{2,\Gamma} + \Lambda_{\Gamma,\Gamma}^{(2)} \right) x_{\Gamma}^{(2)} = b_{\Gamma}^{(2)} + \lambda_{\Gamma}^{(2)} - A_{\Gamma,2} A_{2,2}^{-1} b_2$$

$$\left(S_{\Gamma,\Gamma}^{(1)} + \Lambda_{\Gamma,\Gamma}^{(1)} \right) x_{\Gamma}^{(1)} = d_{\Gamma}^{(1)} + \lambda_{\Gamma}^{(1)}$$

$$\left(S_{\Gamma,\Gamma}^{(2)} + \Lambda_{\Gamma,\Gamma}^{(2)} \right) x_{\Gamma}^{(2)} = d_{\Gamma}^{(2)} + \lambda_{\Gamma}^{(2)}$$


Consistency across interface Γ

$$x_{\Gamma}^{(1)} = x_{\Gamma}^{(2)}$$

$$\lambda_{\Gamma}^{(1)} - \Lambda_{\Gamma,\Gamma}^{(1)} x_{\Gamma}^{(1)} = - \left(\lambda_{\Gamma}^{(2)} - \Lambda_{\Gamma,\Gamma}^{(2)} x_{\Gamma}^{(2)} \right)$$

$$\text{Primal approach: } \lambda_{\Gamma}^{(i)} = \left(S_{\Gamma,\Gamma}^{(i)} + \Lambda_{\Gamma,\Gamma}^{(i)} \right) x_{\Gamma}^{(i)} - d_{\Gamma}^{(i)}$$

$$\text{Dual approach: } x_{\Gamma}^{(i)} = \left(S_{\Gamma,\Gamma}^{(i)} + \Lambda_{\Gamma,\Gamma}^{(i)} \right)^{-1} \left(d_{\Gamma}^{(i)} + \lambda_{\Gamma}^{(i)} \right)$$



2 - SPACE DOMAIN DECOMPOSITION

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Two subdomains

Parallel solutions

$$\left(S_{r,r}^{(1)} + \Lambda_{r,r}^{(1)} \right) x_r^{(1)} = d_r^{(1)} + \lambda_r^{(1)}$$

$$\left(S_{r,r}^{(2)} + \Lambda_{r,r}^{(2)} \right) x_r^{(2)} = d_r^{(2)} + \lambda_r^{(2)}$$




Consistency across interface Γ

$$x_r^{(1)} = x_r^{(2)}$$

$$\lambda_r^{(1)} - \Lambda_{r,r}^{(1)} x_r^{(1)} = - \left(\lambda_r^{(2)} - \Lambda_{r,r}^{(2)} x_r^{(2)} \right)$$

Primal approach

$$\lambda_r^{(i)} = \left(S_{r,r}^{(i)} + \Lambda_{r,r}^{(i)} \right) x_r^{(i)} - d_r^{(i)}$$



2 - SPACE DOMAIN DECOMPOSITION

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Two subdomains

Parallel solutions

$$\left(S_{r,r}^{(1)} + \Lambda_{r,r}^{(1)} \right) x_r^{(1)} = d_r^{(1)} + \lambda_r^{(1)}$$

$$\left(S_{r,r}^{(2)} + \Lambda_{r,r}^{(2)} \right) x_r^{(2)} = d_r^{(2)} + \lambda_r^{(2)}$$

Consistency across interface Γ

$$x_r^{(1)} = x_r^{(2)}$$

$$\lambda_r^{(1)} - \Lambda_{r,r}^{(1)} x_r^{(1)} = - \left(\lambda_r^{(2)} - \Lambda_{r,r}^{(2)} x_r^{(2)} \right)$$

Primal approach




$$\lambda_r^{(i)} = \left(S_{r,r}^{(i)} + \Lambda_{r,r}^{(i)} \right) x_r^{(i)} - d_r^{(i)}$$

Interface problem: Schur complement inversion

$$\left(S_{r,r}^{(1)} + S_{r,r}^{(2)} \right) x_r^{(1)} = d_r^{(1)} + d_r^{(2)}$$

$$\left(S_{r,r}^{(1)} + S_{r,r}^{(2)} \right) x_r^{(2)} = d_r^{(1)} + d_r^{(2)}$$

$$\left(S_{r,r}^{(1)} + S_{r,r}^{(2)} \right) x_r = d_r^{(1)} + d_r^{(2)}$$




2 - SPACE DOMAIN DECOMPOSITION

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Interface problem: Schur complement inversion

$$\sum_i S_{\Gamma, \Gamma}^{(i)} x_{\Gamma} = \sum_i d_{\Gamma}^{(i)}$$



2 - SPACE DOMAIN DECOMPOSITION

Problem




$$Ax = b, \quad x \in \mathbb{C}^n$$

Interface problem: Schur complement inversion

$$\sum_i S_{\Gamma, \Gamma}^{(i)} x_{\Gamma} = \sum_i d_{\Gamma}^{(i)}$$

Asynchronous iterative solution

$$\sum_i S_{\Gamma, \Gamma}^{(i)} = M - N$$



2 - SPACE DOMAIN DECOMPOSITION

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Interface problem: Schur complement inversion

$$\sum_i S_{\Gamma, \Gamma}^{(i)} x_{\Gamma} = \sum_i d_{\Gamma}^{(i)}$$

Asynchronous iterative solution

$$\sum_i S_{\Gamma, \Gamma}^{(i)} = M - N$$




Classical splittings (M, N) : (block-)Jacobi, Gauss-Seidel, SOR, ...

- ◆ Minimum requirement: $\text{diag} \sum_i S_{\Gamma, \Gamma}^{(i)}$
- ◆ \Rightarrow explicit computation of $\sum_i S_{\Gamma, \Gamma}^{(i)}$
- ◆ \Rightarrow **vector decomposition**

$$x_{\Gamma} := \left[(x_{\Gamma})_1 \quad \cdots \quad (x_{\Gamma})_p \right]^T$$

instead of primal domain decomposition approach

$$x_{\Gamma} := x_{\Gamma}^{(1)} = \cdots = x_{\Gamma}^{(p)}$$



2 - SPACE DOMAIN DECOMPOSITION

Problem


$$Ax = b, \quad x \in \mathbb{C}^n$$

Interface problem: Schur complement inversion

Asynchronous iterative solution

$$S_{\Gamma, \Gamma} := \sum_i S_{\Gamma, \Gamma}^{(i)} = M - N$$

Classical splittings $(M, N) \Rightarrow$ vector decomposition



2 - SPACE DOMAIN DECOMPOSITION

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Interface problem: Schur complement inversion

Asynchronous iterative solution

$$S_{\Gamma, \Gamma} := \sum_i S_{\Gamma, \Gamma}^{(i)} = M - N$$


Classical splittings $(M, N) \Rightarrow$ **vector decomposition**

Proposition 1

$$M := \gamma I$$

Sufficient conditions for vector decomposition

$S_{\Gamma, \Gamma}$ is an \mathcal{M} -matrix, $\gamma \geq \max \text{diag } S_{\Gamma, \Gamma}$



2 - SPACE DOMAIN DECOMPOSITION

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Interface problem: Schur complement inversion

Asynchronous iterative solution

$$S_{\Gamma, \Gamma} := \sum_i S_{\Gamma, \Gamma}^{(i)} = M - N$$


Classical splittings $(M, N) \Rightarrow$ vector decomposition

Proposition 1

$$M := \gamma I$$

Sufficient conditions for vector decomposition

$S_{\Gamma, \Gamma}$ is an \mathcal{M} -matrix, $\gamma \geq \max \text{diag } S_{\Gamma, \Gamma}$



2 - SPACE DOMAIN DECOMPOSITION

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Interface problem: Schur complement inversion

Asynchronous iterative solution

$$S_{\Gamma, \Gamma} := \sum_i S_{\Gamma, \Gamma}^{(i)} = M - N$$

Classical splittings $(M, N) \Rightarrow$ vector decomposition

Proposition 1

$$M := \gamma I$$

Sufficient conditions for vector decomposition

$S_{\Gamma, \Gamma}$ is an \mathcal{M} -matrix, $\gamma \geq \max \text{diag } S_{\Gamma, \Gamma}$


\mathcal{M} -matrix

$$(S_{\Gamma, \Gamma})_{i, j \neq i} \leq 0, \quad S_{\Gamma, \Gamma}^{-1} \geq 0$$

$$(S_{\Gamma, \Gamma})_{i, j \neq i} \leq 0, \quad S_{\Gamma, \Gamma} \text{ symmetric and positive definite}$$

[Crabtree and Haynsworth, 1969]

A is an \mathcal{M} -matrix $\Rightarrow S_{\Gamma, \Gamma}$ is an \mathcal{M} -matrix



2 - SPACE DOMAIN DECOMPOSITION

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Interface problem: Schur complement inversion

Asynchronous iterative solution

$$S_{\Gamma, \Gamma} := \sum_i S_{\Gamma, \Gamma}^{(i)} = M - N$$

Classical splittings $(M, N) \Rightarrow$ vector decomposition

Proposition 1

$$M := \gamma I$$

Sufficient conditions for vector decomposition

$S_{\Gamma, \Gamma}$ is an \mathcal{M} -matrix, $\gamma \geq \max \text{diag } S_{\Gamma, \Gamma}$


\mathcal{M} -matrix

$$(S_{\Gamma, \Gamma})_{i, j \neq i} \leq 0, \quad S_{\Gamma, \Gamma}^{-1} \geq 0$$

$$(S_{\Gamma, \Gamma})_{i, j \neq i} \leq 0, \quad S_{\Gamma, \Gamma} \text{ symmetric and positive definite}$$

[Crabtree and Haynsworth, 1969]

A is an \mathcal{M} -matrix $\Rightarrow S_{\Gamma, \Gamma}$ is an \mathcal{M} -matrix



Remark

$$A \text{ is an } \mathcal{M}\text{-matrix} \Rightarrow A_{\Gamma, \Gamma} := \sum_i A_{\Gamma, \Gamma}^{(i)} \geq S_{\Gamma, \Gamma}$$

\Rightarrow Sufficient

$S_{\Gamma, \Gamma}$ is an \mathcal{M} -matrix, $\gamma \geq \max \text{diag } A_{\Gamma, \Gamma}$

2 - SPACE DOMAIN DECOMPOSITION

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Interface problem: Schur complement inversion

Asynchronous iterative solution

$$S_{\Gamma, \Gamma} := \sum_i S_{\Gamma, \Gamma}^{(i)} = M - N$$

Classical splittings $(M, N) \Rightarrow$ **vector decomposition**

Proposition 1

$$M := \gamma I$$


Sufficient conditions for vector decomposition

$S_{\Gamma, \Gamma}$ is an \mathcal{M} -matrix, $\gamma \geq \max \text{diag } S_{\Gamma, \Gamma}$

$S_{\Gamma, \Gamma}$ is an \mathcal{M} -matrix, $\gamma \geq \max \text{diag } A_{\Gamma, \Gamma}$

[Crabtree and Haynsworth, 1969]

A is an \mathcal{M} -matrix $\implies S_{\Gamma, \Gamma}$ is an \mathcal{M} -matrix



Proposition 2

$$M := M_{\Gamma, \Gamma}, \quad A_{\Gamma, \Gamma} = M_{\Gamma, \Gamma} - N_{\Gamma, \Gamma}$$

2 - SPACE DOMAIN DECOMPOSITION

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Interface problem: Schur complement inversion

Asynchronous iterative solution

$$S_{\Gamma, \Gamma} := \sum_i S_{\Gamma, \Gamma}^{(i)} = M - N$$

Classical splittings $(M, N) \Rightarrow$ **vector decomposition**

Proposition 1

$$M := \gamma I$$


Sufficient conditions for vector decomposition

$S_{\Gamma, \Gamma}$ is an \mathcal{M} -matrix, $\gamma \geq \max \text{diag } S_{\Gamma, \Gamma}$

$S_{\Gamma, \Gamma}$ is an \mathcal{M} -matrix, $\gamma \geq \max \text{diag } A_{\Gamma, \Gamma}$

[Crabtree and Haynsworth, 1969]

A is an \mathcal{M} -matrix $\implies S_{\Gamma, \Gamma}$ is an \mathcal{M} -matrix



Proposition 2

$$M := M_{\Gamma, \Gamma}, \quad A_{\Gamma, \Gamma} = M_{\Gamma, \Gamma} - N_{\Gamma, \Gamma}$$

Sufficient conditions for vector decomposition

A is an \mathcal{M} -matrix, $(M_{\Gamma, \Gamma}, N_{\Gamma, \Gamma})$ is an \mathcal{M} -splitting

2 - SPACE DOMAIN DECOMPOSITION

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Interface problem: Schur complement inversion

Asynchronous iterative solution

$$S_{\Gamma, \Gamma} := \sum_i S_{\Gamma, \Gamma}^{(i)} = M - N$$

Classical splittings $(M, N) \Rightarrow$ **vector decomposition**

Proposition 1

$$M := \gamma I$$

Sufficient conditions for vector decomposition

$S_{\Gamma, \Gamma}$ is an \mathcal{M} -matrix, $\gamma \geq \max \text{diag } S_{\Gamma, \Gamma}$


$S_{\Gamma, \Gamma}$ is an \mathcal{M} -matrix, $\gamma \geq \max \text{diag } A_{\Gamma, \Gamma}$

[Crabtree and Haynsworth, 1969]

A is an \mathcal{M} -matrix $\Rightarrow S_{\Gamma, \Gamma}$ is an \mathcal{M} -matrix

Remark

$A_{\Gamma, \Gamma}$ is an \mathcal{M} -matrix \Rightarrow block-Jacobi is an \mathcal{M} -splitting



Proposition 2

$$M := M_{\Gamma, \Gamma}, \quad A_{\Gamma, \Gamma} = M_{\Gamma, \Gamma} - N_{\Gamma, \Gamma}$$

Sufficient conditions for vector decomposition

A is an \mathcal{M} -matrix, $(M_{\Gamma, \Gamma}, N_{\Gamma, \Gamma})$ is an \mathcal{M} -splitting

\mathcal{M} -splitting

$M_{\Gamma, \Gamma}$ is an \mathcal{M} -matrix, $N_{\Gamma, \Gamma} \geq 0$

2 - SPACE DOMAIN DECOMPOSITION

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Interface problem: Schur complement inversion

Asynchronous iterative solution

$$S_{\Gamma, \Gamma} := \sum_i S_{\Gamma, \Gamma}^{(i)} = M - N$$

Classical splittings $(M, N) \Rightarrow$ **vector decomposition**

Proposition 1

$$M := \gamma I$$

Sufficient conditions for vector decomposition

$S_{\Gamma, \Gamma}$ is an \mathcal{M} -matrix, $\gamma \geq \max \text{diag } S_{\Gamma, \Gamma}$

$S_{\Gamma, \Gamma}$ is an \mathcal{M} -matrix, $\gamma \geq \max \text{diag } A_{\Gamma, \Gamma}$

[Crabtree and Haynsworth, 1969]

A is an \mathcal{M} -matrix $\Rightarrow S_{\Gamma, \Gamma}$ is an \mathcal{M} -matrix

Remark

$A_{\Gamma, \Gamma}$ is an \mathcal{M} -matrix \Rightarrow block-Jacobi is an \mathcal{M} -splitting

Proposition 2

$$M := M_{\Gamma, \Gamma}, \quad A_{\Gamma, \Gamma} = M_{\Gamma, \Gamma} - N_{\Gamma, \Gamma}$$

Sufficient conditions for vector decomposition


A is an \mathcal{M} -matrix, $(M_{\Gamma, \Gamma}, N_{\Gamma, \Gamma})$ is an \mathcal{M} -splitting

\mathcal{M} -splitting

$M_{\Gamma, \Gamma}$ is an \mathcal{M} -matrix, $N_{\Gamma, \Gamma} \geq 0$

\Rightarrow **Sufficient**

A is an \mathcal{M} -matrix, $(M_{\Gamma, \Gamma}, N_{\Gamma, \Gamma})$ is a **block-Jacobi**



2 - SPACE DOMAIN DECOMPOSITION

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Interface problem: Schur complement inversion

Asynchronous iterative solution

$$S_{\Gamma,\Gamma} := \sum_i S_{\Gamma,\Gamma}^{(i)} = M - N$$

Classical splittings $(M, N) \Rightarrow$ **vector decomposition**

Proposition 1

$$M := \gamma I$$

Sufficient conditions for vector decomposition


$S_{\Gamma,\Gamma}$ is an \mathcal{M} -matrix, $\gamma \geq \max \text{diag } S_{\Gamma,\Gamma}$

$S_{\Gamma,\Gamma}$ is an \mathcal{M} -matrix, $\gamma \geq \max \text{diag } A_{\Gamma,\Gamma}$

[Crabtree and Haynsworth, 1969]

A is an \mathcal{M} -matrix $\implies S_{\Gamma,\Gamma}$ is an \mathcal{M} -matrix

- ◆ Equivalent sufficient conditions for synchronous convergence of primal Schur decomposition
- ◆ What about asynchronous primal Schur decomposition?



Proposition 2

$$M := M_{\Gamma,\Gamma}, \quad A_{\Gamma,\Gamma} = M_{\Gamma,\Gamma} - N_{\Gamma,\Gamma}$$

Sufficient conditions for vector decomposition

A is an \mathcal{M} -matrix, $(M_{\Gamma,\Gamma}, N_{\Gamma,\Gamma})$ is an \mathcal{M} -splitting

A is an \mathcal{M} -matrix, $(M_{\Gamma,\Gamma}, N_{\Gamma,\Gamma})$ is a **block-Jacobi**

2 - SPACE DOMAIN DECOMPOSITION

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Interface problem: Schur complement inversion

Asynchronous iterative solution

$$S_{\Gamma, \Gamma} := \sum_i S_{\Gamma, \Gamma}^{(i)} = M - N$$

Classical splittings $(M, N) \Rightarrow$ **vector decomposition**

Propositions

$$M := \gamma I$$

Asynchronous vector / Synchronous primal Schur

$S_{\Gamma, \Gamma}$ is an \mathcal{M} -matrix, $\gamma \geq \max \text{diag } S_{\Gamma, \Gamma}$


$S_{\Gamma, \Gamma}$ is an \mathcal{M} -matrix, $\gamma \geq \max \text{diag } A_{\Gamma, \Gamma}$

$$M := M_{\Gamma, \Gamma}, \quad A_{\Gamma, \Gamma} = M_{\Gamma, \Gamma} - N_{\Gamma, \Gamma}$$

Asynchronous vector / Synchronous primal Schur

A is an \mathcal{M} -matrix, $(M_{\Gamma, \Gamma}, N_{\Gamma, \Gamma})$ is an \mathcal{M} -splitting

A is an \mathcal{M} -matrix, $(M_{\Gamma, \Gamma}, N_{\Gamma, \Gamma})$ is a **block-Jacobi**



Asynchronous primal Schur decomposition

$$M := M_{\Gamma, \Gamma}, \quad A_{\Gamma, \Gamma} = M_{\Gamma, \Gamma} - N_{\Gamma, \Gamma}$$

2 - SPACE DOMAIN DECOMPOSITION

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Interface problem: Schur complement inversion

Asynchronous iterative solution

$$S_{\Gamma, \Gamma} := \sum_i S_{\Gamma, \Gamma}^{(i)} = M - N$$

Classical splittings $(M, N) \Rightarrow$ **vector decomposition**

Propositions

$$M := \gamma I$$

Asynchronous vector / Synchronous primal Schur

$S_{\Gamma, \Gamma}$ is an \mathcal{M} -matrix, $\gamma \geq \max \text{diag } S_{\Gamma, \Gamma}$


$S_{\Gamma, \Gamma}$ is an \mathcal{M} -matrix, $\gamma \geq \max \text{diag } A_{\Gamma, \Gamma}$

$$M := M_{\Gamma, \Gamma}, \quad A_{\Gamma, \Gamma} = M_{\Gamma, \Gamma} - N_{\Gamma, \Gamma}$$

Asynchronous vector / Synchronous primal Schur

A is an \mathcal{M} -matrix, $(M_{\Gamma, \Gamma}, N_{\Gamma, \Gamma})$ is an \mathcal{M} -splitting

A is an \mathcal{M} -matrix, $(M_{\Gamma, \Gamma}, N_{\Gamma, \Gamma})$ is a **block-Jacobi**



Asynchronous primal Schur decomposition

$$M := M_{\Gamma, \Gamma}, \quad A_{\Gamma, \Gamma} = M_{\Gamma, \Gamma} - N_{\Gamma, \Gamma}$$

$$A = \tilde{M} - \tilde{N}, \quad \tilde{M} = \begin{bmatrix} A_{1,1} & O & O \\ O & A_{2,2} & O \\ O & O & M_{\Gamma, \Gamma} \end{bmatrix}$$

2 - SPACE DOMAIN DECOMPOSITION

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Interface problem: Schur complement inversion

Asynchronous iterative solution

$$S_{\Gamma, \Gamma} := \sum_i S_{\Gamma, \Gamma}^{(i)} = M - N$$

Classical splittings $(M, N) \Rightarrow$ **vector decomposition**

Propositions

$$M := \gamma I$$

Asynchronous vector / Synchronous primal Schur

$S_{\Gamma, \Gamma}$ is an \mathcal{M} -matrix, $\gamma \geq \max \text{diag } S_{\Gamma, \Gamma}$


$S_{\Gamma, \Gamma}$ is an \mathcal{M} -matrix, $\gamma \geq \max \text{diag } A_{\Gamma, \Gamma}$

$$M := M_{\Gamma, \Gamma}, \quad A_{\Gamma, \Gamma} = M_{\Gamma, \Gamma} - N_{\Gamma, \Gamma}$$

Asynchronous vector / Synchronous primal Schur

A is an \mathcal{M} -matrix, $(M_{\Gamma, \Gamma}, N_{\Gamma, \Gamma})$ is an \mathcal{M} -splitting

A is an \mathcal{M} -matrix, $(M_{\Gamma, \Gamma}, N_{\Gamma, \Gamma})$ is a **block-Jacobi**



Asynchronous primal Schur decomposition

$$M := M_{\Gamma, \Gamma}, \quad A_{\Gamma, \Gamma} = M_{\Gamma, \Gamma} - N_{\Gamma, \Gamma}$$

$$A = \tilde{M} - \tilde{N}, \quad \tilde{M} = \begin{bmatrix} A_{1,1} & O & O \\ O & A_{2,2} & O \\ O & O & M_{\Gamma, \Gamma} \end{bmatrix}$$

Theorem

$$\rho(|\tilde{M}^{-1}\tilde{N}|) < 1, \quad \left| \sum_i M_{\Gamma, \Gamma}^{-1} N_{\Gamma, \Gamma}^{(i)} \right| = \sum_i |M_{\Gamma, \Gamma}^{-1} N_{\Gamma, \Gamma}^{(i)}|$$

2 - SPACE DOMAIN DECOMPOSITION

Problem

$$Ax = b, \quad x \in \mathbb{C}^n$$

Interface problem: Schur complement inversion

Asynchronous iterative solution

$$S_{\Gamma, \Gamma} := \sum_i S_{\Gamma, \Gamma}^{(i)} = M - N$$

Classical splittings $(M, N) \Rightarrow$ **vector decomposition**

Propositions

$$M := \gamma I$$

Asynchronous vector / Synchronous primal Schur

$S_{\Gamma, \Gamma}$ is an \mathcal{M} -matrix, $\gamma \geq \max \text{diag } S_{\Gamma, \Gamma}$


$S_{\Gamma, \Gamma}$ is an \mathcal{M} -matrix, $\gamma \geq \max \text{diag } A_{\Gamma, \Gamma}$

$$M := M_{\Gamma, \Gamma}, \quad A_{\Gamma, \Gamma} = M_{\Gamma, \Gamma} - N_{\Gamma, \Gamma}$$

Asynchronous vector / Synchronous primal Schur

A is an \mathcal{M} -matrix, $(M_{\Gamma, \Gamma}, N_{\Gamma, \Gamma})$ is an \mathcal{M} -splitting

A is an \mathcal{M} -matrix, $(M_{\Gamma, \Gamma}, N_{\Gamma, \Gamma})$ is a **block-Jacobi**



Asynchronous primal Schur decomposition

$$M := M_{\Gamma, \Gamma}, \quad A_{\Gamma, \Gamma} = M_{\Gamma, \Gamma} - N_{\Gamma, \Gamma}$$

$$A = \tilde{M} - \tilde{N}, \quad \tilde{M} = \begin{bmatrix} A_{1,1} & O & O \\ O & A_{2,2} & O \\ O & O & M_{\Gamma, \Gamma} \end{bmatrix}$$



Theorem

$$\rho(|\tilde{M}^{-1}\tilde{N}|) < 1, \quad \left| \sum_i M_{\Gamma, \Gamma}^{-1} N_{\Gamma, \Gamma}^{(i)} \right| = \sum_i |M_{\Gamma, \Gamma}^{-1} N_{\Gamma, \Gamma}^{(i)}|$$

$$N_{\Gamma, \Gamma}^{(i)} = \alpha_i N_{\Gamma, \Gamma}, \quad \sum_i \alpha_i = 1, \quad \alpha_i > 0$$

2 - SPACE DOMAIN DECOMPOSITION

- ◆ 2D Laplacian model problem, 16 subdomains
- ◆ P^k and τ_j^i pre-generated (same for all methods)
- ◆ $S_{\Gamma,\Gamma} = M_{\Gamma,\Gamma} - N$, with $x_\Gamma = \sum_i x_\Gamma^{(i)}$: slight improvement of [Magoulès & Venet, 2018]




03 TIME DOMAIN DECOMPOSITION

3 - TIME DOMAIN DECOMPOSITION

Partial differential equation

$$\delta(u(s, t), s, t) = 0, \quad t \in [0, T], \quad s \in \Omega$$

$u(\Omega, 0)$ given



3 - TIME DOMAIN DECOMPOSITION

Partial differential equation

$$\delta(u(s, t), s, t) = 0, \quad t \in [0, T], \quad s \in \Omega$$

$$u(\Omega, 0) \text{ given}$$


Two time intervals

$$\delta(u_0(s, t), s, t) = 0, \quad t \in [0, T_1]$$

$$u_0(\Omega, 0) = u(\Omega, 0)$$

$$\delta(u_1(s, t), s, t) = 0, \quad t \in [T_1, T]$$

$$u_1(\Omega, T_1) = u_0(\Omega, T_1)$$



3 - TIME DOMAIN DECOMPOSITION

Partial differential equation

$$\delta(u(s, t), s, t) = 0, \quad t \in [0, T], \quad s \in \Omega$$

$$u(\Omega, 0) \text{ given}$$


Two time intervals

$$\delta(u_0(s, t), s, t) = 0, \quad t \in [0, T_1]$$

$$u_0(\Omega, 0) = u(\Omega, 0)$$

$$\delta(u_1(s, t), s, t) = 0, \quad t \in [T_1, T]$$

$$u_1(\Omega, T_1) = u_0(\Omega, T_1)$$



Parallel solutions

$$\tilde{u}_0 \equiv u_0$$

$$\lambda_0(\Omega) = u_0(\Omega, 0)$$

$$\delta(\tilde{u}_1(s, t), s, t) = 0, \quad t \in [T_1, T]$$

$$\tilde{u}_1(\Omega, T_1) = \lambda_1(\Omega)$$

3 - TIME DOMAIN DECOMPOSITION

Partial differential equation

$$\delta(u(s, t), s, t) = 0, \quad t \in [0, T], \quad s \in \Omega$$

$$u(\Omega, 0) \text{ given}$$


Two time intervals

$$\delta(u_0(s, t), s, t) = 0, \quad t \in [0, T_1]$$

$$u_0(\Omega, 0) = u(\Omega, 0)$$

$$\delta(u_1(s, t), s, t) = 0, \quad t \in [T_1, T]$$

$$u_1(\Omega, T_1) = u_0(\Omega, T_1)$$



Parallel solutions

$$\tilde{u}_0 \equiv u_0$$

$$\lambda_0(\Omega) = u_0(\Omega, 0)$$

$$\delta(\tilde{u}_1(s, t), s, t) = 0, \quad t \in [T_1, T]$$

$$\tilde{u}_1(\Omega, T_1) = \lambda_1(\Omega)$$

Consistency across interface T_1

$$\lambda_1(\Omega) = \tilde{u}_0(\Omega, T_1)$$

3 - TIME DOMAIN DECOMPOSITION

Partial differential equation

$$\delta(u(s, t), s, t) = 0, \quad t \in [0, T], \quad s \in \Omega$$

$$u(\Omega, 0) \text{ given}$$

Two time intervals

$$\delta(u_0(s, t), s, t) = 0, \quad t \in [0, T_1]$$

$$u_0(\Omega, 0) = u(\Omega, 0)$$

$$\delta(u_1(s, t), s, t) = 0, \quad t \in [T_1, T]$$

$$u_1(\Omega, T_1) = u_0(\Omega, T_1)$$

Parallel solutions

$$\tilde{u}_0 \equiv u_0$$



$$\lambda_0(\Omega) = u_0(\Omega, 0)$$

$$\delta(\tilde{u}_1(s, t), s, t) = 0, \quad t \in [T_1, T]$$

$$\tilde{u}_1(\Omega, T_1) = \lambda_1(\Omega)$$

Consistency across interface T_1

$$\lambda_1(\Omega) = \tilde{u}_0(\Omega, T_1)$$



Parareal approach:
Two-level time discretization
[Lions et al, 2001]

3 - TIME DOMAIN DECOMPOSITION

Partial differential equation

Two time intervals

$$\delta(u_0(s, t), s, t) = 0, \quad t \in [0, T_1]$$

$$u_0(\Omega, 0) = u(\Omega, 0)$$

$$\delta(u_1(s, t), s, t) = 0, \quad t \in [T_1, T]$$

$$u_1(\Omega, T_1) = u_0(\Omega, T_1)$$

Parallel solutions

$$\tilde{u}_0 \equiv u_0$$

$$\lambda_0(\Omega) = u_0(\Omega, 0)$$

$$\delta(\tilde{u}_1(s, t), s, t) = 0, \quad t \in [T_1, T]$$

$$\tilde{u}_1(\Omega, T_1) = \lambda_1(\Omega)$$

Consistency across interface T_1

$$\lambda_1(\Omega) = \tilde{u}_0(\Omega, T_1)$$

Fine time discretization



$$\alpha(\tilde{u}_0(s, t_{n+1})) = \beta(\tilde{u}_0(s, t_n))$$

$$\alpha(\tilde{u}_1(s, t_{n+1})) = \beta(\tilde{u}_1(s, t_n))$$


\Rightarrow parallel fine propagator

$$F(\lambda_0) := \tilde{u}_0(\Omega, T_1)$$

$$F(\lambda_1) := \tilde{u}_1(\Omega, T)$$



Parareal approach:
Two-level time discretization
[Lions et al, 2001]



3 - TIME DOMAIN DECOMPOSITION

Partial differential equation

Two time intervals

$$\delta(u_0(s, t), s, t) = 0, \quad t \in [0, T_1]$$

$$u_0(\Omega, 0) = u(\Omega, 0)$$

$$\delta(u_1(s, t), s, t) = 0, \quad t \in [T_1, T]$$

$$u_1(\Omega, T_1) = u_0(\Omega, T_1)$$

Parallel solutions

$$\tilde{u}_0 \equiv u_0$$

$$\lambda_0(\Omega) = u_0(\Omega, 0)$$

$$\delta(\tilde{u}_1(s, t), s, t) = 0, \quad t \in [T_1, T]$$

$$\tilde{u}_1(\Omega, T_1) = \lambda_1(\Omega)$$

Consistency across interface T_1

$$\lambda_1(\Omega) = \tilde{u}_0(\Omega, T_1)$$

Fine time discretization

$$\alpha(\tilde{u}_0(s, t_{n+1})) = \beta(\tilde{u}_0(s, t_n))$$

$$\alpha(\tilde{u}_1(s, t_{n+1})) = \beta(\tilde{u}_1(s, t_n))$$

\Rightarrow parallel fine propagator

$$F(\lambda_0) := \tilde{u}_0(\Omega, T_1)$$

$$F(\lambda_1) := \tilde{u}_1(\Omega, T)$$



Coarse time discretization

$$\alpha(u(s, T_1)) = \beta(u(s, 0))$$


$$\alpha(u(s, T)) = \beta(u(s, T_1))$$

\Rightarrow **serial** coarse propagator

$$G(u(\Omega, 0)) := \tilde{u}(\Omega, T_1), \quad G(\tilde{u}(\Omega, T_1)) = \tilde{u}(\Omega, T)$$



Parareal approach:
Two-level time discretization
[Lions et al, 2001]



3 - TIME DOMAIN DECOMPOSITION

Partial differential equation

Two time intervals

Parallel solutions

$$\delta(\tilde{u}_0(s, t), s, t) = 0, \quad t \in [0, T_1]$$

$\lambda_0(\Omega)$ given


$$\delta(\tilde{u}_1(s, t), s, t) = 0, \quad t \in [T_1, T]$$

$$\tilde{u}_1(\Omega, T_1) = \lambda_1(\Omega)$$


Consistency across interface T_1

$$\lambda_1(\Omega) = \tilde{u}_0(\Omega, T_1)$$

Parareal iterations



Parareal approach:
Two-level time discretization
[Lions et al, 2001]



$$F(\lambda_0) := \tilde{u}_0(\Omega, T_1)$$

$$F(\lambda_1) = \tilde{u}_1(\Omega, T)$$

$$G(u(\Omega, 0)) := \tilde{u}(\Omega, T_1)$$

$$G(\tilde{u}(\Omega, T_1)) = \tilde{u}(\Omega, T)$$

3 - TIME DOMAIN DECOMPOSITION

Partial differential equation

Two time intervals

Parallel solutions

$$\delta(\tilde{u}_0(s, t), s, t) = 0, \quad t \in [0, T_1]$$

$\lambda_0(\Omega)$ given

$$\delta(\tilde{u}_1(s, t), s, t) = 0, \quad t \in [T_1, T]$$

$$\tilde{u}_1(\Omega, T_1) = \lambda_1(\Omega)$$



Consistency across interface T_1

$$\lambda_1(\Omega) = \tilde{u}_0(\Omega, T_1)$$

Parareal iterations

$$\lambda_0^0 := u_0(\Omega, 0)$$


$$\lambda_1^0 := G(\lambda_0^0) \quad \text{wait} \quad [0, T_1]$$



Parareal approach:

Two-level time discretization

[Lions et al, 2001]



$$F(\lambda_0) := \tilde{u}_0(\Omega, T_1)$$

$$F(\lambda_1) = \tilde{u}_1(\Omega, T)$$

$$G(u(\Omega, 0)) := \tilde{u}(\Omega, T_1)$$

$$G(\tilde{u}(\Omega, T_1)) = \tilde{u}(\Omega, T)$$

Prediction

3 - TIME DOMAIN DECOMPOSITION

Partial differential equation

Two time intervals

Parallel solutions

$$\delta(\tilde{u}_0(s, t), s, t) = 0, \quad t \in [0, T_1]$$

$\lambda_0(\Omega)$ given

$$\delta(\tilde{u}_1(s, t), s, t) = 0, \quad t \in [T_1, T]$$

$$\tilde{u}_1(\Omega, T_1) = \lambda_1(\Omega)$$

Consistency across interface T_1

$$\lambda_1(\Omega) = \tilde{u}_0(\Omega, T_1)$$



Parareal iterations

$$\lambda_0^0 := u_0(\Omega, 0)$$

$$\lambda_1^0 := G(\lambda_0^0)$$

wait $[0, T_1]$


$$\lambda_2^0 := G(\lambda_1^0) \quad [T_1, T]$$



Parareal approach:

Two-level time discretization

[Lions et al, 2001]



$$F(\lambda_0) := \tilde{u}_0(\Omega, T_1)$$

$$F(\lambda_1) = \tilde{u}_1(\Omega, T)$$

$$G(u(\Omega, 0)) := \tilde{u}(\Omega, T_1)$$

$$G(\tilde{u}(\Omega, T_1)) = \tilde{u}(\Omega, T)$$

Prediction

3 - TIME DOMAIN DECOMPOSITION

Partial differential equation

Two time intervals

Parallel solutions

$$\delta(\tilde{u}_0(s, t), s, t) = 0, \quad t \in [0, T_1]$$

$\lambda_0(\Omega)$ given

$$\delta(\tilde{u}_1(s, t), s, t) = 0, \quad t \in [T_1, T]$$

$$\tilde{u}_1(\Omega, T_1) = \lambda_1(\Omega)$$

Consistency across interface T_1

$$\lambda_1(\Omega) = \tilde{u}_0(\Omega, T_1)$$

Parareal iterations

$$\lambda_0^0 := u_0(\Omega, 0)$$

$$\lambda_1^0 := G(\lambda_0^0)$$

wait

$$[0, T_1]$$



$$\lambda_2^0 := G(\lambda_1^0)$$

$$[T_1, T]$$

$$F(\lambda_0^0)$$

$$F(\lambda_1^0)$$


$$[0, T_1] [T_1, T]$$



Parareal approach:

Two-level time discretization

[Lions et al, 2001]



$$F(\lambda_0) := \tilde{u}_0(\Omega, T_1)$$

$$F(\lambda_1) = \tilde{u}_1(\Omega, T)$$

$$G(u(\Omega, 0)) := \tilde{u}(\Omega, T_1)$$

$$G(\tilde{u}(\Omega, T_1)) = \tilde{u}(\Omega, T)$$

Prediction

3 - TIME DOMAIN DECOMPOSITION

Partial differential equation

Two time intervals

Parallel solutions

$$\delta(\tilde{u}_0(s, t), s, t) = 0, \quad t \in [0, T_1]$$

$\lambda_0(\Omega)$ given

$$\delta(\tilde{u}_1(s, t), s, t) = 0, \quad t \in [T_1, T]$$

$$\tilde{u}_1(\Omega, T_1) = \lambda_1(\Omega)$$

Consistency across interface T_1

$$\lambda_1(\Omega) = \tilde{u}_0(\Omega, T_1)$$

Parareal iterations

$$\lambda_0^0 := u_0(\Omega, 0)$$

$$\lambda_1^0 := G(\lambda_0^0)$$

$$F(\lambda_0^0)$$

$$\lambda_0^1 := \lambda_0^0$$

$$\lambda_1^1 := G(\lambda_0^1) + F(\lambda_0^0) - G(\lambda_0^0)$$

wait

$$[0, T_1]$$

$$\lambda_2^0 := G(\lambda_1^0)$$



$$[T_1, T]$$

$$F(\lambda_1^0)$$

$$[0, T_1] [T_1, T]$$

wait


$$[0, T_1]$$



Parareal approach:

Two-level time discretization

[Lions et al, 2001]



$$F(\lambda_0) := \tilde{u}_0(\Omega, T_1)$$

$$F(\lambda_1) = \tilde{u}_1(\Omega, T)$$

$$G(u(\Omega, 0)) := \tilde{u}(\Omega, T_1)$$

$$G(\tilde{u}(\Omega, T_1)) = \tilde{u}(\Omega, T)$$

Prediction

Gap

3 - TIME DOMAIN DECOMPOSITION

Partial differential equation

Two time intervals

Parallel solutions

$$\delta(\tilde{u}_0(s, t), s, t) = 0, \quad t \in [0, T_1]$$

$\lambda_0(\Omega)$ given

$$\delta(\tilde{u}_1(s, t), s, t) = 0, \quad t \in [T_1, T]$$

$$\tilde{u}_1(\Omega, T_1) = \lambda_1(\Omega)$$

Consistency across interface T_1

$$\lambda_1(\Omega) = \tilde{u}_0(\Omega, T_1)$$

Parareal iterations

$$\lambda_0^0 := u_0(\Omega, 0)$$

$$\lambda_1^0 := G(\lambda_0^0)$$

$$F(\lambda_0^0)$$

$$\lambda_0^1 := \lambda_0^0$$

$$\lambda_1^1 := G(\lambda_0^1) + F(\lambda_0^0) - G(\lambda_0^0)$$

wait

$$[0, T_1]$$

$$\lambda_2^0 := G(\lambda_1^0)$$



$$[T_1, T]$$

$$F(\lambda_1^0)$$

$$[0, T_1] [T_1, T]$$

wait


$$[0, T_1]$$



Parareal approach:

Two-level time discretization

[Lions et al, 2001]



$$F(\lambda_0) := \tilde{u}_0(\Omega, T_1)$$

$$F(\lambda_1) = \tilde{u}_1(\Omega, T)$$

$$G(u(\Omega, 0)) := \tilde{u}(\Omega, T_1)$$

$$G(\tilde{u}(\Omega, T_1)) = \tilde{u}(\Omega, T)$$

Prediction

Gap

Corrected prediction

3 - TIME DOMAIN DECOMPOSITION

Partial differential equation

Two time intervals

Parallel solutions

$$\delta(\tilde{u}_0(s, t), s, t) = 0, \quad t \in [0, T_1]$$

$\lambda_0(\Omega)$ given

$$\delta(\tilde{u}_1(s, t), s, t) = 0, \quad t \in [T_1, T]$$

$$\tilde{u}_1(\Omega, T_1) = \lambda_1(\Omega)$$

Consistency across interface T_1

$$\lambda_1(\Omega) = \tilde{u}_0(\Omega, T_1)$$

Parareal iterations

$$\lambda_0^0 := u_0(\Omega, 0)$$

$$\lambda_1^0 := G(\lambda_0^0)$$

$$F(\lambda_0^0)$$

$$\lambda_0^1 := \lambda_0^0$$

$$\lambda_1^1 := G(\lambda_0^1) + F(\lambda_0^0) - G(\lambda_0^0)$$

wait

$$\lambda_2^0 := G(\lambda_1^0)$$

$$F(\lambda_1^0)$$

wait

$$\lambda_2^1 := G(\lambda_1^1) + F(\lambda_1^0) - G(\lambda_1^0)$$



$$[0, T_1]$$

$$[T_1, T]$$

$$[0, T_1] [T_1, T]$$

$$[0, T_1]$$


$$[T_1, T]$$



Parareal approach:

Two-level time discretization

[Lions et al, 2001]



$$F(\lambda_0) := \tilde{u}_0(\Omega, T_1)$$

$$F(\lambda_1) = \tilde{u}_1(\Omega, T)$$

$$G(u(\Omega, 0)) := \tilde{u}(\Omega, T_1)$$

$$G(\tilde{u}(\Omega, T_1)) = \tilde{u}(\Omega, T)$$

Prediction

Gap

Corrected prediction

3 - TIME DOMAIN DECOMPOSITION

Partial differential equation

Two time intervals

Parallel solutions

$$\delta(\tilde{u}_0(s, t), s, t) = 0, \quad t \in [0, T_1]$$

$$\lambda_0(\Omega) \text{ given}$$

$$\delta(\tilde{u}_1(s, t), s, t) = 0, \quad t \in [T_1, T]$$

$$\tilde{u}_1(\Omega, T_1) = \lambda_1(\Omega)$$

Consistency across interface T_1

$$\lambda_1(\Omega) = \tilde{u}_0(\Omega, T_1)$$

Parareal iterations

$$\lambda_0^0 := u_0(\Omega, 0)$$

$$\lambda_1^0 := G(\lambda_0^0)$$

$$F(\lambda_0^0)$$

$$\lambda_0^1 := \lambda_0^0$$

$$\lambda_1^1 := G(\lambda_0^1) + F(\lambda_0^0) - G(\lambda_0^0)$$

$$\lambda_0^2 := \lambda_0^1$$

wait

$$\lambda_2^0 := G(\lambda_1^0)$$

$$F(\lambda_1^0)$$

wait

$$\lambda_2^1 := G(\lambda_1^1) + F(\lambda_1^0) - G(\lambda_1^0)$$

$$F(\lambda_1^1)$$

$$[0, T_1]$$



$$[T_1, T]$$

$$[0, T_1] [T_1, T]$$


$$[0, T_1]$$

$$[T_1, T]$$

$$[T_1, T]$$



Parareal approach:
Two-level time discretization
[Lions et al, 2001]



$$F(\lambda_0) := \tilde{u}_0(\Omega, T_1)$$

$$F(\lambda_1) = \tilde{u}_1(\Omega, T)$$

$$G(u(\Omega, 0)) := \tilde{u}(\Omega, T_1)$$

$$G(\tilde{u}(\Omega, T_1)) = \tilde{u}(\Omega, T)$$

Prediction

Gap

Corrected prediction

3 - TIME DOMAIN DECOMPOSITION

Partial differential equation

Two time intervals

Parallel solutions

$$\delta(\tilde{u}_0(s, t), s, t) = 0, \quad t \in [0, T_1]$$

$$\lambda_0(\Omega) \text{ given}$$

$$\delta(\tilde{u}_1(s, t), s, t) = 0, \quad t \in [T_1, T]$$

$$\tilde{u}_1(\Omega, T_1) = \lambda_1(\Omega)$$

Consistency across interface T_1

$$\lambda_1(\Omega) = \tilde{u}_0(\Omega, T_1)$$

Parareal iterations

$$\lambda_0^0 := u_0(\Omega, 0)$$

$$\lambda_1^0 := G(\lambda_0^0)$$

$$F(\lambda_0^0)$$

$$\lambda_0^1 := \lambda_0^0$$

$$\lambda_1^1 := G(\lambda_0^1) + F(\lambda_0^0) - G(\lambda_0^0)$$

$$\lambda_0^2 := \lambda_0^1$$

$$\lambda_1^2 := \lambda_1^1$$

wait

$$\lambda_2^0 := G(\lambda_1^0)$$

$$F(\lambda_1^0)$$

wait

$$\lambda_2^1 := G(\lambda_1^1) + F(\lambda_1^0) - G(\lambda_1^0)$$

$$F(\lambda_1^1)$$

$$\lambda_2^2 := G(\lambda_1^2) + F(\lambda_1^1) - G(\lambda_1^1)$$

$$[0, T_1]$$

$$[T_1, T]$$



$$[0, T_1] [T_1, T]$$

$$[0, T_1]$$


$$[T_1, T]$$

$$[T_1, T]$$

$$[T_1, T]$$



Parareal approach:
Two-level time discretization
[Lions et al, 2001]



$$F(\lambda_0) := \tilde{u}_0(\Omega, T_1)$$

$$F(\lambda_1) = \tilde{u}_1(\Omega, T)$$

$$G(u(\Omega, 0)) := \tilde{u}(\Omega, T_1)$$

$$G(\tilde{u}(\Omega, T_1)) = \tilde{u}(\Omega, T)$$

Prediction

Gap

Corrected prediction

3 - TIME DOMAIN DECOMPOSITION

Partial differential equation

Two time intervals

Parallel solutions

$$\delta(\tilde{u}_0(s, t), s, t) = 0, \quad t \in [0, T_1]$$

$$\lambda_0(\Omega) \text{ given}$$

$$\delta(\tilde{u}_1(s, t), s, t) = 0, \quad t \in [T_1, T]$$

$$\tilde{u}_1(\Omega, T_1) = \lambda_1(\Omega)$$

Consistency across interface T_1

$$\lambda_1(\Omega) = \tilde{u}_0(\Omega, T_1)$$

Parareal iterations

$$\lambda_0^0 := u_0(\Omega, 0)$$

$$\lambda_1^0 := G(\lambda_0^0)$$

$$F(\lambda_0^0)$$

$$\lambda_0^1 := \lambda_0^0$$

$$\lambda_1^1 := G(\lambda_0^1) + F(\lambda_0^0) - G(\lambda_0^0)$$

$$\lambda_0^2 := \lambda_0^1$$

$$\lambda_1^2 := \lambda_1^1$$

$$\lambda_i^{k+1} = G(\lambda_{i-1}^{k+1}) + F(\lambda_{i-1}^k) - G(\lambda_{i-1}^k), \quad [T_{i-1}, T_i]$$

wait

$$\lambda_2^0 := G(\lambda_1^0)$$

$$F(\lambda_1^0)$$

wait

$$\lambda_2^1 := G(\lambda_1^1) + F(\lambda_1^0) - G(\lambda_1^0)$$

$$F(\lambda_1^1)$$

$$\lambda_2^2 := G(\lambda_1^2) + F(\lambda_1^1) - G(\lambda_1^1)$$

$$[0, T_1]$$

$$[T_1, T]$$



$$[0, T_1] [T_1, T]$$

$$[0, T_1]$$


$$[T_1, T]$$

$$[T_1, T]$$

$$[T_1, T]$$



Parareal approach:
Two-level time discretization
[Lions et al, 2001]



$$F(\lambda_0) := \tilde{u}_0(\Omega, T_1)$$

$$F(\lambda_1) = \tilde{u}_1(\Omega, T)$$

$$G(u(\Omega, 0)) := \tilde{u}(\Omega, T_1)$$

$$G(\tilde{u}(\Omega, T_1)) = \tilde{u}(\Omega, T)$$

Prediction

Gap

Corrected prediction

3 - TIME DOMAIN DECOMPOSITION




Partial differential equation

N time intervals

Parallel solutions and consistency across interfaces T_i

Parareal iterations

$$\lambda_i^{k+1} = G(\lambda_{i-1}^{k+1}) + F(\lambda_{i-1}^k) - G(\lambda_{i-1}^k), \quad [T_{i-1}, T_i]$$



$$\delta(\tilde{u}_i(s, t), s, t) = 0$$

$$\tilde{u}_i(\Omega, T_i) = \lambda_i(\Omega)$$

Parareal approach:

Two-level time discretization

[Lions et al, 2001]

$$F(\lambda_i) = \tilde{u}_i(\Omega, T_{i+1})$$

$$G(\tilde{u}(\Omega, T_i)) = \tilde{u}(\Omega, T_{i+1})$$

Prediction G

Gap $F - G$

Corrected prediction $G+$

3 - TIME DOMAIN DECOMPOSITION

Partial differential equation

N time intervals

Parallel solutions and consistency across interfaces T_i

Parareal iterations

$$\lambda_i^{k+1} = G(\lambda_{i-1}^{k+1}) + F(\lambda_{i-1}^k) - G(\lambda_{i-1}^k), \quad [T_{i-1}, T_i]$$

Theorem 1




PDE extension of ODE result

[Gander & Vandewalle, 2007]

Iterative error

$$\|\lambda^k - \lambda^*\|_\infty \leq \alpha^k \|\lambda^0 - \lambda^*\|_\infty$$

$$\alpha = \frac{1 - \theta^N}{1 - \theta} \|F - G\|, \quad \theta \neq 1, \quad \theta \geq \|G\|$$



$$\delta(\tilde{u}_i(s, t), s, t) = 0$$

$$\tilde{u}_i(\Omega, T_i) = \lambda_i(\Omega)$$

Parareal approach:

Two-level time discretization

[Lions et al, 2001]

$$F(\lambda_i) = \tilde{u}_i(\Omega, T_{i+1})$$

$$G(\tilde{u}(\Omega, T_i)) = \tilde{u}(\Omega, T_{i+1})$$

Prediction G

Gap $F - G$

Corrected prediction $G+$

3 - TIME DOMAIN DECOMPOSITION

Partial differential equation

N time intervals

Parallel solutions and consistency across interfaces T_i

Parareal iterations

$$\lambda_i^{k+1} = G(\lambda_{i-1}^{k+1}) + F(\lambda_{i-1}^k) - G(\lambda_{i-1}^k), \quad [T_{i-1}, T_i]$$

Theorem 1

PDE extension of ODE result

[Gander & Vandewalle, 2007]

Iterative error




$$\|\lambda^k - \lambda^*\|_\infty \leq \alpha^k \|\lambda^0 - \lambda^*\|_\infty$$

$$\alpha = \frac{1 - \theta^N}{1 - \theta} \|F - G\|, \quad \theta \neq 1, \quad \theta \geq \|G\|$$

Sufficient convergence condition for

$$\|G\| < 1 \text{ (stability region)}$$

$$\|G\| + \|F - G\| < 1 + \|G\|^N \|F - G\|$$



$$\delta(\tilde{u}_i(s, t), s, t) = 0$$

$$\tilde{u}_i(\Omega, T_i) = \lambda_i(\Omega)$$

Parareal approach:

Two-level time discretization

[Lions et al, 2001]

$$F(\lambda_i) = \tilde{u}_i(\Omega, T_{i+1})$$

$$G(\tilde{u}(\Omega, T_i)) = \tilde{u}(\Omega, T_{i+1})$$

Prediction G

Gap $F - G$

Corrected prediction $G+$

3 - TIME DOMAIN DECOMPOSITION

Partial differential equation

N time intervals

Parallel solutions and consistency across interfaces T_i

Parareal iterations

$$\lambda_i^{k+1} = G(\lambda_{i-1}^{k+1}) + F(\lambda_{i-1}^k) - G(\lambda_{i-1}^k), \quad [T_{i-1}, T_i]$$

$$\lambda_i^{k+1} = G\left(\lambda_{i-1}^{\tau_{i-1}^{i,1}(k+1)}\right) + F\left(\lambda_{i-1}^{\tau_{i-1}^{i,2}(k)}\right) - G\left(\lambda_{i-1}^{\tau_{i-1}^{i,2}(k)}\right)$$

Theorem 1

PDE extension of ODE result

[Gander & Vandewalle, 2007]

Iterative error




$$\|\lambda^k - \lambda^*\|_\infty \leq \alpha^k \|\lambda^0 - \lambda^*\|_\infty$$

$$\alpha = \frac{1 - \theta^N}{1 - \theta} \|F - G\|, \quad \theta \neq 1, \theta \geq \|G\|$$

Sufficient convergence condition for

$\|G\| < 1$ (stability region)

$$\|G\| + \|F - G\| < 1 + \|G\|^N \|F - G\|$$



$$\delta(\tilde{u}_i(s, t), s, t) = 0$$

$$\tilde{u}_i(\Omega, T_i) = \lambda_i(\Omega)$$

Parareal approach:

Two-level time discretization

[Lions et al, 2001]

$$F(\lambda_i) = \tilde{u}_i(\Omega, T_{i+1})$$

$$G(\tilde{u}(\Omega, T_i)) = \tilde{u}(\Omega, T_{i+1})$$

Prediction G

Gap $F - G$

Corrected prediction $G +$

3 - TIME DOMAIN DECOMPOSITION

Partial differential equation

N time intervals

Parallel solutions and consistency across interfaces T_i

Parareal iterations

$$\lambda_i^{k+1} = G(\lambda_{i-1}^{k+1}) + F(\lambda_{i-1}^k) - G(\lambda_{i-1}^k), \quad [T_{i-1}, T_i]$$

$$\lambda_i^{k+1} = G\left(\lambda_{i-1}^{\tau_{i-1}^{i,1}(k+1)}\right) + F\left(\lambda_{i-1}^{\tau_{i-1}^{i,2}(k)}\right) - G\left(\lambda_{i-1}^{\tau_{i-1}^{i,1}(k)}\right)$$

Theorem 1

PDE extension of ODE result

[Gander & Vandewalle, 2007]

Iterative error

$$\|\lambda^k - \lambda^*\|_\infty \leq \alpha^k \|\lambda^0 - \lambda^*\|_\infty$$

$$\alpha = \frac{1 - \theta^N}{1 - \theta} \|F - G\|, \quad \theta \neq 1, \theta \geq \|G\|$$

Sufficient convergence condition for




$\|G\| < 1$ (stability region)

$$\|G\| + \|F - G\| < 1 + \|G\|^N \|F - G\|$$

Proposition

Asynchronous convergence (sufficient)

$$\|G\| + \|F - G\| < 1$$



$$\delta(\tilde{u}_i(s, t), s, t) = 0$$

$$\tilde{u}_i(\Omega, T_i) = \lambda_i(\Omega)$$

Parareal approach:

Two-level time discretization

[Lions et al, 2001]

$$F(\lambda_i) = \tilde{u}_i(\Omega, T_{i+1})$$

$$G(\tilde{u}(\Omega, T_i)) = \tilde{u}(\Omega, T_{i+1})$$

Prediction G

Gap $F - G$

Corrected prediction $G +$

3 - TIME DOMAIN DECOMPOSITION

Partial differential equation




N time intervals

Parallel solutions and consistency across interfaces T_i

Parareal iterations

$$\lambda_i^{k+1} = G(\lambda_{i-1}^{k+1}) + F(\lambda_{i-1}^k) - G(\lambda_{i-1}^k), \quad [T_{i-1}, T_i]$$

$$\lambda_i^{k+1} = G\left(\lambda_{i-1}^{\tau_{i-1}^{i,1}(k+1)}\right) + F\left(\lambda_{i-1}^{\tau_{i-1}^{i,2}(k)}\right) - G\left(\lambda_{i-1}^{\tau_{i-1}^{i,1}(k)}\right)$$



$$\delta(\tilde{u}_i(s, t), s, t) = 0$$

$$\tilde{u}_i(\Omega, T_i) = \lambda_i(\Omega)$$

Theorem 1

PDE extension of ODE result

[Gander & Vandewalle, 2007]

Iterative error

$$\|\lambda^k - \lambda^*\|_\infty \leq \alpha^k \|\lambda^0 - \lambda^*\|_\infty$$

$$\alpha = \frac{1 - \theta^N}{1 - \theta} \|F - G\|, \quad \theta \neq 1, \theta \geq \|G\|$$

Sufficient convergence condition for

$\|G\| < 1$ (stability region)

$$\|G\| + \|F - G\| < 1 + \|G\|^N \|F - G\|$$

Proposition

Asynchronous convergence (sufficient)

$$\|G\| + \|F - G\| < 1$$

Theorem 2

$$\|\lambda^k - \lambda^*\|_\infty \leq \tilde{\alpha}^{\tau(k)} \|\lambda^0 - \lambda^*\|_\infty$$

$$\tilde{\alpha} = \|G\| + \|F - G\|, \quad \lim_{k \rightarrow \infty} \tau(k) = \infty$$

Parareal approach:

Two-level time discretization

[Lions et al, 2001]

$$F(\lambda_i) = \tilde{u}_i(\Omega, T_{i+1})$$

$$G(\tilde{u}(\Omega, T_i)) = \tilde{u}(\Omega, T_{i+1})$$

Prediction G

Gap $F - G$

Corrected prediction $G +$

3 - TIME DOMAIN DECOMPOSITION

Partial differential equation

N time intervals

Parallel solutions and consistency across interfaces T_i

Parareal iterations

$$\lambda_i^{k+1} = G(\lambda_{i-1}^{k+1}) + F(\lambda_{i-1}^k) - G(\lambda_{i-1}^k), \quad [T_{i-1}, T_i]$$

$$\lambda_i^{k+1} = G\left(\lambda_{i-1}^{\tau_{i-1}^{j,1}(k+1)}\right) + F\left(\lambda_{i-1}^{\tau_{i-1}^{j,2}(k)}\right) - G\left(\lambda_{i-1}^{\tau_{i-1}^{j,1}(k)}\right)$$

Theorem 1

PDE extension of ODE result

[Gander & Vandewalle, 2007]

Iterative error

$$\|\lambda^k - \lambda^*\|_\infty \leq \alpha^k \|\lambda^0 - \lambda^*\|_\infty$$

$$\alpha = \frac{1 - \theta^N}{1 - \theta} \|F - G\|, \quad \theta \neq 1, \theta \geq \|G\|$$

Sufficient convergence condition for

$\|G\| < 1$ (stability region)

$$\|G\| + \|F - G\| < 1 + \|G\|^N \|F - G\|$$

Proposition

Asynchronous convergence (sufficient)

$$\|G\| + \|F - G\| < 1$$




Theorem 2

$$\|\lambda^k - \lambda^*\|_\infty \leq \tilde{\alpha}^{\tau(k)} \|\lambda^0 - \lambda^*\|_\infty$$

$$\tilde{\alpha} = \|G\| + \|F - G\|, \quad \lim_{k \rightarrow \infty} \tau(k) = \infty$$

Synchronous convergence for $N \rightarrow \infty$

$$\|G\| + \|F - G\| < 1$$



$$\delta(\tilde{u}_i(s, t), s, t) = 0$$

$$\tilde{u}_i(\Omega, T_i) = \lambda_i(\Omega)$$

Parareal approach:

Two-level time discretization

[Lions et al, 2001]

$$F(\lambda_i) = \tilde{u}_i(\Omega, T_{i+1})$$





$$G(\tilde{u}(\Omega, T_i)) = \tilde{u}(\Omega, T_{i+1})$$

Prediction G

Gap $F - G$

Corrected prediction $G +$

3 - TIME DOMAIN DECOMPOSITION



$$t_{n+1} - t_n = 0.002, \quad T_{i+1} - T_i = 0.2$$

$$N = \#Proc., \quad T = N \times (T_{i+1} - T_i)$$

04 ASYNCHRONOUS CONVERGENCE DETECTION

4 - ASYNCHRONOUS CONVERGENCE DETECTION

Problem


$$f(x) = x, \quad x \in E$$

Asynchronous iterations

$$x_i^{k+1} = f_i(x_1^{\tau_1^i(k)}, \dots, x_p^{\tau_p^i(k)}), \quad i \in P^k$$

Convergence detection

$$\bar{x} := (x_1^{k_1}, \dots, x_p^{k_p}) \simeq x^*$$



4 - ASYNCHRONOUS CONVERGENCE DETECTION

Problem

$$f(x) = x, \quad x \in E$$

Asynchronous iterations


$$x_i^{k+1} = f_i(x_1^{\tau_1^i(k)}, \dots, x_p^{\tau_p^i(k)}), \quad i \in P^k$$

Convergence detection

$$\bar{x} := (x_1^{k_1}, \dots, x_p^{k_p}) \simeq x^*$$

Approach

- ◆ Finite time termination [Bertsekas & Tsitsiklis, 1989], [El Baz, 1996], [Savari & Bertsekas, 1996], ...
- ◆ Snapshot-based supervised termination [Savari & Bertsekas, 1996]
- ◆ Predicted termination (finite number of iterations) [Evans & Chikohora, 1998]
- ◆ Local convergence monitoring [Bahi et al, 2005, 2008]
- ◆ Nested-sets-based supervised termination [Miellou et al, 2008]



4 - ASYNCHRONOUS CONVERGENCE DETECTION

Problem

$$f(x) = x, \quad x \in E$$

Asynchronous convergence detection

Approach

- ◆ **Finite time termination** [Bertsekas & Tsitsiklis, 1989], [El Baz, 1996], [Savari & Bertsekas, 1996], ...
- ◆ **Snapshot-based supervised termination** [Savari & Bertsekas, 1996]
- ◆ **Predicted termination (finite number of iterations)** [Evans & Chikohora, 1998]
- ◆ **Local convergence monitoring** [Bahi et al, 2005, 2008]
- ◆ **Nested-sets-based supervised termination** [Miellou et al, 2008]

	Intrusiveness	Centralization	Effectiveness	Messages size
Bertsekas & Tsitsiklis, 1989	altered iterations	—	formal	—
El Baz, 1996	altered iterations	—	formal	—
Savari & Bertsekas, 1996	altered iterations	—	formal	—
Savari & Bertsekas, 1996	non-intrusive	two reductions	exact	$\mathcal{O}(n)$
Evans & Chikohora, 1998	non-intrusive	no reduction	heuristic	0
Bahi et al, 2005	non-intrusive	one reduction	heuristic	$\mathcal{O}(1)$
Bahi et al, 2008	piggybacking	two reductions	heuristic	$\mathcal{O}(1)$
Miellou et al, 2008	—	—	formal	—


4 - ASYNCHRONOUS CONVERGENCE DETECTION

Problem

$$f(x) = x, \quad x \in E$$

Asynchronous convergence detection
Snapshot-based supervised termination

Distributed snapshot [Chandy & Lamport, 1985]



◆ Initiator / First *marker* reception

1. Record local state
2. Send *marker* to neighbors
3. Start recording neighbors' messages

◆ On *marker* reception

1. Stop recording corresponding neighbor's messages

◆ On computation message reception

1. Record message


4 - ASYNCHRONOUS CONVERGENCE DETECTION

Problem

$$f(x) = x, \quad x \in E$$

Asynchronous convergence detection
Snapshot-based supervised termination

Distributed snapshot [Chandy & Lamport, 1985]



$$x_1^1 := f_1(x_1^0, x_2^0)$$

$$x_2^1 := f_2(x_1^0, x_2^0)$$

◆ Initiator / First *marker* reception

1. Record local state
2. Send *marker* to neighbors
3. Start recording neighbors' messages

◆ On *marker* reception

1. Stop recording corresponding neighbor's messages

◆ On computation message reception

1. Record message


4 - ASYNCHRONOUS CONVERGENCE DETECTION

Problem

$$f(x) = x, \quad x \in E$$

Asynchronous convergence detection
Snapshot-based supervised termination

Distributed snapshot [Chandy & Lamport, 1985]



$$x_1^1 := f_1(x_1^0, x_2^0) \quad x_2^1 := f_2(x_1^0, x_2^0)$$

$$x_1^2 := f_1(x_1^1, x_2^0) \quad x_2^2 := f_2(x_1^1, x_2^1)$$

◆ Initiator / First *marker* reception

1. Record local state
2. Send *marker* to neighbors
3. Start recording neighbors' messages

◆ On *marker* reception

1. Stop recording corresponding neighbor's messages

◆ On computation message reception

1. Record message


4 - ASYNCHRONOUS CONVERGENCE DETECTION

Problem

$$f(x) = x, \quad x \in E$$

Asynchronous convergence detection
Snapshot-based supervised termination

Distributed snapshot [Chandy & Lamport, 1985]



$$\begin{array}{ll}
 x_1^1 := f_1(x_1^0, x_2^0) & x_2^1 := f_2(x_1^0, x_2^0) \\
 x_1^2 := f_1(x_1^1, x_2^0) & x_2^2 := f_2(x_1^0, x_2^1) \\
 x_1^3 := f_1(x_1^2, x_2^1) & x_2^3 := f_2(x_1^1, x_2^2)
 \end{array}$$

◆ Initiator / First *marker* reception

1. Record local state
2. Send *marker* to neighbors
3. Start recording neighbors' messages

◆ On *marker* reception

1. Stop recording corresponding neighbor's messages

◆ On computation message reception

1. Record message


4 - ASYNCHRONOUS CONVERGENCE DETECTION

Problem

$$f(x) = x, \quad x \in E$$

Asynchronous convergence detection
Snapshot-based supervised termination

Distributed snapshot [Chandy & Lamport, 1985]



$$\begin{array}{ll}
 x_1^1 := f_1(x_1^0, x_2^0) & x_2^1 := f_2(x_1^0, x_2^0) \\
 x_2^1 & \\
 x_2^2 := f_2(x_1^1, x_2^0) & x_2^2 := f_2(x_1^0, x_2^1) \\
 x_1^2 & \\
 x_1^3 := x_1^2 & x_2^3 := f_2(x_1^1, x_2^2) \\
 x_1^4 := f_1(x_1^3, x_2^2) & x_2^4 := f_2(x_1^2, x_2^3)
 \end{array}$$

◆ Initiator / First *marker* reception

1. Record local state
2. Send *marker* to neighbors
3. Start recording neighbors' messages

◆ On *marker* reception

1. Stop recording corresponding neighbor's messages

◆ On computation message reception

1. Record message


4 - ASYNCHRONOUS CONVERGENCE DETECTION

Problem

$$f(x) = x, \quad x \in E$$

Asynchronous convergence detection
Snapshot-based supervised termination

Distributed snapshot [Chandy & Lamport, 1985]



$$\begin{array}{ll}
 x_1^1 := f_1(x_1^0, x_2^0) & x_2^1 := f_2(x_1^0, x_2^0) \\
 x_2^1 := f_2(x_1^1, x_2^0) & x_2^2 := f_2(x_1^1, x_2^1) \\
 x_1^2 := f_1(x_1^1, x_2^1) & x_2^3 := f_2(x_1^2, x_2^2) \\
 x_1^3 := f_1(x_1^2, x_2^2) & x_2^4 := f_2(x_1^3, x_2^3) \\
 x_1^4 := f_1(x_1^3, x_2^3) & x_2^5 := f_2(x_1^4, x_2^4) \\
 x_1^5 := f_1(x_1^4, x_2^4) &
 \end{array}$$

◆ Initiator / First *marker* reception

1. Record local state
2. Send *marker* to neighbors
3. Start recording neighbors' messages

◆ On *marker* reception

1. Stop recording corresponding neighbor's messages

◆ On computation message reception

1. Record message


4 - ASYNCHRONOUS CONVERGENCE DETECTION

Problem

$$f(x) = x, \quad x \in E$$

Asynchronous convergence detection
Snapshot-based supervised termination

Distributed snapshot [Chandy & Lamport, 1985]



$$\begin{array}{ll}
 x_1^1 := f_1(x_1^0, x_2^0) & x_2^1 := f_2(x_1^0, x_2^0) \\
 x_2^1 := f_2(x_1^0, x_2^0) & x_2^2 := f_2(x_1^1, x_2^1) \\
 x_1^2 := f_1(x_1^1, x_2^1) & x_2^3 := f_2(x_1^1, x_2^2) \\
 x_1^3 := f_1(x_1^2, x_2^2) & x_2^4 := f_2(x_1^2, x_2^3) \\
 x_1^4 := f_1(x_1^3, x_2^3) & x_2^5 := f_2(x_1^3, x_2^4) \\
 x_1^5 := f_1(x_1^4, x_2^4) & \\
 (x_1^2, ?) & (x_1^2, x_2^1)
 \end{array}$$

◆ Initiator / First *marker* reception

1. Record local state
2. Send *marker* to neighbors
3. Start recording neighbors' messages

◆ On *marker* reception

1. Stop recording corresponding neighbor's messages

◆ On computation message reception

1. Record message


4 - ASYNCHRONOUS CONVERGENCE DETECTION

Problem

$$f(x) = x, \quad x \in E$$

Asynchronous convergence detection
Snapshot-based supervised termination

Distributed snapshot [Chandy & Lamport, 1985]



$$\begin{array}{ll}
 x_1^1 := f_1(x_1^0, x_2^0) & x_2^1 := f_2(x_1^0, x_2^0) \\
 x_2^1 := f_1(x_1^1, x_2^0) & x_2^2 := f_2(x_1^1, x_2^1) \\
 x_1^2 := f_1(x_1^2, x_2^1) & x_2^3 := f_2(x_1^2, x_2^2) \\
 x_1^3 := f_1(x_1^3, x_2^2) & x_2^4 := f_2(x_1^3, x_2^3) \\
 x_1^4 := f_1(x_1^4, x_2^3) & x_2^5 := f_2(x_1^4, x_2^4) \\
 (x_1^5, ?) & (x_1^5, x_2^5)
 \end{array}$$

Proposition 1

Asynchronous iterations snapshot (AIS)

◆ Initiator / First marker reception

1. Record local state
2. Send *marker* to neighbors
3. Start recording neighbors' messages

◆ On marker reception

1. Stop recording corresponding neighbor's messages

◆ On computation message reception

1. Record message


4 - ASYNCHRONOUS CONVERGENCE DETECTION

Problem

$$f(x) = x, \quad x \in E$$

Asynchronous convergence detection
Snapshot-based supervised termination

Distributed snapshot [Chandy & Lamport, 1985]



$$\begin{array}{ll}
 x_1^1 := f_1(x_1^0, x_2^0) & x_2^1 := f_2(x_1^0, x_2^0) \\
 x_1^2 := f_1(x_1^1, x_2^0) & x_2^2 := f_2(x_1^0, x_2^1) \\
 x_1^3 := x_1^2 & x_2^3 := f_2(x_1^1, x_2^2) \\
 x_1^4 := f_1(x_1^3, x_2^2) & x_2^4 := f_2(x_1^2, x_2^3) \\
 x_1^5 := f_1(x_1^4, x_2^3) & x_2^5 := f_2(x_1^2, x_2^4) \\
 (x_1^2, ?) & (x_1^2, x_2^1)
 \end{array}$$

Proposition 1

Asynchronous iterations snapshot (AIS)

◆ Local convergence / First *marker* reception

1. Record local state
2. Send *marker* to neighbors

◆ On *marker* reception

1. Stop recording corresponding neighbor's messages

◆ On computation message reception

1. Record message


4 - ASYNCHRONOUS CONVERGENCE DETECTION

Problem

$$f(x) = x, \quad x \in E$$

Asynchronous convergence detection
Snapshot-based supervised termination

Distributed snapshot [Chandy & Lamport, 1985]



$$\begin{array}{ll}
 x_1^1 := f_1(x_1^0, x_2^0) & x_2^1 := f_2(x_1^0, x_2^0) \\
 x_2^1 := f_1(x_1^1, x_2^0) & x_2^2 := f_2(x_1^0, x_2^1) \\
 x_1^2 := f_1(x_1^1, x_2^1) & x_2^3 := f_2(x_1^1, x_2^2) \\
 x_1^3 := f_1(x_1^2, x_2^2) & x_2^4 := f_2(x_1^2, x_2^3) \\
 x_1^4 := f_1(x_1^3, x_2^3) & x_2^5 := f_2(x_1^3, x_2^4) \\
 x_1^5 := f_1(x_1^4, x_2^4) & \\
 (x_1^2, ?) & (x_1^2, x_2^1)
 \end{array}$$

Proposition 1

Asynchronous iterations snapshot (AIS)

◆ Local convergence / First *marker* reception

1. Record local state
2. Send *marker* to neighbors

◆ On *marker* reception

1. Record last corresponding neighbor's message

◆ On computation message reception

1. Record message


4 - ASYNCHRONOUS CONVERGENCE DETECTION

Problem

$$f(x) = x, \quad x \in E$$

Asynchronous convergence detection
Snapshot-based supervised termination

Distributed snapshot [Chandy & Lamport, 1985]



$$\begin{array}{ll}
 x_1^1 := f_1(x_1^0, x_2^0) & x_2^1 := f_2(x_1^0, x_2^0) \\
 x_2^1 := f_2(x_1^1, x_2^0) & x_2^2 := f_2(x_1^0, x_2^1) \\
 x_1^2 := f_1(x_1^1, x_2^1) & x_2^3 := f_2(x_1^1, x_2^2) \\
 x_2^2 := f_2(x_1^2, x_2^2) & x_2^4 := f_2(x_1^2, x_2^3) \\
 x_1^3 := f_1(x_1^2, x_2^2) & x_2^5 := f_2(x_1^2, x_2^4) \\
 x_1^4 := f_1(x_1^3, x_2^2) & (x_1^2, x_2^1) \\
 x_1^5 := f_1(x_1^4, x_2^3) & \\
 (x_1^2, x_2^1) &
 \end{array}$$

Proposition 1

Asynchronous iterations snapshot (AIS)

◆ Local convergence / First marker reception

1. Record local state
2. Send *marker* to neighbors

◆ On marker reception

1. Record last corresponding neighbor's message


4 - ASYNCHRONOUS CONVERGENCE DETECTION

Problem

$$f(x) = x, \quad x \in E$$

Asynchronous convergence detection
Snapshot-based supervised termination

Distributed snapshot [Chandy & Lamport, 1985]



$$x_1^1 := f_1(x_1^0, x_2^0)$$

$$x_2^1 := f_1(x_1^1, x_2^0)$$

$$x_1^3 := x_1^2$$

$$x_1^4 := f_1(x_1^3, x_2^2)$$

$$x_1^5 := f_1(x_1^4, x_2^3)$$

$$(x_1^2, ?)$$

$$x_2^1 := f_2(x_1^0, x_2^0)$$

$$x_2^2 := f_2(x_1^0, x_2^1)$$

$$x_2^3 := f_2(x_1^1, x_2^2)$$

$$x_2^4 := f_2(x_1^2, x_2^3)$$

$$x_2^5 := f_2(x_1^2, x_2^4)$$

$$(?, x_2^1)$$

Proposition 1

Asynchronous iterations snapshot (AIS)

◆ Local convergence / First marker reception

1. Record local state
2. Send *marker* to neighbors

◆ On marker reception

1. Record **last** corresponding neighbor's message

Non First-In-First-Out delivering
⇒ **marker crossing computation message**


4 - ASYNCHRONOUS CONVERGENCE DETECTION

Problem

$$f(x) = x, \quad x \in E$$

Asynchronous convergence detection
Snapshot-based supervised termination

Distributed snapshot [Chandy & Lamport, 1985]



$$\begin{array}{ll}
 x_1^1 := f_1(x_1^0, x_2^0) & x_2^1 := f_2(x_1^0, x_2^0) \\
 x_2^1 := f_1(x_1^1, x_2^0) & x_2^2 := f_2(x_1^0, x_2^1) \\
 x_1^2 := f_1(x_1^1, x_2^1) & x_2^3 := f_2(x_1^1, x_2^2) \\
 x_1^3 := f_1(x_1^2, x_2^2) & x_2^4 := f_2(x_1^2, x_2^3) \\
 x_1^4 := f_1(x_1^3, x_2^3) & x_2^5 := f_2(x_1^3, x_2^4) \\
 x_1^5 := f_1(x_1^4, x_2^4) & \\
 (x_1^2, x_2^1) & (x_1^2, x_2^1)
 \end{array}$$

Proposition 1

Asynchronous iterations snapshot (AIS)

Non FIFO case

♦ [Savari & Bertsekas, 1996]

Embed computation message into marker
 \Rightarrow marker size: $\mathcal{O}(n)$


4 - ASYNCHRONOUS CONVERGENCE DETECTION

Problem

$$f(x) = x, \quad x \in E$$

Asynchronous convergence detection
Snapshot-based supervised termination

Distributed snapshot [Chandy & Lamport, 1985]



$x_1^1 := f_1(x_1^0, x_2^0)$	$x_2^1 := f_2(x_1^0, x_2^0)$
x_2^1	
$x_1^2 := f_1(x_1^1, x_2^0)$	$x_2^2 := f_2(x_1^0, x_2^1)$
$x_1^3 := x_1^2$	$x_2^3 := f_2(x_1^1, x_2^2)$
$x_1^4 := f_1(x_1^3, x_2^2)$	$x_2^4 := f_2(x_1^2, x_2^3)$
$x_1^5 := f_1(x_1^4, x_2^3)$	$x_2^5 := f_2(x_1^2, x_2^4)$
(x_1^2, x_2^1)	(x_1^2, x_2^1)

Proposition 1

Asynchronous iterations snapshot (AIS)

Non FIFO case

♦ [Savari & Bertsekas, 1996]

Embed computation message into marker
⇒ marker size: $\mathcal{O}(n)$

Proposition 2

Non FIFO Asynchronous iterations snapshot (NFAIS)

Non FIFO characterization

A marker can cross at most m computation messages


4 - ASYNCHRONOUS CONVERGENCE DETECTION

Problem

$$f(x) = x, \quad x \in E$$

Asynchronous convergence detection
Snapshot-based supervised termination

Distributed snapshot [Chandy & Lamport, 1985]



$$x_1^1 := f_1(x_1^0, x_2^0)$$

$$x_2^1 := f_1(x_1^1, x_2^0)$$

$$x_1^3 := x_1^2$$

$$x_1^4 := f_1(x_1^3, x_2^2)$$

$$x_1^5 := f_1(x_1^4, x_2^3)$$

$$(x_1^2, x_2^1)$$

$$x_2^1 := f_2(x_1^0, x_2^0)$$

$$x_2^2 := f_2(x_1^0, x_2^1)$$

$$x_2^3 := f_2(x_1^1, x_2^2)$$

$$x_2^4 := f_2(x_1^2, x_2^3)$$

$$x_2^5 := f_2(x_1^2, x_2^4)$$

$$(x_1^2, x_2^1)$$

Proposition 1

Asynchronous iterations snapshot (AIS)

Non FIFO case

♦ [Savari & Bertsekas, 1996]

Embed computation message into marker
⇒ marker size: $\mathcal{O}(n)$

Proposition 2

Non FIFO Asynchronous iterations snapshot (NFAIS)

Non FIFO characterization

A marker can cross at most m computation messages

1. Send marker after m iterations under local convergence
2. Send flag-marker after m subsequent iterations
→ flag armed if continuous local convergence


4 - ASYNCHRONOUS CONVERGENCE DETECTION

Problem

$$f(x) = x, \quad x \in E$$

Asynchronous convergence detection
Snapshot-based supervised termination

Distributed snapshot [Chandy & Lamport, 1985]



$$x_1^1 := f_1(x_1^0, x_2^0)$$

$$x_2^1 := f_1(x_1^1, x_2^0)$$

$$x_1^3 := x_1^2$$

$$x_1^4 := f_1(x_1^3, x_2^2)$$

$$x_1^5 := f_1(x_1^4, x_2^3)$$

$$(x_1^2, x_2^1)$$

$$x_2^1 := f_2(x_1^0, x_2^0)$$

$$x_2^2 := f_2(x_1^0, x_2^1)$$

$$x_2^3 := f_2(x_1^1, x_2^2)$$

$$x_2^4 := f_2(x_1^2, x_2^3)$$

$$x_2^5 := f_2(x_1^2, x_2^4)$$

$$(x_1^2, x_2^1)$$

Proposition 1

Asynchronous iterations snapshot (AIS)

Non FIFO case

♦ [Savari & Bertsekas, 1996]

Embed computation message into marker
⇒ marker size: $\mathcal{O}(n)$

Proposition 2

Non FIFO Asynchronous iterations snapshot (NFAIS)

Non FIFO characterization

A marker can cross at most m computation messages

1. Send marker after m iterations under local convergence
2. Send flag-marker after m subsequent iterations
→ flag armed if continuous local convergence

Practical case

Marker transmits faster than computation message
⇒ no need for flag-marker

4 - ASYNCHRONOUS CONVERGENCE DETECTION

Problem

$$f(x) = x, \quad x \in E$$

Asynchronous convergence detection
 Snapshot-based supervised termination

Theorem

$$\bar{x} := \begin{bmatrix} \bar{x}_1^{(1)} & \dots & \bar{x}_p^{(p)} \end{bmatrix}^T$$

Global residual bound

$$r(\bar{x}) < \sigma(r(\bar{x}^{(1)}), \dots, r(\bar{x}^{(p)})) + C m \varepsilon$$

constant C depending on r , σ and p
 ε used for local convergence

Proposition 1

Asynchronous iterations snapshot (AIS)

Non FIFO case

♦ [Savari & Bertsekas, 1996]

Embed computation message into marker
 \Rightarrow marker size: $\mathcal{O}(n)$

Proposition 2

Non FIFO Asynchronous iterations snapshot (NFAIS)

Non FIFO characterization

A marker can cross at most m computation messages

1. Send marker after m iterations under local convergence
2. Send flag-marker after m subsequent iterations
 \rightarrow flag armed if continuous local convergence

Practical case

Marker transmits faster than computation message
 \Rightarrow no need for flag-marker

4 - ASYNCHRONOUS CONVERGENCE DETECTION

Problem

$$f(x) = x, \quad x \in E$$

Asynchronous convergence detection
Snapshot-based supervised termination

Theorem

$$\bar{x} := \begin{bmatrix} \bar{x}_1^{(1)} & \dots & \bar{x}_p^{(p)} \end{bmatrix}^T$$

Global residual bound

$$r(\bar{x}) < \sigma(r(\bar{x}^{(1)}), \dots, r(\bar{x}^{(p)})) + Cm\varepsilon$$

constant C depending on r , σ and p
 ε used for local convergence

Corollary

$\|\cdot\|_\infty^w$ -based residual

$$\sigma(r(\bar{x}^{(1)}), \dots, r(\bar{x}^{(p)})) < \varepsilon \implies r(\bar{x}) < \tilde{\varepsilon}$$

$$\varepsilon = \tilde{C}(m, w)\tilde{\varepsilon}$$

Proposition 1

Asynchronous iterations snapshot (AIS)

Non FIFO case

♦ [Savari & Bertsekas, 1996]

Embed computation message into marker
 \Rightarrow marker size: $\mathcal{O}(n)$

Proposition 2

Non FIFO Asynchronous iterations snapshot (NFAIS)

Non FIFO characterization

A marker can cross at most m computation messages

1. Send marker after m iterations under local convergence
2. Send flag-marker after m subsequent iterations
 \rightarrow flag armed if continuous local convergence

Practical case

Marker transmits faster than computation message
 \Rightarrow no need for flag-marker

4 - ASYNCHRONOUS CONVERGENCE DETECTION

Problem

$$f(x) = x, \quad x \in E$$

Asynchronous convergence detection

Approach

- ◆ **Finite time termination** [Bertsekas & Tsitsiklis, 1989], [El Baz, 1996], [Savari & Bertsekas, 1996], ...
- ◆ **Snapshot-based supervised termination** [Savari & Bertsekas, 1996], NFAIS
- ◆ **Predicted termination** (finite number of iterations) [Evans & Chikohora, 1998]
- ◆ **Local convergence monitoring** [Bahi et al, 2005, 2008]
- ◆ **Nested-sets-based supervised termination** [Miellou et al, 2008]

	Intrusiveness	Centralization	Effectiveness	Messages size
Bertsekas & Tsitsiklis, 1989	altered iterations	—	formal	—
El Baz, 1996	altered iterations	—	formal	—
Savari & Bertsekas, 1996	altered iterations	—	formal	—
Savari & Bertsekas, 1996	non-intrusive	two reductions	exact	$\mathcal{O}(n)$
Evans & Chikohora, 1998	non-intrusive	no reduction	heuristic	0
Bahi et al, 2005	non-intrusive	one reduction	heuristic	$\mathcal{O}(1)$
Bahi et al, 2008	piggybacking	two reductions	heuristic	$\mathcal{O}(1)$
Miellou et al, 2008	—	—	formal	—
NFAIS	non-intrusive	one reduction	exact	$\mathcal{O}(1)$

4 - ASYNCHRONOUS CONVERGENCE DETECTION

NFAIS: $m = 1$

NBS: Non-blocking synchronization (snapshot without local convergence condition)

Synchronous				NBS		
p	$r \times 10^7$	wt	k	$r \times 10^7$	wt	k
168	8.33	701	281916	5.03	536	346226
240	8.31	516	284118	6.18	378	366231
360	8.33	382	287557	5.72	250	355394
480	8.32	302	289933	5.40	202	406611
600	8.32	278	292163	5.23	168	432390

Savari & Bertsekas, 1996				NFAIS		
p	$r \times 10^7$	wt	k	$r \times 10^7$	wt	k
168	6.55	641	319703	6.54	640	319349
240	6.52	462	342476	6.42	463	343295
360	6.71	310	335008	5.19	314	339204
480	6.43	249	380524	6.63	250	383745
600	6.55	207	404544	6.06	209	410621

Convection-diffusion

$$\frac{\partial u}{\partial t} - \nu \Delta u + a \cdot \nabla u = s$$

Problem size

$$n = 185^3 = 6,331,625$$



Block-Jacobi splitting

+

Gauss-Seidel on blocks

Residual threshold

$$\varepsilon = 10^{-6}$$

p = number of processors

r = global residual after termination

05 CONCLUSION

- ◆ Asynchronous iterations theory
 - Contracting mappings
 - Matrix splittings, maximum norm and spectral radius

- ◆ Asynchronous iterations theory
 - Contracting mappings
 - Matrix splittings, maximum norm and spectral radius
- ◆ Space domain decomposition
 - Primal approach
 - Two diagonal-free splittings of the interface Schur complement
 - Asynchronous convergence for vector and substructures-based decomposition
 - Journal article in progress

- ◆ Asynchronous iterations theory
 - Contracting mappings
 - Matrix splittings, maximum norm and spectral radius
- ◆ Space domain decomposition
 - Primal approach
 - Two diagonal-free splittings of the interface Schur complement
 - Asynchronous convergence for vector and substructures-based decomposition
 - Journal article in progress
- ◆ Time domain decomposition
 - Parareal approach
 - PDE extension of ODE convergence condition
 - Asynchronous convergence for asymptotically equivalent condition
 - Journal article under review

- ◆ Asynchronous iterations theory
 - Contracting mappings
 - Matrix splittings, maximum norm and spectral radius
- ◆ Space domain decomposition
 - Primal approach
 - Two diagonal-free splittings of the interface Schur complement
 - Asynchronous convergence for vector and substructures-based decomposition
 - Journal article in progress
- ◆ Time domain decomposition
 - Parareal approach
 - PDE extension of ODE convergence condition
 - Asynchronous convergence for asymptotically equivalent condition
 - Journal article under review
- ◆ Asynchronous convergence detection
 - Snapshot approach
 - Exact global residual evaluation
 - One reduction operation, data-free marker
 - Non-blocking synchronization
 - Peer-reviewed journal article
- ◆ ⇒ JACK2: MPI-based communication library
 - Peer-reviewed journal article, Proceedings
- ◆ And various other works and publications

- ◆ Asynchronous iterations theory
 - Contracting mappings
 - Matrix splittings, maximum norm and spectral radius
 - ◆ Space domain decomposition
 - Primal approach
 - Two diagonal-free splittings of the interface Schur complement
 - Asynchronous convergence for vector and substructures-based decomposition
 - Journal article in progress
 - ◆ Time domain decomposition
 - Parareal approach
 - PDE extension of ODE convergence condition
 - Asynchronous convergence for asymptotically equivalent condition
 - Journal article under review
 - ◆ Asynchronous convergence detection
 - Snapshot approach
 - Exact global residual evaluation
 - One reduction operation, data-free marker
 - Non-blocking synchronization
 - Peer-reviewed journal article
 - ◆ \Rightarrow JACK2: MPI-based communication library
 - Peer-reviewed journal article, Proceedings
 - ◆ And various other works and publications
- Future work
- ◆ Substructures-based convergence of γ/I splitting
 - ◆ Complete interface tearing
 - ◆ Dual approach
 - ◆ Coarse space correction

- ◆ Asynchronous iterations theory
 - Contracting mappings
 - Matrix splittings, maximum norm and spectral radius
- ◆ Space domain decomposition
 - Primal approach
 - Two diagonal-free splittings of the interface Schur complement
 - Asynchronous convergence for vector and substructures-based decomposition
 - Journal article in progress
- ◆ Time domain decomposition
 - Parareal approach
 - PDE extension of ODE convergence condition
 - Asynchronous convergence for asymptotically equivalent condition
 - Journal article under review
- ◆ Asynchronous convergence detection
 - Snapshot approach
 - Exact global residual evaluation
 - One reduction operation, data-free marker
 - Non-blocking synchronization
 - Peer-reviewed journal article
- ◆ ⇒ JACK2: MPI-based communication library
 - Peer-reviewed journal article, Proceedings
- ◆ And various other works and publications

Future work

- ◆ Substructures-based convergence of γ/I splitting
- ◆ Complete interface tearing
- ◆ Dual approach
- ◆ Coarse space correction

Next goal

Habilitation à Diriger des Recherches

THÈSE DE DOCTORAT

ASYNCHRONOUS DOMAIN DECOMPOSITION METHODS FOR MASSIVELY PARALLEL COMPUTING

PRÉPARÉE ET SOUTENUE PAR
GUILLAUME GBIKPI-BENISSAN

DEVANT LE JURY COMPOSÉ DE

RAPHAËL COUTURIER
FABIENNE JEZEQUEL
PIERRE SPITERI
STÉPHANE VIALLE
FRÉDÉRIC MAGOULÈS

(RAPPORTEUR)
(EXAMINATRICE)
(RAPPORTEUR)
(EXAMINATEUR)
(DIRECTEUR DE THÈSE)

