

CS100 Spring 2025

Quiz 1

Mar 19, 2025

1. (15 points) Name: _____; No.: _____; Email: _____@shanghaitech.edu.cn

2. (25 points) [C] Select the pieces of code that have undefined behaviors.

- A. `#include <stdio.h>`
`int main(void) {`
 `int *ptr = NULL;`
 `printf("%d\n", *ptr);`
`}`
- B. `int main(void) {`
 `int a[10];`
 `for (int i = 0; i <= 10; ++i)`
 `a[i] = 0;`
`}`
- C. `#include <stdio.h>`
`int* foo(void) {`
 `static int a[10];`
 `return a;`
`}`
`int main(void) {`
 `int *ptr = foo();`
 `printf("%d\n", *ptr);`
`}`
- D. `int main(void) {`
 `int x = 1;`
 `x += (x+=2) + (++x);`
`}`
- E. `int main(void) {`
 `int cnt = 0;`
 `for (int i = 1; i <= 10; ++i)`
 `for (int i = 1; i <= 10; ++i)`
 `++cnt;`
`}`
- F. `#include <stdio.h>`
`#include <stdlib.h>`
`int a[] = {1, 2, 3, 4, 5, 6};`
`int main(void) {`
 `printf("%d\n", a[0]);`
 `free(a);`
`}`

3. (30 points) [C] The following code is to allocate $n \times m$ integers memory into 2-dimensional array form. Please fill the blank corresponding to the comments in the code, each blank should be filled with one statement.

```
#include <stdlib.h>
int main(void) {
    int n, m;
    scanf("%d%d", &n, &m);

    int **ptr = malloc(/* (a) Allocate memory for an array of pointers to row */);

    for (int i = 0; i < n; ++i)
        /* (b) Allocate memory for each row */

    for (int i = 0; i < n; ++i)
        for (int j = 0; j < m; ++j)
            ptr[i][j] = i * n + j;

    for (int i = 0; i < n; ++i)
        /* (c) Free memory for each row */

    free(ptr);
}
```

(a) _____

(b) _____

(c) _____

4. (15 points) [C] The following function is intended to remove the first `cnt` characters from a string and shift the remaining characters to the front. Does it implement this behavior correctly? If not, explain what is wrong.

```
#include <string.h>
#include <stddef.h>

/* @brief Removes the first `cnt` characters from the given string and shifts the remaining
 * characters to the front. If `cnt` is greater than or equal to the length of the
 * string, the string will be set to an empty string. The behavior is undefined if
 * `str` does not point to a null-terminated string.
 * @param str A pointer to a null-terminated byte string that will be modified.
 * @param cnt The number of characters to be removed from the beginning of the string.
 */
void pop(char *str, size_t cnt) {
    if (cnt >= strlen(str)) {
        *str = '\0';
        return;
    }
    while (*(str + cnt) != '\0') {
        *str = *(str + cnt);
        ++str;
    }
}
```

For those who are **unfamiliar** with the *C standard library function* `strlen`, the following summary (adapted from en.cppreference.com) provides a clear explanation:

The function `strlen` is defined in the header `<string.h>`:

```
size_t strlen( const char* str );
```

`strlen` returns the length of the given null-terminated byte string, that is, the number of characters in a character array whose first element is pointed to by `str` up to and not including the first null character. The behavior is **undefined** if `str` is not a pointer to a null-terminated byte string.

5. (15 points) [C] Read the following code. Write the output of the code. If the code contains a compile error or undefined behavior, please write 'CE' or 'UB' in the blank.

```
#include <stdio.h>
#define SIZEOF_UINT 32

void trans(unsigned x, char **s) {
    if (x > 1) {
        trans(x >> 1, s);    // Recursive call to process the higher bits
        (*s)++;               // Move the pointer to the next character
    }
    **s = (x & 1u) + '0';    // Store the bit as a character
}

int main(void) {
    // Initialize string filled with '\0's (null characters)
    char str[SIZEOF_UINT + 1] = {'\0'};

    char *ptr = str;

    trans(148, &ptr);

    printf("%s", str);    // Write down the output of this printf statement below

    return 0;
}
```