

1. (2 points) Honor Code

I promise that I will complete this quiz independently and will not use any electronic products or paper-based materials during the quiz, nor will I communicate with other students during this quiz.

I will not violate the Honor Code during this quiz.

☐ True ☐ False

2. (10 points) True or False

Determine whether the following statements are true or false.

- (a) (1') In any queue, you are able to access elements in the middle of the queue without dequeuing the preceding elements. ☐ True ☐ False
- (b) (1') If we implement a queue using a circular array, the minimal memory we need is related to the maximal possible numbers of elements in the queue. ☐ True ☐ False
- (c) (1') Stacks are commonly used in algorithms for parsing expressions and syntax checking. ☐ True ☐ False
- (d) (1') In a stack implemented using a linked list, it is possible that the push operation result in a stack overflow. ☐ True ☐ False
- (e) (1') Linked list is more efficient than array when we only want to find some element with specific value. ☐ True ☐ False
- (f) (1') In any circular doubly linked list, you are able to traverse the entire list starting from any node. ☐ True ☐ False
- (g) (1') In any singly linked list, removing the last element requires $O(1)$ time. ☐ True ☐ False
- (h) (1') If $f(n) = n^{\log n}$ then for all $\alpha \geq 1$, we have $f(n) = \omega(n^\alpha)$. ☐ True ☐ False
- (i) (1') For any two functions $f(n)$ and $g(n)$, if $f(n)$ is $O(g(n))$, then $g(n)$ is $\Omega(f(n))$. ☐ True ☐ False
- (j) (1') For an algorithm, it is impossible that the worst-case running time is $O(n)$ and the best-case running time is $\Omega(n)$. ☐ True ☐ False

3. (4 points) Possible Order Popped from Stack

Suppose there is an initially empty stack of capacity 7, and then we do a sequence of 14 operations, which is a permutation of 7 `push(x)` and 7 `pop()` operations. If the order of the elements pushed to the stack is 1 2 3 4 5 6 7, then for each sequence of elements listed below, determine whether it is a possible order of the popped elements. If possible, write down the 14 operations in order.

(a) (2') 1 2 3 4 7 5 6

(b) (2') 2 4 5 6 3 7 1

4. (7 points) Order the functions

Order the following functions so that for all i, j , if f_i comes before f_j in the order then $f_i = O(f_j)$. Do NOT justify your answers.

$$\begin{aligned}f_1(n) &= \sqrt{n} \\f_2(n) &= n^{\frac{1}{4}} \\f_3(n) &= 2^{\log_2 n} \\f_4(n) &= 3^n \\f_5(n) &= \left(\frac{1}{2}\right)^n \\f_6(n) &= \log_2 n \\f_7(n) &= 2^{\sqrt{n}} \\f_8(n) &= n!\end{aligned}$$

As an answer you may just write the functions as a list, e.g. f_8, f_4, f_1, \dots

5. (4 points) Analysing the Time Complexity of a Function

We are going to analyze the average-case time complexity of function FOO. Assume that all basic operations take constant time.

```
1: function FOO( $a_1, a_2, \dots, a_{n-1}, a_n$ ) ▷  $a$  is an array with  $n$  elements
2:    $max \leftarrow a_1$  ▷  $max$  is the maximal value among the first  $i$  elements
3:   for  $i = 2$  to  $n$  do
4:     if  $max < a_i$  then
5:        $max \leftarrow a_i$ 
6:        $(a_1, a_2, \dots, a_{i-1}, a_i) \leftarrow (a_i, a_{i-1}, \dots, a_2, a_1)$  ▷ Reverse the first  $i$  elements
7:     end if
8:   end for
9: end function
```

The probability of entering the **if** body in the i -th **for** iteration is _____, because it is the probability that a_i has the maximal value among the first i elements. (Assuming all elements in array a is independent and evenly distributed.)

And the time complexity of the **if** body in the i -th **for** iteration is $\Theta(i)$ because we need to reverse the first i elements.

Therefore the average-case time complexity of the **if** statement is $\Theta(\text{_____})$.

And the **for** loop iterates $\Theta(n)$ times, so the average-case complexity of **for** loop is $\Theta(\text{_____})$.

Therefore the average-case time complexity of FOO is $\Theta(\text{_____})$.