


Flow-Tracked Compact Gaussians Zhehao Shen<sup>1</sup> Penghao Wang<sup>1</sup> Yu Hong<sup>1</sup> Zhirui Zhang<sup>1</sup> Shouchen Zhou<sup>1</sup> <sup>1</sup>ShanghaiTech University

#### Contributions


- We propose a deformable Gaussian representation based on monocular RGBD input, aimed at accomplishing the task of dynamic novel view synthesis.
- Utilizing optical flow tracking from 2D images, we provide an optimized initialization for the dynamic Gaussian deform field, significantly accelerating the training speed and enhancing the rendering quality under a monocular setting.
- We showcase a companion compression scheme, supporting high quality rendering with low storage, even under various platforms..

# **Pipeline**



- Setting: RGB-D monocular stream
- Initialize: depth back-projection to generate initial point clouds, further generating Gaussians
- Prior: RAFT method to complete pixel-to-pixel track, projecting initial Gaussians onto pixels in different frames to obtain displacement of corresponding points
- **D-net**: deformable net to predict  $(\delta(x), \delta(y), \delta(z), \delta(r))$
- Encoding: use RANS and Quatization to compress


# Component: Optical Flow Tracking



We employ RAFT as our method for optical flow tracking. RAFT comprises a Feature Extractor, Context Extractor, Visual Similarity Calculator, and Updater to optimize the flow tracking process.

- Feature Extractor & Context Extractor: extract features from two images, followed by the extraction of semantic information from one of the images.
- Visual Similarity Calculator: constructs a 4D correlation volume by calculating the dot product between feature vectors.
- **Updater:** updates and refines flow tracking by iteratively searching the correlation volume based on current optical flow estimates.

## **Component: Residual Compression**




- Residual: compute residual point cloud data for smaller numerical range
- Quantization: numerical quantization to delta point cloud and low bit on SH attribute for low storage

**Instant-NVR** 

RANS Encoding: entropy encoding to efficiently compress the data

#### **Ablation: Scale**

- In the Gaussian parameters (rotation, position, scaling) for shape and position, we found that optimizing the scaling parameter didn't notably improve rendering but increased training time. Consequently, in designing our deform-net, we omitted optimizing the Gaussian scaling.
- Results from training with and without scaling indicate a 9% time difference (with scale: 102 min, without scale: 93 min).



# **Ablation: Tracking**

	Training (min) ↓	PSNR(dB) ↑
Without Flow Tracking	93.23	31.65
Ours-full(before compression)	70.34	32.47
Ours-full(after compression)	70.64	32.30

- Without Flow Tracking: directly use deform net to construct deformable gaussians
- Ours-full: preprocess images to get flow between frames. Utilizing depth and optical flow as an effective initialization strategy for the deform net, aiming to expedite the optimization process.
- Experimental equipment: We completed the experiment with 4 Nvidia 2080Ti graphics cards.

## **Ablation: Compression**

	Per-frame Storage(MB) ↓	PSNR(dB) ↑
Raw Point Cloud	46.23	32.47
High-bit Quantization	7.34	32.23
Low-bit Quantization	3.23	29.56
Ours Residual Encoding	1.35	32.30

- · Raw: directly saved per-frame gaussian point cloud
- High-bit Quantization: 11-bit quantization on the point cloud
- Low-bit Quantization: 9-bit quantization on the point cloud
- Ours: compute the residual between the current frame and the previous frame, and then adopt 9-bit quantization and RANS encodig on the residual data

## Results

- HyperNeRF (top-left): pinhole camera, using depth estimation method from Dynamic View Synthesis from Dynamic Monocular Video
- Dynamic Scene Dataset (top-right): hand-held monocular camcera, short-term dynamic events (~5 seconds)
- **D-NeRF** (bottom-left and bottom-right): a sparse set of images of a dynamic scene
- Instant-NVR (center bottom): RGB-D Kinect camera





TineuVox

Ours

## Comparison

**Ground truth** 



**DynamicNeRF**