

# Machine Learning, 2024 Spring

## Assignment 6

### Notice


Plagiarizer will get 0 points.

$\LaTeX$  is highly recommended. Otherwise you should write as legibly as possible.

**Problem 1** In this problem, you will investigate the relationship between the soft order constraint and the augmented error. The regularized weight  $\mathbf{w}_{\text{reg}}$  is a solution to

$$\min E_{\text{in}}(\mathbf{w}) \text{ subject to } \mathbf{w}^T \Gamma^T \Gamma \mathbf{w} \leq C$$

- (a) If  $\mathbf{w}_{\text{lin}}^T \Gamma^T \Gamma \mathbf{w}_{\text{lin}} \leq C$ , then what is  $\mathbf{w}_{\text{reg}}$  ?
- (b) If  $\mathbf{w}_{\text{lin}}^T \Gamma^T \Gamma \mathbf{w}_{\text{lin}} > C$ , the situation is illustrated below,



The constraint is satisfied in the shaded region and the contours of constant  $E_{\text{in}}$  are the ellipsoids (why ellipsoids?). What is  $\mathbf{w}_{\text{reg}}^T \Gamma^T \Gamma \mathbf{w}_{\text{reg}}$  ?

- (c) Show that with

$$\lambda_C = -\frac{1}{2C} \mathbf{w}_{\text{reg}}^T \nabla E_{\text{in}}(\mathbf{w}_{\text{reg}})$$

$\mathbf{w}_{\text{reg}}$  minimizes  $E_{\text{in}}(\mathbf{w}) + \lambda_C \mathbf{w}^T \Gamma^T \Gamma \mathbf{w}$ . [Hint: use the previous part to solve for  $\mathbf{w}_{\text{reg}}$  as an equality constrained optimization problem using the method of Lagrange multipliers.]

- (d) Show that the following hold for  $\lambda_C$  :
- (i) If  $\mathbf{w}_{\text{lin}}^T \Gamma^T \Gamma \mathbf{w}_{\text{lin}} \leq C$  then  $\lambda_C = 0$  ( $\mathbf{w}_{\text{lin}}$  itself satisfies the constraint).
- (ii) If  $\mathbf{w}_{\text{lin}}^T \Gamma^T \Gamma \mathbf{w}_{\text{lin}} > C$ , then  $\lambda_C > 0$  (the penalty term is positive).

(iii) If  $\mathbf{w}_{\text{lin}}^T \Gamma^T \Gamma \mathbf{w}_{\text{lin}} > C$ , then  $\lambda_C$  is a strictly decreasing function of  $C$ . [Hint: show that  $\frac{d\lambda_C}{dC} < 0$  for  $C \in [0, \mathbf{w}_{\text{lin}}^T \Gamma^T \Gamma \mathbf{w}_{\text{lin}}]$  ].

**Problem 2** [The Lasso algorithm] Rather than a soft order constraint on the squares of the weights, one could use the absolute values of the weights:

$$\min E_{\text{in}}(\mathbf{w}) \text{ subject to } \sum_{i=0}^d |w_i| \leq C$$

The model is called the lasso algorithm.

(a) Formulate and implement this as a quadratic program.

(b) What is the augmented error and discuss the algorithm for solving it. You can solve this problem using iterative soft-thresholding algorithm or a gradient projection method and present your pseudo-code.

**Problem 3** Similar to problem 3 in assignment 3 and assignment 4, you need to use the SUV dataset to implement (using Python or MATLAB) the L1/L2 regularization (penalty/augmented).

- Present your code.
- Present the path plots of L1 and L2 regularization. (Notice: you need to mark the selected value of the regular parameter)
- Analyze the weight difference between L1 and L2 regularization. (Notice: you need to describe the similarities and differences between the solutions of path plots)
- If you only want to build a model that contains 2 variables, which two features would you choose?

**Solution:**