

Course Project, Spring 2016

# Cluster-State Quantum Computing

Mayra Amezcua, Dileep V. Reddy, Zach Schmidt

May 25, 2016

**CIS410/510 Introduction to Quantum Information Theory**

Lecturer: Prof. Xiaodi Wu

Computer and Information Science, University of Oregon



# Table of Contents (optional frame. Can delete.)

## 1 Motivation

- Gates through teleportation

## 2 Cluster states (CS)

- Definition
- Representations
- Properties

## 3 Universal computation through CS

- Linear wire
- Arbitrary single qubit operations
- Two qubit operations

## 4 Advantages and disadvantages

- Parallelizability
- Experimental implementations
- CS model as an analysis tool

## 5 References



# template frame (delete me)

test block

some text

test varblock

Variable block (here 4cm)

test alert

some alert

test example

some example citation <sup>1</sup>

---

<sup>1</sup>Auth, DV, 123, 2001.



The most widely used model of quantum computation at the present time is the quantum circuit model.

A set containing all single-qubit gates and at least one entangling two-qubit gate (such as the controlled-NOT or controlled-PHASE) is universal[?]

A vastly different model, proposed by Briegel and Raussendorf [?], demonstrated that universal quantum computation could be achieved by *measurements alone*!



This so-called cluster model or *one-way quantum computer* (1WQC) relies on an entangled state of a large number of qubits or *cluster state* as the resource.

*These models have no evident classical analogues and they offer a new perspective on the role of entanglement in quantum computation*



If we have a pool of maximally entangled states we can apply any unitary gate  $U$  to any (multi-qubit) input state  $|\psi\rangle$  by measurements alone.

A significant annoyance is that we do not get the exact desired result  $U|\psi\rangle$  but instead get  $PU|\psi\rangle$  where  $P$  is some Pauli operation (on each qubit) depending on the measurement outcome[?].



*Cluster states* form a class of multiparty entangled quantum states which belong to the larger set of so-called graph states.


*Examples of graph states:*

- *Bell states*
- *Greenberger-Horne-Zeilinger (GHZ) states*
- *states that appear in quantum error correction*

Intuitively, graph states can be thought of as multi-qubit states that can be represented by a graph.

- Each qubit is represented by a vertex of the graph
- An edge between vertices represents an interacting pair of qubits







**Figure:** Figure showing representative 2-D cluster state shapes. The vertices are qubits with integer indices, and the edges indicate entanglement connectivity between select neighbors.

Any cluster state can be built with the following algorithm:

- 1 Prepare each of the  $n$  qubits in the state  $|+\rangle$
- 2 Apply controlled-PHASE gates between qubits whose corresponding graph vertices are connected.



A 4-node non-linear cluster state and its associated circuit






The spacial layout of the graph representation of the cluster state plays a role in the computational power of that state.

Operations on a linearly prepared cluster state can be efficiently simulated on a classical computer in  $O(n \log^c(1/n))$ , where  $n$  is the initial number of qubits, and  $c$  is the cost of floating point multiplication [?].

In general, measurement based models can be polynomial time reduced to the gate array model, and thus have the same power, but they are more easily parallelizable [?].







Gate  $C_z^{(0,1)}$ , followed by measurements  $M_X^{(0)}$ ,  $M_X^{(1)}$ , &  $M_X^{(2)}$ .




# Callback to teleportation discussion






Apply  $C_z^{(A,1)}$  and  $C_z^{(B,5)}$  to input quantum information into cluster state.






Apply  $C_z^{(A,1)}$  and  $C_z^{(B,5)}$  to input quantum information into cluster state.







## Four Optical Qubit Cluster State



This generates a square cluster state. Two pairs of entangle photons are created and then separate pairs are entangled.



## Cluster States in Optical Frequency Combs







[Jorrand and Perdrix, 2005] Jorrand, P. and Perdrix, S. (2005).

Unifying quantum computation with projective measurements only and one-way quantum computation.

In *Moscow, Russia*, pages 44–51. International Society for Optics and Photonics.

[Jozsa, 2006] Jozsa, R. (2006).

An introduction to measurement based quantum computation.

*NATO Science Series, III: Computer and Systems Sciences. Quantum Information Processing-From Theory to Experiment*, 199:137–158.

[Nielsen, 2006] Nielsen, M. A. (2006).

Cluster-state quantum computation.

*Reports on Mathematical Physics*, 57(1):147–161.

[Raussendorf and Briegel, 2000] Raussendorf, R. and Briegel, H. J. (2000).

Quantum computing via measurements only.

*eprint arXiv:quant-ph/0010033*.

