



POWER SOLUTIONS

Logistics Reference Guide

Product Identification & Inventory Management

Document: WC-PS-LRG-v1.1 | Revision Date: February 2026
INTERNAL USE - LOGISTICS DEPARTMENT

TABLE OF CONTENTS

1. Introduction 3

2. Product Portfolio Overview 3

3. Product Identification Guide 4

4. Specifications Summary 5

5. Shipping & Storage Requirements 7

6. Inventory Quick Reference 8

1. Introduction

This document provides the Logistics and Inventory department with essential information for identifying, storing, handling, and tracking WakeCap Power Solutions. These are complete solar power systems designed to provide off-grid power for WakeCap equipment and third-party devices in remote locations.

1.1 Document Purpose

- Enable quick product identification by model number, appearance, and packaging
- Provide shipping dimensions and weights for logistics planning
- Define storage requirements and handling precautions
- Support inventory management with part numbers and specifications

1.2 Product Naming Convention

WakeCap Power Solutions use a standardized naming system based on battery capacity:

Product Name	Model Code	Battery Capacity	Form Factor
WakeCap Power 30	WP-30	30Ah	Pole/Wall Mount Unit
WakeCap Power 60	WP-60	60Ah	Bracket Mount Kit
WakeCap Power 400	WP-400T	400Ah	Compact Trailer
WakeCap Power 900	WP-900T	900Ah (24V)	Full-Size Trailer

2. Product Portfolio Overview

The Power Solutions portfolio consists of four tiers, each designed for progressively higher power demands. Selection is based on the total load (watts) that needs to be powered.

2.1 WakeCap Power 30 (WP-30)

The smallest power solution, designed specifically for powering WakeCap Gateway devices. Compact pole or wall-mounted design suitable for installation on existing structures.

- Primary Use: WakeCap Gateway
- Maximum Load: ~8W continuous
- Battery: 30Ah Lithium Iron Phosphate (LiFePO4)
- Solar: 80W monocrystalline panel

[IMAGE: WP-30 product photo with dimensions overlay]

2.2 WakeCap Power 60 (WP-60)

A mid-size bracket-mounted kit for low-power devices such as single cameras or sensor systems. Integrated design with solar panel and battery enclosure.

- Primary Use: Single bullet cameras, small sensors
- Maximum Load: ~15W continuous
- Battery: 60Ah Lithium Iron Phosphate (LiFePO4)
- Solar: 100W monocrystalline panels (2 × 50W)

[IMAGE: WP-60 product photo with dimensions overlay]

2.3 WakeCap Power 400 (WP-400T)

A trailer-mounted power station for medium to high power loads. Features a 6.5-meter pneumatic mast for elevated equipment mounting. Towable and repositionable.


- Primary Use: Multiple cameras, PTZ cameras, communication equipment
- Maximum Load: ~100W continuous
- Battery: 400Ah GEL Lead Acid (2 × 200Ah @ 12V)
- Solar: 450W monocrystalline panels (3 × 150W)

[IMAGE: WP-400T product photo with trailer and mast visible]

2.4 WakeCap Power 900 (WP-900T)

The largest power solution - a full-size trailer for high-demand deployments. Features a 9-meter manual mast and 24V DC system for extended runtime with heavy loads.

- Primary Use: Multi-camera surveillance, high-power PTZ systems
- Maximum Load: ~350W continuous
- Battery: 900Ah High-Temperature Lead Acid (6 × 150Ah @ 24V)
- Solar: 1305W monocrystalline panels (3 × 435W)



3. Product Identification Guide

Use the following visual and label identifiers to distinguish between products:

3.1 Visual Identification

Product	Key Visual Features
WP-30	Small box-style enclosure, single solar panel (~780mm), pole clamps included
WP-60	Medium enclosure with dual tilted panels (~940mm width), bracket mount system
WP-400T	White trailer body, 3 solar panels, 6.5m pneumatic mast, single axle
WP-900T	Larger trailer body, 3 large solar panels, 9m mast tower, equipment cabinet

3.2 Label Location & Information

Each product has an identification label containing:

- Model Number (WP-30, WP-60, WP-400T, WP-900T)
- Serial Number
- Manufacturing Date
- Rated Voltage and Capacity

Label locations:

- WP-30: On battery enclosure rear panel
- WP-60: On battery enclosure side panel
- WP-400T: Inside equipment cabinet door
- WP-900T: Inside main equipment cabinet

3.3 Part Numbers Reference

Product	WakeCap Part Number	Supplier Model	Barcode Prefix
WakeCap Power 30	[TBD]	G8030	[TBD]
WakeCap Power 60	[TBD]	TS-100W60AH	[TBD]
WakeCap Power 400	[TBD]	[TBD]	[TBD]
WakeCap Power 900	[TBD]	VTS3P	[TBD]

Note: All products are manufactured in China.

4. Specifications Summary

The following tables provide key specifications for logistics planning and inventory records.

4.1 Physical Specifications

Specification	WP-30	WP-60	WP-400T	WP-900T
System Weight	~6 kg	23 kg	525 kg	1,300 kg
Packaging Dimensions (mm)	780×530×200	940×780×240	2000×1400×2300	2320×1495×2350
Packaging Volume (m³)	~0.08	0.175	~6.4	~8.1
Operating Dimensions (mm)	780×530×varies	940×780×varies	2000×2250×6500	2320×1495×2350
Solar Panel Area	2 × 390×530mm	2 × 390×510mm	3 × panels	3 × large panels
Mast Height	N/A	N/A	6.5 meters	9 meters

4.2 Electrical Specifications

Specification	WP-30	WP-60	WP-400T	WP-900T
System Voltage	12V DC	12V DC	12V DC	24V DC
Battery Capacity	30Ah (384Wh)	60Ah (768Wh)	400Ah (4,800Wh)	900Ah (21,600Wh)
Battery Type	LiFePO4	LiFePO4	GEL Lead Acid	Lead Acid
Solar Panel Power	80W	100W	450W	1,305W
MPPT Controller	Built-in (>95%)	10A (96.5%)	30A (95%)	60A EPEVER (98%)
Output Voltage	12V ±0.5V	10.5-12.6V	12V DC	24V DC
Max Output Current	3A	10A	<30A (25A typical)	<60A (55A typical)

4.3 Environmental Ratings

Specification	WP-30	WP-60	WP-400T	WP-900T
IP Rating	IP66	IP66	IP65	IP65
Operating Temp	-20°C to +50°C	-30°C to +85°C	-20°C to +80°C	-20°C to +85°C
Storage Temp	-40°C to +60°C	-30°C to +85°C	-20°C to +80°C	-20°C to +85°C
Wind Rating	60 m/s (panel)	60 m/s (panel)	100 km/h	100 km/h
Humidity	15% to 85%	15% to 85%	15% to 85%	15% to 85%

5. Shipping & Storage Requirements

5.1 Shipping Classifications

Product	Freight Class	Hazmat Status	Special Requirements
WP-30	Standard	Lithium Battery (UN3481)	Battery documentation required
WP-60	Standard	Lithium Battery (UN3481)	Battery documentation required
WP-400T	Oversize	Lead Acid Battery	Upright transport only
WP-900T	Oversize/Heavy	Lead Acid Battery	Heavy equipment trailer

5.2 Lithium Battery Shipping (WP-30, WP-60)

Products containing lithium iron phosphate batteries require:

- UN3481 hazmat labeling (Lithium Ion Batteries Packed with Equipment)
- Batteries shipped at 40-50% state of charge
- Shipping documentation per IATA/IMDG regulations
- Temperature-controlled storage if ambient exceeds 45°C

5.3 Trailer Shipping (WP-400T, WP-900T)

Trailer units require special handling:

- Flatbed truck or roll-on transport
- Secure mast in lowered/locked position
- Solar panels folded/secured for transport
- Wheel chocks and tie-down straps required
- Outriggers retracted and locked

5.4 Storage Requirements

Requirement	WP-30 / WP-60	WP-400T / WP-900T
Storage Area	Indoor warehouse	Outdoor compound / covered area
Temperature Range	-40°C to +60°C	-20°C to +50°C
Humidity	Below 85% RH	Weather protected
Orientation	Any (packaged)	Level ground, wheels chocked
Battery Maintenance	Recharge every 6 months	Recharge every 3 months
Stacking	Max 3 units (WP-30/60)	Not stackable

5.5 Handling Precautions

- Never drop or impact solar panels - glass breakage risk
- Keep battery terminals protected and insulated
- Do not expose to direct sunlight during extended storage
- Trailers: Engage parking brake before unhitching
- Use appropriate lifting equipment for trailer units

6. Inventory Quick Reference

Use this table for quick inventory checks and order processing:

Field	WP-30	WP-60	WP-400T	WP-900T
Product Name	WakeCap Power 30	WakeCap Power 60	WakeCap Power 400	WakeCap Power 900
Short Code	WP-30	WP-60	WP-400T	WP-900T
Part Number	[TBD]	[TBD]	[TBD]	[TBD]
Supplier Model	G8030	TS-100W60AH	[TBD]	VTS3P
Unit Weight	~6 kg	23 kg	525 kg	1,300 kg
Box Dimensions	780×530×200mm	940×780×240mm	N/A (Trailer)	N/A (Trailer)
Pallet Qty	[TBD]	[TBD]	1 unit	1 unit
Container Qty (40ft)	[TBD]	[TBD]	[TBD]	8 units
Lead Time	~4 weeks*	~4 weeks*	~8 weeks*	~8 weeks*
Warranty	[TBD]	[TBD]	2 years	[TBD]
Country of Origin	China	China	China	China

* Lead times are approximate and depend on availability. Actual delivery may be shorter or longer.

6.1 Included Accessories

Standard package contents for each product:

WP-30 Package Contents:

- Solar Panel × 2 (40W each)
- Solar Panel Mounting Bracket (pre-installed) × 1
- Battery Arm (including battery pack) × 1
- Battery Arm Mounting Plate × 1
- Pole Mounting Clamps (Ø150mm) × 2
- Mounting Hardware (screws, spring-loaded) × 1 set
- User Manual × 1

WP-60 Package Contents:

- Solar Panel × 2 (50W each, 390×510mm)
- Integrated Battery Enclosure × 1
- Mounting Bracket (galvanized, powder-coated) × 1
- PV Cables with Aviation Connectors × 1 set

- DC Output Cable (5.5×2.1mm connector, 1m) × 1
- User Manual × 1

WP-400T Package Contents:

- Complete Trailer Unit × 1
- Solar Panels × 3 (150W each, pre-mounted)
- GEL Batteries × 2 (200Ah, pre-installed)
- MPPT Controller (30A, pre-installed)
- 6.5m Pneumatic Mast (integrated)
- CCTV Mounting Box
- Spring Cables × 1 set
- User Manual × 1

WP-900T Package Contents:

- Complete Trailer Unit × 1
- Solar Panels × 3 (435W each, pre-mounted)
- Lead Acid Batteries × 6 (150Ah, pre-installed)
- EPEVER 60A MPPT Controller (pre-installed)
- 9m Manual Mast Tower (integrated)
- Camera Box (412×412×416mm)
- CAT6 Cables × 2
- Power Cables (1.5mm²) × 2
- User Manual × 1

END OF DOCUMENT

WakeCap Power Solutions - Logistics Reference Guide v1.1
For questions, contact: [Zishan Shahzad – zishan.shahzad@wakecap.com]