

WAKECAP

POWER SOLUTIONS

Product Catalogue

Off-Grid Solar Power Systems for Remote Equipment

WP-384 • WP-768 • WP-4800T • WP-21600T

WC-PS-PC-v1.1 | February 2026

WakeCap Power 384

WP-384

80W Solar | 384Wh LiFePO₄ | Off-Grid Power System

Ultra-compact, pole-mounted solar power system for lightweight remote e LiFePO₄ battery, and IP66 enclosure for harsh desert and coastal environm

KEY FEATURES

- ✓ Integrated MPPT controller (>95% efficiency) with BMS
- ✓ LiFePO₄ battery, 2000–5000 cycle life
- ✓ IP66 dust-tight, water-jet resistant
- ✓ LED indicators: charge, output, battery
- ✓ Optional RS485 remote monitoring
- ✓ Pole/wall mount (60–150mm pole)

[IMAGE: WP-384 complete system — compact pole-mounted unit with integrated controller box, battery arm, two 40W solar panels in butterfly configuration, LED indicators on front panel]

80W

Solar Power

384Wh

Battery

8W

Max Load

TECHNICAL SPECIFICATIONS

Parameter	Value	Unit
Model	G8030 (TD-G8030)	—
Solar Panels	2 x 40W Grade-A Mono	80W total
Panel Efficiency	≥23%	—
Battery	LiFePO ₄ , 2P4S	30Ah / 384Wh
Output Voltage	12 ±0.5 V DC	—
Max Output Current	3A	—

Parameter
Runtime (no solar)
Recharge Time
Operating Temp
Protection
Dimensions (panels)
Installation



100W	768Wh	15W
Solar Power	Battery	Max Load

TECHNICAL SPECIFICATIONS

Parameter	Value	Unit	Parameter
Model	TS-100W60AH	—	MPPT Efficiency
Solar Panels	2 x 50W N-Type A+ Mono	100W total	Operating Temp
Panel Efficiency	>22%	—	Protection
Battery	LiFePO ₄	60Ah / 768Wh	System Weight
Voltage Range	10.5–12.6 V DC	—	Package Size
Max Current (In/Out)	10A / 10A	—	Output Connector

WakeCap Power 768

WP-768

100W Solar | 768Wh LiFePO₄ | Off-Grid Power System

Modular pole-mounted solar power system for medium-demand remote eco-friendly applications. Features a 60Ah LiFePO₄ battery, and aviation-style waterproof connectors for reliable field use.

KEY FEATURES

- ✓ 10A MPPT controller, 96.5% efficiency
- ✓ 60Ah LiFePO₄ with integrated BMS
- ✓ N-Type A+ Grade mono panels, >22%
- ✓ Aviation waterproof connectors
- ✓ Adjustable panel tilt 0–30°
- ✓ Controller self-consumption: 0.06W

WakeCap Power 4800T

WP-4800T

450W Solar | 4800Wh GEL | Trailer-Mounted Power Station

Mobile trailer-mounted solar power station for temporary and semi-permanent battery bank, and integrated equipment cabinet with thermal management (DC) and WP-4800T-AC (220V AC).

KEY FEATURES

- ✓ 6.5m pneumatic mast (5 sections, Al alloy)
- ✓ 2×200Ah LEOCH GEL batteries (400Ah)
- ✓ 30A MPPT charge controller
- ✓ Equipment cabinet with fan cooling
- ✓ DC variant (WP-4800T-DC): 12V DC output
- ✓ AC variant (WP-4800T-AC): 220V AC output

[IMAGE: WP-4800T trailer power station — single-axle trailer, three 150W solar panels, 6.5m pneumatic mast extended, equipment cabinet, outriggers deployed, in desert setting]

450W

Solar Power

4.8kWh

Battery

100W

Max Load

TECHNICAL SPECIFICATIONS

Parameter	Value	Unit
Model	WP-4800T	—
Variants	WP-4800T-DC / WP-4800T-AC	—
DC Output	12 V DC	WP-4800T-DC
AC Output	220 V AC	WP-4800T-AC
Solar Panels	3 x 150W Monocrystalline	450W total
Battery	GEL Deep Cycle (LEOCH)	400Ah / 4800Wh

Parameter
MPPT Rating
Runtime (180W load)
Mast
System Weight
Packed Size
Protection



1305W

Solar Power

21.6kWh

Battery

350W

Max Load

TECHNICAL SPECIFICATIONS

Parameter	Value	Unit	Parameter
Model	WP-21600T	—	MPPT Controller
Variants	WP-21600T-DC / WP-21600T-AC	—	Max PV Input
DC Output	24 V DC	WP-21600T-DC	Mast
AC Output	220 V AC	WP-21600T-AC	Camera Box
Solar Panels	3 x 435W Monocrystalline	1305W total	System Weight
Battery	High-Temp Lead Acid, 3S2P	900Ah / 21,600Wh	Protection / Wind

WakeCap Power 21600T

WP-21600T

1305W Solar | 21.6kWh Lead Acid | Heavy-Duty Trailer Power Station

Highest-capacity trailer power station in the WakeCap portfolio. 9m manual mast (24V), and EPEVER 60A MPPT controller for heavy-duty applications. Available in DC (WP-21600T-DC) and AC (WP-21600T-AC) variants.

KEY FEATURES

- ✓ 9m manual mast with CAT6 + power routing
- ✓ 6×150Ah lead-acid batteries (3S2P, 24V)
- ✓ EPEVER 60A MPPT, 98% efficiency
- ✓ 3×435W mono panels (1305W total)
- ✓ DC variant (WP-21600T-DC): 24V DC output
- ✓ AC variant (WP-21600T-AC): 220V AC output

Product Comparison

Side-by-side comparison of all WakeCap Power Solutions products.

Parameter	WP-384	WP-768	WP-4800T
Solar Power	80W	100W	450W
Panel Config	2 x 40W	2 x 50W	3 x 150W
Panel Efficiency	≥23%	>22%	>20%
Battery Chemistry	LiFePO ₄	LiFePO ₄	GEL Lead Acid
Battery Capacity	30Ah / 384Wh	60Ah / 768Wh	400Ah / 4.8kWh
Cycle Life	2000–5000	2000–5000	500–800
Calendar Life	8–10 years	8–10 years	5–7 years
System Voltage	12V DC	12V DC	12V DC
Max Target Load	8W	15W	100W
Max Load (24h)	~8W	~15W	~100W
MPPT Efficiency	>95%	96.5%	95%
IP Rating	IP66	IP66	IP65
Operating Temp	-20 to +50°C	-30 to +85°C	-20 to +85°C
Form Factor	Pole Mount	Pole Mount	Trailer
Mast	—	—	6.5m Pneumatic
System Weight	~5.5 kg	23 kg	525 kg
Vehicle Access	Light vehicle	Light vehicle	Pickup + trailer
Ground Area	N/A (pole)	N/A (pole)	~4 m ²
Output Variants	—	—	DC (12V) / AC (220V)

WakeCap Technologies

Contact: Zishan Shahzad — zishan.shahzad@wakecap.com