



CECS545-Artificial Intelligence

Logical Agents

Dr. Roman Yampolskiy

Outline

- ◇ Knowledge-based agents
- ◇ Wumpus world
- ◇ Logic in general—models and entailment
- ◇ Propositional (Boolean) logic
- ◇ Equivalence, validity, satisfiability
- ◇ Inference rules and theorem proving
 - forward chaining
 - backward chaining
 - resolution

Automating Deductive Reasoning

- Aims of automated deduction
 - Deduce new knowledge from old
 - Prove/disprove some open conjectures
- Theorem proving
 - Search for a path from axioms to theorem statement
 - Operators are **(sound) inference rules**
- Applications:
 - Agents that use **deductive inference**
 - Mechanising and automating mathematics
 - Verifying hardware and software specifications
 - The semantic web

Inference Rules

- **A entails B** iff
 - B is true when A is true
 - Any model of A is a model of B
- Then this is a sound inference rule

$$\frac{A}{B}$$

- Axioms \Rightarrow C \Rightarrow D \Rightarrow ... \Rightarrow Z \Rightarrow Theorem
 - Each step is application of **inference rule**
 - Theorem is **entailed** by the axioms

Tautologies

- S: $(X \rightarrow (Y \wedge Z)) \leftrightarrow ((X \rightarrow Y) \wedge (X \rightarrow Z))$
 - Show that no matter what truth values for X, Y and Z
 - The statement S is always true

X	Y	Z	$Y \wedge Z$	$X \rightarrow Y$	$X \rightarrow Z$	$X \rightarrow (Y \wedge Z)$	$((X \rightarrow Y) \wedge (X \rightarrow Z))$	S
true	true	true	true	true	true	true	true	true
true	true	false	false	true	false	false	false	true
true	false	true	false	false	true	false	false	true
true	false	false	false	false	false	false	false	true
false	true	true	true	true	true	true	true	true
false	true	false	false	true	true	true	true	true
false	false	true	false	true	true	true	true	true
false	false	false	false	true	true	true	true	true

- Columns 7 and 8 are always the same

Inference with Tautologies

- $P \wedge Q \leftrightarrow Q \wedge P$ is obviously true
 - Regardless of meaning or truth values of P and Q
 - This is content-free and a **tautology**
- One way to define a rule of inference:
 - We can replace $P \wedge Q$ with $Q \wedge P$, and vice versa
 - They are true for same models
 - Replacing one for other preserves soundness

Propositional Inference Rules

- Rewrite rules are good for bidirectional search
 - But we don't need equivalence, just entailment
- Classic example
 - All men are mortal, socrates is a man
 - Therefore: Socrates is mortal
- This is an instance of an inference rule
 - Known as **Modus Ponens** (Aristotle)


$$\frac{A \rightarrow B, \quad A}{B}$$

- Above line: what we know, below: what we can deduce

Soundness of Modus Ponens

A	B	$A \rightarrow B$	Top: $A \rightarrow B, A$	Bottom: B
True	True	True	True	True
True	False	False	False	False
False	True	True	False	True
False	False	True	False	True

Knowledge bases



Knowledge base = set of sentences in a **formal** language

Declarative approach to building an agent (or other system):

TELL it what it needs to know

Then it can **ASK** itself what to do—answers should follow from the KB

Agents can be viewed at the **knowledge level**

i.e., **what they know**, regardless of how implemented

Or at the **implementation level**

i.e., data structures in KB and algorithms that manipulate them

A simple knowledge-based agent

```
function KB-AGENT(percept) returns an action  
  static: KB, a knowledge base  
         t, a counter, initially 0, indicating time  
  
  TELL(KB, MAKE-PERCEPT-SENTENCE(percept, t))  
  action ← ASK(KB, MAKE-ACTION-QUERY(t))  
  TELL(KB, MAKE-ACTION-SENTENCE(action, t))  
  t ← t + 1  
  return action
```

The agent must be able to:

- Represent states, actions, etc.

- Incorporate new percepts

- Update internal representations of the world

- Deduce hidden properties of the world

- Deduce appropriate actions

Wumpus World PEAS description

Performance measure

gold +1000, death -1000

-1 per step, -10 for using the arrow

Environment

Squares adjacent to wumpus are smelly

Squares adjacent to pit are breezy


Glitter iff gold is in the same square

Shooting kills wumpus if you are facing it

Shooting uses up the only arrow

Grabbing picks up gold if in same square

Releasing drops the gold in same square



Actuators Left turn, Right turn,

Forward, Grab, Release, Shoot

Sensors Breeze, Glitter, Smell

Wumpus world characterization

Observable?? No—only **local** perception

Deterministic?? Yes—outcomes exactly specified

Episodic?? No—sequential at the level of actions

Static?? Yes—Wumpus and Pits do not move


Discrete?? Yes

Single-agent?? Yes—Wumpus is essentially a natural feature


Exploring a wumpus world

OK			
OK <div>A</div>	OK		


Exploring a wumpus world




Exploring a wumpus world




Exploring a wumpus world




Exploring a wumpus world




Exploring a wumpus world




Exploring a wumpus world



Exploring a wumpus world




Other tight spots



Breeze in (1,2) and (2,1)
 \Rightarrow no safe actions

Assuming pits uniformly distributed,
 (2,2) has pit w/ prob 0.86, vs. 0.31



Smell in (1,1)
 \Rightarrow cannot move

Can use a strategy of **coercion**:

shoot straight ahead

wumpus was there \Rightarrow dead \Rightarrow safe

wumpus wasn't there \Rightarrow safe

Logic in general

Logics are formal languages for representing information such that conclusions can be drawn

Syntax defines the sentences in the language

Semantics define the “meaning” of sentences;
i.e., define **truth** of a sentence in a world

E.g., the language of arithmetic

$x + 2 \geq y$ is a sentence; $x^2 + y >$ is not a sentence

$x + 2 \geq y$ is true iff the number $x + 2$ is no less than the number y

$x + 2 \geq y$ is true in a world where $x = 7$, $y = 1$

$x + 2 \geq y$ is false in a world where $x = 0$, $y = 6$

Entailment

Entailment means that one thing **follows from** another:

$$KB \models \alpha$$

Knowledge base KB entails sentence α

if and only if

α is true in all worlds where KB is true

E.g., the KB containing “the Giants won” and “the Reds won” entails “Either the Giants won or the Reds won”

E.g., $x + y = 4$ entails $4 = x + y$

Entailment is a relationship between sentences (i.e., **syntax**) that is based on **semantics**

Note: brains process **syntax** (of some sort)

Models

Logicians typically think in terms of **models**, which are formally structured worlds with respect to which truth can be evaluated


We say m is a model of a sentence α if α is true in m

$M(\alpha)$ is the set of all models of α

Then $KB \models \alpha$ if and only if $M(KB) \subseteq M(\alpha)$

E.g. $KB = \text{Giants won and Reds won}$

$\alpha = \text{Giants won}$




Entailment in the wumpus world









Situation after detecting nothing in $[1,1]$,
moving right, breeze in $[2,1]$

Consider possible models for ?s
assuming only pits


3 Boolean choices \Rightarrow 8 possible models



Wumpus models




Wumpus models



KB = wumpus-world rules + observations


Wumpus models



KB = wumpus-world rules + observations


α_1 = "[1,2] is safe", $KB \models \alpha_1$, proved by model checking

Wumpus models



KB = wumpus-world rules + observations

Wumpus models



KB = wumpus-world rules + observations

α_2 = "[2,2] is safe", $KB \not\models \alpha_2$

Inference

$KB \vdash_i \alpha$ = sentence α can be derived from KB by procedure i

Consequences of KB are a haystack; α is a needle.

Entailment = needle in haystack; inference = finding it

Soundness: i is sound if

whenever $KB \vdash_i \alpha$, it is also true that $KB \models \alpha$

Completeness: i is complete if

whenever $KB \models \alpha$, it is also true that $KB \vdash_i \alpha$

Preview: we will define a logic (first-order logic) which is expressive enough to say almost anything of interest, and for which there exists a sound and complete inference procedure.

That is, the procedure will answer any question whose answer follows from what is known by the KB .

Propositional logic: Syntax

Propositional logic is the simplest logic—illustrates basic ideas

The proposition symbols P_1, P_2 etc are sentences

If S is a sentence, $\neg S$ is a sentence (negation)

If S_1 and S_2 are sentences, $S_1 \wedge S_2$ is a sentence (conjunction)

If S_1 and S_2 are sentences, $S_1 \vee S_2$ is a sentence (disjunction)

If S_1 and S_2 are sentences, $S_1 \Rightarrow S_2$ is a sentence (implication)

If S_1 and S_2 are sentences, $S_1 \Leftrightarrow S_2$ is a sentence (biconditional)

Propositional logic: Semantics

Each model specifies true/false for each proposition symbol

E.g. $P_{1,2}$ $P_{2,2}$ $P_{3,1}$
true true false

(With these symbols, 8 possible models, can be enumerated automatically.)

Rules for evaluating truth with respect to a model m :

$\neg S$ is true iff S is false

$S_1 \wedge S_2$ is true iff S_1 is true **and** S_2 is true

$S_1 \vee S_2$ is true iff S_1 is true **or** S_2 is true

$S_1 \Rightarrow S_2$ is true iff S_1 is false **or** S_2 is true

i.e., is false iff S_1 is true **and** S_2 is false

$S_1 \Leftrightarrow S_2$ is true iff $S_1 \Rightarrow S_2$ is true **and** $S_2 \Rightarrow S_1$ is true

Simple recursive process evaluates an arbitrary sentence, e.g.,

$\neg P_{1,2} \wedge (P_{2,2} \vee P_{3,1}) = \text{true} \wedge (\text{false} \vee \text{true}) = \text{true} \wedge \text{true} = \text{true}$

Truth tables for connectives

P	Q	$\neg P$	$P \wedge Q$	$P \vee Q$	$P \Rightarrow Q$	$P \Leftrightarrow Q$
<i>false</i>	<i>false</i>	<i>true</i>	<i>false</i>	<i>false</i>	<i>true</i>	<i>true</i>
<i>false</i>	<i>true</i>	<i>true</i>	<i>false</i>	<i>true</i>	<i>true</i>	<i>false</i>
<i>true</i>	<i>false</i>	<i>false</i>	<i>false</i>	<i>true</i>	<i>false</i>	<i>false</i>
<i>true</i>	<i>true</i>	<i>false</i>	<i>true</i>	<i>true</i>	<i>true</i>	<i>true</i>

Wumpus world sentences

Let $P_{i,j}$ be true if there is a pit in $[i, j]$.

Let $B_{i,j}$ be true if there is a breeze in $[i, j]$.

$$\neg P_{1,1}$$

$$\neg B_{1,1}$$

$$B_{2,1}$$

“Pits cause breezes in adjacent squares”

$$B_{1,1} \Leftrightarrow (P_{1,2} \vee P_{2,1})$$

$$B_{2,1} \Leftrightarrow (P_{1,1} \vee P_{2,2} \vee P_{3,1})$$

“A square is breezy **if and only if** there is an adjacent pit”

Logical equivalence

Two sentences are **logically equivalent** iff true in same models:

$\alpha \equiv \beta$ if and only if $\alpha \models \beta$ and $\beta \models \alpha$

$$(\alpha \wedge \beta) \equiv (\beta \wedge \alpha) \quad \text{commutativity of } \wedge$$

$$(\alpha \vee \beta) \equiv (\beta \vee \alpha) \quad \text{commutativity of } \vee$$

$$((\alpha \wedge \beta) \wedge \gamma) \equiv (\alpha \wedge (\beta \wedge \gamma)) \quad \text{associativity of } \wedge$$

$$((\alpha \vee \beta) \vee \gamma) \equiv (\alpha \vee (\beta \vee \gamma)) \quad \text{associativity of } \vee$$

$$\neg(\neg\alpha) \equiv \alpha \quad \text{double-negation elimination}$$

$$(\alpha \Rightarrow \beta) \equiv (\neg\beta \Rightarrow \neg\alpha) \quad \text{contraposition}$$

$$(\alpha \Rightarrow \beta) \equiv (\neg\alpha \vee \beta) \quad \text{implication elimination}$$

$$(\alpha \Leftrightarrow \beta) \equiv ((\alpha \Rightarrow \beta) \wedge (\beta \Rightarrow \alpha)) \quad \text{biconditional elimination}$$

$$\neg(\alpha \wedge \beta) \equiv (\neg\alpha \vee \neg\beta) \quad \text{De Morgan}$$

$$\neg(\alpha \vee \beta) \equiv (\neg\alpha \wedge \neg\beta) \quad \text{De Morgan}$$

$$(\alpha \wedge (\beta \vee \gamma)) \equiv ((\alpha \wedge \beta) \vee (\alpha \wedge \gamma)) \quad \text{distributivity of } \wedge \text{ over } \vee$$

$$(\alpha \vee (\beta \wedge \gamma)) \equiv ((\alpha \vee \beta) \wedge (\alpha \vee \gamma)) \quad \text{distributivity of } \vee \text{ over } \wedge$$

Validity and satisfiability

A sentence is **valid** if it is true in **all** models,

e.g., *True*, $A \vee \neg A$, $A \Rightarrow A$, $(A \wedge (A \Rightarrow B)) \Rightarrow B$

Validity is connected to inference via the **Deduction Theorem**:

$KB \models \alpha$ if and only if $(KB \Rightarrow \alpha)$ is valid

A sentence is **satisfiable** if it is true in **some** model

e.g., $A \vee B$, C

A sentence is **unsatisfiable** if it is true in **no** models

e.g., $A \wedge \neg A$

Satisfiability is connected to inference via the following:

$KB \models \alpha$ if and only if $(KB \wedge \neg \alpha)$ is unsatisfiable

i.e., prove α by *reductio ad absurdum*

Proof methods

Proof methods divide into (roughly) two kinds:

Application of inference rules

- Legitimate (sound) generation of new sentences from old
- **Proof** = a sequence of inference rule applications
 - Can use inference rules as operators in a standard search alg.
- Typically require translation of sentences into a **normal form**

Model checking

- truth table enumeration (always exponential in n)
- improved backtracking, e.g., Davis–Putnam–Logemann–Loveland
- heuristic search in model space (sound but incomplete)
 - e.g., min-conflicts-like hill-climbing algorithms

Forward and backward chaining

Horn Form (restricted)

KB = **conjunction** of **Horn clauses**

Horn clause =

◇ proposition symbol; or

◇ (conjunction of symbols) \Rightarrow symbol

E.g., $C \wedge (B \Rightarrow A) \wedge (C \wedge D \Rightarrow B)$

Modus Ponens (for Horn Form): complete for Horn KBs

$$\frac{\alpha_1, \dots, \alpha_n, \quad \alpha_1 \wedge \dots \wedge \alpha_n \Rightarrow \beta}{\beta}$$

Can be used with **forward chaining** or **backward chaining**.

These algorithms are very natural and run in **linear** time

Forward chaining

Idea: fire any rule whose premises are satisfied in the *KB*,
add its conclusion to the *KB*, until query is found

$$P \Rightarrow Q$$

$$L \wedge M \Rightarrow P$$


$$B \wedge L \Rightarrow M$$

$$A \wedge P \Rightarrow L$$


$$A \wedge B \Rightarrow L$$

A


B




Forward chaining example




Forward chaining example




Forward chaining example




Forward chaining example




Forward chaining example




Forward chaining example



Forward chaining example



Forward chaining example



Backward chaining

Idea: work backwards from the query q :

- to prove q by BC,

- check if q is known already, or

- prove by BC all premises of some rule concluding q


Avoid loops: check if new subgoal is already on the goal stack

Avoid repeated work: check if new subgoal


- 1) has already been proved true, or

- 2) has already failed


Backward chaining example




Backward chaining example




Backward chaining example




Backward chaining example




Backward chaining example




Backward chaining example




Backward chaining example




Backward chaining example




Backward chaining example



Backward chaining example



Backward chaining example



Forward vs. backward chaining

FC is **data-driven**, cf. automatic, unconscious processing,
e.g., object recognition, routine decisions

May do lots of work that is irrelevant to the goal

BC is **goal-driven**, appropriate for problem-solving,
e.g., Where are my keys? How do I get into a PhD program?

Complexity of BC can be **much less** than linear in size of KB

Conversion to CNF

$$B_{1,1} \Leftrightarrow (P_{1,2} \vee P_{2,1})$$

1. Eliminate \Leftrightarrow , replacing $\alpha \Leftrightarrow \beta$ with $(\alpha \Rightarrow \beta) \wedge (\beta \Rightarrow \alpha)$.

$$(B_{1,1} \Rightarrow (P_{1,2} \vee P_{2,1})) \wedge ((P_{1,2} \vee P_{2,1}) \Rightarrow B_{1,1})$$

2. Eliminate \Rightarrow , replacing $\alpha \Rightarrow \beta$ with $\neg\alpha \vee \beta$.

$$(\neg B_{1,1} \vee P_{1,2} \vee P_{2,1}) \wedge (\neg(P_{1,2} \vee P_{2,1}) \vee B_{1,1})$$

3. Move \neg inwards using de Morgan's rules and double-negation:

$$(\neg B_{1,1} \vee P_{1,2} \vee P_{2,1}) \wedge ((\neg P_{1,2} \wedge \neg P_{2,1}) \vee B_{1,1})$$

4. Apply distributivity law (\vee over \wedge) and flatten:

$$(\neg B_{1,1} \vee P_{1,2} \vee P_{2,1}) \wedge (\neg P_{1,2} \vee B_{1,1}) \wedge (\neg P_{2,1} \vee B_{1,1})$$

Summary

Logical agents apply **inference** to a **knowledge base** to derive new information and make decisions

Basic concepts of logic:

- **syntax**: formal structure of **sentences**
- **semantics**: **truth** of sentences wrt **models**
- **entailment**: necessary truth of one sentence given another
- **inference**: deriving sentences from other sentences
- **soundness**: derivations produce only entailed sentences
- **completeness**: derivations can produce all entailed sentences

Wumpus world requires the ability to represent partial and negated information, reason by cases, etc.

Forward, backward chaining are linear-time, complete for Horn clauses
Resolution is complete for propositional logic

Propositional logic lacks expressive power

The End!

