

Problem 6

Problem Description

In this problem you will train decision tree and random forest models using sklearn on a real world dataset. The dataset is the *Cylinder Bands Data Set* from the UCI Machine Learning Repository: <https://archive.ics.uci.edu/ml/datasets/Cylinder+Bands>. The dataset is generated from rotogravure printers, with 39 unique features, and a binary classification label for each sample. The class is either 0, for 'band' or 1 for 'no band', where banding is an undesirable process delay that arises during the rotogravure printing process. By training ML models on this dataset, you could help identify or predict cases where these process delays are avoidable, thereby improving the efficiency of the printing. For the sake of this exercise, we only consider features 21-39 in the above link, and have removed any samples with missing values in that range. No further processing of the data is required on your behalf. The data has been partitioned into a training and testing set using an 80/20 split. Your models will be trained on just the train set, and accuracy results will be reported on both the training and testing sets.

Fill out the notebook as instructed, making the requested plots and printing necessary values.

You are welcome to use any of the code provided in the lecture activities.

Summary of deliverables:

- Accuracy function
- Report accuracy of the DT model on the training and testing set
- Report accuracy of the Random Forest model on the training and testing set

Imports and Utility Functions:

```
In [39]: import numpy as np
from sklearn.tree import DecisionTreeClassifier
from sklearn.ensemble import RandomForestClassifier
```

Load the data

Use the `np.load()` function to load "w5-hw1-train.npy" (training data) and "w5-hw1-test.npy" (testing data). The first 19 columns of each are the features. The last column is the label

```
In [40]: # YOUR CODE GOES HERE
train_data = np.load(r"C:\Users\zsqu4\Desktop\ML HW\ML-for-engineers\HW5\data\w5-hw1.npy")
train_X = train_data[:, :19]
train_y = train_data[:, 19]

test_data = np.load(r"C:\Users\zsqu4\Desktop\ML HW\ML-for-engineers\HW5\data\w5-hw1.npy")
test_X = test_data[:, :19]
test_y = test_data[:, 19]
```

Write an accuracy function

Write a function `accuracy(pred, label)` that takes in the model's prediction, and returns the percentage of predictions that match the corresponding labels.

```
In [41]: # YOUR CODE GOES HERE
def accuracy(pred, label):
    return 100 * np.sum(pred == label) / len(label)
```

Train a decision tree model

Train a decision tree using `DecisionTreeClassifier()` with a `max_depth` of 10 and using a `random_state` of 0 to ensure repeatable results. Print the accuracy of the model on both the training and testing sets.

```
In [42]: # YOUR CODE GOES HERE
dt = DecisionTreeClassifier(max_depth=10, random_state=0)
# dt.fit(test_X, test_y)

dt.fit(train_X, train_y)
pred_train = dt.predict(train_X)
acc_train = accuracy(pred_train, train_y)

pred_test = dt.predict(test_X)
acc_test = accuracy(pred_test, test_y)

print(acc_train)
print(acc_test)
```

65.75342465753425

93.12714776632302

```
[1. 1. 0. 1. 1. 1. 0. 1. 0. 1. 0. 0. 1. 1. 0. 1. 1. 0. 0. 1. 1. 1. 1. 1.
 1. 1. 1. 1. 0. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 0. 0.
 0. 1. 1. 1. 1. 1. 1. 0. 1. 0. 1. 1. 1. 0. 1. 1. 1. 1. 1. 1. 0. 0. 0.
 1.]
[1. 1. 1. 0. 1. 0. 0. 0. 0. 0. 1. 0. 1. 0. 1. 1. 1. 0. 0. 1. 1. 0. 0.
 0. 1. 1. 0. 0. 1. 0. 0. 1. 1. 1. 1. 1. 1. 1. 1. 1. 0. 1. 1. 1. 0. 1.
 1. 1. 0. 1. 1. 1. 1. 0. 0. 1. 1. 1. 1. 1. 1. 1. 1. 0. 1. 0. 0. 1.
 1.]
```

Train a random forest model

Train a random forest model using `RandomForestClassifier()` with a `max_depth` of 10, a `n_estimators` of 100, and using a random state of 0 to ensure repeatable results. Print the accuracy of the model on both the training and testing sets.

```
In [45]: # YOUR CODE GOES HERE
rfc = RandomForestClassifier(max_depth= 10, n_estimators=100,random_state= 0)

rfc.fit(train_X,train_y)
pred_train = rfc.predict(train_X)
acc_train = accuracy(pred_train,train_y)

pred_test = rfc.predict(test_X)
acc_test = accuracy(pred_test,test_y)

print(acc_train)
print(acc_test)
```

100.0

82.1917808219178

Discuss the performance of the models

Compare the training and testing accuracy of the two models, and explain why the random forest model is advantageous compared to a standard decision tree model

YOUR ANSWER GOES HERE

The overall accuracy of random forest model is much higher than that of decision tree model. Random forest model is more advantageous as it is much less prone to overfitting ,opposite to decision tree model ,which often tends to overfit at deep levels.