

M10-L1 Problem 1

In this problem you will implement the K-Means algorithm from scratch, and use it to cluster two datasets: a "blob" shaped dataset with three classes, and a "moon" shaped dataset with two classes.

```
In [112... import numpy as np
import matplotlib.pyplot as plt

from sklearn.datasets import make_blobs, make_moons


## DO NOT MODIFY
def plotter(x, y, labels = None, centers = None):
    fig = plt.figure(dpi = 200)
    for i in range(len(np.unique(y))):
        if labels is not None:
            plt.scatter(x[labels == i, 0], x[labels == i, 1], alpha = 0.5)
        else:
            plt.scatter(x[y == i, 0], x[y == i, 1], alpha = 0.5)
    if labels is not None:
        if (labels != y).any():
            plt.scatter(x[labels != y, 0], x[labels != y, 1], s = 100, c = 'None',
            if centers is not None:
                plt.scatter(centers[:,0], centers[:,1], c = 'red', label = 'Cluster Centers')
    plt.xlabel('$x_0$')
    plt.ylabel('$x_1$')
    if labels is not None or centers is not None:
        plt.legend()
    plt.show()
```

We will use `sklearn.datasets.make_blobs()` to generate the dataset. The `random_state = 12` argument is used to ensure all students have the same data.

```
In [113... ## DO NOT MODIFY
x, y = make_blobs(n_samples = 300, n_features = 2, random_state = 12)
```

Visualize the data using the `plotter(x,y)` function. You do not need to pass the `labels` or `centers` arguments

```
In [114... ## YOUR CODE GOES HER
plotter(x,y)
```



Now we will begin to create our own K-Means function.

First you will write a function `find_cluster(point, centers)` which returns the index of the cluster center closest to the given point.

- `point` is a one dimensional numpy array containing the x_0 and x_1 coordinates of a single data point
- `centers` is a 3×2 numpy array containing the coordinates of the three cluster centers at any given iteration
- **return** the index of the closest cluster center

```
In [115... ## FILL IN THE FOLLOWING FUNCTION
def find_cluster(point, centers):
    index = -1
    closest = np.inf
    for i, center in enumerate(centers):
        dis = np.sqrt((center[0]-point[0])**2 + (center[1]-point[1])**2)
        if dis < closest:
            closest = dis
            index = i
    return index
```

Next, write a function `assign_labels(x, centers)` which will loop through all the points in `x` and use the `find_cluster()` function we just wrote to assign the label

of the closest cluster center. Your function should return the labels

- `x` is a 300×2 numpy array containing the coordinates of all the points in the dataset
- `centers` is a 3×2 numpy array containing the coordinates of the three cluster centers at any given iteration
- **return** a one dimensional numpy array of length 300 containing the corresponding label for each point in `x`

```
In [116... ## FILL IN THE FOLLOWING FUNCTION
def assign_labels(x, centers):
    labels = np.zeros(x.shape[0], dtype=int)
    for idx, point in enumerate(x):
        labels[idx] = find_cluster(point, centers)
    return labels
```

Next, write a function `update_centers(x, labels)` which will compute the new cluster centers using the centroid of each cluster, provided all the points in `x` and their corresponding labels

- `x` is a 300×2 numpy array containing the coordinates of all the points in the dataset
- `labels` is a one dimensional numpy array of length 300 containing the corresponding label for each point in `x`
- **return** a 3×2 numpy array containing the coordinates of the three cluster centers

```
In [117... ## FILL IN THE FOLLOWING FUNCTION
def update_centers(x, labels):
    unique_labels = np.unique(labels)
    updated_centers = np.zeros((len(unique_labels), x.shape[1]))
    for i, label in enumerate(unique_labels):
        cluster_points = x[labels == label]
        updated_centers[i] = np.mean(cluster_points, axis=0)
    return updated_centers
```

Finally write a function `myKMeans(x, init_centers)` which will run the KMeans algorithm, provided all the points in `x` and the coordinates of the initial cluster centers in `init_centers`. Run the algorithm until there is no change in cluster membership in subsequent iterations. Your function should return both the `labels`, the labels of each point in `x`, and `centers`, the final coordinates of each of the cluster centers.


- `x` is a 300×2 numpy array containing the coordinates of all the points in the dataset
- `init_centers` is a 3×2 numpy array containing the coordinates of the three cluster centers provided to you

- **return** `labels` and `centers` as defined above

```
In [ ]: ## FILL IN THE FOLLOWING FUNCTION
def myKMeans(x, init_centers):
    labels = assign_labels(x,init_centers)
    new_labels = np.zeros(len(labels))
    new_centers = np.zeros(init_centers.shape)
    while True:
        new_centers = update_centers(x, labels)
        new_labels = assign_labels(x, new_centers)
        if np.array_equal(new_labels, labels):
            break
        labels = new_labels.copy()
    return labels, new_centers
```

Now use your `myKMeans()` function to cluster the provided data points `x` and set the initial cluster centers as `init_centers = np.array([[-5,5],[0,0],[-10,10]])`. Then use the provided plotting function, `plotter(x,y,labels,centers)` to visualize your model's clustering.

```
In [119... ## YOUR CODE GOES HERE
init_centers = np.array([[ -5,5],[0,0],[ -10,10]])
labels,centers = myKMeans(x,init_centers)
plotter(x,y,labels,centers)
```



Moon Dataset


Now we will try using our `myKMeans()` function on a more challenging dataset, as generated below.

```
In [120... ## DO NOT MODIFY
x,y = make_moons(n_samples = 300, noise = 0.1, random_state = 0)
```

Visualize the data using the `plotter(x,y)` function.

```
In [121... ## YOUR CODE GOES HERE

plotter(x,y)
```



Using your `myKMeans()` function and `init_centers = np.array([[0,1], [1,-0.5]])` cluster the data, and visualize the results using `plotter(x,y,labels,centers)`.

```
In [122... ## YOUR CODE GOES HERE
init_centers = np.array([[0,1],[1,-0.5]])
labels,centers = myKMeans(x,init_centers)
plotter(x,y,labels,centers)
```

