



University of
Nottingham

UK | CHINA | MALAYSIA

Progression Review Report

Formalizing Higher-Order Containers

Zhili Tian

Supervised by Thorsten Altenkirch

& Ulrik Buchholtz



FP LAB
NOTTINGHAM

Functional Programming Lab

School of Computer Science

University of Nottingham

July 17, 2025

Abstract

Giving a short overview of the work in your project.[1]

Contents

1	Introduction	1
1.1	Background and Motivation	1
1.2	Aims and Objectives	1
1.3	Progress to Date	1
1.4	Overview of the Report	2
2	Prerequisites	3
2.1	Type Theory	3
2.2	Category Theory	6
3	Conducted Research	8
3.1	Literature Review	8
3.2	Types and Categorical Semantics	8
3.2.1	Inductive Types	8
3.2.2	Coinductive Types	11
3.3	Containers	11
3.3.1	Strict Positivity	11
3.3.2	Syntax and Semantics	12
3.3.3	Categorical Structure	12
3.3.4	Semiring Structure	13
3.3.5	W and M	14
3.4	Questions	15
3.4.1	Bush	15
4	Research Outcomes	16
4.1	Higher-order Containers	16
4.1.1	Higher-order Functoriality	16
4.1.2	Syntax and Semantics	16

4.1.3	Algebraic Structure	16
4.1.4	Simply-Typed Lambda Calculus	16
5	Conclusions	17
6	Future Work Plan	18
7	Appendix	19
	References	19

Chapter 1

Introduction

1.1 Background and Motivation

The concept of types is one of the most important features in most modern programming languages. It is introduced to classify variables and functions, enabling more meaningful and readable codes as well as ensuring type correctness. Types such as *boolean*, *natural number*, *list*, *binary tree*, etc. are massively used in everyday programming.

TODO

1.2 Aims and Objectives

TODO

- bla bla
- bla bla

1.3 Progress to Date

TODO : progress and achievements during this stage, training courses, seminars and presentations.

1.4 Overview of the Report

- Chapter 2 - Literature Review: reviews the related literature, and further motivates our project
- Chapter 3 - Conducted Research: covers background knowledge, topics studied and questions. We introduce type theory, category theory, containers, etc.
- Chapter 4 - Future Work Plan: TODO

Chapter 2

Prerequisites

We adopt Martin-Löf type theory - MLTT and category theory as the framework. In particular, we use Agda, an implemented programming language, for our study and in this report.

Assuming $a : A$ and $b : B$, the following are standard Agda syntax for common algebraic data types:

- $\mathbf{1}$ - Empty Type, with no term
- \mathbf{r} - Unit Type, with $\mathbf{tt} : \mathbf{r}$
- \times - Product Type, with $a, b : A \times B$
- \mathbf{u} - Coproduct (Sum) Type, with $\mathbf{inj}_1 a : A \mathbf{u} B$, and $\mathbf{inj}_2 b : A \mathbf{u} B$

2.1 Type Theory

Type theory is a formal language of mathematical logics, designed to serve as a foundation for mathematics and programming languages. Various flavors of type theories exist, differing in their treatment of equality, interpretation of types, computational univalence, etc. We introduce basic concepts in type theory and outline the development.

Universes

In type theory, everything has a type, even types have a type. We call it the universe and denote it as \mathbf{Type} . Such that:

$\perp, \tau, \mathbb{N}, \dots : \text{Type}$

But what is the type of `Type`? It turns out if we naively postulate `Type` : `Type`, then it leads to Girard's paradox which causes inconsistency in the system. The solution is to build hierarchy of the universes:

`Type` : `Type`₁ : `Type`₂ : ...

where each universe is bigger than the previous ones. In addition, if a type is in a universe, it is also in a bigger universe.

Type Families

The concepts of Type families can be viewed as generalization of ordinary functions, where the codomain is allowed to be `Type`. For example a predicate that tells the evenness can be defined as a type family over `ℕ`:

```
isEven : ℕ → Type
isEven zero = τ
isEven (suc zero) = ⊥
isEven (suc (suc n)) = isEven n
```

MLTT

Per Martin-Löf introduced MLTT as a constructive foundations for mathematics. It is also known as the intuitionistic type theory or dependent type theory. From a programming point of view, it adds type level control of data types. For example we can define vector:

```
data Vec (A : Type) : ℕ → Type where
  [] : Vec A 0
  _::_ : {n : ℕ} → A → Vec A n → Vec A (suc n)
```

According to this definition, `Vec ℕ 3` should have exactly 3 numbers:

```
vec : Vec ℕ 3
vec = 1 :: 2 :: 3 :: []
```


Curry-Howard Correspondence

It also generalizes function type \rightarrow into dependent function type Π and pair type \times into dependent pair type Σ .

```
 $\Pi : (A : \text{Type}) (B : A \rightarrow \text{Type}) \rightarrow \text{Type}$ 
 $\Pi A B = (a : A) \rightarrow B a$ 

record  $\Sigma (A : \text{Type}) (B : A \rightarrow \text{Type}) : \text{Type}$  where
  constructor  $_, -$ 
  field
     $\text{proj}_1 : A$ 
     $\text{proj}_2 : B \text{ proj}_1$ 
```

Most importantly, the Curry-Howard correspondence interprets Π as universal quantification \forall , and Σ as existential quantification. We can show there is some even number exists using Σ :

```
 $\exists\text{Even} : \Sigma \mathbb{N} \text{ isEven}$ 
 $\exists\text{Even} = 2, \text{tt}$ 
```

Equalities

It is also important to distinguish different notions of equality. The definitional equality is a very strong notion of equality which two terms are reduced to the same normal forms. However, most theorems and results of practical interests do not hold definitionally. Their proofs normally involves doing case analysis, building extra lemmas, etc. We refer this weaker notion of equality the propositional equality.

In Agda, (definitional) equality is represented by identity type, which is a binary type family over any type A , and it is witnessed by `refl`.

```
data  $_{\equiv} \{A : \text{Type}\} (x : A) : A \rightarrow \text{Type}$  where
   $\text{refl} : x \equiv x$ 
```

Therefore, if a proposition is hold directly by `refl`, then It is definitional equality. In contrast, if an explicit proof is required, then it is propositional equality.

```
 $\text{thm0} : 1 + 1 \equiv 2$ 
 $\text{thm0} = \text{refl}$ 
```

```

thm1 : (n : ℕ) → 1 + n ≡ n + 1
thm1 zero = refl
thm1 (suc n) = cong suc (thm1 n)
where
  cong : {A B : Type} (f : A → B) {x y : A} → x ≡ y → f x ≡ f y
  cong f refl = refl

```

Function Extensionality

Here arises another question - what is the good notion of equality of functions? Function extensionality suggests that two functions should be considered as equal if they yield the same output for every input. However, in intensional type theory, for example Agda, where equality is defined as definitional equality, the `funExt` is not provable within the system and must instead be postulated.

```

postulate
  funExt : {A : Type} {B : A → Type} {f g : (x : A) → B x} →
    ((x : A) → f x ≡ g x) → f ≡ g

```

On the other hand, an extensional type theory suggests to treat two notions of equality as the same one. That is, it forces the proposition equality back into the definitional one. However, this approach has significant drawbacks: type checking becomes undecidable, and computation loses canonicity.

HoTT

The homotopy type theory provides a solution to lacking of extensionality in MLTT by adding the univalence axiom. The univalence axiom is introduced by Vladimir Voevodsky

Cubical TT

Finally, cubical type theory!!!

2.2 Category Theory

Categories

We define a category as follow:

Functors

Natural Transformations

Algebra

Chapter 3

Conducted Research

In this section, we will review related literatures, outline the topics studied and illustrate the current challenge. We assume the reader has basic knowledge in logics and functional programming.

3.1 Literature Review

TODO

3.2 Types and Categorical Semantics

3.2.1 Inductive Types

We give an informal definition of inductive types followed by some examples. An inductive type `A` is given by a finite number of data constructors, and a rule says how to define a function out of `A` to arbitrary type `B`.

Natural Number

The definition of natural number `N` follows exactly the Peano axiom. The first constructor says `zero` is a `N`. The second constructor is a function that sends `N` to `N`, which in other word, if `n` is a `N`, so is the `suc n`.

```
data N : Type where
  zero : N
  suc  : N → N
{-# BUILTIN NATURAL N #-}
```

```

_ :  $\mathbb{N} \uplus \mathbb{N}$ 
_ = inj1 zero

_ :  $\mathbb{N} \times \mathbb{N}$ 
_ = zero , zero

```

The \mathbb{N} itself is not so useful until we spell out its induction principle `indN`. In principle, whenever we need to define a function out of \mathbb{N} , we always using `indN`. That also corresponds to one of the Peano axioms.

```

indN : (P :  $\mathbb{N} \rightarrow \text{Type}$ )
      → P zero
      → ((n :  $\mathbb{N}$ ) → P n → P (suc n))
      → (n :  $\mathbb{N}$ ) → P n
indN P z s zero = z
indN P z s (suc n) = s n (indN P z s n)

double :  $\mathbb{N} \rightarrow \mathbb{N}$ 
double = indN (λ _ →  $\mathbb{N}$ ) zero (λ n dn → suc (suc dn))

```

It is rather verbose to explicitly call induction every time. Fortunately, we are able to instead use pattern-matching in Agda, which implements induction internally and guarantees correctness.

```

double' :  $\mathbb{N} \rightarrow \mathbb{N}$ 
double' zero = zero
double' (suc n) = suc (suc n)

```

Inductive Types are Initial Algebras

The category of algebra in `Type` of a given endofunctor $F : \text{Type} \rightarrow \text{Type}$ is defined as:

- Objects are:
 - A carrier type $A : \text{Type}$, and
 - A function $\alpha : F A \rightarrow A$
- Morphisms of (A, α) and (B, β) are:
 - A morphism $f : A \rightarrow B$, and

– A commuting diagram:

$$\begin{array}{ccc}
 F\ A & \xrightarrow{F\ f} & F\ B \\
 \downarrow \alpha & & \downarrow \beta \\
 A & \xrightarrow{f} & B
 \end{array}$$

After proving identity and composition of morphisms, we obtain a category of algebras. It turns out that in every such category, there exists an initial object which corresponds to an inductive type. We show a concrete example and discuss the general theory in later section.

Natural Number is Initial Algebra of Maybe

Natural number (together with its constructor) is the initial algebra of the $\tau\mathbb{M}_-$ functor, which is also known as the **Maybe**. To prove this, we first combine and rewrite **zero** and **suc** into equivalent form:

$$\begin{aligned}
 [z,s] &: \tau\mathbb{M}\ \mathbb{N} \rightarrow \mathbb{N} \\
 [z,s]\ (\text{inj}_1\ tt) &= \text{zero} \\
 [z,s]\ (\text{inj}_2\ n) &= \text{suc}\ n
 \end{aligned}$$

To show the initiality, we show for arbitrary algebra, there exists a unique morphism from algebra \mathbb{N} . That is to undefine **fold**:

$$\begin{aligned}
 \text{fold} &: (\tau\mathbb{M}\ X \rightarrow X) \rightarrow \mathbb{N} \rightarrow X \\
 \text{fold}\ \alpha\ \text{zero} &= \alpha\ (\text{inj}_1\ tt) \\
 \text{fold}\ \alpha\ (\text{suc}\ n) &= \alpha\ (\text{inj}_2\ (\text{fold}\ \alpha\ n))
 \end{aligned}$$

Then we construct the morphism mapping part of $\tau\mathbb{M}_-$ and check the following diagram commutes:

$$\begin{array}{ccc}
 \tau\mathbb{M}\ \mathbb{N} & \xrightarrow{\tau\mathbb{M}_1\ (\text{fold}\ \alpha)} & \tau\mathbb{M}\ X \\
 \downarrow [z,s] & & \downarrow \alpha \\
 \mathbb{N} & \xrightarrow{\text{fold}\ \alpha} & X
 \end{array}$$

$$\begin{aligned}
 \tau\mathbb{M}_1 &: (X \rightarrow Y) \rightarrow \tau\mathbb{M}\ X \rightarrow \tau\mathbb{M}\ Y \\
 \tau\mathbb{M}_1\ f\ (\text{inj}_1\ tt) &= \text{inj}_1\ tt \\
 \tau\mathbb{M}_1\ f\ (\text{inj}_2\ x) &= \text{inj}_2\ (f\ x) \\
 \text{commute} &: (\beta : \tau\mathbb{M}\ X \rightarrow X)\ (x : \tau\mathbb{M}\ \mathbb{N}) \\
 &\rightarrow \text{fold}\ \beta\ ([z,s]\ x) \equiv \beta\ (\tau\mathbb{M}_1\ (\text{fold}\ \beta)\ x) \\
 \text{commute}\ \beta\ (\text{inj}_1\ tt) &= \text{refl} \\
 \text{commute}\ \beta\ (\text{inj}_2\ n) &= \text{refl}
 \end{aligned}$$

3.2.2 Coinductive Types

One of the greatest power of category theory is that, whenever we define something, we always get an opposite version for free. Indeed, if we inverse all the morphisms in above diagram, then we will:

- talk about the category of coalgebras;
- obtain a definition of conatural number \mathbb{N}_∞ ;
- derive that \mathbb{N}_∞ is the terminal coalgebra of $\tau \cup _$

The definition of coalgebras is trivial. We define conatural number as a coinductive type:

```
record  $\mathbb{N}_\infty$  : Type where
  coinductive
  field
    pred $\infty$  :  $\tau \cup \mathbb{N}_\infty$ 
open  $\mathbb{N}_\infty$ 
```

We also define the inverse of `fold`, which is `unfold`:

```
unfold : (X  $\rightarrow$   $\tau \cup X$ )  $\rightarrow$  X  $\rightarrow$   $\mathbb{N}_\infty$ 
pred $\infty$  (unfold  $\alpha^-$  x) with  $\alpha^-$  x
... | inj $_1$  tt = inj $_1$  tt
... | inj $_2$  x' = inj $_2$  (unfold  $\alpha^-$  x')
```

That gives rise to the following commutative diagram:

$$\begin{array}{ccc}
 X & \xrightarrow{\text{unfold } \alpha^-} & \mathbb{N}_\infty \\
 \downarrow \alpha^- & & \downarrow \text{pred}_\infty \\
 \tau \cup X & \xrightarrow{\tau \cup_1 (\text{unfold } \alpha^-)} & \tau \cup \mathbb{N}_\infty
 \end{array}$$

3.3 Containers

3.3.1 Strict Positivity

Containers are categorical and type-theoretical abstraction to describe strictly positive datatypes. A strictly positive type is the type where all data constructors do not include itself on the left-side of a function arrow in the domain. One typical counterexample is `Weird`:

```

{--# NO_POSITIVITY_CHECK #-}
data Weird : Set where
  foo : (Weird → 1) → Weird

¬weird : Weird → 1
¬weird (foo x) = x (foo x)

bad : 1
bad = ¬weird (foo ¬weird)

```

`Weird` is not strictly positive as in the domain of `foo`, `Weird` itself appears on the left-side of \rightarrow . Losing strict positivity can cause issues like non-normalizable, non-terminating, inconsistency, etc. In this case, we can construct a term in the empty type using `¬weird` which is inconsistent to the definition.

3.3.2 Syntax and Semantics

A container is given by a shape $S : \text{Type}$ with a position $P : S \rightarrow \text{Type}$:

```

record Cont : Type1 where
  constructor _<_
  field
    S : Type
    P : S → Type

```

A container should give rise to an endofunctor $\text{Type} \Rightarrow \text{Type}$. Again we explicitly distinguish mapping objects part and mapping morphisms part of functors:

```

record [ ]0 (SP : Cont) (X : Type) : Type where
  constructor _,-
  open Cont SP
  field
    s : S
    k : P s → X

[ ]1 : (SP : Cont) → (X → Y) → [ SP ]0 X → [ SP ]0 Y
[ SP ]1 f (s , k) = s , f ∘ k

```

3.3.3 Categorical Structure

Containers and their morphisms form a category. The morphisms are defined as follow:


```

record ContHom (SP TQ : Cont) : Type where
  constructor _◁_
  open Cont SP
  open Cont TQ renaming (S to T; P to Q)
  field
    f : S → T
    g : (s : S) → Q (f s) → P s

```

where we can also show that it has identity and composition.

```

[[_]Hom : ContHom SP TQ → (X : Set) → [[ SP ]_◦ X → [[ TQ ]_◦ X
[[ f ◁ g ]Hom X (s , k) = f s , k ◦ g s

```

3.3.4 Semiring Structure

Containers are also known as **polynomial functors** as they forms a semiring structure. Namely, we can define zero, one, addition and multiplication for containers:

```

zero-C : Cont
zero-C = 1 ◁ λ ()

one-C : Cont
one-C = τ ◁ λ { tt → 1 }

_×C_ : Cont → Cont → Cont
(S ◁ P) ×C (T ◁ Q) = (S × T) ◁ λ (s , t) → P s ∪ Q t

_∪C_ : Cont → Cont → Cont
(S ◁ P) ∪C (T ◁ Q) = (S ∪ T) ◁ λ { (inj1 s) → P s ; (inj2 t) → Q t }

```

such that semiring laws should hold. In fact, both multiplication and addition are commutative, associative and left- and right-annihilated by their units. Even better, we can define Π and Σ for containers which are the infinite generalization of \times and \cup :

```

ΠC : (I → Cont) → Cont
ΠC {I} C̃ = ((i : I) → C̃ i .S) ◁ λ f → Σ [ i ∈ I ] C̃ i .P (f i)

ΣC : (I → Cont) → Cont
ΣC {I} C̃ = (Σ [ i ∈ I ] C̃ i .S) ◁ λ (i , s) → C̃ i .P s

```

3.3.5 W and M

We now give the definition of general form of inductive types, which is the W type:

```
data W (SP : Cont) : Type where
  sup : [ SP ]_0 (W SP) → W SP
```

From the definition, W is an inductive type that specified by a container. In another word, any inductive type can be specified by a strictly positive functor! We can retrieve the definition of N through the $\tau \wr$ functor:

```
 $\tau \wr$ Cont : Cont
 $\tau \wr$ Cont = S  $\triangleleft$  P
  where
    S : Type
    S =  $\tau \wr \tau$ 

    P : S → Type
    P (inj1 tt) =  $\perp$ 
    P (inj2 tt) =  $\tau$ 

NW : Type
NW = W  $\tau \wr$ Cont
```

Dually, the general form of coinductive types - M type is just the terminal coalgebra of containers, and we can redefine N^∞ using M :

```
record M (SP : Cont) : Type where
  coinductive
  field
    inf : [ SP ]_0 (M SP)

N∞M : Type
N∞M = M  $\tau \wr$ Cont
```

Commutative diagrams:

$$\begin{array}{ccc}
 [SP]_0 (W SP) & \xrightarrow{[SP]_1 (\text{fold } \alpha)} & [SP]_0 X \\
 \downarrow \text{sup} & & \downarrow \alpha \\
 W SP & \xrightarrow{\text{fold } \alpha} & X
 \end{array}$$

$$\begin{array}{ccc}
X & \xrightarrow{\text{unfold } \alpha^-} & M \text{ SP} \\
\downarrow \alpha^- & & \downarrow \text{inf} \\
\llbracket \text{SP} \rrbracket_0 X & \xrightarrow{\llbracket \text{SP} \rrbracket_1 (\text{unfold } \alpha^-)} & \llbracket \text{SP} \rrbracket_0 (M \text{ SP})
\end{array}$$

3.4 Questions

3.4.1 Bush

```

record Bush0 (X : Type) : Type where
  coinductive
  field
    head : X
    tail : Bush0 (Bush0 X)
open Bush0

{--# TERMINATING #-}
Bush1 : (X → Y) → Bush0 X → Bush0 Y
head (Bush1 f a) = f (head a)
tail (Bush1 f a) = Bush1 (Bush1 f) (tail a)

```

We now look at the definition of a coinductive type `Bush`. Is `Bush X` a terminal coalgebra of any endofunctor? It turns out that previews scheme is no longer applicable. The solution is to lift the space from `Type` to `Type → Type` and observe whether `Bush` is the terminal coalgebra of a higher endofunctor.

$$\begin{array}{ccc}
F & \xrightarrow{\text{unfold } \alpha^-} & \text{Bush}_0 \\
\downarrow \alpha^- & & \downarrow \langle \text{head}, \text{tail} \rangle \\
H F & \xrightarrow{H_1 (\text{unfold } \alpha^-)} & H \text{ Bush}_0
\end{array}$$

Chapter 4

Research Outcomes

4.1 Higher-order Containers

4.1.1 Higher-order Functoriality

4.1.2 Syntax and Semantics

4.1.3 Algebraic Structure

4.1.4 Simply-Typed Lambda Calculus

Chapter 5

Conclusions

This is conclusions.

Chapter 6

Future Work Plan

This is future work plan.

Chapter 7

Appendix

This is appendix.

Bibliography

- [1] ABBOTT, M., ALTENKIRCH, T., AND GHANI, N. Containers: Constructing strictly positive types. *Theoretical Computer Science* 342, 1 (2005), 3–27. Applied Semantics: Selected Topics.