

CS 511: Homework Assignment 3

Due: Saturday XX XXXX, 11:55 PM

1 Assignment Policies

Collaboration Policy. This homework may be done individually or in pairs. Use of the Internet is allowed, but should not include searching for existing solutions.

Under absolutely no circumstances code can be exchanged between students. Excerpts of code presented in class can be used.

Assignments from previous offerings of the course must not be reused. Violations will be penalized appropriately.

Late Policy. Late submissions are allowed with a penalty of 2 points per hour past the deadline.

2 Assignment

The idea behind this assignment is to get familiar with Erlang and to learn how to work with some of the data structure provided by the language; notably lists, maps, and records. You are asked to implement various operations that provide support to a *shipping company*. The shipping company administers (cargo) *ships*. Ships transport *containers* and navigate from one *port* to another. Each port has a number of *docks* where the ships may load and unload. Containers can either be in transit on a ship or in a port (in the latter case, no distinction is made regarding the specific dock).

You are supplied with two files:

- `shipping.hrl`. The Erlang header file for the assignment. It contains all the record declarations you should need to complete this assignment. These are described in further detail below.
- `shipping.erl`. The module file that includes all the functions that need to be completed. This is the file you will be editing.

2.0.1 Shipping Header File (shipping.hrl)

- Ship This record contains the fields:
 - name a string value
 - id a unique integer value
 - container_cap the maximum number of containers that a ship can hold
- Container This record contains the fields:
 - id a unique integer value
 - weight any positive integer value
- Port This record contains the fields:
 - name a string value
 - id a unique integer value
 - docks a list of docks for the port. A dock can be represented by an unique integer or a character and is only required to be unique at a given port (i.e. **Port "New York"**, **Dock 'A'** and **Port "Los Angeles"**, **Dock 'A'** are both valid)
 - container_cap the maximum number of containers that a ship can hold
- Shipping State This record contains the fields:
 - ships a list of the ship records currently in the system
 - containers a list of the container records currently in the system
 - ports a list of the port records currently in the system
 - ship_locations a tuple containing a port_id, dock_id, and ship_id (i.e. (1,'A',3)) if **port 1**, **dock 'A'** contains **ship 3**
 - ship_inventory a map that takes a **ship id** and maps it to the **list of containers ids** on that ship.
 - port_inventory a map that takes a **port id** and maps it to the **list of containers ids** at that port.

3 Shipping Module

We next describe each of the functions you are asked to implement. All of them have to be defined in `shipping.erl`.

To illustrate some of the functions described below we will use a sample shipping company **ShipCo**. The shipping state of **ShipCo** may be obtained by calling `shipping:shipco()`.

It is provided for you in the stub. Before you try out the examples below, remember to compile and then load the record definitions into the interpreter, as follows:

```
1> c(shipping).
shipping.erl:2: Warning: export_all flag enabled - all functions will be exported
{ok,shipping}
2> rr(shipping).
[container,port,ship,shipping_state]
```

1. `get_ship(Shipping_State, Ship_ID)`

This method returns a ship record for the given id. For example, `shipping:get_ship(shipping:shipco(), 1)`, will return the ship whose id is 1.

```
3> shipping:get_ship(shipping:shipco(),1).
#ship{id = 1,name = "Santa Maria",container_cap = 20}
```

2. `get_container(Shipping_State, Container_ID)`

This method returns a container record for the given id. For example:

```
4> shipping:get_container(shipping:shipco(),4).
#container{id = 4,weight = 62}
```

3. `get_port(Shipping_State, Port_ID)`

This method returns a port records for the given id.

```
5> shipping:get_port(shipping:shipco(),3).
#port{id = 3,name = "Miami",
      docks = ['A','B','C','D'],
      container_cap = 200}
```

4. `get_occupied_docks(Shipping_State, Port_ID)`

This method returns a list of all the occupied docks for a given port.

```
6> shipping:get_occupied_docks(shipping:shipco(),3).
['C']
```

5. `get_ship_location(Shipping_State, Ship_ID)`

This method returns the location, {Port_ID, Dock_ID}, of a given ship.

```
7> shipping:get_ship_location(shipping:shipco(),3).
{1,'A'}
```

6. `get_container_weight(Shipping_State, Container_IDs)`

This method returns the total weight of all of the container ids in the list Container_IDs.

```
8> shipping:get_container_weight(shipping:shipco(),[3,5]).
243
```

7. `get_ship_weight(Shipping_State, Ship_ID)`

This method returns the total weight of a ship, measured by the total weight of the ship's containers.

```
9> shipping:get_ship_weight(shipping:shipco(),2).  
676
```

8. `load_ship(Shipping_State, Ship_ID, Container_IDs)`

This method returns a shipping state in which the containers in the list of `Container_IDs` are moved from a port to the ship with the given `Ship_ID`. Make sure that all the containers are at the same port as the ship they are loading onto. In the case that loading the ship would put the ship over capacity, return an atom **error** and do not add any containers to the ship. Here is an example. Notice how containers 16, 18 and 20 have been removed from dock 1 and loaded onto ship 1.

```
10> shipping:load_ship(shipping:shipco(), 1, [16,18,20]).  
{ok,#shipping_state{  
  ships = [#ship{id = 1,name = "Santa Maria",container_cap = 20},  
           #ship{id = 2,name = "Nina",container_cap = 20},  
           #ship{id = 3,name = "Pinta",container_cap = 20},  
           #ship{id = 4,name = "SS Minnow", container_cap = 20},  
           #ship{id = 5,name = "Sir Leaks-A-Lot",container_cap = 20}],  
  containers = [...], %% not shown  
  ports = [#port{id = 1,name = "New York",  
                docks = ['A','B','C','D'],  
                container_cap = 200},  
           #port{id = 2,name = "San Francisco",  
                docks = ['A','B','C','D'],  
                container_cap = 200},  
           #port{id = 3,name = "Miami",  
                docks = ['A','B','C','D'],  
                container_cap = 200}],  
  ship_locations = [{1,'B',1},  
                    {1,'A',3},  
                    {3,'C',2},  
                    {2,'D',4},  
                    {2,'B',5}],  
  ship_inventory = #{1 => [14,15,9,2,6,16,18,20], %% loaded here  
                    2 => [1,3,4,13],  
                    3 => [],  
                    4 => [2,8,11,7],  
                    5 => [5,10,12]},  
  port_inventory = #{1 => [17,19], %% removed from port 1  
                    2 => [21,22,23,24,25],  
                    3 => [26,27,28,29,30]}}}
```

9. `unload_ship_all(Shipping_State, Ship_ID)`

This method returns a shipping state in which **all** of the containers that are on a given

ship are offloaded to the port in which the ship is docked. In the case that offloading to a port would put the port over capacity, return an error and do not unload any containers to the port.

```
11> shipping:unload_ship_all(shipping:shipco(), 2).
{ok, #shipping_state{
  ships = [#ship{id = 1, name = "Santa Maria", container_cap = 20},
           #ship{id = 2, name = "Nina", container_cap = 20},
           #ship{id = 3, name = "Pinta", container_cap = 20},
           #ship{id = 4, name = "SS Minnow", container_cap = 20},
           #ship{id = 5, name = "Sir Leaks-A-Lot", container_cap = 20}],
  containers = [...], %% not shown
  ports = [#port{id = 1, name = "New York",
                 docks = ['A', 'B', 'C', 'D'],
                 container_cap = 200},
           #port{id = 2, name = "San Francisco",
                 docks = ['A', 'B', 'C', 'D'],
                 container_cap = 200},
           #port{id = 3, name = "Miami",
                 docks = ['A', 'B', 'C', 'D'],
                 container_cap = 200}],
  ship_locations = [{1, 'B', 1},
                    {1, 'A', 3},
                    {3, 'C', 2},
                    {2, 'D', 4},
                    {2, 'B', 5}],
  ship_inventory = #{1 => [14, 15, 9, 2, 6],
                    2 => [], %% no more containers
                    3 => [],
                    4 => [2, 8, 11, 7],
                    5 => [5, 10, 12]},
  port_inventory = #{1 => [16, 17, 18, 19, 20],
                    2 => [21, 22, 23, 24, 25],
                    3 => [26, 27, 28, 29, 30, 1, 3, 4, 13]} %% loaded here
}}
```

10. unload_ship(Shipping_State, Ship_ID, Container_IDs)

This method returns a shipping state in which **the given containers** on a ship are offloaded to the port in which the ship is docked. Make sure that all the containers are located on the ship. In the case that offloading to a port would put the port over capacity, return an error and do not offload any containers to the port.

```
12> shipping:unload_ship(shipping:shipco(), 1, [2, 16, 18]).
The given conatiners are not all on the same ship...
error

13> shipping:unload_ship(shipping:shipco(), 1, [14, 2]).
{ok, #shipping_state{
  ships = [#ship{id = 1, name = "Santa Maria", container_cap = 20},
```

```

        #ship{id = 2,name = "Nina",container_cap = 20},
        #ship{id = 3,name = "Pinta",container_cap = 20},
        #ship{id = 4,name = "SS Minnow",container_cap = 20},
        #ship{id = 5,name = "Sir Leaks-A-Lot",container_cap = 20}]],
containers = [...], %% not shown
ports = [#port{id = 1,name = "New York",
              docks = ['A','B','C','D'],
              container_cap = 200},
        #port{id = 2,name = "San Francisco",
              docks = ['A','B','C','D'],
              container_cap = 200},
        #port{id = 3,name = "Miami",
              docks = ['A','B','C','D'],
              container_cap = 200}],
ship_locations = [{1,'B',1},
                  {1,'A',3},
                  {3,'C',2},
                  {2,'D',4},
                  {2,'B',5}],
ship_inventory = #{1 => [15,9,6], %% removed from here
                  2 => [1,3,4,13],
                  3 => [1],
                  4 => [2,8,11,7],
                  5 => [5,10,12]},
port_inventory = #{1 => [16,17,18,19,20,14,2], %% placed here
                  2 => [21,22,23,24,25],
                  3 => [26,27,28,29,30]}}}

```

11. set_sail(Shipping_State, Ship_ID, {Port_ID, Dock})

This method changes the given ship's port and dock location to the new port and dock location. Be sure to check whether or not the new port and dock is occupied. If it is, then return the atom **error**.

```

14> shipping:set_sail(shipping:shipco(), 4, {2,'B'}).
error

15> shipping:set_sail(shipping:shipco(), 4, {3,'A'}).
{ok,#shipping_state{
  ships = [#ship{id = 1,name = "Santa Maria",container_cap = 20},
           #ship{id = 2,name = "Nina",container_cap = 20},
           #ship{id = 3,name = "Pinta",container_cap = 20},
           #ship{id = 4,name = "SS Minnow",container_cap = 20},
           #ship{id = 5,name = "Sir Leaks-A-Lot",container_cap = 20}],
  containers = [...], %% not shown
  ports = [#port{id = 1,name = "New York",
                  docks = ['A','B','C','D'],
                  container_cap = 200},
           #port{id = 2,name = "San Francisco",
                  docks = ['A','B','C','D'],
                  container_cap = 200},
           #port{id = 3,name = "Miami",
                  docks = ['A','B','C','D'],
                  container_cap = 200}],
  ship_locations = [{1,'B',1},
                    {1,'A',3},
                    {3,'C',2},
                    {2,'D',4},
                    {2,'B',5}],
  ship_inventory = #{1 => [15,9,6], %% removed from here
                    2 => [1,3,4,13],
                    3 => [1],
                    4 => [2,8,11,7],
                    5 => [5,10,12]},
  port_inventory = #{1 => [16,17,18,19,20,14,2], %% placed here
                    2 => [21,22,23,24,25],
                    3 => [26,27,28,29,30]}}}

```

```

    #port{id = 3,name = "Miami",
        docks = ['A','B','C','D'],
        container_cap = 200}},
    ship_locations = [{1,'B',1},
                      {1,'A',3},
                      {3,'C',2},
                      {3,'A',4}, %% new port and dock
                      {2,'B',5}],
    ship_inventory = #{1 => [14,15,9,2,6],
                      2 => [1,3,4,13],
                      3 => [],
                      4 => [2,8,11,7],
                      5 => [5,10,12]},
    port_inventory = #{1 => [16,17,18,19,20],
                      2 => [21,22,23,24,25],
                      3 => [26,27,28,29,30]}}

```

4 Your Task

Your task is to complete all the functions in `shipping.erl` as mentioned above. You **DO NOT** have to touch `shipping.hrl`. Some example modules to help you complete some of these functions would be the `lists` and `maps` modules.

5 Submission Instructions

Submit a file **hw1_Surname.zip** (where **Surname** should be replaced by your surname) through Canvas containing all the files included in the stub but where all required operations have been implemented.