Evaluating Collective Forecasts on Temporal Operational Graphs: Calibration, Dependence, and Group Risk

Anonymous manuscript for author review

Abstract

Individual event probabilities on temporal operational graphs do not determine the uncertainty of group counts or simultaneous delays. We build a current-cohort forecasting benchmark on a compute-cluster trace and two loan-workflow releases, separating marginal prediction, shared dependence, typed incidence and group-risk evaluation. Controls include temporal neural and tree predictors, classical factor scenarios, direct count distributions, historical residuals and discrete probabilistic reconciliation. Original frozen evaluations motivate explicitly retrospective calibration and graph diagnostics; a separately frozen workflow period provides fresh confirmation. Typed factors reduce cluster count CRPS by 24.3% against independence, but only 2.2% beyond a global factor. Recent same-version calibration and direct count fitting substantially change the workflow comparison. In fresh confirmation, global dependence improves count CRPS by 12.7% while worsening a reserve-loss proxy by 20.4%; a development-selected direct count model outperforms it on both. Count and peak-group-delay rankings also differ. The contribution is a reproducible application benchmark and controlled empirical evidence for evaluating mean bias, collective uncertainty and operational risk separately, with explicit limits on temporal replication and deployment interpretation.

1 Introduction

A cluster operator sees pending and running tasks belonging to jobs and machines. A workflow analyst sees unresolved applications linked to their recent handlers. Both need collective forecasts: how many current entities will remain unresolved, and which groups might fall behind together? Temporal models can supply each entity's event probability, but those probabilities alone do not specify the distribution of group counts or the largest group delay. Moreover, a well-scored count distribution need not support the particular decision quantile used by an operator.

This study asks a practical evaluation question: *what additional evidence is needed before individual forecasts on a temporal operational graph can be used as collective scenarios?* Three issues are easily conflated. Individual predictions may share a mean bias. Outcomes may retain common variation after conditioning on observed history. Typed relations may identify additional association beyond a global factor. Improving the first issue, adding the second, and exploiting the third require different controls. An apparent "graph benefit" against independent sampling can otherwise be mostly a benefit of shared uncertainty available without typed relations.

We define a common current-cohort target for a public compute-cluster trace and two releases of a loan-processing workflow. At each origin, a causal adapter reconstructs the active entities and their observed memberships. Scenarios assign each entity a first-exit bin across four horizons, including survival beyond the final horizon. The cohort is not selected using future exits, arrivals or assignments. The resulting counts can be projected onto overlapping jobs and machines or onto recent-handler groups.

The contribution is a reproducible benchmark and controlled empirical study, not a new copula architecture. We compare strong individual predictors, matched-marginal global and typed factors, direct count distributions, historical residuals, and discrete probabilistic reconciliation. Delayed calibration controls separate mean error from dependence, and threshold-free joint scores test whether count accuracy extends to a group-risk profile. An initial two-log evaluation motivates retrospective diagnostics; a separately frozen third-log period supplies fresh confirmation. The manuscript identifies these evidence stages explicitly.

Three findings organize the study. Shared factors are strong controls, so the incremental contribution of typed incidence must be measured against them. Calibration can materially change both collective scores and asymmetric loss, but transferring residuals across predictor versions is unreliable. Finally, methods that forecast individual group counts well can rank differently on the largest standardized group delay. These findings motivate an evaluation workflow that checks marginal bias, group-count uncertainty, and joint group risk separately, rather than treating one score as validation of a scenario generator.

2 Related work

Temporal graphs and event generation. GraphMixer illustrates strong temporal encoding with simple

components [Cong et al., 2023]; our Mixer-style survival predictor is an independent adaptation, not a reproduction of its link-prediction protocol. CEP3 models community event times [Wang et al., 2022], and DG-Gen generates continuous-time dynamic graphs [Hosseini et al., 2025]. Their generation targets differ from conditional first exits of an already active population. We make no numerical superiority claim over these systems. Such a comparison requires explicit state initialization, unknown future-count stopping and outcome adapters.

Joint forecasting and reconciliation. TACTiS and TACTiS-2 learn flexible multivariate copulas [Drouin et al., 2022, Ashok et al., 2024]; separating learned marginals from spatial copulas is also established [Huk et al., 2025]. Our positive-factor Gaussian and Marshall–Olkin controls [Marshall and Olkin, 1967] are deliberately restrictive classical families. Typed current incidence specifies shared randomness for changing entities; neither that construction nor the marginal–dependence decomposition is claimed as a new statistical principle.

Probabilistic reconciliation already conditions forecast distributions on aggregation constraints, including discrete counts [Zambon et al., 2024]. We adapt a two-level importance-conditioning step to vectors of first-exit category counts and compare it with direct Dirichlet–multinomial forecasts and bottom-up aggregation. This is an established-method comparator, not a new reconciliation algorithm or an exact reproduction of an entire software package. Proper multivariate scores complement marginal scores; the limited dependence sensitivity of energy scores motivates an additional variogram score [Scheuerer and Hamill, 2015].

Operational forecasting. RIMS combines learned predictions and intercase simulation [Meneghello et al., 2025], while AgentSimulator models resource interactions [Kirchdorfer et al., 2025]. Closely related work initializes business-process simulation from current states and estimates conditional uncertainty, including on BPI 2017 [Avramenko et al., 2026]. Current-state forecasting and operational uncertainty are therefore established problems. Our empirical distinction is to hold individual probabilities fixed when testing incidence, then separately test correction of those probabilities, direct count alternatives and joint group-risk scores across workflow and compute logs. Executable workload generation, such as Mimesys [Kim et al., 2026], has a different output contract: our first-exit scenarios do not reproduce full workloads, future arrivals or repeated process transitions.

3 Forecast contract and controls

Let V_t be the entities active after processing all events recorded by origin t, and let $g_r(i,t)$ denote entity i's observed membership in relation type r. For ordered horizons $h_1 < \cdots < h_K$, the outcome $Y_{ik} = \mathbb{1}\{T_i \le t + h_k\}$ records the first exit from the current task state or the first qualifying application resolution. Each forecast draw assigns one of $K+1$ categories, with the final category indicating survival beyond h_K. This contract does not predict subsequent returns, exact within-bin times, or outcomes of future arrivals.

An individual predictor supplies monotone CDFs F_{ik}. For a current group A, the expected exit count is $\sum_{i\in A} F_{ik}$ under every coupling, whereas its variance also includes pairwise outcome covariances. Thus a coupling can change aggregate dispersion and tails but cannot fix a biased expected count. We exploit this distinction in two separate experiments: matched-marginal dependence comparisons and controlled marginal correction.

3.1 Entity-coherent factor scenarios

For each draw, generate independent standard normal global, relation-group, and private factors and set

$$Z_i = a_i Z_0 + \sum_r b_{ir} Z_{r,g_r(i,t)} + c_i \epsilon_i, \quad a_i^2 + \sum_r b_{ir}^2 + c_i^2 = 1. \tag{1}$$

Using $U_i = \Phi(Z_i)$ and $Y_{ik} = \mathbb{1}\{U_i \le F_{ik}\}$ preserves each individual CDF and gives ordered horizon outcomes. Shared draws persist across streamed entity chunks. Missing memberships transfer their squared loading to private noise. Identities index incidence; no identity embedding or future assignment is used. The construction handles simultaneous job and machine membership without a dense entity covariance matrix.

Independent sampling uses only private noise. Global models learn state-specific global/private weights; typed models add one weight per observed relation type. The initial study also includes context-dependent weight offsets and an exponential common-shock family. All weights are nonnegative, with at least .02 private variance. These families cannot express arbitrary negative association. We fit them by composite binary pair likelihood using earlier out-of-sample individual forecasts, random fitting horizon pairs, and January or original-development checkpoint selection. Different calibration treatments receive separate dependence fits in the fresh replication; retrospective BPI 2017 diagnostics retain original weights to isolate marginal correction.

We permute noise-sharing incidence within current state and half-unit last-horizon logit-risk bins, retaining true evaluation groups. This preserves individual probabilities, fitted weights and group sizes within strata. Additional Borg controls remove job or machine variance and transfer it to private noise. These sampler interventions assess predictive grouping under a fitted model, not causal effects of reassigning actual tasks or people.

3.2 Delayed calibration

A shared logit intercept preserves horizon order:

$$F_{ik}^{(\beta)} = \text{logit}^{-1}\{\text{logit}(F_{ik}) + \beta\}. \quad (2)$$

We fit $\beta \in [-2, 2]$ by equal-origin, equal-horizon Bernoulli loss with $10^{-4}\beta^2$ regularization. The static control uses an earlier calibration window. Rolling correction uses origins in the previous 60 days whose entire 14-day outcome window has matured; fewer than four eligible origins triggers an expanding-history fallback. Updated labels enter only after maturity.

A retrospective failure motivates an explicit version control: calibration residuals from earlier separately fitted predictors need not describe the current predictor's bias. We therefore compare that transfer with history from the same fitted predictor. This is a practical calibration control, not a new online-learning algorithm. Static calibration data also selected the original neural checkpoint/temperature, so its own fit score is not an independent validation estimate.

3.3 Direct counts and discrete reconciliation

For group A, average the individual first-exit category probabilities to obtain $\bar{\pi}_A$. A conditional Dirichlet–multinomial (DM) baseline uses

$$N_A \sim \text{DM}(|A|, \kappa q_A), \qquad q_A = \text{softmax}(\log \bar{\pi}_A + \delta). \quad (3)$$

We fit one concentration and optionally four category offsets (the fifth is zero) per projection type, with equal-origin and equal-within-origin-group likelihood weights. Offsets have fixed weak shrinkage. Concentration-only and bias-adjusted candidates are selected on development count CRPS. Training uses complete out-of-sample cohorts, never sampled partial group counts. Every group draw is bounded, integer-valued and ordered across horizons. Separately drawn overlapping projections need not correspond to a common entity realization.

For the retrospective original-log analyses we also fit DM on the more recent development forecasts, matching the fitting window of historical residuals. Leave-one-origin-out development CRPS selects concentration-only versus bias-adjusted DM; all development origins then fit the final predictor. These selection folds can use later development origins and are not online validation. Exact beta-binomial cumulative-count marginals supply CRPS and discrete quantiles for this control; joint-profile scores still use sampled DM trajectories. This stronger comparison avoids attributing an advantage to dependence when it comes from access to recent same-version errors.

For the workflow hierarchy, include every handler group, plus an unknown handler group, in a complete partition. Independently sampled bottom count vectors N_g are reweighted by the population forecast mass

$$w^{(m)} \propto p_{\text{pop}}\left(\sum_g N_g^{(m)}\right). \quad (4)$$

This two-level conditioning adaptation [Zambon et al., 2024] uses 8,192 proposal draws and resamples 512 coherent group/population trajectories. We report effective sample sizes and verify its distribution against an enumerated small example. Bottom-up aggregation without conditioning is a separate control. Neither count method preserves individual CDFs. The implemented hierarchy is complete for workflow handlers; it is not a full crossed job–machine reconciliation implementation. Historical aggregate residual resampling remains a comparator in the original two logs.

4 Evaluation

We score current-state population counts and observed relation groups of at least five entities. Fair ensemble CRPS [Ferro, 2014] is divided by current group size, then averaged equally over groups within projection, horizons, projection types and origins. This weighting is a benchmark convention, not an inferred organizational utility. Coverage and width of 90% intervals are reported separately by projection.

For remaining current-cohort count $R = |A| - C$, the reserve proxy chooses forecast quantile b at $r/(r+1)$ and scores

$$\ell_r(b, R) = \{r(R-b)_+ + (b-R)_+\}/|A|, \quad r \in \{3, 9\}. \quad (5)$$

It measures a specified quantile tradeoff, not money or realized staffing savings. CRPS integrates quantile losses [Gneiting and Raftery, 2007]; improving it does not guarantee improvement at this particular quantile.

For joint group risk, let $x_g = C_g/|g|$. We use an energy score with $d(x, y) = \sqrt{G^{-1}\sum_g (x_g - y_g)^2}$ and a power-.5 variogram score [Scheuerer and Hamill, 2015]. The latter averages 2,048 outcome-independent ordered group pairs; subtracting the ensemble variance divided by draw count removes finite-ensemble bias of its squared moment error. Its estimate can be slightly negative. We additionally score the distribution of

$$D_k = \max_g \frac{\mu_{gk} - C_{gk}}{\sqrt{1 + \sum_{i \in g} F_{ik}(1 - F_{ik})}}, \qquad \mu_{gk} = \sum_{i \in g} F_{ik}. \quad (6)$$

This is the largest standardized slow-progress deviation relative to a fixed reference forecast. Every compared method uses the same reference F, including recalibrated methods. It measures forecast-relative group risk, not an observed capacity threshold or an organizational SLA.

We average three random seeds within each origin before paired circular moving-block resampling (10,000

replicates). Borg blocks span one/two days; BPI 2017 blocks span 14/28 days; the fresh BPI 2012 analysis prespecifies seven days with fourteen-day sensitivity. Short traces provide few blocks, so intervals describe these observed periods and offer limited evidence for other operating regimes. Cases and random seeds are not independent temporal replications.

5 Data and evidence stages

5.1 Timestamp-bounded adapters

Borg. All 500 task-event shards of Google ClusterData2011-2 supply the compute application [Google, 2011]. We replay pending/running states in timestamp and source order, retaining unknown preceding age for time-zero records. The target is first state change at 1/5/15/60 minutes, including failures, evictions and kills as well as completion. Current job and known running-machine memberships define the graph. The evaluated final prefix contains 144.6 million events; 28 six-hour origins span elapsed days 22–28.75, with 3,760,001 task–origin queries and 105,077–171,603 active tasks per origin. Those repeated queries are not independent replications.

BPI 2017. The application workflow [van Dongen, 2017] uses first `A_Pending`, `A_Denied` or `A_Cancelled` after creation at 1/3/7/14 days. This is a documented application milestone, not repayment or necessarily the final event. Last observed workflow handling supplies the relation. We exclude retrospective trace attributes, eventual offer outcomes and future assignments. The original final period comprises 61 daily noon UTC origins during November–December 2016, with 114,051 case–origin queries and 1,484–2,189 cases per cohort.

BPI 2012. A fresh workflow release [van Dongen, 2012] supplies an analogous target: first `A_APPROVED`, `A_DECLINED` or `A_CANCELLED` after `A_SUBMITTED`. We normalize these four activity names only to reuse the replay adapter, retaining their original target definition. All other activity names remain distinct; workflow lifecycle values are normalized to lower case. Missing handlers share no entity-level factor. This is additional temporal/source evidence, not a claim about another independent bank. February 1–28, 2012 provides 28 final daily origins, with 23,749 case–origin queries, 793–889 cases per cohort, and follow-up through March 14 00:00 UTC. Activity vocabulary is derived from the individual fit prefix only.

In every source, observed events through the origin build features and memberships; outcomes are attached separately. Entire longest-horizon windows must be observable. Prefix state carries across date partitions without revealing future events. Recorded event time is the availability proxy; the archives do not establish live ingestion latency or exclusive resource ownership. The municipal BPI 2015 candidate was deferred after a development-source audit exposed inconsistent activity labels and ambiguous closure semantics. No outcome definition was forced to obtain another favorable benchmark.

5.2 Initial frozen evaluation

The initial study compares HGB personal/global/relational arms and temporal Mixer, GRU and tabular MLP ensembles. Borg uses 32 base features plus a 144-event-count extension; BPI 2017 uses 103 features. Temporal models use the last 16 events per task/job/machine or case/handler scope, width 64 and a five-category first-exit head. Selection uses equal-origin mean Brier over the four horizons, including monotone calibration variants and three-seed neural means; no best-seed selection is permitted.

Borg individual training/calibration/development end at days 18/20/22; dependence uses forward-fold predictions in days 8–10, 12–14 and 16–18, each produced by earlier fitted and calibrated predictors. BPI 2017 uses training before September, September calibration and October development, with June/July/August forward folds for dependence. Selected individual models are HGB global for pending tasks, HGB relational for running tasks, and the temperature-calibrated Mixer ensemble for BPI 2017. Gaussian typed and global models are selected for Borg and BPI respectively.

An immutable 264-file manifest froze code, models and evaluation choices before those final periods were opened. This was a development-informed holdout freeze, not external preregistration. A lossless Borg timestamp-type repair after a replay failure retained all original data and changed no timestamp value or frozen model. The original study and review archive remain preserved.

5.3 Retrospective diagnostics and fresh confirmation

The initial outcomes motivated the direct DM controls, delayed calibration, factor removals and joint-profile scores. Their analyses on the original final periods are therefore *retrospective*. Direct count training uses 24 complete Borg six-hour OOF cohorts and 50 complete BPI 2017 OOF cohorts. The stronger development-fitted DM control instead uses the eight Borg or 17 BPI 2017 current-version development origins, matching the historical residual fitting period. Both fitting regimes are retained. The original residual comparator instead fits on development residuals, with leave-one-origin-out development scoring. It uses three sampling seeds; a one-seed caption in an earlier review version was incorrect, without affecting any reported number.

For fresh confirmation, BPI 2012 individual fitting ends before November 1, 2011; November calibrates the

individual model, December fits dependence and direct counts, and January selects configurations. The global-feature HGB with identity correction wins individual Brier. Identity/global wins Gaussian development count CRPS; bias-DM wins the direct comparison; bias-DM conditioning wins the conditioning comparison. Static and rolling correction remain prespecified controls, with dependence fitted separately for each treatment. All six Gaussian fits per seed use only development data.

Before retaining any February outcomes, a second immutable manifest froze 82 assets, the primary comparisons, metrics, origins and bootstrap settings. The raw parser had previously discarded every event at or after February 1 before retaining its activity or outcome. Final predictors remain fixed; only the explicitly prespecified rolling correction may use earlier February outcomes after their 14-day maturity delay. January 19–31 origins provide cross-boundary calibration history but are not final score origins. We retain all prespecified outcomes irrespective of which method wins.

6 Results

6.1 Count gains survive strong controls only in some settings

The original frozen Borg typed Gaussian model reduces count-fraction CRPS from .03417 under independence to .02587, a 24.3% improvement (Table 1). Ratio-9 reserve loss falls from .13106 to .05280. The global factor already reaches .02646 CRPS: the additional typed gain is 2.2%, not 24.3%. The paired typed-minus-global CRPS interval is $[-.00105, -.00018]$ with one-day blocks. Removing job variance increases job-level CRPS from .01451 to .01922; removing machine variance changes machine CRPS from .02507 to .02525. The strongest demonstrated typed signal is therefore job grouping, with a much smaller machine contribution.

Stronger direct controls do not remove Borg's count result. The development-fitted DM model reaches .02853 CRPS and .06931 reserve loss. Typed-minus-DM CRPS is $-.00266$, with one-day block interval $[-.00366, -.00169]$. The earlier-OOF DM and historical residual controls are weaker. Nevertheless, macro coverage is insufficient evidence of uniform calibration: original typed population coverage is about .763 while job and machine coverage are about .978 and .976. A macro value near .90 hides this imbalance.

BPI 2017 gives a different ranking. The original global model improves CRPS by 8.3% over independence but increases the reserve loss by 9.6%. Development-fitted bias-DM reaches .04077 CRPS and .11396 loss, outperforming the original global forecast on both. Its CRPS difference is $-.00518$ with 14-day block interval $[-.00983, -.00096]$. Conditioning reconciles handler/population trajectories but does not improve on the unreconciled direct count model; its population and group tradeoffs must be inspected separately. The early-OOF DM is weaker than its same-version development fit, showing why comparator training windows matter.

6.2 Calibration changes the operational comparison

The first retrospective correction transferred June–August OOF errors to the current BPI 2017 predictor. It made October global-model CRPS worse, from .04102 to .05422. Those OOF forecasts came from different fitted predictors. Using earlier September forecasts from the *same* predictor reverses that failure: delayed correction gives October CRPS .03845. The later-period global score improves from .04589 to .04072, with paired difference $-.00517$ and 14-day interval $[-.00859, -.00192]$. Its fourteen-day mean resolution forecast rises from .525 to .578, against observed .579. These are controlled follow-ups, not untouched final estimates.

The corrected global model and development-fitted direct DM have almost identical count CRPS: difference $-.00005$, interval $[-.00134, .00120]$. Correction therefore does not establish superiority over a strong direct alternative. Nor is the decision effect uniform. Corrected global reserve loss falls from .12899 to .11816, whereas corrected independence worsens from .11761 to .14405. The same improved marginal means produce different reserve quantiles under different joint laws (Table 2). Identity rows here use a common diagnostic random stream, so they differ slightly from the independently generated original frozen table.

6.3 Fresh confirmation favors the direct model

The February BPI 2012 confirmation was evaluated once under the separately frozen protocol. The development-selected identity/global model improves CRPS by 12.7% over independence (.06253 versus .07162), but worsens reserve loss by 20.4% (.16694 versus .13864). Its CRPS difference is $-.00909$, with seven-day block interval $[-.01081, -.00721]$. Typed factors are worse than the global control by .00274 CRPS, interval $[.00187, .00357]$.

The development-selected bias-DM is substantially stronger: .03893 CRPS, .9145 coverage and .11246 reserve loss. Relative to the selected Gaussian, CRPS improves 37.7% and reserve loss 32.6%; the CRPS-difference interval is $[-.03183, -.01436]$. Bottom-up and conditioned bias-DM have similar count CRPS but less favorable coverage and reserve loss. Concentration-only DM is much weaker, implicating mean correction rather than dispersion alone.

This confirmation is a demanding extrapolation for the individual predictor, which had only 4,854 training case–origin queries before November. Its fourteen-day

Table 1: Count forecasts on original final periods and fresh BPI 2012 confirmation. Lower CRPS and loss are better; nominal coverage is .90. The three factor rows retain the original individual CDFs. Revised controls on Borg/BPI 2017 are retrospective. DM development-fit scores are exact; sampled methods use 512 draws and three seeds. A dash denotes an unimplemented comparison.

	Borg			BPI 2017			BPI 2012 (fresh)		
Method	CRPS	Cov.	Loss_9	CRPS	Cov.	Loss_9	CRPS	Cov.	Loss_9
Independent	0.0342	0.6594	0.1311	0.0501	0.5356	0.1177	0.0716	0.4745	0.1386
Global factor	0.0265	0.9797	0.0551	0.0460	0.8897	0.1290	0.0625	0.8562	0.1669
Typed factors	0.0259	0.9059	0.0528	0.0465	0.7935	0.1222	0.0653	0.6655	0.1554
DM, earlier fit	0.0287	0.9342	0.0744	0.0450	0.9002	0.1287	0.0389	0.9145	0.1125
DM, development fit	0.0285	0.9440	0.0693	0.0408	0.9298	0.1140	—	—	—
Bottom-up DM	—	—	—	0.0424	0.7749	0.1326	0.0389	0.8289	0.1176
Conditioned DM	—	—	—	0.0418	0.7617	0.1319	0.0390	0.8125	0.1198
Historical residuals	0.0309	0.8746	0.0840	0.0439	0.8311	0.1258	—	—	—

Table 2: BPI 2017 controlled same-version correction. Original Gaussian weights are fixed. These are retrospective diagnostics; improved mean calibration does not guarantee a better reserve quantile.

		October development		November–December	
Correction	Dependence	CRPS	Loss_9	CRPS	Loss_9
Identity	Independent	0.0433	0.0954	0.0501	0.1176
Identity	Global factor	0.0410	0.1195	0.0459	0.1290
Identity	Typed factors	0.0411	0.1088	0.0465	0.1222
Static	Independent	0.0401	0.0945	0.0469	0.1197
Static	Global factor	0.0386	0.1147	0.0435	0.1244
Static	Typed factors	0.0383	0.1039	0.0439	0.1188
Rolling 60D	Independent	0.0401	0.0947	0.0435	0.1441
Rolling 60D	Global factor	0.0385	0.1146	0.0407	0.1182
Rolling 60D	Typed factors	0.0382	0.1037	0.0408	0.1199

February mean is .468 versus observed .617. Static correction raises it to .575 and rolling correction to .532; both improve aggregate CRPS, but neither beats bias-DM. Static correction also outperforms rolling correction on count CRPS in this period. These outcomes confirm the need for strong bias/direct-count controls, not universal success of an online update or a conclusion about the best possible individual model for this source. Only four seven-day or two fourteen-day blocks are available, limiting the strength of temporal inference.

6.4 Joint group risk changes the ranking

Table 3 evaluates full group profiles and the largest standardized slow-progress deviation. In BPI 2017, recent direct DM improves count CRPS over the original global model, but its peak-deviation CRPS is worse (.53433 versus .46081). The paired increase is .07351 with 14-day interval [.00348, .14454]. Thus access to better individual group-count distributions does not establish better prediction of their joint extreme. Delayed correction plus global dependence reaches .43633 peak CRPS and .08803 profile energy; typed correction offers no clear general advantage.

Borg's global and typed factors substantially improve peak-deviation scores over independence, primarily through jobs. Direct DM is also competitive on joint profiles and peaks, despite weaker count CRPS. In fresh BPI 2012, bias-DM wins both count and peak-deviation comparisons against the selected global model (.39031 versus .47902 peak CRPS). There is no universal coherence-versus-accuracy ranking. Full variogram results and projection-level scores are released rather than selecting only a favorable multivariate metric.

An earlier simultaneous-alarm endpoint required at least 20% of groups to fall more than two reference standard deviations behind. It was absent in Borg and occurred only once across BPI 2017 final horizon–origin outcomes. That endpoint is uninformative here and was not promoted as a successful warning task. Threshold-free profile and peak scores were specified before opening the fresh period.

7 Discussion

An evidence requirement, not a universal winning architecture. The benchmark exposes distinctions that an individual-event leaderboard cannot resolve. A shared factor can improve collective dispersion without changing a single individual probability. Typed incidence can then add a smaller, projection-specific gain.

Table 3: Joint group-profile scores. ES is RMS-normalized energy score; Peak is CRPS of the maximum standardized slow-progress deviation. Scales differ across datasets. Original-period rows are retrospective; all fresh endpoints were frozen before opening February.

	Borg		BPI 2017		BPI 2012 (fresh)	
Method	ES	Peak	ES	Peak	ES	Peak
Independent	0.0597	15.7604	0.0957	0.4613	0.1058	0.5183
Global factor	0.0575	7.5434	0.0942	0.4608	0.1023	0.4790
Typed factors	0.0546	4.1726	0.0942	0.6686	0.1015	0.7362
DM, earlier fit	0.0543	3.9903	0.0923	0.9984	0.0859	0.3903
DM, development fit	0.0544	4.0844	0.0879	0.5343	—	—
Bottom-up DM	—	—	0.0879	0.5380	0.0861	0.3907
Conditioned DM	—	—	0.0879	0.5539	0.0860	0.3922
Rolling correction + global	—	—	0.0880	0.4363	0.0928	0.4882




Figure 1: Left: retrospective BPI 2017 fourteen-day population mean predictions under original and delayed same-version correction. Right: matched-marginal factor comparisons on original final periods and fresh BPI 2012. The global factor captures much of the improvement over independence; typed incidence has an application-specific incremental contribution.

Correcting a common bias or forecasting counts directly can change the ranking again. These are empirical reasons to include global, direct-count and calibration controls before attributing collective accuracy to a temporal graph architecture.

Which output is needed? If the application asks only for a few fixed group counts, direct count models are strong and economical candidates. Entity-level factor scenarios supply a different capability: the same realization can be projected onto overlapping jobs and machines or an alternative grouping without fitting another count model. A complete handler hierarchy can also be reconciled coherently. Neither capability guarantees better prediction. In particular, separate good group marginals need not give the right extreme across groups, and a globally coherent scenario can still have biased means or incorrect tails. The joint profile and peak-deviation scores therefore complement count CRPS.

Calibration and dependence interact. Replacing biased individual probabilities changes both expected group counts and the quantile needed by a reserve proxy. A coupling that improved CRPS before correction need not have the same decision effect afterward. The same-version requirement matters because a sequence of chronological OOF predictors is not one stationary calibration object. Nevertheless, delayed updates can lag a regime change, and the fresh replication does not justify claiming that rolling correction always beats a fixed earlier map. A factor estimated from forecast residuals may absorb misspecification; its value is predictive rather than evidence of an identified common cause.

Limits of generalization. The evidence covers one compute cluster and two workflow releases, with only seven final Borg days and 28 fresh workflow origins. Four or two bootstrap blocks in the latter are weak support for long-run uncertainty. Repeated cases, millions of tasks and Monte Carlo seeds do not multiply independent temporal replications. Retrospective follow-ups are separated from their motivating outcomes, and the single fresh confirmation should not be interpreted as broad external validation. No live operator study, policy deployment, measured cost saving or resource-capacity ground

truth is available.

The benchmark conditions on the currently active cohort and excludes future arrivals, subsequent exits/returns and membership evolution. Last handler is an observed association, not exclusive ownership. Positive factor families cannot represent general negative dependence. A full crossed job–machine probabilistic reconciliation baseline, adaptations of TACTiS or graph point-process generators, and complete business-process simulation remain unimplemented comparisons. The paper makes no superiority claim over them. The three individual architectures and fixed training budgets are useful controls, not an exhaustive model search.

Implications for scientific dataset generation. A reusable scenario source should declare the conditioning population, observable history and outcome contract before generating records. It should also test both individual and collective statistics under meaningful group projections. Our adapters, score suite and provenance checks provide a bounded foundation for that purpose. They are not a full synthetic-data factory and have not been validated by training downstream models on synthetic data. Extending them requires arrivals, repeated transitions and separate utility and privacy studies. Original public-source license and attribution terms remain applicable.

8 Conclusion

Collective forecasts on temporal operational graphs require more than accurate individual event probabilities. In these traces, shared dependence, marginal bias and typed incidence contribute differently across applications and projections. Strong direct count models can outperform more elaborate entity-scenario constructions, while group-risk scores reveal behavior that count CRPS alone does not capture. The practical contribution is a reproducible evaluation contract and controlled benchmark: compare shared and typed dependence, test recent same-version calibration, include direct and reconciled count alternatives, and report the intended operational quantity separately.

References

Arjun Ashok, Étienne Marcotte, Valentina Zantedeschi, Nicolas Chapados, and Alexandre Drouin. TACTiS-2: Better, faster, simpler attentional copulas for multivariate time series. In *International Conference on Learning Representations*, 2024. URL https://arxiv.org/abs/2310.01327.

Maksym Avramenko, David Chapela-Campa, Marlon Dumas, and Fredrik Milani. Short-term business process simulation: current-state initialization and uncertainty quantification. *Process Science*, 3:12, 2026. doi: 10.1007/s44311-026-00045-9.

Weilin Cong, Si Zhang, Jian Kang, Baichuan Yuan, Hao Wu, Xin Zhou, Hanghang Tong, and Mehrdad Mahdavi. Do we really need complicated model architectures for temporal networks? In *International Conference on Learning Representations*, 2023. URL https://arxiv.org/abs/2302.11636.

Alexandre Drouin, Étienne Marcotte, and Nicolas Chapados. TACTiS: Transformer-attentional copulas for time series. In *International Conference on Machine Learning*, volume 162 of *PMLR*, pages 5447–5493, 2022. URL https://proceedings.mlr.press/v162/drouin22a.html.

Christopher A. T. Ferro. Fair scores for ensemble forecasts. *Quarterly Journal of the Royal Meteorological Society*, 140(683):1917–1923, 2014. doi: 10.1002/qj.2270.

Tilmann Gneiting and Adrian E. Raftery. Strictly proper scoring rules, prediction, and estimation. *Journal of the American Statistical Association*, 102(477):359–378, 2007. doi: 10.1198/016214506000001437.

Google. ClusterData2011-2 documentation, 2011. URL https://github.com/google/cluster-data/blob/master/ClusterData2011_2.md. Public cluster trace; documentation accessed October 2026.

Ryien Hosseini, Filippo Simini, Venkatram Vishwanath, and Henry Hoffmann. A deep probabilistic framework for continuous time dynamic graph generation. *Proceedings of the AAAI Conference on Artificial Intelligence*, 39(16):17249–17257, 2025. doi: 10.1609/aaai.v39i16.33896.

David Huk, Rilwan A. Adewoyin, and Ritabrata Dutta. Probabilistic rainfall downscaling: Joint generalized neural models with censored spatial gaussian copula, 2025. URL https://arxiv.org/abs/2308.09827. arXiv:2308.09827, version 2.

Donghyun Kim, Zichao Hu, Joydeep Biswas, Aditya Akella, and Daehyeok Kim. Mimesys: Generating realistic executable testing environments from resource usage traces. In *USENIX Symposium on Operating Systems Design and Implementation*, pages 2205–2221, 2026. URL https://www.usenix.org/conference/osdi26/presentation/kim-donghyun.

Lukas Kirchdorfer, Robert Blümel, Timotheus Kampik, Han van der Aa, and Heiner Stuckenschmidt. Discovering multi-agent systems for resource-centric business process simulation. *Process Science*, 2:4, 2025. doi: 10.1007/s44311-025-00009-5.

Albert W. Marshall and Ingram Olkin. A multivariate exponential distribution. *Journal of the American Statistical Association*, 62(317):30–44, 1967. doi: 10.1080/01621459.1967.10482885.

Francesca Meneghello, Chiara Di Francescomarino, Chiara Ghidini, and Massimiliano Ronzani. Runtime integration of machine learning and simulation for business processes: Time and decision mining predictions. *Information Systems*, 128:102472, 2025. doi: 10.1016/j.is.2024.102472.

Michael Scheuerer and Thomas M. Hamill. Variogram-based proper scoring rules for probabilistic forecasts of multivariate quantities. *Monthly Weather Review*, 143 (4):1321–1334, 2015. doi: 10.1175/MWR-D-14-00269.1.

Boudewijn van Dongen. BPI Challenge 2012, 2012. URL https://doi.org/10.4121/uuid:3926db30-f712-4394-aebc-75976070e91f.

Boudewijn van Dongen. BPI Challenge 2017, 2017. URL https://data.4tu.nl/articles/dataset/BPI_Challenge_2017/12696884.

Xuhong Wang, Sirui Chen, Yixuan He, Minjie Wang, Quan Gan, and Junchi Yan. CEP3: Community event prediction with neural point process on graph. In *Learning on Graphs Conference*, volume 198 of *PMLR*, pages 39:1–39:17, 2022. URL https://proceedings.mlr.press/v198/wang22c.html.

Lorenzo Zambon, Dario Azzimonti, and Giorgio Corani. Efficient probabilistic reconciliation of forecasts for real-valued and count time series. *Statistics and Computing*, 34:21, 2024. doi: 10.1007/s11222-023-10343-y.

A Implementation and reproduction details

Individual and dependence models. The original HGB runs use 250 iterations, 31 leaves, minimum leaf size 100, learning rate .05 and L2 regularization 1. Neural models use width 64, up to 30 epochs, AdamW at .001, gradient clipping at 5 and calibration-window early stopping with patience 5. Case/job/machine histories contain at most 16 prior events per scope; time lags are computed at the origin. All initial neural architectures have three-seed ensembles. The fresh HGB control uses 15 leaves and minimum leaf size 50 because its fit window is smaller; it does not repeat the full neural architecture search. This difference is a limitation of the fresh replication, not a claim of universal model optimality.

Pair sampling draws 1,000 uniform entity pairs per origin and, per relation, 1,000 uniformly selected group pairs and 1,000 group-size-weighted pairs. It never conditions on future labels. Static/global AdamW uses learning rate .02 and up to 50 epochs, with development pair-likelihood patience 8. The context model in the initial study uses two width-32 SiLU layers, bounded logit offsets and shrinkage .01. Gaussian probabilities use 32-point double-precision quadrature. Private variance is at least .02. The common-shock, context and complete individual-arm results remain in the original artifact; no consistent context-network advantage was established.

DM fits use $\log \kappa \in [-2, 12]$ and four offsets in $[-2, 2]$, with $10^{-3}\|\delta\|^2$ penalty. Two fixed concentration initializations are optimized with analytic gradients and a converged minimum is retained. A first finite-difference Borg fit stopped at a line-search failure before producing scores; its directory and source snapshot are preserved. The analytic-gradient correction changed the repeated BPI count CRPS by less than 4×10^{-6}. Exact cumulative beta-binomial CRPS is checked against an enumerated pairwise expectation. Reconciliation uses log-normalized importance weights; all fitting and sampling functions are independently checked on small known distributions.

Historical residual comparator. For each development origin/group, store the four-dimensional residual $(C - \mu)/\sqrt{1 + \sum_i F_i(1 - F_i)}$. Each draw selects one common historical origin, then size-bin-matched group residual vectors. Counts are clipped, rounded and monotonized. Development scoring omits its own origin; final scoring uses all development residuals. It changes group means and does not enforce agreement between overlapping projections. Contrary to one caption in the original review PDF, its saved evaluator and result files use seeds 0, 1 and 2, not one seed. The correction affects reporting only.

Interval and Monte Carlo interpretation. Seed averaging occurs before temporal block resampling. The original 512-to-1,024-draw sensitivity changes macro CRPS by at most .000122 and preserves within-family rankings. This does not establish sampling precision for every newly added peak or variogram score; close differences are not treated as decisive. Fair variogram estimates use sampled group pairs and can be slightly negative after finite-ensemble correction. Main tables separate exact direct-count marginal scores from sampled distributions; exact discrete quantiles and finite-ensemble quantiles can differ slightly. Projection/horizon CSVs and paired block-size sensitivities accompany the reported macro values.

Computation and integrity. The experiments use two RTX A6000 GPUs, with CPU replay, HGB and direct-count fits. Original Borg evaluation of five controls over 28 origins requires about 245–251 seconds per

512-draw process under concurrent shared-device execution, with at most .67 GiB allocated PyTorch memory; it excludes replay, training and individual inference and is not an isolated latency benchmark. The original 264-file freeze and the fresh 82-file freeze are verified after evaluation. Original code, results and the immutable review archive remain intact; new diagnostics and manuscript sources live in separate directories. The test suite covers causal replay, temporal eligibility, coherent sampling, known DM moments, exact reconciliation on a small enumerated distribution, and dependence-sensitive profile scores.

Data and access. Raw-source manifests retain checksums and publisher URLs. Google trace attribution follows its CC-BY-4.0 release; BPI datasets retain the 4TU General Terms of Use specified in their metadata. The artifact does not relicense third-party data or software. The reproduction package supplies executable analysis, fitted parameters and score evidence; large original logs are acquired through the documented source workflow. Author identities, permanent public artifact links and any venue-specific disclosure must be finalized by the researcher before submission. No external submission or release has been made during this study.