Does Structural Change Predict Value? Semantic Information Value as an LLM-Free Admission Signal for Agent Memory: A Degeneracy Analysis and a Matched-Size Test on LoCoMo and LongMemEval-S

Mohammad Zuber Taj[1]

Independent researcher, New Jersey, United States
us.zubertaj@gmail.com

Abstract. Agent memory systems decide what to store with a language-model call per candidate fact. We ask whether the structure of the memory graph carries that information, and give the first implementation and quantitative test, in an agent-memory setting, of al-Saffar and Heileman's 2010 semantic information value (SIV): trust times degree-weighted impact, and the realised graph-edit change of a write. At fact granularity the formulation is degenerate: on LoCoMo trust is exactly zero for a share 0.773 of candidates, the product ranks below random admission at every memory budget, and the realised change is a clock (Spearman -0.854 with position) because consolidation never fires. A redesign that separates anchoring from agreement, excludes speaker hubs from impact and adds pattern novelty, fitted leave-one-conversation-out and compared at matched memory size, retains more gold evidence than random (+0.057 evidence hit, exact permutation $p = 0.004$), than the 2010 measures and than A-MAC's lexical features, but no more than a turn-length heuristic. On LongMemEval-S (500 independent memories) the same gate, cross-fitted over questions, retains +0.073 more evidence than random ($p = 0.003$) while the turn-length heuristic falls below random. Answering the questions with a fixed model confirms that the offline proxy carries signal but overstates the gate's benefit (F1 gain over random +0.026, $p = 0.064$). Mem0's verbatim gate admits 0.975 of candidate turns at 742 model calls per thousand, so it does not gate here. Under sourceless poisoning the gate admits more false facts than random; provenance weighting is the defence. Pre-registration, code, run artefacts and number files are released.

Keywords: agent memory · knowledge graphs · information value · admission control · provenance · pre-registration

1 Introduction

Long-term memory for conversational agents is a write path with a gate: a candidate fact is extracted from a turn and a decision is made to add it, to update or

invalidate what it contradicts, or to drop it. In most systems that report results on the public long-conversation benchmarks, that decision is a language-model call. Mem0 asks a model to choose among ADD, UPDATE, DELETE and NONE (NOOP in the paper's wording) [9]; Zep's Graphiti resolves duplicates and invalidates contradicted edges with model prompts [33,42]; Nemori spends two calls per write on a predicted schema and its deviation [26]; GAM defines a graph divergence as its consolidation trigger and then declines to compute it, calling the computation "expensive and sensitive to lexical noise", and uses a model as a proxy [38]. The cheap alternatives are usage-based (MemoryOS promotes by a heat score of visits, length and recency [24]) or text-based (A-MAC scores confidence by ROUGE-L and novelty by embedding distance, with one model call for utility [43]). None of them scores a candidate by the structure of the memory graph it lands in.

That structure was proposed as a value signal before there were agents to use it. In 2008 al-Saffar and Heileman introduced the recipient's world-view graph (their 2010 paper names it the *context graph*) and valued a piece of information by the impact it would have on it and the trust in its source [2,3]; in 2010 they cast both as RDF graph properties [1]: *trust* as the share of the target's edges already in the context graph, *impact* as the degree-weighted share of overlapping vertices, their product as the *predicted* semantic information value, and the edit distance, with uniform costs, between the context graph before and after learning as the *actual* value. The measures are linear-time because IRI labels make vertex alignment trivial. They were demonstrated in a browser plug-in over DBpedia and never evaluated quantitatively; the authors wrote that traditional evaluation does not apply to subjective valuation. We found no later implementation (the first author's publication page lists only PDFs) and no agent-memory paper that cites them.

Claim under test. Graph-structural features of a candidate memory fact (agreement with what the memory holds, anchoring to known entities, degree-weighted impact, pattern novelty) carry measurable information about the fact's downstream value for question answering, at zero gate-time model calls.

What this paper is not. It does not propose a new measure. Trust, impact and the two SIVs are al-Saffar and Heileman's; the novelty term is Joslyn and al-Saffar's motif information gain over the extant ontology [23,4]; agreement-based trust is Knowledge-Based Trust [11]; graph priors for fact admission are Knowledge Vault's [10]; informativeness of triples is RELIN's [8]; the RDF delta is Berners-Lee and Connolly's [6]. What no work we could find does, as of the preregistration date, is to admit agent-memory facts with a graph-informational measure and measure the result against question answering at matched memory size.

What we found, in one paragraph. The 2010 measures degenerate at fact granularity, measurably and for arithmetic reasons (Section 6.1). A redesigned, LLM-free gate over seven graph features beats random, the 2010 measures and A-

MAC's lexical features at matched memory size on LoCoMo but only matches a turn-length heuristic (Section 6.2); on LongMemEval-S, cross-fitted over questions, it beats random while the length heuristic falls below random (Section 6.5); answering the questions with a fixed model shows that the offline evidence-recall proxy carries signal but overstates the gate's benefit by about half (Section 6.3). The verbatim Mem0 gate admits nearly every candidate on LoCoMo, which turns the pre-registered non-inferiority question into a cost question (Section 6.4); structural novelty admits poison unless provenance is weighted (Section 6.7); and the memory graph has no entity-to-entity edges on either dataset, which on LoCoMo we trace to the benchmark's observations rather than to the extractor (Section 6.8). The realised-change hypothesis (H2) is not tested on either arm as run and is deferred with the reasons stated.

Contributions.

- The first implementation and quantitative evaluation of SIV (trust, impact, SIV_p, SIV_a) in an agent-memory setting, under a pre-registered design, with a degeneracy analysis of the 2010 formulation at fact granularity and a redesign that separates agreement from anchoring and excludes hubs from impact (Sections 4 and 6.1).
- A matched-size, leave-one-conversation-out comparison protocol with an exact sign-flip permutation test over conversations, applied to nine LLM-free policies besides admit-all and to the verbatim Mem0 gate (Sections 5, 6.2 and 6.4).
- A validation of evidence recall, the offline proxy that every LLM-free development loop of this kind relies on, against answers from a fixed model, including the two pipeline details (dates on facts, the official temporal hint) without which temporal questions cannot be answered from a fact store (Section 6.3).
- A measurement of how reallocatable an agreement-and-novelty admission value is under self-consistent sourceless poisoning and how much a provenance tier recovers (Section 6.7), complementary to Fei et al. [15].
- A graph-shape precondition table and a measurement showing that entity-to-entity topology is absent from LoCoMo's observations themselves (2.3% non-speaker subjects), with the implication for where such claims can be tested (Section 6.8).
- An offline replication of the matched-size test on LongMemEval-S with the question as the unit of inference, a gate cross-fitted per dataset, and the length-plus-revisit heuristic falling below random (Section 6.5).
- Code, the frozen pre-registration with its deviation log, run artefacts and the number files behind every table.

2 Background and related work

2.1 Information value of graphs

al-Saffar and Heileman introduced subjective information valuation in two 2008 papers [2,3]: the value of an information piece to a consumer is a function of the

impact it would have on a graph representing the consumer's world view (named the *context graph* in the 2010 paper) and of the trust the consumer places in its provenance. Their 2010 paper [1] restates this over plain RDF graphs. Given a target graph G_t and a context graph G_c, the *actual* value is the dissimilarity between G_c and the revised graph $G'_c = l(G_c, G_t)$ after learning (their eqs. 1–5), computed as a graph edit distance [7] with uniform costs, $(|E'_c| - |E_c|)/|E'_c|$; the *predicted* value replaces the unknown learning function by plain union (eq. 6) and non-uniform edge costs $t \times \deg(v)$ for edges attached to vertices the two graphs share, with cost 1 for the edges of new disconnected components (eq. 7); trust is the share of target edges already in the context (eq. 8), impact the degree-weighted share of shared vertices (eq. 9), and SIV_p their product (eq. 10). The 2008 papers took trust from explicitly stated provenance; the 2010 paper derives it from agreement. Both framings matter here: our provenance tier is a return to the 2008 design, and our poisoning arm tests the 2010 one. al-Saffar, Joslyn and colleagues' *extant ontology*, the frequency-weighted class–predicate–class graph computed by one aggregate query over a triple store [4], and the information gain of typed motifs relative to independence [23] are the source of our novelty term. The delta of two RDF graphs as insert and delete sets, and the observation that blank nodes make it a graph-isomorphism problem while IRIs make it trivial, is older still [6]; our SIV_a is a weighted instance of that delta.

Valuing triples by graph statistics has a decade of Semantic Web precedent that the agent-memory literature has not used: RELIN's informativeness from triple frequencies [8], the entity-summarisation lineage that followed [25], and the statistical rejection of implausible triples from predicate–type distributions [32]. At web scale, Knowledge Vault fuses graph-based priors with extractor confidences and admits triples above a calibrated probability [10], and Knowledge-Based Trust estimates a source's trustworthiness from the correctness of the facts extracted from it [11]. The 2010 trust ratio is the naive version of that idea and lacks the extraction-error model; we return to this in Section 7.

2.2 Agent memory systems and their write paths

We group the systems by what happens when a candidate fact arrives. *LLM gates.* Mem0 extracts candidate memories and lets a model choose ADD, UPDATE, DELETE or NONE against the most similar stored memories (ten in the paper, five per candidate fact in the code) [9]; the open-source release carries this gate through tag 1.0.11 (the last PyPI release with it, April 2026); it is absent from tag 1.1.0 onwards, and the current code (2.2.1) writes through an add-only path, which is why we run the 1.0.11 prompt verbatim (Section 5). Zep's Graphiti deduplicates entities and edges by model judgement after embedding and full-text candidate retrieval, invalidates contradicted edges by model judgement and keeps bitemporal validity [33,42]. Nemori frames writing as prediction error but implements it as two model calls [26]. A-MEM lets a model write note attributes and links [40]; Generative Agents score importance with a model at write time [30]; MemGPT makes the model manage its own memory

tiers [29]. *Arithmetic gates.* MemoryOS promotes from mid- to long-term memory when a heat score (visits, interaction length, exponential recency) crosses a threshold [24]; MemoryBank forgets by an Ebbinghaus curve [44]. *LLM-light linear gates.* A-MAC scores a candidate by five factors (utility from one model call, ROUGE-L confidence, embedding novelty, recency, a type prior) with cross-validated weights; it reports admission-label precision and recall and no downstream QA, so we re-implement lexical analogues of its LLM-free features inside our pipeline (Table 3), with novelty computed against the live memory (A-MAC's released experiment scripts compute it against an empty list) and recency omitted as constant at write time [43]. *Learned gates.* Memory-R1 trains the manager with reinforcement learning; it remains a model call at inference [41]. *Efficiency.* LightMem reports large reductions in calls and tokens through lightweight filtering [14]; we therefore report write-path calls and tokens per thousand candidates rather than a headline fraction. *Graph consolidation.* GAM declines to compute the graph divergence that would trigger consolidation [38]; Kumiho lists degree-based entrenchment as future work [31]; HippoRAG's node specificity is a frequency-based graph weight applied at read time [17]; the 2026 systems that use degree or centrality (Selective Forgetting, EngramRAG and STRATA; arXiv 2608.28978, 2609.32049 and 2610.19386) apply it to prune or decay nodes or to protect them at garbage collection, after admission, and none scores a candidate before it is written. The surveys we consulted list no structural write policy [12,22], and the 2026 survey of graph-based personalised memory (arXiv 2609.08599) names no system that uses degree, centrality or connectivity for write decisions; CoALA supplies the vocabulary [35].

2.3 Context graphs, selection integrity and benchmarks

"Context graph" now names a vendor category [16] and a formal object with relation contexts [39]; al-Saffar and Heileman's sense predates both and, in their 2010 paper, came with a formula, and the memory graph of Section 3 is a context graph in that sense. Fei et al. show that sourceless structural writes reroute the selector of a graph memory and silently misdirect downstream actions; exposure is predicted by the *reallocatability* of the selector's structural term [15,18]. We infer, and Section 6.7 tests, that agreement-based trust, degree-based impact and pattern novelty, all computed over a writable memory graph, are reallocatable in their sense (Fei et al. do not discuss overlap-based trust, so the inference is ours), which makes the poisoning arm central rather than optional. LoCoMo [27] releases ten long dyadic conversations with per-session observations, dialogue-turn evidence ids and five question categories; LongMemEval [37] releases 500 questions over per-question session haystacks with answer-bearing turns marked and a knowledge-update type. This paper uses LoCoMo for the full arm and LongMemEval-S for the offline matched-size replication (Section 6.5); Section 6.8 explains why the deferred hypotheses need LongMemEval-S's entity density and knowledge-update questions.

3 Problem statement and memory model

Setting. A conversation arrives as a stream of turns grouped into sessions. A fixed extractor turns each turn into a candidate set $G_t = (V_t, E_t)$ of one to five typed triples (s, p, o) with a source turn, a session, a speaker, an observation time, a provenance tier and a confidence. An *admission policy* assigns the candidate a score; a *gate* turns the score into an admit or reject decision; admitted triples are written into the memory graph $G_c = (V_c, E_c)$; at the end of each session a consolidation step c runs. Every question is then answered from a retrieval over the admitted graph that is identical for every policy. The only thing that varies between runs is the policy.

Memory model. The memory is an entity-centric knowledge graph [20]. Nodes are entities typed Person, Place, Org, Event, Date, Pet, Thing or NamedEntity. Edges are facts (s, p, o) with properties `source_turns`, `session`, `speaker`, `observed_at`, `tier` $\in$ {verbatim-user, extractor-inferred, llm-summary, poisoned}, `confidence`, `method`, `text`, `valid_from` and `valid_to`. Consolidation sets `valid_to`; nothing is deleted, and "live" means `valid_to` unset. The hub set H holds the two speakers; the measures exclude it where stated. Entity resolution applies four rules in order: exact match of the normalised surface form within type (R1), a hub-name match regardless of type (R2), Person/NamedEntity cross-type exact match (R3), and a token-sort fuzzy ratio of at least 90 within type for names of five or more characters with a length difference of at most twelve (R4) [5]; dates are never fuzzy-matched. The graph exports to RDF in reifier style [19], under which the measures below are three aggregate queries.

Admission as score plus gate. Every policy returns one score per candidate set and never sees gold evidence. Exact duplicates of live facts are suppressed for every policy, including admit-all. Two gates are used: a fixed threshold, and an *online quantile* gate that admits a candidate when its score exceeds the running $(1 - q)$ quantile of the scores seen so far in the conversation, decides the first $w = 20$ warm-up candidates by alternation towards the target rate (identically for every policy), admits ties only while the realised rate is below q, nudges the quantile level by the gap between q and the realised rate, and admits or rejects unconditionally while the realised rate is outside $q \pm 0.05$ (a budget band added after the first runs, because a score that trends with graph size defeats any running quantile). Memory size is matched across policies by bisection on q (Section 5, *Matched size*).

4 Measures

All measures are LLM-free and linear in $|E_t|$ given degree, pattern and predicate counts maintained over the live edges. Let $G_c = (V_c, E_c)$ be the live memory after entity resolution of the candidate's vertices, $G_t = (V_t, E_t)$ the candidate and H

Table 1. The 2010 measures, why each degenerates for one-to-five-triple candidates, and the redesign. The 2010 forms are kept and reported as policies.

2010 form	Why it degenerates here	Redesign
Trust $T_{\text{edge}} = \lvert E_t \cap E_c\rvert / \lvert E_t\rvert$	For $\lvert E_t\rvert \leq 5$ it takes at most eleven values (10 observed); a new fact scores 0, an exact duplicate scores 1, so trust $\times$ impact ranks redundancy above news.	Anchoring A (share of non-hub candidate vertices already known) and soft agreement T_{soft} (best per-subject similarity): "about known things" versus "already known".
Impact $I = \frac{\sum_{v \in V_t \cap V_c} \deg v}{\sum_{v \in V_c} \deg v}$	The speakers sit in almost every triple and carry most of the degree mass.	I': log-degree mass of shared *non-hub* vertices over the same for memory.
$\text{SIV}_p = T_{\text{edge}} \times I$	Inherits both; zero for almost every non-duplicate.	Logistic gate over the features of Table 2, fitted leave-one-conversation-out.
SIV_a with $G'_c = G_c \cup G_t$ (eq. 6)	Under plain union the delta is the new-triple ratio: content-blind and monotone in memory size.	$G'_c = c(G_c \cup G_t)$ with a consolidation c (entity merge, functional-fact invalidation, symmetric closure); the plain form is kept as a control.
Directional prior: new disconnected knowledge costs 1, connected knowledge $t \times \deg v$	Encodes "new unknown concepts matter less", which is backwards when gold evidence is new.	Tested as H3 rather than assumed.

the hub set. Table 1 summarises the 2010 forms, why each degenerates at fact granularity, and the redesign.

Trust, anchoring, soft agreement. The 2010 trust is $T_{\text{edge}}(G_t, G_c) = \lvert E_t \cap E_c\rvert / \lvert E_t\rvert$, membership tested after entity resolution of s and o and exact match of p; it is reported as-is. The redesign separates two things the ratio conflates. *Anchoring* is the share of non-hub candidate vertices already known,

$$A(G_t, G_c) = \frac{\lvert (V_t \setminus H) \cap V_c\rvert}{\lvert V_t \setminus H\rvert}, \tag{1}$$

undefined, and the candidate excluded from anchoring-based analyses, when $V_t \setminus H$ is empty. *Soft agreement* is the mean, over candidate edges whose subject resolves, of the best token-set Jaccard similarity of the verbalised (p, o) to a live fact with the same subject; unresolved subjects contribute zero.

Impact. The 2010 impact $I = \sum_{v \in V_t \cap V_c} \deg(v) / \sum_{v \in V_c} \deg(v)$ is reported as-is. The redesign excludes hubs and damps degree: $I' = \sum_{v \in (V_t \cap V_c) \setminus H} \log(1 + \deg v) \,/\, \sum_{v \in V_c \setminus H} \log(1 + \deg v)$. The pre-registered per-type variant was not implemented (Table 5).

Novelty. With Π the set of patterns $(\tau(s), p, \tau(o))$ over live edges and $c(\pi)$ their counts, $N(G_t) = \frac{1}{|E_t|} \sum_{(s,p,o) \in E_t} -\log \hat{p}(\tau(s), p, \tau(o))$ with $\hat{p}(\pi) = (c(\pi) + 1)/(|E_c| + |\Pi| + 1)$, and N_p is the same over predicates alone: the extant-ontology statistic of [4] used as a surprisal.

Predicted value. $\mathrm{SIV}_p = T_{\mathrm{edge}} \times I$ is run unmodified as `siv_2010`, and I alone as `impact_2010`. The redesigned predicted value is a logistic function of the standardised feature vector of Table 2, with ℓ_2-regularised, class-balanced weights fitted on the nine conversations other than the one evaluated on LoCoMo (Section 5) and by five-fold cross-fitting over questions on LongMemEval-S (Section 6.5). The label of a candidate is whether its source turn is a gold evidence turn of some question of the same conversation. Two fitted variants are run: the *structural-only* gate over the seven graph features $\{T_{\mathrm{edge}}, A, T_{\mathrm{soft}}, I, I', N, N_p\}$, which is the headline policy, and the *structural + surface* gate over all thirteen. A hand-set prior weight vector, fixed before any fitting but absent from the frozen pre-registration, is kept as a third, unfitted variant (`graph_gate`); on raw features it is a novelty-minus-redundancy score.

Actual value. The revision is the consolidation the memory performs, $G'_c = c(G_c \cup G_t)$, where c (i) merges entities by the rules above, (ii) invalidates a contradicted functional fact (same subject, a predicate in {lives_in, moved_to, works_at, works_as, married_to, dating, engaged_to, studies, born_in, has_age}, different object: the older edge receives `valid_to`), and (iii) closes the symmetric predicates {married_to, dating, engaged_to, has_sibling, friend_of}. The realised change is

$$\mathrm{SIV}_a(G_t, G_c) = \frac{w(E'_c \setminus E_c) + w(E_{\mathrm{inv}})}{w(E'_c)}, \tag{2}$$

with weights adapted from the cost rule of eq. 7 of [1] (there used for the *predicted* value; the 2010 actual value is unweighted): $w(e) = t(e) \cdot \max(\deg u, \deg v, 1)$ for an edge attached to an existing vertex and $w(e) = 1$ for an edge whose vertices are both new. The 2010 definition, written $\mathrm{SIV}_a^{\mathrm{plain}}$ in this paper (`siva_2010`), uses unit weights and plain union and equals the new-triple ratio; eq. (2) is this paper's redesign (`siva_cons`), and Section 6.1 compares the two. In the first column of Table 1 and in the contributions list the bare symbol SIV_a names the 2010 measure. Two properties matter for interpretation. When every live and candidate edge touches a hub, the hub degree cancels and SIV_a coincides with $\mathrm{SIV}_a^{\mathrm{plain}}$ unless c fires. And both are of order $|E_t|/|E_c|$, so they fall with memory size, i.e. with position in the conversation; the size-invariant companion $\mathrm{SIV}_a \cdot |E'_c|$ (`siva_scaled`) is also recorded. Section 6.1 measures both properties.

Table 2. The feature vector of the gate (`measures.FEATURE_NAMES`). The first seven rows are the graph-structural subset used by the headline policy. AUC is the area under the ROC curve of the single feature against the admission label over the 2375 candidate turns of the admit-all stream (Section 6.1).

Code name	Symbol	Definition	AUC
`t_edge`	T_{edge}	the 2010 trust	0.436
`anchoring`	A	eq. (1)	0.488
`t_soft`	T_{soft}	best per-subject Jaccard to a live fact	0.427
`impact`	I	the 2010 impact	0.410
`impact_log`	I'	hub-excluded log-degree impact	0.493
`novelty`	N	pattern surprisal	0.518
`novelty_pred`	N_p	predicate surprisal	0.507
`n_edges`	$\lvert E_t \rvert$	candidate size	0.490
`n_new_vertices`	–	non-hub candidate vertices not in V_c	0.575
`n_nonhub`	$\lvert V_t \setminus H \rvert$	non-hub candidate vertices	0.573
`confidence`	t	mean tier-derived confidence (constant in this arm)	0.500
`recency`	–	$\log(1 +$ hours since last mention$)$	0.568
`text_len`	–	tokens in the source turn	0.629

5 Experimental design

The pipeline is held identical across policies; only the admission policy varies. The design, hypotheses, margin and sample sizes were frozen before the first full run (Section 5); this paper reports the LoCoMo arm in full and the offline LongMemEval-S arm (Section 6.5).

Dataset and extraction. LoCoMo [27] has ten conversations between two speakers over many sessions, 1,986 questions in five categories (single-hop 841, multi-hop 282, temporal 321, open-domain 96, adversarial 446), each with gold evidence dialogue ids, and 2,541 per-session observation sentences that cite the turns they came from. The released category codes map to multi-hop (1), temporal (2), open-domain (3), single-hop (4) and adversarial (5); the first loader and the frozen pre-registration had the first four names permuted, corrected here as an erratum. The *oracle extraction arm* converts the observations to triples with a deterministic rule over a spaCy `en_core_web_sm` dependency parse: the subject is the known name heading or owning the nominal subject, else the speaker; the predicate is the lemma of the main verb folded into a closed vocabulary, with type-guarded functional predicates (a residence needs a Place object, an employer an Org, a spouse a Person) and owner-qualified canonical objects for relation nouns ("Melanie's kids" $\rightarrow$ (Melanie, has_child, Melanie's child)); the object

is the head noun of the first complement with its compound and adjectival children; named entities and absolute dates become `mentions` and `mentions_date` extras. A sentence the parse cannot handle (2.9% of sentences) takes a labelled token rule. The arm makes no model call at run time, but the observations were produced by the benchmark's authors with gpt-3.5-turbo seeing the whole session and cover 40% of turns and 76% of gold evidence turns; we do not call this arm "LLM-free extraction". A hand check of 18 consecutive primary triples found 8 correct, 4 weak and 6 wrong; the check is by a single annotator; the pre-registered 200-mention entity-resolution precision sample (frozen section 6.2) is still owed and is a further deviation beside those of Tables 4 and 5. Over the ten conversations the extractor emits 3199 triples from 2375 candidate turns, 8 of them with a functional predicate (all correct on inspection), and consolidation finds 0 contradictions in the corpus.

Retrieval and answering. BM25 [34] over the verbalised live facts, top-$k = 20$, then one-hop expansion over the admitted graph from the retrieved facts' non-hub entities, capped at 40 facts; superseded facts are retrieved with a validity note. The *offline arm* replaces answering by *evidence hit*: does the retrieved set contain a fact whose source turn is a gold evidence turn of the question? It is model-free and is what every development run uses. The *online arm* asks a fixed model (Claude Haiku 5.5, thinking disabled, effort `low`, 128 output tokens, a fixed system prompt permitting "No information available") to answer from the retrieved facts, and scores with the official LoCoMo rules: token F1 with the official normalisation, exact match, and the adversarial category scored by abstention. The Messages API offers no temperature control under this configuration, so "temperature 0" of the pre-registration is replaced by a deterministic-by-cache protocol (every answer is cached under its prompt, policy and gate description) and declared as a deviation. Two passes are reported (Section 6.3): pass 1 verbalises a fact as its observation sentence; pass 2 appends the observation date to every fact and the official LoCoMo suffix "Use DATE of CONVERSATION to answer with an approximate date" to temporal questions, as the official evaluation does.

Matched size and leave-one-conversation-out fitting. Policies with a threshold are compared at matched memory size: for each conversation the target is a fraction $f \in \{0.25, 0.5, 0.75\}$ of admit-all's live facts after consolidation, and the online-quantile budget q is found by bisection (eight iterations, tolerance 5%) on the memory the policy itself builds. Realised size gaps are 1–4% (Table 6). Learned gates are fitted on the other nine conversations and run on the tenth, so every one of the ten conversations is a test unit; a run refuses weights fitted on a conversation it evaluates. Random admission uses one seed per run (the pre-registration asked for five).

Policies. Table 3 lists them. The Mem0 gate deserves a note. We copied the prompt `DEFAULT_UPDATE_MEMORY_PROMPT` and the message builder `get_update_`

`memory_messages` byte for byte from mem0ai 1.0.11 (Apache-2.0), the last release that runs the classic gate; its old-memory list is the union of the top-5 BM25 matches of each candidate fact over the live facts (Mem0: vector search, limit 5 per fact, union, deduplicate), the new facts are the candidate texts, and a turn is admitted when any returned event is ADD or UPDATE. DELETE events are counted but not applied, because consolidation is the shared pipeline step. The gate has no budget knob, so the other policies are matched to *its* realised memory size, which is the one point of the size-versus-score comparison the frozen pre-registration (section 8) prescribes for a policy without a threshold.

Poisoning arm. Per conversation, a fabricated fact is injected with probability 10% at every dialogue turn, whether or not that turn yields a real candidate, so the 1206 injected facts (repeats included) are just over a quarter of the candidate stream: predicates are drawn from the predicate distribution of the real candidates seen so far, subjects are the speakers or hub-adjacent known entities, objects come from the corpus vocabulary, each fact is verbalised with its predicate and repeated once a few turns later (self-consistency), and the random stream is seeded per conversation and consumed identically whatever the policy decides, so the injected set is paired across policies. In the *sourceless* condition the injected tier confidence equals the real candidates' (0.6), so no policy can see the poison; in the *lower* condition the poison carries tier 0.4; the switch `-tier-weight` multiplies any policy's score by the mean tier confidence. We report the admission rate of injected facts, the share of questions that retrieve at least one injected fact, and evidence hit. The pre-registered 0/2/10% grid and the online QA-harm metric are deferred (Table 4).

Statistics. The unit of inference on LoCoMo is the conversation, of which there are ten; on LongMemEval-S it is the question, and with 479 paired units the sign-flip test draws 20,000 random sign assignments from a fixed seed instead of enumerating all 2^k. The primary statistic is the per-conversation mean paired difference in the metric between two policies, tested by the exact two-sided sign-flip permutation over all 2^{10} assignments (smallest attainable $p = 0.002$), with a t-interval on nine degrees of freedom and the number of conversations with a positive difference. Holm correction [21] is applied over the family of comparisons in one table, not over the pre-registered four-hypothesis family. On LongMemEval-S the unit is the question, the same paired sign-flip statistic is computed over the questions with gold evidence, and with more than twelve units the sign assignments are sampled (20,000 draws, fixed seed) rather than enumerated. A cluster bootstrap and a question-level paired bootstrap [13] (2,000 resamples) are reported as secondary; the latter is anti-conservative because questions within a conversation are not independent. Wilson intervals [36] are used for rates. Per-category comparisons are exploratory and reported as intervals.

Pre-registration statement. The design, the four hypotheses (H1 non-inferiority of the graph gate to a Mem0-style gate within 2.0 F1 points at matched size; H2 positive Spearman correlation of SIV_a with per-question answer value; H3

Table 3. Admission policies. Only the policy varies between runs. "Calls" are write-path model calls per candidate turn.

Policy	Code name	Calls	What it computes
admit-all	`admit_all`	0	everything; the ceiling
random	`random`	0	uniform score at matched size
heat	`heat`	0	$a\log(1+\text{visits}) + b\cdot\text{length}/50 + ce^{-\Delta t/\mu}$ over the candidate's non-hub entities; a MemoryOS-inspired length-plus-revisit heuristic
SIV-2010	`siv_2010`	0	$T_{\text{edge}} \times I$ unmodified; the gate's tie rule stands in for the 2010 cold-start exception
impact-2010	`impact_2010`	0	I alone
graph gate, prior	`graph_gate`	0	logistic over Table 2 with hand-set weights
graph gate, structural (headline)	`graph_gate_struct`	0	the seven graph features, weights fitted leave-one-out
graph gate, full	`graph_gate_full`	0	all thirteen features, fitted leave-one-out
A-MAC-lite	`amac_lite`	0	lexical analogues of A-MAC's LLM-free features (ROUGE-L of the candidate against the previous 20 turns; one minus the largest token-set Jaccard to any live fact, in place of its embedding novelty; share of candidate predicates in a durable-profile list, in place of its type prior; recency omitted as constant at write time) with hand-set weights 0.3/0.3/0.2; no utility call
A-MAC, fitted	`amac_fit`	0	the same features, weights fitted leave-one-out by the same learner as the graph gate
Mem0 gate	`mem0_gate`	1	the verbatim 1.0.11 ADD/UPDATE/DELETE/NONE prompt; admit on ADD or UPDATE

inversion of the 2010 directional prior; H4 reallocatability under sourceless poisoning and recovery by a provenance tier), the margin and the H2 sample size were written down before the first full run [28]; sections 1–13 of the pre-registration as they stood on 18 October 2026 are frozen verbatim in the released repository (`00-preregistration.frozen-2026-10-18.md`, SHA-256 `4d9abb17...5e5`), and every later decision is a declared deviation; the frozen copy postdates the first admit-all pass and the kick-off comparisons made with the earlier gate (implementation-log items 1–8), none of which is reported here. Tables 4 and 5 list the main ones; declared in the text are the per-dataset fitting of the gate weights and the evidence-hit-only scoring on LongMemEval-S (Section 6.5), the hand-set prior weights, which are not in the frozen document (Section 4), the table-wise Holm families (Section 7) and the budget band of the quantile gate (Section 3).

6 Results

Every number in this section is a macro written by the experiment code from the run directories (`numbers.tex`, `numbers_online.tex`, `numbers_lme.tex`), except the single-feature AUCs quoted from Table 2, the ratios to the ceiling, the per-conversation ranges and the dataset descriptives, which are typed from the run reports. Every run summary carries the code hash, the data-file hash and the weight-file hash it was produced with.

6.1 Graph shape and the degeneracy of the 2010 measures

The admit-all stream holds 2375 candidate turns (3199 triples); a share 0.718 of candidate sets hold a single triple. T_{edge} takes 10 distinct values; it is 0 for a share 0.773 of candidates and 1 for 0.061, so SIV_p is 0 on the same 0.773 and can only prefer repetition. Anchoring is undefined or zero on three quarters of candidates (per conversation 0.67–0.82). The 2010 realised change (unit weights, plain union: the new-triple ratio) and the degree-weighted, consolidation-aware redesign are rank-identical ($\rho = 0.990$) because consolidation fires on 0.000 of admissions, and both are clocks: Spearman -0.854 with within-conversation position and -0.865 with memory size; the size-invariant `siva_scaled` is not (-0.07). Table 2 gives each feature's single-feature AUC against the admission label: every 2010 measure is *below* 0.5 (it ranks evidence turns lower than non-evidence turns), the redesigned structural features sit at 0.49–0.52 except soft agreement (0.427), which, like the 2010 trust it refines, ranks evidence turns lower than non-evidence turns, and the strongest single correlate of the label is the length of the source turn (0.629), followed by the counts of new and of all non-hub vertices (0.575, 0.573) and recency (0.568).

Precondition. After consolidation, a share 0.133 of non-hub vertices have degree at least two and 0.000 of live edges join two non-hub vertices (per conversation 0.10–0.16 and 0.000 respectively). Every memory in this arm is two speaker stars with repeated leaves. The "structural" features therefore measure

Table 4. Deviations from the frozen pre-registration (18 Oct 2026) and from the design critique of the first runs.

Pre-registered	Run	Reason
two datasets; LLM extraction arm	LoCoMo oracle arm; LongMemEval-S offline arm with a first-person heuristic extractor over user and assistant turns, scored by evidence hit, gate weights fitted per dataset by five-fold cross-fitting over questions	budget and time; the LLM-extraction arm on both datasets and the LongMemEval-S judge-accuracy arm are the next runs
H2: SIV_a versus repeated-answer value	not tested	consolidation never fires here (0 contradictions), SIV_a and $\mathrm{SIV}_a^{\mathrm{plain}}$ are rank-identical ($\rho = 0.990$) and both are clocks (Section 6.1)
H3 as answer-value delta per fact	exploratory evidence-label rate by anchoring	no repeated answering; reported as intervals
eight-feature gate; disjoint split with 5-fold CV	thirteen features; structural-only and full variants; leave-one-conversation-out on LoCoMo; five-fold cross-fitting over questions on LongMemEval-S, so weights are fitted per dataset	features added in implementation; ten conversations make a disjoint split too small; hand-set weights do not transfer between datasets (Section 6.5)
online-quantile gate at common q	bisection on q to $\pm 5\%$ live facts	the quantile gate alone left a 24% spread
random, five draws	one seed	cost of the sweep; seeds differ per run
Mem0-style gate	verbatim 1.0.11 prompt with BM25 old-memory lookup; DELETE not applied; temperature not settable; other policies matched to its size	faithfulness where possible; the API adapter offers no temperature
A-MAC with utility call; learned gate	not run	model-call baselines beyond budget
poisoning 0/2/10%, tiered condition, QA harm	10% per dialogue turn only; sourceless and lower tier with and without the multiplier; retrieval share instead of QA harm	QA harm needs the online arm on every poison run

Table 5. Deviations from the frozen pre-registration, continued from Table 4.

Pre-registered	Run	Reason
question-level bootstrap primary	conversation-level exact permutation primary	questions are clustered in ten conversations
answering at temperature 0	Haiku 5.5, thinking disabled, cached; dated facts and the official temporal hint in pass 2	no temperature under the API configuration; temporal questions unanswerable from undated facts
deterministic token rule for extraction	spaCy entity layer with type-guarded predicates; labelled fallback on 2.9% of sentences	the token rule produced speaker stars with repeated leaves (critique E1)
inverse and symmetric closure in c	symmetric only	inverse set defined, closure not implemented
per-type variant of I'	not implemented	–
category names in the coverage sentence	corrected	loader erratum
SIV_a "with 2010 weights" as the consolidation-aware form, $\mathrm{SIV}_a^{\mathrm{plain}}$ as the control	`siva_2010` is the unweighted 2010 union ratio; `siva_cons` the degree-weighted consolidation-aware redesign	labels were the wrong way round in the frozen text (log item 13)
Fei et al. "show agreement trust is reallocatable"	claim withdrawn; the sourceless condition tests this paper's own inference	their criterion is top-k reallocatability, not overlap trust (log item 14)
LoCoMo under MIT; observations by GPT-4	CC BY-NC 4.0; gpt-3.5-turbo	data facts corrected from the repository (log item 15)
one gate fit on a held-out split	weights fitted per dataset: leave-one-conversation-out on LoCoMo, five-fold over questions on LongMemEval-S	hand-set weights do not transfer (Section 6.5; log items 17–18)

recurrence of objects around the speakers, not graph topology, and we word every claim below as being about turn-level admission features over an entity-centric fact store. Section 6.8 shows that this is a property of the benchmark's observations.

6.2 Matched-size comparison, offline

Table 6 reports every policy at half of admit-all's memory, with the evidence hit retained at a quarter and three quarters; Figure 1 draws the curves. The structural-only gate retains 0.431 of the 0.643 ceiling at half size (67%), random 0.379 (59%), the 2010 product 0.323 (50%). The two 2010 measures are the two worst policies at every budget and both fall below random throughout (the

Table 6. LoCoMo oracle arm, leave-one-conversation-out gates, memory matched to 50% of admit-all's live facts (1,986 questions, ten conversations). Evidence hit with its question-level 95% interval (secondary), the hit at 25% and 75% memory, the realised admit rate, live facts and size gap. Write-path model calls are zero for every row.

Policy	Hit 50%	95% CI	25%	75%	Admit	Live	Gap
admit-all	0.643				1.00	2618	–
graph gate, full	0.436	[0.414, 0.457]	0.262	0.578	0.41	1301	0.019
graph gate, structural	**0.431**	[0.409, 0.453]	0.240	0.577	0.46	1335	0.018
graph gate, prior	0.410	[0.389, 0.431]	0.229	0.548	0.44	1315	0.018
heat	0.405	[0.383, 0.426]	0.196	0.562	0.46	1309	0.018
random	0.379	[0.358, 0.401]	0.197	0.508	0.48	1315	0.021
A-MAC, fitted	0.378	[0.356, 0.399]	0.224	0.521	0.48	1304	0.017
A-MAC-lite	0.351	[0.330, 0.372]	0.205	0.520	0.48	1328	0.027
impact-2010	0.342	[0.321, 0.364]	0.128	0.459	0.49	1316	0.036
SIV-2010	0.323	[0.303, 0.343]	0.149	0.470	0.50	1301	0.030




Fig. 1. Evidence hit retained against memory size (fraction of admit-all's live facts), leave-one-conversation-out, all ten conversations as test units.

product is last at half size, Impact alone at a quarter and at three quarters; Table 6), for the arithmetic reason of Section 6.1.

Primary test. Table 7 gives the exact sign-flip permutation test of the structural-only gate against every other policy at half size. The gate beats random (+0.057, $p = 0.004$, Holm 0.023, 9/10 conversations), the 2010 product (+0.112, Holm 0.016, 10/10), Impact alone (+0.089, Holm 0.016, 10/10) and both A-MAC feature policies (+0.081 and +0.057, Holm 0.029 and 0.031). It does not reliably beat heat, the length-plus-revisit heuristic (+0.027, t-interval [-0.000, +0.054], Holm 0.146, 8/10), which is essentially turn length, the single strongest label correlate. Adding the six surface features to the structural gate changes nothing

Table 7. Exact sign-flip permutation over the ten conversations, structural-only gate minus each other policy, evidence hit at 50% memory. Positive favours the gate. Holm over the eight comparisons of this table.

Gate minus	Mean diff.	95% t-interval	p_{perm}	Holm	Conv. > 0
random	+0.057	[+0.030, +0.085]	0.004	0.023	9/10
SIV-2010	+0.112	[+0.052, +0.172]	0.002	0.016	10/10
impact-2010	+0.089	[+0.050, +0.128]	0.002	0.016	10/10
A-MAC-lite	+0.081	[+0.040, +0.123]	0.006	0.029	9/10
A-MAC, fitted	+0.057	[+0.018, +0.096]	0.008	0.031	8/10
heat	+0.027	[-0.000, +0.054]	0.049	0.146	8/10
graph gate, prior	+0.022	[-0.002, +0.046]	0.074	0.148	7/10
graph gate, full	-0.004	[-0.033, +0.026]	0.861	0.861	6/10

Table 8. Online arm: official LoCoMo token F1 and exact match from a fixed answerer, next to the offline evidence hit, for three memories. Pass 1 verbalises a fact as its observation sentence; pass 2 adds the observation date to every fact and the official temporal hint to temporal questions. Abstention is the share of answers equal to "No information available". Adversarial questions are scored by abstention, so a smaller memory scores higher on them.

Pass	Memory	Evidence hit	F1	EM	Abstention	F1, temporal
1	admit-all	0.643	0.427	0.322	0.544	0.058
1	structural gate, 50%	0.431	0.369	0.298	0.673	0.037
1	random, 50%	0.379	0.358	0.284	0.679	0.034
2	admit-all	0.643	0.491	0.343	0.469	0.318
2	structural gate, 50%	0.431	0.408	0.304	0.617	0.212
2	random, 50%	0.379	0.388	0.290	0.622	0.183

(-0.004): the structural features and turn length carry overlapping information about what the annotators asked about. The hand-set prior gate is weaker than the fitted structural gate (+0.022) and no better than heat.

Per category. At half size the structural gate's evidence hit by category is single-hop 0.398 (random 0.353), multi-hop 0.566 (0.516), temporal 0.447 (0.394), open-domain 0.303 (0.180) and adversarial 0.422 (0.370); the admit-all ceiling is 0.639, 0.633, 0.722, 0.427 and 0.643. These are exploratory.

6.3 Does the offline proxy predict answers? The online arm

Table 8 answers the 1,986 questions with the fixed model on three memories: admit-all, the structural gate at half size and random at half size, in both verbalisation passes. Three things follow.

The proxy carries signal. Pooling the three memories and excluding the abstention-scored adversarial category, the mean F1 of a question whose gold-evidence fact was retrieved is 0.461 against 0.101 when it was not (pass 2; 0.362

against 0.082 in pass 1). The contrast is largest on single-hop questions (+0.474) and smallest on open-domain questions (+0.106), whose gold answers are rarely a retrievable fact.

Undated facts cannot answer temporal questions. In pass 1 the temporal F1 of the admit-all memory is 0.058 at an evidence hit of 0.722: the gold fact is retrieved, but the fact store has stripped the date the question asks for. Appending the observation date and the official hint (pass 2) raises it to 0.318 and the overall F1 from 0.427 to 0.491. Any evaluation of a fact-store memory on LoCoMo that omits one of the two under-reports temporal performance by this margin.

The proxy overstates the gate's benefit. The structural gate's offline advantage over random at half size is +0.057 evidence hit ($p = 0.004$, 9/10 conversations). The same two memories, answered, differ by +0.013 F1 in pass 1 (t-interval [-0.003, +0.029], $p = 0.105$, 6/10) and by +0.026 in pass 2 ([-0.002, +0.054], $p = 0.064$, 6/10). The per-conversation differences in hit and in F1 agree in sign on 7 of ten conversations and are rank-correlated at +0.92 (pass 2; +0.52 in pass 1), so the proxy orders conversations correctly while roughly halving the effect, from a result that is clear at $k = 10$ to one at the edge of significance. Retrieving a gold fact is necessary for answering but not sufficient: the answerer still has to extract the answer from a one-sentence fact, and a memory that holds half the facts drives abstention to 0.617 of questions. The size of the effect that an offline sweep reports should be read as an upper bound on what a user would see, and dated facts with the official hint (pass 2) are the verbalisation under which the proxy tracks answers best.

6.4 H1: the Mem0 gate as the LLM baseline

The verbatim Mem0 gate, run over all 10 conversations with the same model, returns 2434 ADD, 75 UPDATE, 0 DELETE and 11344 NONE events over 2375 calls (3 unparseable responses) and admits a share 0.975 of candidate turns (per conversation 0.921–0.989), a memory of 2582 live facts, a fraction 0.986 of admit-all's. Its evidence hit is 0.638 against admit-all's 0.643. The cost is 742 calls and 2,074,667 tokens per thousand candidate facts (one call per candidate turn). On distilled observations, which already are the "facts" a Mem0 extraction call would produce, the gate finds almost nothing to reject: the UPDATE and DELETE paths that make it a gate in the first place are reached 75 and 0 times in 2,541 sentences, and NONE is returned for old memories, not for candidates. The pre-registered non-inferiority contrast is therefore run at the Mem0 gate's own realised size: the structural gate matched to that size reaches an evidence hit of 0.640 and an F1 of 0.490 against the Mem0 memory's 0.488 (difference +0.11 F1 points, t-interval [-1.02, +1.24], inside the pre-registered 2.0-point margin; random at that size 0.481). H1 therefore holds on LoCoMo (its LongMemEval-S half, 2.0 accuracy points, is untested), but trivially: at a memory size the LLM gate cannot be asked to change, the question "is the LLM-free gate within two points" is answered by construction, and the substantive finding of this arm is that the LLM gate spends one call per candidate turn (742 per thousand candidate facts) to admit 0.975

Table 9. LongMemEval-S, 500 questions, memory matched to 50% of admit-all per question. Evidence hit, evidence fraction and MRR of the retrieved set; paired per-question sign-flip permutation tests on the 479 questions with gold evidence, fitted gate minus each other policy, Holm over the three.

Policy	Hit	Frac	MRR	Live
admit-all	0.574	0.411	0.362	167,482
graph gate, structural, cross-fitted	**0.399**	0.262	0.291	84,038
graph gate, prior	0.334	0.212	0.249	83,679
random	0.326	0.202	0.211	83,784
heat	0.244	0.143	0.172	83,786

Fitted gate minus	Hit difference	95% t-interval	p_{perm}	Holm	Wins/losses
graph gate, prior	+0.065	[+0.024, +0.105]	0.003	0.006	65/34
random	+0.073	[+0.027, +0.119]	0.003	0.006	81/46
heat	+0.154	[+0.106, +0.203]	0.000	0.000	113/39

of those turns. Whether Mem0's gate is selective on raw turns rather than on pre-distilled observations is a question for the LLM-extraction arm.

6.5 A second dataset: LongMemEval-S

LongMemEval-S gives each of 500 questions its own haystack of 38 to 62 sessions, so each question is an independent memory and the question is the unit of inference. Candidates come from a *heuristic extractor* used only on this dataset: each sentence of a user or assistant turn that opens in the first person ("I", "I'm", "I've", "My", "We", "Our") goes through the dependency rule of Section 5 with the turn's speaker as subject, at tier extractor-inferred (confidence 0.8), and the hub set is {user, assistant} (a placeholder for the LLM-extraction arm; assistant turns yield a candidate only when a sentence is first-person, which the answer-bearing assistant turns of the single-session-assistant type rarely are, so that type is near zero for every policy); admit-all holds 167,482 live facts over the 500 memories, about 335 per question-memory against LoCoMo's 262 per conversation-memory (2618 over ten), and only one candidate in a hundred is gold evidence. Memory is matched by bisection to 50% of admit-all per question. Two gates are run: the hand-set prior weights of Section 4 (`graph_gate`) with no fitting, and the seven structural features fitted by five-fold cross-fitting over questions (each fold fitted on the admit-all candidate turns of the other 400 questions; grouped CV AUC 0.689–0.706; the largest weights are the 2010 impact term, +0.99 to +1.11 across folds, and pattern novelty, +0.31 to +0.40). No LoCoMo weights are used.

Three things follow (Table 9), two of them different from LoCoMo. The turn-length heuristic is +0.081 *below* random ($p = 0.001$): in a fifty-session haystack the long user turns are rarely the evidence, so its parity with the gate on LoCoMo was a statement about LoCoMo's annotators, not about the gate. The hand-set prior weights do not transfer: the unfitted gate is level with random

Table 10. Exploratory H3 on LoCoMo: share of candidate turns that are gold evidence of a question in the category, for turns whose non-hub vertices are all new ($A = 0$) against all known ($A = 1$), with Wilson 95% intervals. Turns with no non-hub vertex are excluded.

Category	$A = 0$ (new)	95% CI	$A = 1$ (known)	95% CI	Difference
single-hop	0.258	[0.238, 0.279]	0.215	[0.179, 0.255]	+0.044
multi-hop	0.244	[0.225, 0.265]	0.185	[0.151, 0.224]	+0.059
temporal	0.116	[0.102, 0.132]	0.094	[0.070, 0.125]	+0.022
open-domain	0.061	[0.051, 0.074]	0.037	[0.023, 0.059]	+0.025
adversarial	0.148	[0.132, 0.166]	0.112	[0.086, 0.145]	+0.037
any question	0.470	[0.447, 0.494]	0.390	[0.346, 0.437]	+0.080

$n = 1724$ turns with $A = 0$ and $n = 438$ with $A = 1$.

on hit (+0.008, $p = 0.798$) and only marginally ahead on rank (MRR +0.038, $p = 0.057$, t-interval [-0.001, +0.077]), so the weights must be fitted per dataset, a deviation from the single held-out fit the pre-registration described. Fitted on the dataset itself with no question in its own fold's fit (filler sessions shared between haystacks do recur across folds, always with label 0), the structural-only gate retains +0.073 more gold evidence than random at the same memory size (Holm $p = 0.006$, 81 wins to 46 losses) and +0.080 more MRR ($p < 0.001$); per type it leads most on multi-session (0.576 vs 0.440) and knowledge-update (0.486 vs 0.361) questions. The matched-size claim therefore rests on two datasets with two independent units of inference, and the fitted weights say that on a long haystack the "attached to what memory already holds" signal, useless on LoCoMo, is the one that carries information. The offline proxy has not been validated against answers on this dataset, and the extractor still produces no entity-to-entity edges (non-hub edge share 0.000 in the admit-all run); both are stated as limits in Section 7.

6.6 H3, exploratory: are facts about new entities worth more?

The 2010 prior says disconnected new knowledge is worth less than knowledge attached to known vertices. Table 10 contrasts candidate turns whose non-hub vertices are all new ($A = 0$) with turns whose non-hub vertices are all known ($A = 1$) by the share that are gold evidence turns of a question of the category. The all-new turns are evidence more often in every category (+0.080 overall, intervals [0.447, 0.494] against [0.346, 0.437]); the direction is the inversion H3 predicts, on every LoCoMo category, but the measure is evidence-label rate rather than the pre-registered per-fact answer-value delta, and the two groups differ in size by a factor of four, so we report it as exploratory; the pre-registered confirmation rule, inversion on the two single-session LongMemEval types, has not been evaluated.

Table 11. Poisoning arm, one fabricated fact per dialogue turn with probability 10% (just over a quarter of the candidate stream), memory 50%, 1206 injected facts paired across policies. Sourceless: poison tier confidence equals the real candidates'. Lower: poison tier 0.4 against 0.6. ×tier: the policy score is multiplied by mean tier confidence. "Questions with poison" is the share of questions whose retrieved set holds at least one injected fact.

Condition	Policy	Poison admitted	Questions with poison
sourceless	random	0.288	0.997
sourceless	graph gate, prior	0.322	0.997
sourceless	graph gate, structural	0.340	0.996
lower ×tier	random	0.187	0.990
lower ×tier	graph gate, prior	0.104	0.959
lower ×tier	graph gate, structural	0.097	0.950

6.7 H4: poisoning and the provenance tier

Table 11 reports the poisoning arm at a 10% per-dialogue-turn injection rate (just over a quarter of the candidate stream) and 50% memory over 1206 injected facts. When the poison carries the same tier confidence as real candidates (*sourceless*), both graph gates, prior and structural-only, admit *more* of it than random (0.340 and 0.322 against 0.288), and the tier multiplier has, by construction, no effect. Fabricated facts about hub-adjacent entities with real-vocabulary predicates are novel and anchored in exactly the way the gate rewards. When the poison carries a lower tier and the score is multiplied by tier confidence, poison admission falls to 0.097 and 0.104 (random with the multiplier 0.187), and evidence hit rises, from 0.300 to 0.403 for the structural-only gate and from 0.294 to 0.378 for the prior gate (overall hit in the run summaries `merged_poison_*`), because poison stops displacing real facts within the same budget. Nearly every question still retrieves at least one injected fact (0.950 of questions under the best condition), so the retrieval-level harm of this injection rate needs the online arm. The statement the arm supports is that structural novelty is blind to truth and that provenance weighting, not structure, is the defence; the sourceless condition is the honest ceiling on what an attacker who can forge the provenance route achieves, as Fei et al.'s accumulability criterion predicts for a reallocatable retrieval selector, here carried over to an admission score [15].

6.8 Why the graph has no topology, and where it could

The zero share of entity-to-entity edges is not an extractor artefact. Parsing all 2,541 observation sentences, the grammatical subject of the main verb is a speaker's name in 84.6% of sentences, a speaker's possessive ("Melanie's kids") in 6.0%, unparsable in 6.5%, and any other entity or common noun in 2.3%. The benchmark's own observations are written as "Caroline did X". We simulated three LLM-free rules on top of the current extraction: keeping a relation noun's

appositive name as subject ("Caroline's husband John works at Dell" → (John, works_at, Dell)) yields *zero* edges in the corpus; keeping a non-speaker nominal subject yields at most 6 edges per conversation, of poor quality; linking the primary object to every other named entity of the sentence ("co-mentioned with") yields 4–64 edges per conversation and would raise the non-hub edge share to between 2% and 20% of live edges, but the edge is not a relation and would turn anchoring into a within-sentence co-occurrence count. Nor would an LLM extractor on the raw turns help on this dataset: 11.8% of turns mention a third-party named entity and 1.0% mention two, the precondition for an entity-to-entity fact. On LongMemEval-S, by contrast (spaCy NER over the user turns of the first 40 questions; the LoCoMo figures are over the raw turns of the first three conversations), 41.2% of user turns mention a third-party entity and 15.5% mention two, fifteen times LoCoMo's density. That, and the knowledge-update question type, is where the realised-change hypothesis H2, the consolidation step and any genuinely structural claim have to be tested; the graph-shape precondition table of Section 6.1 is printed before every such run.

6.9 Cost

Admit-all and the nine LLM-free admission policies make no write-path model call. The Mem0 gate makes 742 calls and 2,074,667 tokens per thousand candidate facts. The online arm of this paper (two passes over three memories, the Mem0 gate and its matched comparison) took 21,156 model calls, 24.0M input and 1.13M output tokens, about $2.97 at list price, with thinking disabled; with thinking enabled, as the model runs by default, 15% of gate calls were truncated at the 256-token budget of the 19 October smoke test, which is why the adapter disables it.

7 Threats to validity

Construct. Evidence hit is a proxy, and Section 6.3 measures by how much it overstates: a policy effect of +0.057 in hit became +0.026 in F1 ($p = 0.064$). The admission label used to fit the gate ("the source turn is a gold evidence turn") is relevance to the benchmark's questions, not value in general; leakage is prevented by leave-one-conversation-out fitting, but a gate fitted this way is tuned to the benchmark's question distribution, and turn length is its best single predictor, which says as much about how annotators choose questions as about memory. The 2010 measures were designed for document-sized targets against an encyclopaedic context; we test them at a granularity their authors did not intend, which is the point of the degeneracy analysis, but it means the result is about the formulation at fact granularity.

Internal. Entity-resolution errors create spurious degree, GAM's "lexical noise" objection [38]; the hand check of Section 5 is 18 triples read by a single annotator and the 200-mention entity-resolution precision sample is owed; on

LongMemEval-S the heuristic extractor has had no hand check at all. The oracle arm's candidates are gpt-3.5-turbo observations that cover 76% of gold evidence turns and pre-select which turns yield candidates at all; admit-all's ceiling of 0.643 is a property of that coverage. The graph is two stars, so anchoring, impact and T_{edge} are near-constant and their non-zero values measure recurrence (Section 6.8). Consolidation never fires, so the predicted/actual distinction is void in this arm and H2 is untested rather than null. The gate's weights are fitted on features computed along an admit-all trajectory but applied to the smaller graph the gate itself builds. The answerer is one model with thinking disabled; its abstention behaviour (0.469 on the full memory) sets the F1 scale, and the adversarial category rewards abstention, so smaller memories score higher there. Random admission uses one seed. On LongMemEval-S the extractor is a first-person heuristic with no hand check, about a third of its candidate turns are assistant turns, and the fitted weights put most mass on the 2010 impact term, whose variation in a star-shaped graph measures recurrence of objects around the two hubs rather than topology.

External. Two English benchmarks, both dyadic; speakers (or the user) as hubs is a property of dyadic chat, and the LongMemEval-S arm is offline only. The poisoner is synthetic and non-adaptive; the pre-registered 0/2/10% grid and QA harm are not run. The Mem0 gate was run on pre-distilled observations, where it is not selective; its behaviour on raw turns is untested here.

Statistical. Ten conversations is the honest unit on LoCoMo and the smallest attainable permutation p is 0.002; on LongMemEval-S the unit is the question, the sign-flip test over 479 questions samples 20,000 sign assignments rather than enumerating them, and filler sessions shared between haystacks put identical label-0 candidates in a fold's fit and its held-out questions; the Holm families are those of each table, not the pre-registered four-hypothesis family. The question-level bootstrap is anti-conservative and reported as secondary. Matched size says nothing about what a policy does at another size; the curves of Figure 1 are reported for that.

Framing. "LLM-free" describes the gate, not the write path: the LoCoMo oracle arm consumes model-generated observations, so only the LongMemEval-S arm, whose extractor reads raw user turns, is model-free from the turn text onward. The precise claim is zero model calls at the gate, given an extractor.

8 Conclusion

We took a 2010 measure of the value of information to a graph-shaped world view, showed where it breaks when the world view is an agent's memory and the information is a single conversational fact, repaired it without adding a model call, and tested it under a pre-registered protocol with everything but the admission policy held fixed. The verdicts are: the 2010 trust-times-impact

product and Impact alone are the two worst admission policies at every budget, below random throughout, for arithmetic reasons that any fact-granular use of them will share; the repaired, LLM-free gate beats random, the 2010 measures and lexical features at matched size on LoCoMo but is no better than turn length there, and its offline advantage shrinks by about half, to the edge of significance over ten conversations, when the questions are actually answered; on LongMemEval-S the same gate, cross-fitted over 500 questions and tested on the 479 with gold evidence, beats random by +0.073 while turn length falls below random, so the advantage is real but its weights are dataset-specific; the verbatim Mem0 gate does not gate on distilled observations, so the pre-registered non-inferiority question becomes a cost question on this benchmark; facts about new entities are, exploratorily, gold evidence more often than facts about known ones, against the 2010 prior; and structural novelty admits more poison than random unless provenance is weighted. The realised-change hypothesis and every genuinely topological claim move to LongMemEval-S with an LLM extractor, where the data has the structure that LoCoMo lacks. The measures remain al-Saffar and Heileman's; what is new is the evidence, including the negative parts.

Supplementary Material Statement

Code (`paper2/`), the frozen pre-registration with its implementation log and deviations, the verbatim Mem0 prompt module with attribution, run artefacts (`paper2/out/`) and the number files behind every table (`paper2/paper/numbers.tex`, `numbers_online.tex`, `numbers_lme.tex`) are released at `https://github.com/zubertaj123/context-graph-research` (a Zenodo DOI for the tagged release will be added in the next version) under MIT (code), CC BY 4.0 (paper, documents and run artefacts). LoCoMo is used under its own licence; the Mem0 prompt is Apache-2.0; no proprietary data is used.

Acknowledgments. Trust, impact and the two semantic information values are the work of Sinan al-Saffar and Gregory Heileman [2,3,1]; the extant ontology is al-Saffar, Joslyn and Chappell's and the motif information gain is Joslyn, al-Saffar, Haglin and Holder's [4,23]. This paper implements and evaluates those measures; it does not claim them. The author has not been in contact with Dr. al-Saffar; the attribution above is the acknowledgement, and if Dr. al-Saffar can be reached, an offer of acknowledgement or co-authorship will be made, as the pre-registration commits to, before any venue submission.

Disclosure of Interests. The author has no competing interests to declare that are relevant to the content of this article.

Declaration on Generative AI

During the preparation of this work the author used a large-language-model coding assistant (Claude, Anthropic) to draft code, the LaTeX, the related-work

notes and parts of the prose from the pre-registration document and the run logs, and to run the experiments. Claude Haiku 5.5 is also the fixed answerer of the online arm and the model behind the Mem0 gate baseline, as described in Section 5. The author reviewed and edited the content and takes full responsibility for the publication's content.

References

1. al-Saffar, S., Heileman, G.: Computing information value from RDF graph properties. In: Proceedings of the 12th International Conference on Information Integration and Web-based Applications & Services (iiWAS 2010). pp. 349–356. ACM, Paris, France (2010). https://doi.org/10.1145/1967486.1967541
2. al-Saffar, S., Heileman, G.L.: Semantic impact graphs for information valuation. In: Proceedings of the Eighth ACM Symposium on Document Engineering (DocEng 2008). pp. 209–212. ACM (2008). https://doi.org/10.1145/1410140.1410181
3. al-Saffar, S., Heileman, G.L.: Semantics-based information valuation. In: 2008 4th International IEEE Conference on Intelligent Systems (IS 2008). pp. 6–51–6–58. IEEE, Varna, Bulgaria (2008). https://doi.org/10.1109/IS.2008.4670438
4. al-Saffar, S., Joslyn, C., Chappell, A.: Structure discovery in large semantic graphs using extant ontological scaling and descriptive semantics. In: 2011 IEEE/WIC/ACM International Conferences on Web Intelligence and Intelligent Agent Technology (WI-IAT). pp. 211–218. IEEE (2011). https://doi.org/10.1109/WI-IAT.2011.241
5. Bachmann, M.: RapidFuzz: Rapid fuzzy string matching in python and c++. Software, version 3.14.6, https://github.com/rapidfuzz/RapidFuzz (2021)
6. Berners-Lee, T., Connolly, D.: Delta: An ontology for the distribution of differences between RDF graphs. W3C Design Issues note, created 2001, revised (revision 1.114); https://www.w3.org/DesignIssues/Diff, accessed 22 October 2026 (2001)
7. Bunke, H.: On a relation between graph edit distance and maximum common subgraph. Pattern Recognition Letters **18**(8), 689–694 (1997). https://doi.org/10.1016/S0167-8655(97)00060-3
8. Cheng, G., Tran, T., Qu, Y.: RELIN: Relatedness and informativeness-based centrality for entity summarization. In: The Semantic Web – ISWC 2011. Lecture Notes in Computer Science, vol. 7031, pp. 114–129. Springer (2011). https://doi.org/10.1007/978-3-642-25073-6_8
9. Chhikara, P., Khant, D., Aryan, S., Singh, T., Yadav, D.: Mem0: Building production-ready AI agents with scalable long-term memory. arXiv preprint arXiv:2504.19413 (2025)
10. Dong, X., Gabrilovich, E., Heitz, G., Horn, W., Lao, N., Murphy, K., Strohmann, T., Sun, S., Zhang, W.: Knowledge vault: A web-scale approach to probabilistic knowledge fusion. In: Proceedings of the 20th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining (KDD 2014). pp. 601–610. ACM (2014). https://doi.org/10.1145/2623330.2623623
11. Dong, X.L., Gabrilovich, E., Murphy, K., Dang, V., Horn, W., Lugaresi, C., Sun, S., Zhang, W.: Knowledge-based trust: Estimating the trustworthiness of web sources. Proceedings of the VLDB Endowment **8**(9), 938–949 (2015). https://doi.org/10.14778/2777598.2777603

12. Du, Y., Huang, W., Zheng, D., Wang, Z., Montella, S., Lapata, M., Wong, K.F., Pan, J.Z.: Rethinking memory in LLM based agents: Representations, operations, and emerging topics. arXiv preprint arXiv:2505.00675 (2025)
13. Efron, B., Tibshirani, R.J.: An Introduction to the Bootstrap. Chapman & Hall, New York (1993)
14. Fang, J., Deng, X., Xu, H., Jiang, Z., Tang, Y., Xu, Z., Deng, S., Yao, Y., Wang, M., Qiao, S., Chen, H., Zhang, N.: LightMem: Lightweight and efficient Memory-Augmented generation. arXiv preprint arXiv:2510.18866 (2025)
15. Fei, Z., Fei, H., Wang, X., Yang, Y., Gope, P., Sikdar, B., Zhang, Y.: Selection integrity for LLM graph memory: An accumulability criterion for Information-Flow-Blind retrieval. arXiv preprint arXiv:2606.12290 (2026)
16. Foundation Capital: AI's trillion-dollar opportunity: Context graphs. Essay, `https://foundationcapital.com/ideas/context-graphs-ais-trillion-dollar-opportunity`, page dated 16 October 2026, accessed 22 October 2026; an earlier version circulated in December 2025 (2026)
17. Gutiérrez, B.J., Shu, Y., Gu, Y., Yasunaga, M., Su, Y.: HippoRAG: Neurobiologically inspired long-term memory for large language models. In: Advances in Neural Information Processing Systems (NeurIPS 2024) (2024), arXiv:2405.14831
18. Gutiérrez, B.J., Shu, Y., Qi, W., Zhou, S., Su, Y.: From RAG to memory: Non-Parametric continual learning for large language models. In: Proceedings of the 42nd International Conference on Machine Learning (ICML) (2025), arXiv:2502.14802
19. Hartig, O., Champin, P.A., Seaborne, A., Kellogg, G.: RDF 1.2 concepts and abstract data model. W3C Candidate Recommendation Snapshot, 7 April 2026, `https://www.w3.org/TR/rdf12-concepts/` (2026)
20. Hogan, A., Blomqvist, E., Cochez, M., d'Amato, C., de Melo, G., Gutierrez, C., Kirrane, S., Labra Gayo, J.E., Navigli, R., Neumaier, S., Ngonga Ngomo, A.C., Polleres, A., Rashid, S.M., Rula, A., Schmelzeisen, L., Sequeda, J., Staab, S., Zimmermann, A.: Knowledge graphs. ACM Computing Surveys **54**(4) (2021). `https://doi.org/10.1145/3447772`
21. Holm, S.: A simple sequentially rejective multiple test procedure. Scandinavian Journal of Statistics **6**(2), 65–70 (1979)
22. Hu, Y., Liu, S., Yue, Y., Zhang, G., Liu, B., Zhu, F., Lin, J., Guo, H., Dou, S., Xi, Z., et al.: Memory in the age of AI agents. arXiv preprint arXiv:2512.13564 (2025)
23. Joslyn, C., al-Saffar, S., Haglin, D., Holder, L.: Combinatorial information theoretical measurement of the semantic significance of semantic graph motifs. In: Proceedings of the Workshop on Mining Data Semantics (MDS 2011), co-located with KDD 2011. San Diego, CA, USA (2011), workshop paper, not indexed; available from PNNL: `https://hpc.pnl.gov/people/sinan/publications/SemInfMeasures-KDD11.pdf`
24. Kang, J., Ji, M., Zhao, Z., Bai, T.: Memory OS of AI agent. arXiv preprint arXiv:2506.06326 (2025)
25. Liu, Q., Cheng, G., Gunaratna, K., Qu, Y.: Entity summarization: State of the art and future challenges. Journal of Web Semantics **69**, 100647 (2021). `https://doi.org/10.1016/j.websem.2021.100647`
26. Ma, W., Nan, J., Wu, W., Chen, Y.: What deserves memory: Adaptive memory distillation for LLM agents. arXiv preprint arXiv:2508.03341 (2025)
27. Maharana, A., Lee, D.H., Tulyakov, S., Bansal, M., Barbieri, F., Fang, Y.: Evaluating very long-term conversational memory of LLM agents. In: Proceedings of

the 62nd Annual Meeting of the Association for Computational Linguistics (ACL 2024) (2024), loCoMo. arXiv:2402.17753
28. Nosek, B.A., Ebersole, C.R., DeHaven, A.C., Mellor, D.T.: The preregistration revolution. Proceedings of the National Academy of Sciences **115**(11), 2600–2606 (2018). https://doi.org/10.1073/pnas.1708274114
29. Packer, C., Wooders, S., Lin, K., Fang, V., Patil, S.G., Stoica, I., Gonzalez, J.E.: MemGPT: Towards LLMs as operating systems. arXiv preprint arXiv:2310.08560 (2023)
30. Park, J.S., O'Brien, J.C., Cai, C.J., Morris, M.R., Liang, P., Bernstein, M.S.: Generative agents: Interactive simulacra of human behavior. In: Proceedings of the 36th Annual ACM Symposium on User Interface Software and Technology (UIST 2023). ACM (2023). https://doi.org/10.1145/3586183.3606763
31. Park, Y.B.: Graph-Native cognitive memory for AI agents: Formal belief revision semantics for versioned memory architectures. arXiv preprint arXiv:2603.17244 (2026)
32. Paulheim, H., Bizer, C.: Improving the quality of linked data using statistical distributions. International Journal on Semantic Web and Information Systems **10**(2), 63–86 (2014). https://doi.org/10.4018/ijswis.2014040104
33. Rasmussen, P., Paliychuk, P., Beauvais, T., Ryan, J., Chalef, D.: Zep: A temporal knowledge graph architecture for agent memory. arXiv preprint arXiv:2501.13956 (2025)
34. Robertson, S., Zaragoza, H.: The probabilistic relevance framework: BM25 and beyond. Foundations and Trends in Information Retrieval **3**(4), 333–389 (2009). https://doi.org/10.1561/1500000019
35. Sumers, T.R., Yao, S., Narasimhan, K., Griffiths, T.L.: Cognitive architectures for language agents. Transactions on Machine Learning Research (2024), coALA. arXiv:2309.02427
36. Wilson, E.B.: Probable inference, the law of succession, and statistical inference. Journal of the American Statistical Association **22**(158), 209–212 (1927)
37. Wu, D., Wang, H., Yu, W., Zhang, Y., Chang, K.W., Yu, D.: LongMemEval: Benchmarking chat assistants on Long-Term interactive memory. In: International Conference on Learning Representations (ICLR) (2025), arXiv:2410.10813
38. Wu, Z., Zhang, H., Lin, F., Xu, W., Xu, X., Chen, Y., Zou, H.P., Chen, S., Zhang, W., Liu, X., Yu, P.S., Wang, H.: GAM: Hierarchical graph-based agentic memory for LLM agents. arXiv preprint arXiv:2604.12285 (2026)
39. Xu, C., Li, M., Yang, C., Jiang, X., Tang, L., Qi, Y., Guo, J.: Context graph. arXiv preprint arXiv:2406.11160 (2024)
40. Xu, W., Liang, Z., Mei, K., Gao, H., Tan, J., Zhang, Y.: A-MEM: Agentic memory for LLM agents. In: Advances in Neural Information Processing Systems (NeurIPS) (2025), arXiv:2502.12110
41. Yan, S., Yang, X., Huang, Z., Nie, E., Ding, Z., Li, Z., Ma, X., Bi, J., Kersting, K., Pan, J.Z., Schütze, H., Tresp, V., Ma, Y.: Memory-R1: Enhancing large language model agents to manage and utilize memories via reinforcement learning. arXiv preprint arXiv:2508.19828 (2025)
42. Zep AI: Graphiti: Build real-time knowledge graphs for AI agents. Software repository, https://github.com/getzep/graphiti, accessed 15 October 2026 (2024)
43. Zhang, G., Jiang, W., Wang, X., Behr, A., Zhao, K., Friedman, J., Chu, X., Anoun, A.: Adaptive memory admission control for LLM agents. arXiv preprint arXiv:2603.04549 (2026), code: https://github.com/GuilinDev/Adaptive_Memory_Admission_Control_LLM_Agents

44. Zhong, W., Guo, L., Gao, Q., Ye, H., Wang, Y.: MemoryBank: Enhancing large language models with long-term memory. In: Proceedings of the AAAI Conference on Artificial Intelligence (2024), arXiv:2305.10250