

History of Linux and the command line

Zubin

January 31, 2026

Contents

1	Compiler vs interpreter	3
1.1	The Interpreter	3
1.2	The Compiler	3
1.3	Summary	3
2	Memory representation:	
	RAM, cells, word, byte, bit, memory address	4
2.1	Types of Memory	4
2.2	Structure of RAM	4
2.3	Memory Addressing	4
2.4	Memory and C Programming	4
3	Manage the memory with the command line:	
	free, top, htop	5
3.1	The free Command	5
3.2	The top Command	5
3.3	The htop Command	5
4	Memory consumption of a program using htop, virtual memory	6
4.1	Memory Usage by Data Type	6
4.2	Virtual vs. Physical Memory	6
4.3	Memory Management Tips	6
5	Interactive programs in C using scanf, fflush	7
5.1	Basic Interactive Program with scanf	7
5.2	The Problem of Buffered Output	7
5.3	The Solution: Flushing the Buffer with fflush	7
5.4	Important Considerations	8
6	Use scanf and file redirection to simulate an input	8
6.1	Creating an Input File	8

6.2	Method 1: Using Pipes	9
6.3	Method 2: Input Redirection	9
7	Don't use scanf, use fgets getline or readline	9
7.1	The Problem with scanf	9
7.2	Better Alternatives	10
8	Use the math library	10
8.1	Using the pow function	10
8.2	Locating the Library Binary	10
8.3	Header Files	10
8.4	Linking with the -l Option	11
9	Use multiple libraries in C	11
9.1	Locating Headers and Libraries	11
9.2	Including Headers	11
9.3	Linking Libraries	12
9.3.1	Method 1: Absolute Path	12
9.3.2	Method 2: Using the -l Flag	12
10	GCC details	12
10.1	The Build Command and Flags	12
10.2	Compilation Stages	13
10.2.1	1. The Preprocessor	13
10.2.2	2. Compilation (Translation)	13
10.2.3	3. The Linker	13
11	Object files	14
11.1	Creating Separate Files	14
11.2	Compiling Object Files	14
11.2.1	Compiling the Module	14
11.2.2	Compiling the Main Program	14
11.3	Linking	14
12	Modify object files	15
12.1	Modifying the Source Code	15
12.1.1	Updating the Main Program	15
12.1.2	Updating the Module	15
12.1.3	Updating the Header	16
12.2	Compiling and Linking	16
12.3	Partial Recompilation	16

1 Compiler vs interpreter

In the C programming language, we use a compiler. To understand the difference between an interpreter and a compiler, we can use an analogy of landing on a planet where inhabitants speak a strange language called "Gobbledygook". To get a mechanic to repair your spaceship, you need a translator.

1.1 The Interpreter

If you choose an interpreter:

- **Process:** The interpreter reads your first instruction, translates it immediately, and the mechanic executes it. Then it reads the second, translates, and executes, and so on.
- **Characteristics:** The interpreter stays with you, translating line by line.
- **Pros:** It allows you to correct mistakes as you go (interactive).
- **Cons:** It is a slow process because the mechanic waits for translation between steps.
- **Etymology:** "Inter" means between. The interpreter is always between your program and the computer.

1.2 The Compiler

If you choose a compiler:

- **Process:** The compiler takes your complete list of instructions and translates the whole lot at once. It then hands the translated list back to you and leaves.
- **Characteristics:** You hand the complete list to the mechanic, who executes them all in one go very quickly.
- **Pros:** Execution is very fast and efficient.
- **Cons:** Takes extra preparation time initially. If there is a mistake, it is too late to fix it during execution.
- **Etymology:** "Compile" means to pile together. It piles together your entire program and translates it all at once.

1.3 Summary

- **Interpreter:** Runs slowly, starts right away, allows you to see how things are going.
- **Compiler:** Takes preparation time, but runs very quickly and efficiently.

2 Memory representation:

RAM, cells, word, byte, bit, memory address

How does the computer remember where it has stored the value for a certain variable? To answer this, we need to understand computer memory.

2.1 Types of Memory

One role of the operating system is to manage the computer's memory.

- **RAM (Random Access Memory):** Temporary, volatile memory used to execute programs. It is quick to access.
- **Non-volatile Memory:** Permanent storage, such as the hard drive, used for storing files.

2.2 Structure of RAM

Most programs use RAM during execution.

- **Bit:** A single binary memory cell (0 or 1).
- **Word:** A group of bits forming the fundamental unit of data moved between RAM and the processor.
- **Word Size:** The number of bits in a word (e.g., 8, 16, 32, 64 bits).
- **Byte:** A unit consisting of 8 bits.

2.3 Memory Addressing

To locate data, memory cells are grouped into words, and each word is assigned an address.

- **Memory Address:** A whole number describing the location of a word in memory (similar to house addresses on a street).
- **Example:** If a computer has 8-bit words:
 - Address 0 points to the first word (first 8 bits).
 - Address 1 points to the second word (next 8 bits).

2.4 Memory and C Programming

In C, it is possible to access these memory addresses directly.

- **Access:** You can obtain the address where a variable's value is stored.
 - **Optimization:** This allows for low-level memory management and optimization of execution speed.
-

3 Manage the memory with the command line: free, top, htop

To manage memory, we first need to see how much memory is used by the programs running on the Linux system.

3.1 The free Command

The free command displays the amount of free and used system memory.

- **Options:** Use `-b` (bytes), `-k` (kilobytes), `-m` (megabytes), or `-g` (gigabytes) to set the unit.
- **Example:** `free -m` displays the table in megabytes.
- **Output:** The Mem line shows the total, used, and free memory.

3.2 The top Command

The top command shows memory usage per process.

- **Statistics:** The header shows total used and free memory.
- **VSZ (Virtual Size):** Represents the virtual memory for each program (sometimes labeled **VIRT**).
- **Sorting:** Press the **M** key to sort processes by memory usage.
- **Visualization:** Pressing the **S** key (in this specific version) switches to a view showing only memory usage.

3.3 The htop Command

htop provides a visual representation of system resources.

- **Visuals:** Bars indicate used and free memory.
- **Sorting:**
 1. Press **F6** to select "Sort by".
 2. Select **M_SIZE** (Memory Size) and press **Enter**.

3. This sorts the list by the **VIRT** column.

Monitoring memory helps identify programs putting too much pressure on the system, which can then be killed if necessary.

4 Memory consumption of a program using htop, virtual memory

We can analyze how much memory a C program uses by running it and monitoring it with htop. To do this effectively, the program must pause (e.g., waiting for user input via scanf) so it stays active in memory.

4.1 Memory Usage by Data Type

By declaring arrays of different types with one million elements, we can observe how memory consumption changes in the VIRT (Virtual Memory) column of htop:

- **Basic Program:** A simple program might use ≈ 952 KB.
- **Char Array (1,000,000 chars):** Usage increases to $\approx 1,800$ KB.
- **Int Array (1,000,000 ints):** Usage increases significantly to $\approx 4,728$ KB (approx. 4 MB).
- **Double Array (1,000,000 doubles):** Usage doubles compared to integers, reaching $\approx 8,632$ KB (approx. 8 MB).

4.2 Virtual vs. Physical Memory

An important observation is that even when a program reserves a large amount of memory (high VIRT), the system's physical memory usage (the bar at the top of htop) may not increase correspondingly.

- **Virtual Memory:** The amount of memory the program has asked for or reserved.
- **Physical Memory:** The actual RAM hardware used.
- **Lazy Allocation:** Linux is smart; if a program reserves memory (like a large array) but never writes to or reads from it, the system does not immediately allocate physical RAM. Physical memory is consumed only when the virtual memory is actually used.

4.3 Memory Management Tips

- **Optimization:** Ensure that large arrays or variables are used efficiently.

- **Dynamic Allocation:** If you allocate memory dynamically in C, always remember to **free** it to return it to the system for other programs.
-

5 Interactive programs in C using `scanf`, `fflush`

This section explains how to create interactive C programs and handle a common issue related to terminal output buffering.

5.1 Basic Interactive Program with `scanf`

An interactive program prompts the user for input and reads it from the terminal.

- **Prompting:** Use `printf` to display a question to the user.
- **Reading Input:** Use `scanf` to wait for and read the user's input.
- **Example:** A program can ask for a family name, first name, and age.
 - `scanf("%s", familyName)` reads a string into a character array.
 - `scanf("%d", &age)` reads an integer into an integer variable.
- Typically, each prompt with `printf` ends with a newline character (`\n`) to move the cursor to the next line for the user's input.

5.2 The Problem of Buffered Output

The `printf` function in C uses a buffer, which is a temporary memory area.

- **Buffering:** Output is not always sent directly to the screen. It is first stored in a buffer. The buffer is "flushed" (its contents are sent to the terminal) when certain conditions are met.
- **Newline Trigger:** A common trigger for flushing the buffer is encountering a newline character (`\n`).
- **The Issue:** If you write a `printf` statement for a prompt without a trailing `\n`, the text may not appear on the screen immediately. The program might wait for the user's input with `scanf` before the prompt is even visible. All the buffered prompts might appear in a single line only after the program finishes or the buffer is flushed for another reason.

5.3 The Solution: Flushing the Buffer with `fflush`

To ensure prompts appear immediately without a newline, you can manually flush the output buffer.

- **The Command:** The `fflush(stdout)` function forces the standard output buffer (`stdout`) to be written to the screen.
- **Implementation:** Place `fflush(stdout);` immediately after each `printf` statement that you want to appear on the screen right away.
- **Example:**

```
printf("What is your first name? ");  
fflush(stdout);  
scanf("%s", firstName);
```

- This ensures the question is visible before the program waits for the `scanf` input, even without a `\n`. The user's answer will then appear on the same line as the question.

5.4 Important Considerations

- **System Variability:** This buffering behavior is not consistent across all Linux systems. Some systems or C libraries might flush output more frequently, even without a newline.
 - **Best Practice:** To write portable and predictable interactive programs, always ensure the output buffer is flushed. The two main ways are:
 1. End your prompt strings with `\n`.
 2. Call `fflush(stdout);` after the prompt.
-

6 Use scanf and file redirection to simulate an input

We can automate or simulate user input for interactive programs using pipes and file redirection. This is useful for testing or when running programs in scripts.

6.1 Creating an Input File

First, create a file containing the inputs expected by the program, separated by newlines.

- **Example:** Create a file named `answers` with the following content:

```
sharrock  
remi  
18
```

- You can create this using `nano` or `cat > answers`.

6.2 Method 1: Using Pipes

You can pipe the output of a command (like `cat`) into your program.

- **Command:** `cat answers | ./program`
- **Explanation:** The shell takes the output of `cat answers` and feeds it as standard input to `./program`. The `scanf` functions in the program read from this stream just as if it were typed on the keyboard.

6.3 Method 2: Input Redirection

You can redirect a file directly into the program's standard input using the less-than sign (`<`).

- **Command:** `./program < answers`
 - **Explanation:** This tells the shell to open the file `answers` and connect it to the input of `./program`.
 - **Note:** This is the reverse of output redirection (`>`), which sends output to a file. Here, we send a file to the input.
-

7 Don't use `scanf`, use `fgets` `getline` or `readline`

Using `scanf` for string input can be dangerous and lead to unexpected behavior for both programmers and users.

7.1 The Problem with `scanf`

`scanf` splits input based on whitespace (spaces, tabs, newlines).

- **Scenario:** A program asks for Family Name, First Name, and Age sequentially.
- **Input:** If the user types "Sharrock Remi 18" at the first prompt and hits Enter.
- **Result:**
 - Family Name becomes "Sharrock".
 - First Name automatically becomes "Remi" (consuming the next part of the buffer).
 - Age automatically becomes "18".
- The program skips waiting for the subsequent inputs because `scanf` consumed the space-separated values from the first line. This behavior makes `scanf` risky for robust user interaction.

7.2 Better Alternatives

To handle string input more safely, consider these functions:

- **fgets:** Reads the entire line, including spaces. Note that it also captures the newline character (`\n`) at the end, which you may need to remove.
- **getline:** A POSIX-standard function (available on most Unix-like systems) that reads an entire line.
- **GNU readline:** A powerful function specific to Linux/GNU systems.

For robust C programming, it is recommended to research these functions or take a dedicated C programming course.

8 Use the math library

8.1 Using the pow function

We can use the math library to perform calculations, such as finding the square of a number, instead of writing our own function. The `pow` function calculates a number raised to the power of another.

- **Prototype:** Also known as the declaration, header, or signature. It defines the return type, function name, and parameter types.
- **Example:** `double pow(double x, double y);`
- **Usage:** `pow(a, 2)` calculates a^2 .

To use this function, we need to link our program to the binary file containing its definition.

8.2 Locating the Library Binary

Compiled library files are typically stored in `/usr/lib`.

- The math library is often named `libm.a` (archive) or `libm.so` (shared object).
- **Linking with Absolute Path:** You can compile by specifying the full path to the library:

```
gcc program.c /usr/lib/libm.a -o program
```

8.3 Header Files

Header files, which contain function prototypes, are located in `/usr/include`.

- The header for the math library is `math.h`.

- **Including the Header:** Instead of typing the prototype manually, use the `#include` directive at the top of your C file. This copies the content of the header file into your program.

```
#include <math.h>
```

8.4 Linking with the -l Option

A more common and convenient way to link libraries is using the `-l` flag.

- **Naming Convention:** To derive the flag, take the library name (e.g., `libm.a`), remove the `lib` prefix and the file extension.
- **Example:** `libm.a` becomes `m`.
- **Command:**

```
gcc program.c -lm -o program
```

9 Use multiple libraries in C

We will now look at a program that uses several external libraries. This requires including header files (definitions and prototypes) and linking object files (compiled code).

9.1 Locating Headers and Libraries

To find the necessary files on the system:

- **Header Files:** Located in `/usr/include`. We can list them to a file: `ls /usr/include > headers.txt`.
 - `curses.h`: Allows cursor manipulation and colors.
 - `menu.h`: Allows creation of menus.
- **Object Files:** Located in `/usr/lib`. We can list them: `ls /usr/lib > libraries.txt`.
 - `libcurses.so`: The compiled code for `curses`.
 - `libmenu.so`: The compiled code for `menus`.

9.2 Including Headers

In the C program, we must include the headers for the functions we are using:

```
#include <urses.h>
#include <menu.h>
#include <stdlib.h>
```

Note: `stdlib.h` is included because the program uses `calloc` for memory allocation.

9.3 Linking Libraries

To include the actual code for the functions, we must link the libraries during the build process.

9.3.1 Method 1: Absolute Path

Add the exact path to the library on the build line:

```
gcc program.c /usr/lib/libcurses.so /usr/lib/libmenu.so -o program
```

The standard library (`stdlib`) is automatically linked, so it does not need to be added here.

9.3.2 Method 2: Using the `-l` Flag

A more convenient way is to use the `-l` flag followed by the library name (without "lib" or extension):

```
gcc program.c -lcurses -lmenu -o program
```

10 GCC details

In this section, we explain the details of the build command and the steps performed by the compiler (GCC) to turn C source code into an executable program.

10.1 The Build Command and Flags

When you press the "Run It" button in WebLinux, or build manually, a command like this is executed:

```
gcc -std=C11 -Wall -fmax-errors=10 -Wextra -o program program.c
```

Here is a breakdown of the flags used:

- **-std=C11**: Specifies the C standard to use. C11 is a modern standard.

- **-Wall:** Displays all warnings. It is important to look at these and fix them, as they often indicate errors.
- **-fmax-errors=10:** Tells the compiler to stop after 10 errors so the user is not overwhelmed.
- **-Wextra:** Enables extra warnings that are not included in `-Wall`.
- **-o program:** Specifies the name of the output file (the executable). If this flag is omitted, GCC creates an executable named `a.out` by default.

10.2 Compilation Stages

When you run GCC, it performs three main steps: preprocessing, compilation, and linking. We can invoke these steps separately.

10.2.1 1. The Preprocessor

The preprocessor performs simple textual replacement. For example, it finds the contents of header files (like `stdio.h`) and copies them verbatim into the source code.

10.2.2 2. Compilation (Translation)

This step translates the source code into machine language, creating a so-called **object file**.

- To perform only this step, use the `-c` flag.
- **Command:** `gcc -c program.c -o program.o`
- This creates `program.o`. It is the binary, computer-readable version of the code, but it cannot be executed directly (it lacks system libraries).

10.2.3 3. The Linker

The linker bundles the object file with necessary system libraries to produce the final executable.

- **Command:** `gcc program.o -o program`
- This takes the object file `program.o` and creates the executable `program`, which can be run with `./program`.

Understanding these steps is essential for separate compilation, where source code is split across multiple files.

11 Object files

In this section, we demonstrate **separate compilation**, which means spreading source code over several files and assembling them into one final executable. This is essential for organizing large programs by topic.

11.1 Creating Separate Files

We separate the `average_temperature` function from the main program into its own file.

- **weatherstats.c**: Contains the source code for the `average_temperature` function.
- **weatherstats.h**: A header file containing the function prototype.
- **program.c**: Contains the main function.

To use the function in `program.c`, we must include the header.

```
#include "weatherstats.h"
```

Note: We use quotation marks (") instead of angle brackets (<>). Angle brackets tell the compiler to look in standard system paths (like `/usr/include`), whereas quotation marks tell it to look in the current directory.

11.2 Compiling Object Files

We compile each source file into an object file (`.o`) individually.

11.2.1 Compiling the Module

```
gcc -c weatherstats.c -o weatherstats.o
```

We must use the `-c` flag. If omitted, GCC tries to build an executable and fails because `weatherstats.c` has no main function.

11.2.2 Compiling the Main Program

```
gcc -Wall -c program.c -o program.o
```

Using `-Wall` ensures we see warnings, such as "implicitly declared function" if we forget to include the header file.

11.3 Linking

Finally, we invoke the linker to bundle the object files into an executable.

```
gcc -o program program.o weatherstats.o
```

This creates the final executable program by combining the machine language from both object files.

12 Modify object files

To reinforce what we have learned so far about spreading source code over multiple files, compiling, and linking, we will walk through the steps required to modify this code. You will see that these steps can become tedious, which motivates the use of **Makefiles** (covered in the next topic) to automate the process.

Suppose we want to add a maximum temperature feature to our `weatherstats` source file and call it from the main program.

12.1 Modifying the Source Code

12.1.1 Updating the Main Program

In `program.c`, we add a call to the new function and print the result.

```
double max = maxTemp(temperatures, 7);  
printf("Highest temp:  %.2lf\n", max);
```

12.1.2 Updating the Module

We add the `maxTemp` function to `weatherstats.c`.

```
double maxTemp(double *temperatures, int size) {  
    double max = temperatures[0];  
    int i;  
    for (i = 1; i < size; i++) {  
        if (max < temperatures[i]) {  
            max = temperatures[i];  
        }  
    }  
    return max;  
}
```

12.1.3 Updating the Header

We must add the function prototype to `weatherstats.h` so the compiler knows about it when compiling `program.c`.

```
double maxTemp(double *temperatures, int size);
```

12.2 Compiling and Linking

Now we must translate the code into machine language.

1. Compile `program.c`:

```
gcc -Wall -c program.c -o program.o
```

2. Compile `weatherstats.c`:

```
gcc -Wall -c weatherstats.c -o weatherstats.o
```

3. Link them together:

```
gcc -o program program.o weatherstats.o
```

Running `./program` will now display both the average and the maximum temperature.

12.3 Partial Recompilation

If we modify only one file, we do not need to recompile everything. For example, if we change a temperature value (e.g., changing 5.3 to 15.3) in `program.c`:

1. Recompile only the changed file:

```
gcc -Wall -c program.c -o program.o
```

We do not need to recompile `weatherstats.c` since it hasn't changed.

2. Relink:

```
gcc -o program program.o weatherstats.o
```

When we run the program now, we get the updated result. As you can see, making modifications to source code spread out over multiple files can be rather tedious, which is why we will look at Makefiles next.