AES (Advanced Encryption Standard) Algorithm:

AES is an itterative rather than Feistel cipher. It is based on 'substitution - permutation network' AES performs all its computations on bytes rather than bits. Hence AES treats the 128 bits of plaintext block as 16 bytes. These 16 bytes are arranged in a 4 rows and 4 columns matrix.

The number of rounds in AES is variable and depends on the length of the key. AES uses 10 rounds for 128-bit key, 12 rounds for 192-bit keys and 14 rounds for 256-bit keys.

The schematic of AES structure is given as follows:



Rounds	Key Size
10	128 bit
12	192 bit
14	256 bit

Schematic of each round of AES:



Substitute Bytes Transformation:

The substitute bytes transformation called Sub Bytes is a simple lookup table. AES defines a 16X16 matrix of byte values called an S-box, that contains permutation of all possiable 256 8 bit values.

Each individual byte is mapped into a new byte in the following ways:

The leftmost 4 bits of the byte are used as a row value and the rightmost 4 bits of the byte are used as a Column value These rows and columns values serve as indexes into the S-box to select an unique 8 bit output value.

For example:

The hexadecimal value 95 references row 9 and Column 5.

Shift Rows Transformation:

The shift row Transformation is known as ShiftRows. In this the first row is not altered. For the second row, a 1 byte circular left shift is performed. For the third row a 2 byte circular left shift is performed. For the fourth row a 3 byte circular left shift is performed.

For example,

87	F2	4D	97
EC	6E	4C	90
4A	C3	46	E7
8C	D8	95	A6

→

87	F2	4D	97
6E	4C	90	EC
46	E7	4A	C3
A6	8C	D8	95

MixColumns Transformation:

The mix columns transformation also known as MixColumns, operates on each column individually. Each byte of a column is mapped into a new value that is a function of all four bytes in that column. The transformation can be defined by the following matrix multiplication.

$$\begin{bmatrix} 02 & 03 & 01 & 01 \\ 01 & 02 & 03 & 01 \\ 01 & 01 & 02 & 03 \\ 03 & 01 & 01 & 02 \end{bmatrix} \begin{bmatrix} S_{00} & S_{01} & S_{02} & S_{03} \\ S_{10} & S_{11} & S_{12} & S_{13} \\ S_{20} & S_{21} & S_{22} & S_{23} \\ S_{30} & S_{31} & S_{32} & S_{33} \end{bmatrix} = \begin{bmatrix} S'_{00} & S'_{01} & S'_{02} & S'_{03} \\ S'_{10} & S'_{11} & S'_{12} & S'_{13} \\ S'_{20} & S'_{21} & S'_{22} & S'_{23} \\ S'_{30} & S'_{31} & S'_{32} & S'_{33} \end{bmatrix}$$

The MixColumn transformation on a single column can be expressed as,

$$S'_{0,j} = (2 \cdot S_{0,j}) \oplus (3 \cdot S_{1,j}) \oplus S_{2,j} \oplus S_{3,j}$$

$$S'_{1,j} = S_{0,j} \oplus (2 \cdot S_{1,j}) \oplus (3 \cdot S_{2,j}) \oplus S_{3,j}$$

$$S'_{2,j} = S_{0,j} \oplus S_{1,j} \oplus (2 \cdot S_{2,j}) \oplus (3 \cdot S_{3,j})$$

$$S'_{3,j} = (3 \cdot S_{0,j}) \oplus S_{1,j} \oplus S_{2,j} \oplus (2 \cdot S_{3,j})$$

For example,

87	F2	4D	97
6E	4C	90	EC
46	E7	4A	C3
A6	8C	D8	95

→

47	40	A3	4C
37	D4	70	9F
94	E4	3A	42
ED	A5	A6	BC

Add Round Key Transformation:

- In the Add Round key Transformation also known as AddRoundKey, the 128 bits are bitwise XORed with the 128 bits of the Round Key. The operation is viewed as a columnwise operation between the 4 bytes of a column and one word of the round key. It can be viewed as a byte-level operation.

For example:

47	40	A3	4C
37	D4	70	9F
94	E4	3A	42
ED	A5	A6	BC

128 bits value

$\oplus$

AC	19	28	57
77	FA	D1	5C
66	DC	29	00
F3	21	41	6A

round key

=

EB	59	8B	1B
40	2E	A1	C3
F2	38	13	42
1E	84	E7	D6

Application of AES Algorithm:

AES is widely used in many applications.

i) **Wireless Security:** AES is used in securing wireless network such as wifi network, to ensure data confidentiality

ii) **Database Encryption:** AES can be applied to encrypt sensitive data stored in database.

iii) **Secure Communication:** AES is widely used in protocols like internet communications, emails, instant messaging and voice/video calls.

iv) **Virtual Private Networks:** AES is commonly used in VPN protocols to secure the communication between a user's device and a remote server.