TS3A4751 0.9Ω 低电压、单电源、4 通道 SPST 模拟开关

1 特性

- 低通态电阻 (R_{ON})
  - 最大值 0.9Ω（电源电压为 3V）
  - 最大值 1.5Ω（电源电压为 1.8V）
- R_{ON} 稳定性：最大值 0.4Ω（电压为 3V）
- R_{ON} 通道匹配
  - 最大值 0.05Ω（电源电压为 3V）
  - 最大值 0.15Ω（电源电压为 1.8V）
- 1.6V 至 3.6V 单电源运行
- 兼容 1.8V CMOS 逻辑（电源电压为 3V）
- 高电流处理能力（100mA 持续电流）
- 快速开关：t_{ON} = 5ns，t_{OFF} = 4ns
- 支持数字和模拟 应用
- ESD 保护性能超出 JESD-22 标准
  - ±4000V 人体放电模型 (A114-A)
  - 300V 机器模型 (A115-A)
  - ±1000V 组件充电模式 (C101)

2 应用

- 电源布线
- 电池供电型系统
- 音频和视频信号路由
- 低压数据采集系统
- 通信电路
- PCMCIA 卡
- 手机
- 调制解调器
- 硬盘

3 说明

TS3A4751 器件是一款双向、4 通道、常开 (NO) 单刀单掷 (SPST) 模拟开关，由单个 1.6V 至 3.6V 电源供电。此器件具有快速开关速度，可处理轨至轨模拟信号，并且静态功耗非常低。

当使用 3V 电源时，该数字输入兼容 1.8V CMOS。

TS3A4751 器件具有四个常开 (NO) 开关。TS3A4751 采用 14 引脚薄型紧缩小外形封装 (TSSOP)，以及节省空间的 14 引脚 VQFN (RGY) 封装和微型 X2QFN (RUC) 封装。

器件信息(1)

器件型号	封装	封装尺寸（标称值）
TS3A4751	TSSOP (14)	5.00mm × 4.40mm
	VQFN (14)	3.50mm × 3.50mm
	X2QFN (14)	2.00mm × 2.00mm

(1) 如需了解所有可用封装，请参阅数据表末尾的可订购产品附录。

简化原理图



目录

4 修订历史记录

Changes from Revision E (January 2015) to Revision F **Page**

- Changed Supply Voltage from: 3.3 V to: 3.6 V in the *Recommended Operating Conditions* 5

Changes from Revision D (July 2008) to Revision E **Page**

- 已添加 *引脚配置和功能* 部分、*ESD 额定值* 表、*特性* *说明* 部分、*器件功能模式*、*应用和实施* 部分、*电源相关建议* 部分、*布局* 部分、*器件和文档支持* 部分以及*机械、封装和可订购信息* 部分 1

5 Pin Configuration and Functions

PW PACKAGE
(TOP VIEW)



RGY PACKAGE
(TOP VIEW)



RGY PACKAGE
(BOTTOM VIEW)



If the exposed center pad is used, it must be connected as a secondary ground or left electrically open.

RUC PACKAGE
(TOP VIEW)



RUC PACKAGE
(BOTTOM VIEW)



Pin Functions

PIN		I/O	DESCRIPTION
NO.	NAME		
1	NO1	I/O	Normally open signal path
2	COM1	I/O	Common signal path
3	NO2	I/O	Normally open signal path
4	COM2	I/O	Common signal path
5	IN2	I	Logic control input
6	IN3	I	Logic control input
7	GND	—	Ground
8	NO3	I/O	Normally open signal path
9	COM3	I/O	Common signal path
10	COM4	I/O	Common signal path
11	NO4	I/O	Normally open signal path
12	IN4	I	Logic control input
13	IN1	I	Logic control input
14	V_{CC}	I	Positive supply voltage

6 Specifications

6.1 Absolute Maximum Ratings

over operating free-air temperature range (unless otherwise noted)(1)

			MIN	MAX	UNIT
V_{CC}	Supply voltage referenced to GND(2)		–0.3	4	V
V_{NO} V_{COM} V_{IN}	Analog and digital voltage		–0.3	V_{CC} + 0.3	V
I_{NO} I_{COM}	On-state switch current	V_{NO}, V_{COM} = 0 to V_{CC}	–100	100	mA
I_{CC} I_{GND}	Continuous current through V_{CC} or GND			±100	mA
V	Peak current pulsed at 1 ms, 10% duty cycle	COM, $V_{I/O}$		±200	mA
T_A	Operating temperature		–40	85	°C
T_J	Junction temperature			150	°C
T_{stg}	Storage temperature		–65	150	°C

(1) Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions* is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
(2) Signals on COM or NO exceeding V_{CC} or GND are clamped by internal diodes. Limit forward diode current to maximum current rating.

6.2 ESD Ratings

			VALUE	UNIT
$V_{(ESD)}$	Electrostatic discharge	Human body model (HBM), per ANSI/ESDA/JEDEC JS-001(1)	±4000	V
		Charged-device model (CDM), per JEDEC specification JESD22-C101 or ANSI/ESDA/JEDEC JS-002(2)	±1000	
		Machine Model	±300	

(1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.
(2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

6.3 Recommended Operating Conditions

over operating free-air temperature range (unless otherwise noted)

		MIN	MAX	UNIT
V_{CC}	Supply Voltage	1.65	3.6	V
V_{NO} V_{COM} V_{IN}	Analog and digital voltage range	0	V_{CC}	V

6.4 Thermal Information

THERMAL METRIC(1)		TS3A4751			UNIT
		PW	RGY	RUC	
		14 PINS			
$R_{\theta JA}$	Junction-to-ambient thermal resistance	132.3	68.5	196.4	°C/W
$R_{\theta JC(top)}$	Junction-to-case (top) thermal resistance	60.6	83.1	73.9	
$R_{\theta JB}$	Junction-to-board thermal resistance	74.2	44.6	130.7	
ψ_{JT}	Junction-to-top characterization parameter	11.2	7.8	2.1	
ψ_{JB}	Junction-to-board characterization parameter	73.6	44.7	130.6	
$R_{\theta JC(bot)}$	Junction-to-case (bottom) thermal resistance	N/A	24.6	N/A	

(1) For more information about traditional and new thermal metrics, see the *IC Package Thermal Metrics* application report, SPRA953.

6.5 Electrical Characteristics for 1.8-V Supply

V_{CC} = 1.65 V to 1.95 V, T_A = –40°C to 85°C, V_{IH} = 1 V, V_{IL} = 0.4 V (unless otherwise noted)(1) (2)

PARAMETER		TEST CONDITIONS		T_A	MIN	TYP(3)	MAX	UNIT
ANALOG SWITCH								
V_{COM}, V_{NO}	Analog signal range				0		V_{CC}	V
R_{on}	ON-state resistance	V_{CC} = 1.8 V, I_{COM} = –10 mA, V_{NO} = 0.9 V		25°C		1	1.5	Ω
				Full			2	
ΔR_{on}	ON-state resistance match between channels(4)	V_{CC} = 1.8 V, I_{COM} = –10 mA, V_{NO} = 0.9 V		25°C		0.09	0.15	Ω
				Full			0.25	
$R_{on(flat)}$	ON-state resistance flatness(5)	V_{CC} = 1.8 V, I_{COM} = –10 mA, 0 ≤ V_{NO} ≤ V_{CC}		25°C		0.7	0.9	Ω
				Full			1.5	
$I_{NO(OFF)}$	NO OFF leakage current(6)	V_{CC} = 1.95 V, V_{COM} = 0.15 V, 1.65 V, V_{NO} = 1.8 V, 0.15 V		25°C	–1	0.5	1	nA
				Full	–10		10	
$I_{COM(OFF)}$	COM OFF leakage current(6)	V_{CC} = 1.95 V, V_{COM} = 0.15 V, 1.65 V, V_{NO} = 1.65 V, 0.15 V		25°C	–1	0.5	1	nA
				Full	–10		10	
$I_{COM(ON)}$	COM ON leakage current(6)	V_{CC} = 1.95 V, V_{COM} = 0.15 V, 1.65 V, V_{NO} = 0.15 V, 1.65 V, or floating		25°C	–1	0.01	1	nA
				Full	–3		3	
DYNAMIC								
t_{ON}	Turn-on time	V_{NO} = 1.5 V, R_L = 50 Ω, C_L = 35 pF, See Figure 1		25°C		6	18	ns
				Full			20	
t_{OFF}	Turn-off time	V_{NO} = 1.5 V, R_L = 50 Ω, C_L = 35 pF, See Figure 1		25°C		5	10	ns
				Full			12	
Q_C	Charge injection	V_{GEN} = 0, R_{GEN} = 0, C_L = 1 nF, See Figure 5		25°C		3.2		pC
$C_{NO(OFF)}$	NO OFF capacitance	f = 1 MHz, See Figure 2		25°C		23		pF
$C_{COM(OFF)}$	COM OFF capacitance	f = 1 MHz, See Figure 2		25°C		20		pF
$C_{COM(ON)}$	COM ON capacitance	f = 1 MHz, See Figure 2		25°C		43		pF
BW	Bandwidth	R_L = 50 Ω, Switch ON		25°C		123		MHz
O_{ISO}	OFF isolation(7)	R_L = 50 Ω, C_L = 5 pF, See Figure 3	f = 1 MHz	25°C		–61		dB
			f = 10 MHz			–36		
X_{TALK}	Crosstalk	R_L = 50 Ω, C_L = 5 pF, See Figure 3	f = 10 MHz	25°C		–95		dB
			f = 100 MHz			–73		
THD	Total harmonic distortion	f = 20 Hz to 20 kHz, V_{COM} = 2 V_{P-P}	R_L = 32 Ω	25°C		0.14%		
			R_L = 600 Ω			0.013%		
DIGITAL CONTROL INPUTS (IN1–IN4)								
V_{IH}	Input logic high			Full	1			V
V_{IL}	Input logic low			Full			0.4	V
I_{IN}	Input leakage current	V_I = 0 or V_{CC}		25°C		0.1	5	nA
				Full	–10		10	
SUPPLY								
V_{CC}	Power-supply range				1.6		3.6	V
I_{CC}	Positive-supply current	V_I = 0 or V_{CC}		25°C			0.05	µA
				Full			0.5	

(1) The algebraic convention, whereby the most negative value is a minimum and the most positive value is a maximum.
(2) Parts are tested at 85°C and specified by design and correlation over the full temperature range.
(3) Typical values are at T_A = 25°C.
(4) $\Delta r_{on} = r_{on(max)} - r_{on(min)}$
(5) Flatness is defined as the difference between the maximum and minimum value of r_{on} as measured over the specified analog signal ranges.
(6) Leakage parameters are 100% tested at the maximum-rated hot operating temperature and specified by correlation at T_A = 25°C.
(7) OFF isolation = $20_{log}10$ (V_{COM}/V_{NO}), V_{COM} = output, V_{NO} = input to OFF switch

6.6 Electrical Characteristics for 3-V Supply

V_{CC} = 2.7 V to 3.6 V, T_A = –40°C to 85°C, V_{IH} = 1.4 V, V_{IL} = 0.5 V (unless otherwise noted).(1) (2)

PARAMETER		TEST CONDITIONS		T_A	MIN	TYP(3)	MAX	UNIT
ANALOG SWITCH								
V_{COM}, V_{NO}	Analog signal range				0		V_{CC}	V
R_{on}	ON-state resistance	V_{CC} = 2.7 V, I_{COM} = –100 mA, V_{NO} = 1.5 V		25°C		0.7	0.9	Ω
				Full			1.1	
ΔR_{on}	ON-state resistance match between channels(4)	V_{CC} = 2.7 V, I_{COM} = –100 mA, V_{NO} = 1.5 V		25°C		0.03	0.05	Ω
				Full			0.15	
$R_{on(flat)}$	ON-state resistance flatness(5)	V_{CC} = 2.7 V, I_{COM} = –100 mA, V_{NO} = 1 V, 1.5 V, 2 V		25°C		0.23	0.4	Ω
				Full			0.5	
$I_{NO(OFF)}$	NO OFF leakage current(6)	V_{CC} = 3.6 V, V_{COM} = 0.3 V, 3 V, V_{NO} = 3 V, 0.3 V		25°C	–2	1	2	nA
				Full	–18		18	
$I_{COM(OFF)}$	COM OFF leakage current(6)	V_{CC} = 3.6 V, V_{COM} = 0.3 V, 3 V, V_{NO} = 3 V, 0.3 V		25°C	–2	1	2	nA
				Full	–18		18	
$I_{COM(ON)}$	COM ON leakage current(6)	V_{CC} = 3.6 V, V_{COM} = 0.3 V, 3 V, V_{NO} = 0.3 V, 3 V, or floating		25°C	–2.5	0.01	2.5	nA
				Full	–5		5	
DYNAMIC								
t_{ON}	Turn-on time	V_{NO} = 1.5 V, R_L = 50 Ω, C_L = 35 pF, See Figure 1		25°C		5	14	ns
				Full			15	
t_{OFF}	Turn-off time	V_{NO} = 1.5 V, R_L = 50 Ω, C_L = 35 pF, See Figure 1		25°C		4	9	ns
				Full			10	
Q_C	Charge injection	V_{GEN} = 0, R_{GEN} = 0, C_L = 1 nF, See Figure 5		25°C		3		pC
$C_{NO(OFF)}$	NO OFF capacitance	f = 1 MHz, See Figure 2		25°C		23		pF
$C_{COM(OFF)}$	COM OFF capacitance	f = 1 MHz, See Figure 2		25°C		20		pF
$C_{COM(ON)}$	COM ON capacitance	f = 1 MHz, See Figure 2		25°C		43		pF
BW	Bandwidth	R_L = 50 Ω, Switch ON		25°C		125		MHz
O_{ISO}	OFF isolation(7)	R_L = 50 Ω, C_L = 5 pF, See Figure 3	f = 10 MHz	25°C		–40		dB
			f = 1 MHz			–62		
X_{TALK}	Crosstalk	R_L = 50 Ω, C_L = 5 pF, See Figure 3	f = 10 MHz	25°C		–73		dB
			f = 1 MHz			–95		
THD	Total harmonic distortion	f = 20 Hz to 20 kHz, V_{COM} = 2 V_{P-P}	R_L = 32 Ω	25°C		0.04%		
			R_L = 600 Ω			0.003%		
DIGITAL CONTROL INPUTS (IN1–IN4)								
V_{IH}	Input logic high			Full	1.4			V
V_{IL}	Input logic low			Full			0.5	V
I_{IN}	Input leakage current	V_I = 0 or V_{CC}		25°C		0.5	1	nA
				Full	–20		20	
SUPPLY								
V_{CC}	Power-supply range				1.6		3.6	V
I_{CC}	Positive-supply current	V_{CC} = 3.6 V, V_{IN} = 0 or V_{CC}		25°C			0.075	μA
				Full			0.75	

(1) The algebraic convention, whereby the most negative value is a minimum and the most positive value is a maximum.
(2) Parts are tested at 85°C and specified by design and correlation over the full temperature range.
(3) Typical values are at V_{CC} = 3 V, T_A = 25°C.
(4) $\Delta r_{on} = r_{on(max)} - r_{on(min)}$
(5) Flatness is defined as the difference between the maximum and minimum value of r_{on} as measured over the specified analog signal ranges.
(6) Leakage parameters are 100% tested at the maximum-rated hot operating temperature and specified by correlation at T_A = 25°C.
(7) OFF isolation = $20_{log}10$ (V_{COM}/V_{NO}), V_{COM} = output, V_{NO} = input to OFF switch



Figure 1. Switching Times



Figure 2. NO and COM Capacitance



Measurements are standardized against short at socket terminals. OFF isolation is measured between COM and OFF terminals on each switch. Bandwidth is measured between COM and ON terminals on each switch. Signal direction through switch is reversed; worst values are recorded.

OFF isolation = 20 log V_O/V_I

(1) Add 50-Ω termination for OFF isolation

Figure 3. OFF Isolation, Bandwidth, and Crosstalk

Channel ON: COM to NO	$V_I = V_{CC}$	C_L = 50 pF
$V_{SOURCE} = V_{CC}$ P-P	f_{SOURCE} = 20 Hz to 20 kHz	R_L = 600Ω



A. C_L includes probe and jig capacitance.

Figure 4. Total Harmonic Distortion (THD)



Figure 5. Charge Injection (Q_C)

6.7 Typical Characteristics



Figure 6. R_{on} vs V_{COM}



Figure 7. R_{on} vs V_{COM} (V_{CC} = 1.8 V)



Figure 8. R_{on} vs V_{COM} (V_{CC} = 2.7 V)



Figure 9. I_{ON} and I_{OFF} vs Temperature (V_{CC} = 3.6 V)



Figure 10. Q_C vs V_{COM}



Figure 11. t_{ON} and t_{OFF} vs Supply Voltage

Typical Characteristics (continued)



Figure 12. t_{ON} and t_{OFF} vs Temperature



Figure 13. I_{CC} vs V_{CC}



Figure 14. Gain vs Frequency
(V_{CC} = 3 V)



Figure 15. OFF Isolation vs Frequency
(V_{CC} = 3 V)



Figure 16. Total Harmonic Distortion vs Frequency
(R_L = 32 Ω)



Figure 17. Total Harmonic Distortion vs Frequency
(R_L = 600 Ω)

Typical Characteristics (continued)



Figure 18. Crosstalk vs Frequency (V_{CC} = 3 V)

7 Detailed Description

7.1 Overview

The TS3A4751 is a bidirectional, 4-channel, normally open (NO) single-pole single-throw (SPST) analog switch that operates from a single 1.6-V to 3.6-V supply. This device has fast switching speeds, handles rail-to-rail analog signals, and consumes very low quiescent power.

The digital input is 1.8-V CMOS compatible when using a 3-V supply.

The TS3A4751 has four normally open (NO) switches. The TS3A4751 is available in a 14-pin thin shrink small-outline package (TSSOP) and in space-saving 14-pin VQFN (RGY) and micro X2QFN (RUC) packages.

7.2 Functional Block Diagram



7.3 Feature Description

This device has fast switching speeds, handles rail-to-rail analog signals, and consumes very low quiescent power.

The digital input is 1.8-V TTL/CMOS compatible when using a 3-V supply.

7.4 Device Functional Modes

Table 1. Function Table

IN	NO TO COM, COM TO NO
L	OFF
H	ON

8 Application and Implementation

NOTE

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

8.1 Application Information

8.1.1 Logic Inputs

The TS3A4751 logic inputs can be driven up to 3.6 V, regardless of the supply voltage. For example, with a 1.8-V supply, IN may be driven low to GND and high to 3.6 V. Driving IN rail to rail minimizes power consumption.

8.1.2 Analog Signal Levels

Analog signals that range over the entire supply voltage (V_{CC} to GND) can be passed with very little change in R_{on} (see *Typical Characteristics*). The switches are bidirectional, so NO and COM can be used as either inputs or outputs.

8.2 Typical Application



Figure 19. Typical Application Diagram

Typical Application (continued)

8.2.1 Design Requirements

Ensure that all of the signals passing through the switch are with in the specified ranges to ensure proper performance.

8.2.2 Detailed Design Procedure

The TS3A4751 and can be properly operated without any external components. However, it is recommended that unused pins should be connected to ground through a 50-Ω resistor to prevent signal reflections back into the device. It is also recommneded that the digital control pins (INX) be pulled up to V_{CC} or down to GND to avoid undesired switch positions that could result from the floating pin.

8.2.3 Application Curve



Figure 20. R_{on} vs V_{COM}

9 Power Supply Recommendations

Proper power-supply sequencing is recommended for all CMOS devices. Do not exceed the absolute maximum ratings because stresses beyond the listed ratings can cause permanent damage to the devices. Always sequence V_{CC} on first, followed by NO or COM.

Although it is not required, power-supply bypassing improves noise margin and prevents switching noise propagation from the V_{CC} supply to other components. A 0.1-μF capacitor, connected from V_{CC} to GND, is adequate for most applications.

10 Layout

10.1 Layout Guidelines

High-speed switches require proper layout and design procedures for optimum performance.

Reduce stray inductance and capacitance by keeping traces short and wide.

Ensure that bypass capacitors are as close to the device as possible.

Use large ground planes where possible.

10.2 Layout Example



Figure 21. Layout Schematic

11 器件和文档支持

11.1 接收文档更新通知

要接收文档更新通知，请导航至 TI.com.cn 上的器件产品文件夹。单击右上角的*通知我* 进行注册，即可每周接收产品信息更改摘要。有关更改的详细信息，请查看任何已修订文档中包含的修订历史记录。

11.2 社区资源

下列链接提供到 TI 社区资源的连接。链接的内容由各个分销商“按照原样”提供。这些内容并不构成 TI 技术规范，并且不一定反映 TI 的观点；请参阅 TI 的 《使用条款》。

TI E2E™ Online Community ***TI's Engineer-to-Engineer (E2E) Community.*** Created to foster collaboration among engineers. At e2e.ti.com, you can ask questions, share knowledge, explore ideas and help solve problems with fellow engineers.

Design Support ***TI's Design Support*** Quickly find helpful E2E forums along with design support tools and contact information for technical support.

11.3 商标

E2E is a trademark of Texas Instruments.
All other trademarks are the property of their respective owners.

11.4 静电放电警告

这些装置包含有限的内置 ESD 保护。 存储或装卸时，应将导线一起截短或将装置放置于导电泡棉中，以防止 MOS 门极遭受静电损伤。

11.5 术语表

SLYZ022 — *TI 术语表*。

这份术语表列出并解释术语、缩写和定义。

12 机械、封装和可订购信息

以下页面包含机械、封装和可订购信息。这些信息是指定器件的最新可用数据。数据如有变更，恕不另行通知，且不会对此文档进行修订。如需获取此产品说明书的浏览器版本，请查阅左侧的导航栏。

PACKAGING INFORMATION

Orderable part number	Status (1)	Material type (2)	Package | Pins	Package qty | Carrier	RoHS (3)	Lead finish/ Ball material (4)	MSL rating/ Peak reflow (5)	Op temp (°C)	Part marking (6)
TS3A4751PWR	Active	Production	TSSOP (PW) | 14	2000 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	YC751
TS3A4751PWR.B	Active	Production	TSSOP (PW) | 14	2000 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	YC751
TS3A4751RGYR	Active	Production	VQFN (RGY) | 14	3000 | LARGE T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 85	YC751
TS3A4751RGYR.B	Active	Production	VQFN (RGY) | 14	3000 | LARGE T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 85	YC751
TS3A4751RGYRG4	Active	Production	VQFN (RGY) | 14	3000 | LARGE T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 85	YC751
TS3A4751RGYRG4.B	Active	Production	VQFN (RGY) | 14	3000 | LARGE T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 85	YC751
TS3A4751RUCR	Active	Production	QFN (RUC) | 14	3000 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	3MO
TS3A4751RUCR.B	Active	Production	QFN (RUC) | 14	3000 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	3MO
TS3A4751RUCRG4.B	Active	Production	QFN (RUC) | 14	3000 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	3MO

(1) **Status:** For more details on status, see our product life cycle.

(2) **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

(3) **RoHS values:** Yes, No, RoHS Exempt. See the TI RoHS Statement for additional information and value definition.

(4) **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

(5) **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

(6) **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative

and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

TAPE AND REEL INFORMATION

REEL DIMENSIONS



TAPE DIMENSIONS



A0	Dimension designed to accommodate the component width
B0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers

QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
TS3A4751PWR	TSSOP	PW	14	2000	330.0	12.4	6.9	5.6	1.6	8.0	12.0	Q1
TS3A4751RGYR	VQFN	RGY	14	3000	330.0	12.4	3.75	3.75	1.15	8.0	12.0	Q1
TS3A4751RGYRG4	VQFN	RGY	14	3000	330.0	12.4	3.75	3.75	1.15	8.0	12.0	Q1
TS3A4751RUCR	QFN	RUC	14	3000	180.0	9.5	2.2	2.2	0.5	4.0	8.0	Q2

TAPE AND REEL BOX DIMENSIONS



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
TS3A4751PWR	TSSOP	PW	14	2000	353.0	353.0	32.0
TS3A4751RGYR	VQFN	RGY	14	3000	353.0	353.0	32.0
TS3A4751RGYRG4	VQFN	RGY	14	3000	353.0	353.0	32.0
TS3A4751RUCR	QFN	RUC	14	3000	189.0	185.0	36.0

GENERIC PACKAGE VIEW

RGY 14

VQFN - 1 mm max height

3.5 x 3.5, 0.5 mm pitch

PLASTIC QUAD FLATPACK - NO LEAD

This image is a representation of the package family, actual package may vary.
Refer to the product data sheet for package details.



4231541/A

PACKAGE OUTLINE

RGY0014A

VQFN - 1 mm max height

PLASTIC QUAD FLATPACK - NO LEAD



NOTES:

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. The package thermal pad must be soldered to the printed circuit board for thermal and mechanical performance.



LAND PATTERN EXAMPLE
SCALE:20X



SOLDER MASK DETAILS

4219040/A 09/2015

NOTES: (continued)

4. This package is designed to be soldered to a thermal pad on the board. For more information, see Texas Instruments literature number SLUA271 (www.ti.com/lit/slua271).



SOLDER PASTE EXAMPLE
BASED ON 0.125 mm THICK STENCIL

EXPOSED PAD
80% PRINTED SOLDER COVERAGE BY AREA
SCALE:20X

4219040/A 09/2015

NOTES: (continued)

5. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.

PACKAGE OUTLINE

PW0014A

TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE



NOTES:

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm per side.
5. Reference JEDEC registration MO-153.



LAND PATTERN EXAMPLE
EXPOSED METAL SHOWN
SCALE: 10X



SOLDER MASK DETAILS

4220202/B 12/2023

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.
7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.



SOLDER PASTE EXAMPLE
BASED ON 0.125 mm THICK STENCIL
SCALE: 10X

4220202/B 12/2023

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

GENERIC PACKAGE VIEW

RUC 14

X2QFN - 0.4 mm max height

2 x 2, 0.4 mm pitch

PLASTIC QUAD FLATPACK - NO LEAD

This image is a representation of the package family, actual package may vary.
Refer to the product data sheet for package details.



PACKAGE OUTLINE

RUC0014A

X2QFN - 0.4 mm max height

PLASTIC QUAD FLAT PACK- NO LEAD



NOTES:

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.



LAND PATTERN EXAMPLE
EXPOSED METAL SHOWN
SCALE: 23X



SOLDER MASK DETAILS

4220584/A 05/2019

NOTES: (continued)

3. For more information, see Texas Instruments literature number SLUA271 (www.ti.com/lit/slua271).



SOLDER PASTE EXAMPLE
BASED ON 0.100mm THICK STENCIL
SCALE: 23X

4220584/A 05/2019

NOTES: (continued)

4. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.

重要通知和免责声明

TI“按原样”提供技术和可靠性数据（包括数据表）、设计资源（包括参考设计）、应用或其他设计建议、网络工具、安全信息和其他资源，不保证没有瑕疵且不做出任何明示或暗示的担保，包括但不限于对适销性、某特定用途方面的适用性或不侵犯任何第三方知识产权的暗示担保。

这些资源可供使用 TI 产品进行设计的熟练开发人员使用。您将自行承担以下全部责任：(1) 针对您的应用选择合适的 TI 产品，(2) 设计、验证并测试您的应用，(3) 确保您的应用满足相应标准以及任何其他功能安全、信息安全、监管或其他要求。

这些资源如有变更，恕不另行通知。TI 授权您仅可将这些资源用于研发本资源所述的 TI 产品的相关应用。 严禁以其他方式对这些资源进行复制或展示。您无权使用任何其他 TI 知识产权或任何第三方知识产权。您应全额赔偿因在这些资源的使用中对 TI 及其代表造成的任何索赔、损害、成本、损失和债务，TI 对此概不负责。

TI 提供的产品受 TI 的销售条款或 ti.com 上其他适用条款/TI 产品随附的其他适用条款的约束。TI 提供这些资源并不会扩展或以其他方式更改 TI 针对 TI 产品发布的适用的担保或担保免责声明。

TI 反对并拒绝您可能提出的任何其他或不同的条款。

邮寄地址：Texas Instruments, Post Office Box 655303, Dallas, Texas 75265