

Hands-on Lab: Stored Procedures in MySQL using phpMyAdmin

Estimated time needed: 20 minutes

In this lab, you will learn how to create tables and load data in the MySQL database service using the phpMyAdmin graphical user interface (GUI) tool.

Software Used in this Lab

In this lab, you will use [MySQL](#). MySQL is a Relational Database Management System (RDBMS) designed to efficiently store, manipulate, and retrieve data.



To complete this lab you will utilize MySQL relational database service available as part of IBM Skills Network Labs (SN Labs) Cloud IDE. SN Labs is a virtual lab environment used in this course.

Database Used in this Lab

Mysql_learners database has been used in this lab.

Data Used in this Lab

The data used in this lab is internal data. You will be working on the **PETSALE** table.

ID ▲	ANIMAL	SALEPRICE	SALEDATE	QUANTITY
1	Cat	450.09	2018-05-29	9
2	Dog	666.66	2018-06-01	3
3	Parrot	50.00	2018-06-04	2
4	Hamster	60.60	2018-06-11	6
5	Goldfish	48.48	2018-06-14	24

This lab requires you to have the PETSALE table populated with sample data on mysql phpadmin interface. You might have created and populated a PETSALE table in a previous lab. But for this lab, it is recommended you download the PETSALE-CREATE-v2.sql script below, upload it to phpadmin console and run it. The script will create a new PETSALE table dropping any previous PETSALE table if exists, and will populate it with the required sample data.

- [PETSALE-CREATE-v2.sql](#)

Objectives

After completing this lab, you will be able to:

- Create stored procedures
- Execute stored procedures

Exercise 1

In this exercise, you will create and execute a stored procedure to read data from a table on mysql phpadmin using SQL.

1. Make sure you have created and populated the **PETSALE** table following the steps in the **"Data Used in this Lab"** section of this lab.

ID ▲	ANIMAL	SALEPRICE	SALEDATE	QUANTITY
1	Cat	450.09	2018-05-29	9
2	Dog	666.66	2018-06-01	3
3	Parrot	50.00	2018-06-04	2
4	Hamster	60.60	2018-06-11	6
5	Goldfish	48.48	2018-06-14	24

2.
 - You will create a stored procedure routine named **RETRIEVE_ALL**.
 - This **RETRIEVE_ALL** routine will contain an SQL query to retrieve all the records from the PETSALE table, so you don't need to write the same query over and over again. You just call the stored procedure routine to execute the query everytime.
 - To create the stored procedure routine, copy the code below and paste it to the textarea of the **SQL** page. Click **Go**.

1. 1
2. 2
3. 3
4. 4
5. 5

```

6. 6
7. 7
8. 8
9. 9
10. 10
11. 11
12. 12

1. DELIMITER //
2.
3. CREATE PROCEDURE RETRIEVE_ALL()
4.
5. BEGIN
6.
7.     SELECT * FROM PETSale;
8.
9.
10. END //
11.
12. DELIMITER ;

```

Copied!

Run SQL query/queries on database Mysql_learners: [+](#)

```

1 DELIMITER //
2
3 CREATE PROCEDURE RETRIEVE_ALL()
4
5 BEGIN
6
7     SELECT * FROM PETSale;
8
9
10 END //
11
12 DELIMITER ;

```

Clear Format Get auto-saved query

☐ Bind parameters [+](#)

[Delimiter ;] ☐ Show this query here again ☐ Retain query box ☐ Rollback when finished ☒ Enable foreign key checks [Go](#)

Hide query box

✓ MySQL returned an empty result set (i.e. zero rows). (Query took 0.0064 seconds.)

[CREATE PROCEDURE RETRIEVE_ALL\(\)](#) [BEGIN](#) [SELECT * FROM PETSale;](#) [END](#)

[\[Edit inline\]](#) [\[Edit\]](#) [\[Create PHP code\]](#)

3. To call the RETRIEVE_ALL routine, open another SQL tab by clicking **Open in new Tab**

→ ↻ 🔒 lakshmiH-8080.theiadocker-1-labs-prod-theiak8s-4-tor01.proxy.cognitiveclass.ai/tbl_sql.php?db=HR&table=EMPLOYEES

Apps Count_Coursera_DS... DataAnayst_Count... DataEngg_Count.xlsx OS_DA_DE_CountS... www.google.com Checking your Bro... (251) Zoho People New Tab LakshmiHolla-2808/... Reading list

Server: mysql:3306 » Database: HR » Table: EMPLOYEES

Browse Structure SQL Search Insert Export Import Privileges Operations Triggers

Run SQL query/queries on table HR

```

1 SELECT * FROM `EMPLOYEES`

```

Columns

EMP_ID
F_NAME
L_NAME
SSN
B_DATE
SEX
ADDRESS
JOB_ID
SALARY
MANAGER_ID
DEP_ID

SELECT * SELECT INSERT UPDATE DELETE Clear Format Get auto-saved query

☐ Bind parameters [+](#)

[Delimiter ;] ☐ Show this query here again ☐ Retain query box ☐ Rollback when finished ☒ Enable foreign key checks [Go](#)

Delete the default line which appears so that you will get a blank window.

copy the code below and paste it to the textarea of the SQL page. Click [Go](#).

```

1. 1
1. CALL RETRIEVE_ALL;

```

Copied!

11 CALL RETRIEVE_ALL;

Clear Format Get auto-saved query

☐ Bind parameters

Delimiter ; ☐ Show this query here again ☐ Retain query box ☐ Rollback when finished ☒ Enable foreign key checks Go

Hide query box

Showing rows 0 - 4 (5 total, Query took 0.0010 seconds)

CALL RETRIEVE_ALL

[Edit inline] [Edit] [Create PHP code]

☐ Show all | Number of rows: 25 | Filter rows: Search this table

Options

	ANIMAL	SALEPRICE	SALEDATE	QUANTITY
1	Cat	450.09	2018-05-29	9
2	Dog	666.66	2018-06-01	3
3	Parrot	50.00	2018-06-04	2
4	Hamster	60.60	2018-06-11	6
5	Goldfish	48.48	2018-06-14	24

4. You can view the created stored procedure routine RETRIEVE_ALL. On the left panel, expand the mysql option. Click on **Procedures** then click on the **RETRIEVE_ALL** and view the procedure.

phpMyAdmin

Server: mysql3306 Database: mysql Table: PETSale

Browse Structure SQL Search Insert Export Import Privileges Operations % Triggers

Recent Favorites

- New
- information_schema
- mysql
 - Procedures
 - RETRIEVE_ALL
 - Tables
 - performance_schema
 - sys

Routine 'RETRIEVE_ALL' has been modified.

```
DROP PROCEDURE `RETRIEVE_ALL`; CREATE DEFINER='root'@'%' PROCEDURE `RETRIEVE_ALL`() NOT DETERMINISTIC CONTAINS SQL SQL SECURITY DEFINER BEGIN SELECT * FROM PETSale; END
```

[Edit inline] [Edit] [Create PHP code]

Run SQL query/queries on table mysql.PETSale:

1 SELECT * FROM 'PETSale' WHERE 1

Columns

- ID
- ANIMAL
- SALEPRICE
- SALEDATE
- QUANTITY

SELECT * SELECT INSERT UPDATE DELETE Clear Format Get auto-saved query

☐ Bind parameters

Delimiter ; ☐ Show this query here again ☐ Retain query box ☐ Rollback when finished ☒ Enable foreign key checks Go

Console

After clicking on the Procedure **Retrieve_All**, you can view the procedure definition and execute it by clicking on **GO**.

phpMyAdmin

Server: mysql3306 Database: mysql Table: PETSale

Browse Structure SQL Search Insert Export Import Privileges Operations % Triggers

Recent Favorites

- New
- information_schema
- mysql
 - Procedures
 - RETRIEVE_ALL
 - Tables
 - performance_schema
 - sys

RETRIEVE_ALL

Details

Routine name: RETRIEVE_ALL

Type: PROCEDURE

Parameters

Direction	Name	Type	Length/Values	Options
	Add parameter			

Definition

```
1 BEGIN
2
3 SELECT * FROM PETSale;
4
5
6 END
```

Is deterministic ☐

Adjust privileges ☒

Definer: 'root'@' %'

Security type: DEFINER

Go Close

Operations % Triggers

```
DROP PROCEDURE `RETRIEVE_ALL`; CREATE DEFINER='root'@'%' PROCEDURE `RETRIEVE_ALL`() NOT DETERMINISTIC CONTAINS SQL SQL SECURITY DEFINER BEGIN SELECT * FROM PETSale; END
```

[Edit inline] [Edit] [Create PHP code]

Columns

- ID
- ANIMAL
- SALEPRICE
- SALEDATE
- QUANTITY

Go

5. If you wish to drop the stored procedure routine RETRIEVE_ALL, copy the code below and paste it to the textarea of the **SQL** page. Click **Go**.

```
1. 1
2. 2
3. 3

1. DROP PROCEDURE RETRIEVE_ALL;
2.
3. CALL RETRIEVE_ALL;
```

Copied!

StructureSQLSearchQueryExportImportOperationsPrivilegesRoutinesEventsTriggersDesigner

123456

DROP PROCEDURE RETRIEVE_ALL;

CALL RETRIEVE_ALL;

ClearFormatGet auto-saved query

☐ Bind parameters ⓘ

[Delimiter :]☐ Show this query here again☐ Retain query box☐ Rollback when finished☒ Enable foreign key checks

Go

Error

SQL query: [Copy](#)

CALL RETRIEVE_ALL

MySQL said: ⓘ

#1305 - PROCEDURE Mysql_learners.RETRIEVE_ALL does not exist

Exercise 2

In this exercise, you will create and execute a stored procedure to write/modify data in a table on Db2 using SQL.

1. Make sure you have created and populated the **PETSALE** table following the steps in the **“Data Used in this Lab”** section of this lab.

ID ▲	ANIMAL	SALEPRICE	SALEDATE	QUANTITY
1	Cat	450.09	2018-05-29	9
2	Dog	666.66	2018-06-01	3
3	Parrot	50.00	2018-06-04	2
4	Hamster	60.60	2018-06-11	6
5	Goldfish	48.48	2018-06-14	24

- 2.
- You will create a stored procedure routine named **UPDATE_SALEPRICE** with parameters **Animal_ID** and **Animal_Health**.
 - This **UPDATE_SALEPRICE** routine will contain SQL queries to update the sale price of the animals in the PETSALE table depending on their health conditions, **BAD** or **WORSE**.
 - This procedure routine will take animal ID and health condition as parameters which will be used to update the sale price of animal in the PETSALE table by an amount depending on their health condition. Suppose -
 - For animal with ID XX having BAD health condition, the sale price will be reduced further by 25%.
 - For animal with ID YY having WORSE health condition, the sale price will be reduced further by 50%.
 - For animal with ID ZZ having other health condition, the sale price won't change.
- To create the stored procedure routine, copy the code below and paste it to the textarea of the **SQL** page. Click **Go**.

```
1. 1
2. 2
3. 3
4. 4
5. 5
6. 6
7. 7
8. 8
9. 9
10. 10
11. 11
12. 12
```

```

13. 13
14. 14
15. 15
16. 16
17. 17
18. 18
19. 19
20. 20
21. 21
22. 22
23. 23
24. 24
25. 25
26. 26

1. DELIMITER @
2. CREATE PROCEDURE UPOATE_SALEPRICE (
3.   IN Animal_ID INTEGER, IN Animal_Health VARCHAR(5) )
4. BEGIN
5.
6.   IF Animal_Health = 'BAD' THEN
7.     UPDATE PETSALE
8.     SET SALEPRICE = SALEPRICE - (SALEPRICE * 0.25)
9.     WHERE ID = Animal_ID;
10.
11.   ELSEIF Animal_Health = 'WORSE' THEN
12.     UPDATE PETSALE
13.     SET SALEPRICE = SALEPRICE - (SALEPRICE * 0.5)
14.     WHERE ID = Animal_ID;
15.
16.   ELSE
17.     UPDATE PETSALE
18.     SET SALEPRICE = SALEPRICE
19.     WHERE ID = Animal_ID;
20.
21.   END IF;
22.
23. END @
24.
25. DELIMITER ;
26.

```

Copied!

Run SQL query/queries on database Mysql_learners:

```

15
16     ELSE
17         UPDATE PETSALE
18         SET SALEPRICE = SALEPRICE
19         WHERE ID = Animal_ID;
20
21     END IF;
22
23 END @
24
25 DELIMITER ;
26

```

Clear Format Get auto-saved query

☐ Bind parameters

[Delimiter :] ☐ Show this query here again ☐ Retain query box ☐ Rollback when finished ☒ Enable foreign key checks Go

Hide query box

MySQL returned an empty result set (i.e. zero rows). (Query took 0.0214 seconds.)

```

CREATE PROCEDURE UPDATE_SALEPRICE ( IN Animal_ID INTEGER, IN Animal_Health VARCHAR(5) ) BEGIN IF Animal_Health = 'BAD' THEN UPDATE PETSALE SET SALEPRICE = SALEPRICE - (SALEPRICE * 0.25) WHERE ID = Animal_ID; ELSEIF Animal_Health = 'WORSE' THEN UPDATE PETSALE SET SALEPRICE = SALEPRICE - (SALEPRICE * 0.5) WHERE ID = Animal_ID; ELSE UPDATE PETSALE SET SALEPRICE = SALEPRICE WHERE ID = Animal_ID; END IF; END

```

[Edit inline] [Edit] [Create PHP code]

3. Let's call the UPDATE_SALEPRICE routine. We want to update the sale price of animal with ID 1 having **BAD** health condition in the PETSALE table. open another **SQL** tab by clicking **Open in new Tab**

lakhsmih-8080.theiadocker-1-labs-prod-theia&s-4-tor01.proxy.cognitiveclass.ai/tbl_sql.php?db=HR&table=EMPLOYEES

phpMyAdmin

Server: mysql:3306 Database: HR Table: EMPLOYEES

Run SQL query/queries on table HR

1. SELECT * FROM 'EMPLOYEES'

Columns

EMP_ID
F_NAME
L_NAME
SSN
B_DATE
SEX
ADDRESS
JOB_ID
SALARY
MANAGER_ID
DEP_ID

SELECT * FROM 'EMPLOYEES'

Bind parameters

Delimiter ; Show this query here again Retain query box Rollback when finished ☒ Enable foreign key checks Go

Delete the default line which appears so that you will get a blank window.

copy the code below and paste it to the textarea of the SQL page. Click Go.

Note if you have dropped RETREIVE_ALL procedure rerun the creation script of that procedure before executing these lines.

```
1. 1
2. 2
3. 3
4. 4
5. 5

1. CALL RETRIEVE_ALL;
2. CALL UPDATE_SALEPRICE(1, 'BAD');
3.
4.
5. CALL RETRIEVE_ALL;
```

Copied!

Showing rows 0 - 4 (5 total, Query took 0.0007 seconds.)

CALL RETRIEVE_ALL

Show all Number of rows: 25 Filter rows: Search this table

+ Options

ID	ANIMAL	SALEPRICE	SALEDATE	QUANTITY
1	Cat	450.09	2018-05-29	9
2	Dog	666.66	2018-06-01	3
3	Parrot	50.00	2018-06-04	2
4	Hamster	60.60	2018-06-11	6
5	Goldfish	48.48	2018-06-14	24

Showing rows 0 - 4 (5 total, Query took 0.0015 seconds.)

CALL RETRIEVE_ALL

Show all Number of rows: 25 Filter rows: Search this table

+ Options

ID	ANIMAL	SALEPRICE	SALEDATE	QUANTITY
1	Cat	337.57	2018-05-29	9
2	Dog	666.66	2018-06-01	3
3	Parrot	50.00	2018-06-04	2
4	Hamster	60.60	2018-06-11	6
5	Goldfish	48.48	2018-06-14	24

4. Let's call the UPDATE_SALEPRICE routine once again. We want to update the sale price of animal with ID 3 having **WORSE** health condition in the PETSALe table. copy the code below and paste it to the textarea of the SQL page. Click Go. You will have all the records retrieved from the PETSALe table.

```
1. 1
2. 2
3. 3
4. 4
5. 5

1. CALL RETRIEVE_ALL;
2. CALL UPDATE_SALEPRICE(3, 'WORSE');
3.
4.
5. CALL RETRIEVE_ALL;
```

Copied!

CALL RETRIEVE_ALL

Showing rows 0 - 4 (5 total, Query took 0.0005 seconds)

CALL RETRIEVE_ALL

Showing rows 0 - 4 (5 total, Query took 0.0005 seconds)

Options

1

ANIMAL

SALEPRICE

SALEDATE

QUANTITY

1

Cat

337.57

2018-05-29

9

2

Dog

666.66

2018-06-01

3

3

Parrot

50.00

2018-06-04

2

4

Hamster

60.60

2018-06-11

6

5

Goldfish

48.48

2018-06-14

24

Query results operations

Options

1

ANIMAL

SALEPRICE

SALEDATE

QUANTITY

1

Cat

337.57

2018-05-29

9

2

Dog

666.66

2018-06-01

3

3

Parrot

25.00

2018-06-04

2

4

Hamster

60.60

2018-06-11

6

5

Goldfish

48.48

2018-06-14

24

5. You can view the created stored procedure routine UPDATE_SALEPRICE. Click on the **Routines** and view the procedure.

StructureSQLSearchQueryExportImportOperationsPrivilegesRoutinesEventsTriggersDesigner

Routines

Name	Action	Type	Returns
RETRIEVE_ALL	Edit Execute Export Drop	PROCEDURE	
UPDATE_SALEPRICE	Edit Execute Export Drop	PROCEDURE	

[Check all](#) [With selected:](#) [Export](#) [Drop](#)

New

[Add routine](#)

6. If you wish to drop the stored procedure routine UPDATE_SALEPRICE, copy the code below and paste it to the textarea of the SQL page. Click **Go**.

```
1. 1
2. 2
3. 3
```

```
1. DROP PROCEDURE UPDATE_SALEPRICE;
2.
3. CALL UPDATE_SALEPRICE;
```

Copied!

7

8

9 DROP PROCEDURE UPDATE_SALEPRICE;

10

11 CALL UPDATE_SALEPRICE;

ClearFormatGet auto-saved query

☐ Bind parameters

[Delimiter ;] ☐ Show this query here again ☐ Retain query box ☐ Rollback when finished ☒ Enable foreign key checks

Go

Hide query box

Error

SQL query: [Copy](#)

DROP PROCEDURE UPDATE_SALEPRICE

MySQL said: [?](#)

#1305 - PROCEDURE Mysql_learners.UPDATE_SALEPRICE does not exist

Congratulations! You have completed this lab on creating stored procedures in MySQL, and are ready for the next topic.

Author(s)

[Lakshmi Holla](#)

[Malika Singla](#)

Changelog

Date	Version	Changed by	Change Description
2021-08-09	0.2	Sathya Priya	Updated HTML tags and SQL link
2021-11-01	0.1	Lakshmi Holla, Malika Singla	Initial Version

© IBM Corporation 2021. All rights reserved.