



Hands-on Lab: Committing and Rolling back a Transaction using a Stored Procedure

Estimated time needed: 10 minutes

A transaction is simply a sequence of operations performed using one or more SQL statements as a single logical unit of work. A database transaction must be ACID (Atomic, Consistent, Isolated and Durable). The effects of all the SQL statements in a transaction can either be applied to the database using the COMMIT command or undone from the database using the ROLLBACK command.

In this lab, you will learn some commonly used TCL (Transaction Control Language) commands of SQL through the creation of a stored procedure routine. You will learn about COMMIT, which is used to permanently save the changes done in the transactions in a table, and about ROLLBACK, which is used to undo the transactions that have not been saved in a table. ROLLBACK can only be used to undo the changes in the current unit of work.

Software Used in this Lab

In this lab, you will use an [IBM Db2 Database](#). Db2 is a Relational Database Management System (RDBMS) from IBM, designed to store, analyze and retrieve data efficiently.

To complete this lab you will utilize a Db2 database service on IBM Cloud. If you did not already complete this lab task earlier in this module, you will not yet have access to Db2 on IBM Cloud, and you will need to follow the lab below first:

- [Hands-on Lab : Sign up for IBM Cloud, Create Db2 service instance and Get started with the Db2 console](#)

Data Used in this Lab

The data used in this lab is internal data. You will be working on the **BankAccounts** and **ShoeShop** tables.

ACCOUNTNUMBER	ACCOUNTNAME	BALANCE
B001	Rose	300.00
B002	James	1345.00
B003	Shoe Shop	124200.00
B004	Corner Shop	76000.00

PRODUCT	STOCK	PRICE
Boots	11	200.00
High heels	8	600.00
Brogues	10	150.00
Trainers	14	300.00

This lab requires you to have the **BankAccounts** and **ShoeShop** tables populated with sample data on Db2. Download the `BankAccounts-CREATE.sql` and `ShoeShop-CREATE.sql` scripts below, upload them to the Db2 console and run them. The scripts will create new tables called BankAccounts and ShoeShop while dropping any previous BankAccounts and ShoeShop tables if they exist, and will populate them with the sample data required for this lab.

- [BankAccounts-CREATE.sql](#)
- [ShoeShop-CREATE.sql](#)

Please go through the lab below to learn how to upload and run a script on Db2 console (for this case, you need don't need to know anything else other than how to upload and run a script):

- [Hands-on Lab : Create tables using SQL scripts and load data into tables](#)

Objectives

After completing this lab, you will be able to:

- Permanently save the changes done in a transaction
- Undo the transaction that has not been saved

Instructions

When you approach the exercises in this lab, follow the instructions to run the queries on Db2:

- Go to the [Resource List](#) of IBM Cloud by logging in where you can find the Db2 service instance that you created in a previous lab under **Services** section. Click on the **Db2-xx service**. Next, open the Db2 Console by clicking on **Open Console** button. Click on the 3-bar menu icon in the top left corner and go to the **Run SQL** page. The Run SQL tool enables you to run SQL statements.
 - If needed, follow [Hands-on Lab : Sien up for IBM Cloud, Create Db2 service instance and Get started with the Db2 console](#)

Exercise

Task A: Example exercise

Let us go through an example on committing and rolling back a transaction

1. Make sure you have created and populated the **BankAccounts** and **ShoeShop** tables by following the **"Data Used in this Lab"** section of this lab.

ACCOUNTNUMBER	ACCOUNTNAME	BALANCE
B001	Rose	300.00
B002	James	1345.00
B003	Shoe Shop	124200.00
B004	Corner Shop	76000.00

PRODUCT	STOCK	PRICE
Boots	11	200.00
High heels	8	600.00
Brogues	10	150.00
Trainers	14	300.00

2.
- You will create a stored procedure routine named **TRANSACTION_ROSE** which will include TCL commands like COMMIT and ROLLBACK.
 - Now develop the routine based on the given scenario to execute a transaction.
 - **Scenario:** Let's buy Rose a pair of Boots from ShoeShop. So we have to update the Rose balance as well as the ShoeShop balance in the BankAccounts table. Then we also have to update Boots stock in the ShoeShop table. After Boots, let's also attempt to buy Rose a pair of Trainers.
 - To create the stored procedure routine on Db2, copy the code below and paste it to the textbox of the **Run SQL** page. Click **Run all**.

```
1. 1
2. 2
3. 3
4. 4
5. 5
6. 6
7. 7
8. 8
9. 9
10. 10
11. 11
12. 12
13. 13
14. 14
15. 15
16. 16
17. 17
18. 18
19. 19
20. 20
21. 21
22. 22
23. 23
24. 24
25. 25
26. 26
27. 27
28. 28
29. 29
30. 30
31. 31
32. 32
33. 33
34. 34
35. 35
36. 36
37. 37
38. 38
39. 39
40. 40
1. --SET TERMINATOR @
2. CREATE PROCEDURE TRANSACTION_ROSE -- Name of this stored procedure routine
3.
4. LANGUAGE SQL -- language used in this routine
5. MODIFIES SQL DATA -- This routine will only write/modify data in the table
6.
7. BEGIN
8.
9. DECLARE SQLCODE INTEGER DEFAULT 0; -- Host variable SQLCODE declared and assigned 0
10. DECLARE retcode INTEGER DEFAULT 0; -- Local variable retcode with declared and assigned 0
11. DECLARE CONTINUE HANDLER FOR SQLCODE
12. SET retcode = SQLCODE; -- Handler tell the routine what to do when an error or warning occurs
13. -- Value of SQLCODE assigned to local variable retcode
14.
15. UPDATE BankAccounts
16. SET Balance = Balance-200
17. WHERE AccountName = 'Rose';
18.
19. UPDATE BankAccounts
20. SET Balance = Balance+200
21. WHERE AccountName = 'Shoe Shop';
22.
23. UPDATE ShoeShop
24. SET Stock = Stock-1
25. WHERE Product = 'Boots';
26.
27. UPDATE BankAccounts
28. SET Balance = Balance-300
29. WHERE AccountName = 'Rose';
30.
31. IF retcode < 0 THEN -- SQLCODE returns negative value for error, zero for success, positive value for warning
32. ROLLBACK WORK;
33.
34. ELSE
35. COMMIT WORK;
36.
37. END IF;
38.
39. END
40. @ -- Routine termination character
```

Copied

```

1  --#SET TERMINATOR @
2  CREATE PROCEDURE TRANSACTION_ROSE
3
4  LANGUAGE SQL
5  MODIFIES SQL DATA
6
7  BEGIN
8
9      DECLARE SQLCODE INTEGER DEFAULT 0;
10     DECLARE retcode INTEGER DEFAULT 0;
11     DECLARE CONTINUE HANDLER FOR SQLEXCEPTION
12
13     SET retcode = SQLCODE;
14
15     UPDATE BankAccounts
16     SET Balance = Balance-200
17     WHERE AccountName = 'Rose';
18
19     UPDATE BankAccounts
20     SET Balance = Balance+200
21     WHERE AccountName = 'Shoe Shop';
22
23     UPDATE ShoeShop
24     SET Stock = Stock-1
25     WHERE Product = 'Boots';
26
27     UPDATE BankAccounts
28     SET Balance = Balance-300
29     WHERE AccountName = 'Rose';
30
31
32     IF retcode < 0 THEN
33         ROLLBACK WORK;
34
35     ELSE
36         COMMIT WORK;
37
38     END IF;
39
40 END
41 @
42

```

✓ CREATE PROCEDURE TRANSACTION_ROSE LANGUAGE SQL MODIFIES SQL DATA BEGIN DEC.

Status: **Success** | Affected Rows: **0**

3. Let's now check if the transaction has been committed or not. Copy the code below in a **new blank script** and paste it to the textbox of the **Run SQL** page. Click **Run all**.

```

1. 1
2. 2
3. 3
4. 4
5. 5
1. CALL TRANSACTION_ROSE; -- Caller query
2.
3. SELECT * FROM BankAccounts;
4.
5. SELECT * FROM ShoeShop;

```

[Copied!](#)

4. We can observe that the transaction has been executed. But when we observe the tables, no changes have permanently been saved through COMMIT. All the possible changes happened might have been undone through ROLLBACK since the whole transaction fails due to the failure of a SQL statement or more. Let's go through the possible reason behind the failure of the transaction and how COMMIT - ROLLBACK works on a stored procedure:

- The first three UPDATEs should run successfully. Both the balance of Rose and ShoeShop should have been updated in the BankAccounts table. The current balance of Rose should stand at 300 - 200 (price of a pair of Boots) = 100. The current balance of ShoeShop should stand at 124200 + 200 = 124400. The stock of Boots should also be updated in the ShoeShop table after the successful purchase for Rose, 11 - 1 = 10.
- The last UPDATE statement tries to buy Rose a pair of Trainers, but her balance becomes insufficient (Current balance of Rose: 100 < Price of Trainers: 300) after buying a pair of Boots. So, the last UPDATE statement fails. Since the whole transaction fails if any of the SQL statements fail, the transaction won't be committed.
- The **SQLCODE** which is a stand-alone host variable contains success/failure/warning information of each SQL statement execution. Now since **SQLCODE** variable gets reset back as the next SQL statement runs, **retcode** is our local variable to catch the return value of this **SQLCODE**. **SQLCODE** returns negative value for each SQL statement if not executed successfully. So, on any error occurrence, all the changes are rolled back. Commit only takes place after the transaction gets executed successfully without any error.

1

CALL TRANSACTION_ROSE;

2

3

SELECT * FROM BankAccounts;

4

5

SELECT * FROM ShoeShop;

6

▼

✓

CALL TRANSACTION_ROSE

Status: **Success**

|

Affected Rows: **0**

▼

✓

SELECT * FROM BankAccounts

Result set 1

Search

ACCOUNTNUMBER	ACCOUNTNAME
B001	Rose
B002	James
B003	Shoe Shop
B004	Corner Shop

▼

✓

SELECT * FROM ShoeShop

Result set 1

Search

PRODUCT	STOCK
Boots	11
High heels	8
Brogues	10
Trainers	14

Task B: Practice exercise

Now let's practice an exercise on committing and rolling back a transaction.

1. Problem:

Create a stored procedure **TRANSACTION_JAMES** to execute a transaction based on the following scenario: First buy James 4 pairs of Trainers from ShoeShop. Update his balance as well as the balance of ShoeShop. Also, update the stock of Trainers at ShoeShop. Then attempt to buy James a pair of Brogues from ShoeShop. If any of the UPDATE statements fail, the whole transaction fails. You will roll back the transaction. Commit the transaction only if the whole transaction is successful.

► Hint

► Solution

Congratulations! You have completed this lab, and you are ready for the next topic.

Author(s)

- Sandip Saha Joy

Other Contributor(s)

- Lin Joyner

Changelog

Date	Version	Changed by	Change Description
2020-12-24	1.1	Steve Ryan	ID Reviewed
2020-12-20	1.0	Sandip Saha Joy	Created initial version