SQL Cheat Sheet: JOIN statements



Joins

Topic	Syntax	Description	Example
Cross Join	<pre>SELECT column_name(s) FROM table1 CROSS JOIN table2;</pre>	The CROSS JOIN is used to generate a paired combination of each row of the first table with each row of the second table.	SELECT DEPT_ID_DEP, LOCT_ID FROM DEPARTMENTS CROSS JOIN LOCATIONS;
Inner Join	<pre>SELECT column_name(s) FROM table1 INNER JOIN table2 ON table1.column_name = table2.column_name; WHERE condition;</pre>	You can use an inner join in a SELECT statement to retrieve only the rows that satisfy the join conditions on every specified table.	<pre>select E.F_NAME, E.L_NAME, JH.START_DATE from EMPLOYEES as E INNER JOIN JOB_HISTORY as JH on E.EMP_ID=JH.EMPL_ID where E.DEP_ID ='5';</pre>
Left Outer Join	<pre>SELECT column_name(s) FROM table1 LEFT OUTER JOIN table2 ON table1.column_name = table2.column_name WHERE condition;</pre>	The LEFT OUTER JOIN will return all records from the left side table and the matching records from the right table.	select E.EMP_ID,E.L_NAME,E.DEP_ID,D.DEP_NAME from EMPLOYEES AS E LEFT OUTER JOIN DEPARTMENTS AS D ON E.DEP_ID=D.DEPT_ID_DEP;
Right Outer Join	<pre>SELECT column_name(s) FROM table1 RIGHT OUTER JOIN table2 ON table1.column_name = table2.column_name WHERE condition;</pre>	The RIGHT OUTER JOIN returns all records from the right table, and the matching records from the left table.	select E.EMP_ID,E.L_NAME,E.DEP_ID,D.DEP_NAME from EMPLOYEES AS E RIGHT OUTER JOIN DEPARTMENTS AS D ON E.DEP_ID=D.DEPT_ID_DEP;
Full Outer Join	SELECT column_name(s) FROM table1 FULL OUTER JOIN table2 ON table1.column_name	The FULL OUTER JOIN clause results in the inclusion of rows from two tables. If a value	select E.F_NAME,E.L_NAME,D.DEP_NAME from EMPLOYEES AS E FULL OUTER JOIN

= table2.column name WHERE condition;

is missing when rows are joined, that value DEPARTMENTS AS D ON is null in the result table.

A self join is regular join but it can be

E.DEP_ID=D.DEPT_ID_DEP;

Self Join

SELECT column name(s) FROM table1 T1, table1 T2 WHERE condition;

used to joined with itself.

SELECT B.* FROM EMPLOYEES A JOIN EMPLOYEES B ON A.MANAGER ID = B.MANAGER ID WHERE A.EMP ID = 'E1001';

Joins in MySQL using phpMyAdmin

SELECT column name(s) FROM table1 LEFT OUTER JOIN table2 ON table1.column name = table2.column name WHERE condition

UNION

Full Outer Join

SELECT column name(s)

FROM table1

RIGHT OUTER JOIN table2 ON table1.column name = table2.column name WHERE condition

The UNION operator is used to combine the result-set of two or more SELECT statements.

select E.F NAME, E.L NAME, D.DEP NAME from EMPLOYEES AS E LEFT OUTER JOIN DEPARTMENTS AS D ON E.DEP ID=D.DEPT ID DEP

UNION

select E.F_NAME, E.L_NAME, D.DEP_NAME

from EMPLOYEES AS E

RIGHT OUTER JOIN DEPARTMENTS AS D ON

E.DEP ID=D.DEPT ID DEP

Author(s)

D.M Naidu

Changelog

Date	Version	Changed by	Change Description
2023-05-04	1.1	Benny Li	Formatting changes

2022-10-04 1.0 D.M.Naidu Initial Version