



Ghulam Ishaq Khan Institute of Engineering Sciences and Technology

AC47

Hamza Hasan, Mujtaba Omar, Syed Basim Mehmood

2023-02-24

- 1 Contest
- 2 Mathematics
- 3 Data structures
- 4 Numerical
- 5 Number theory
- 6 Combinatorial
- 7 Graph
- 8 Geometry
- 9 Strings
- 10 Various

# Contest (1)

template.cpp46 lines

```
#include<bits/stdc++.h>
using namespace std;
#define nl cout<<"\n"
#define vi vector<int>
#define vll vector<ll>
#define vb vector<bool>
#define vc vector<char>
#define fastio ios_base::sync_with_stdio(false); cin.tie(NULL);
        cout.tie(NULL)
#define tcs int t;cin>>t;for(int T=1;T<=t;T++)
#define sp <<" "<<
#define rep(l, r, i) for (int i = l; i < r; ++i)
#define per(l, r, i) for (int i = r; i >= l; --i)
#define repp(l, r, i) for (int i = l; i <= r; ++i)
#define forn(a,b) for (int i = a; i <= b; ++i)
#define all(a) begin(a), end(a)
#define pb(a) push_back(a)
#define pii pair<int,int>
#define fi first
#define se second
#define mp(a, b) make_pair(a, b)
#define int long long
#define ll long long
#define dd double

ll mod=1e9+7;

ll gcd(ll a, ll b){ll tmp; while (b != 0) tmp = a, a = b, b = tmp%b; return a;}
ll po(ll x,ll y,ll _prime=mod) {if(y<0)return 0;y%=( _prime-1);
    ll res=1;while(y>0) {if(y&1)res=(res*x)% _prime;x=(x*x)% _prime;y>>=1;}return (res%_prime);}
void solve(){

}

int32_t main(){
    // fastio;
```

templateExtras.h40 lines

```
// freopen("in.txt","r",stdin);
// freopen("out.txt","w+",stdout);
tcs{
    // cout<<"Case #"<<T<<": ";
    solve(); nl;
}
return 0;
}
/*
*/

template<class K, class V>ostream& operator<<(ostream&s,const pair<K,V>&p){s<<'<'<<p.first<< ", "<<p.second<<'>';return s;}

template<class T, class=typename T::value_type, class=typename enable_if<!is_same<T,string>::value>::type> ostream& operator<<(ostream&s,const T&v){s<<'[';for(auto&x:v){s<<x<< ", "; if(v.size()) s<<"\b\b"; s<<'>';return s;}

void debug_out(vector<string> args, int idx, int LINE_NUM) {
    cerr << endl;
}

template <typename Head, typename... Tail> void debug_out(
    vector<string> args, int idx, int LINE_NUM, Head H, Tail ... T) {
    if(idx > 0) cerr << ", "; else cerr << "Line(" << LINE_NUM << ") ";
    cerr << args[idx] << " = " << H;
    debug_out(args, idx + 1, LINE_NUM, T...);
}

template<typename... All> void debug_out(string s, int idx, int LINE_NUM, All... VA_ARGS){
    split(s, ", ", args);
    debug_out(args, idx, LINE_NUM, VA_ARGS...);
}

#ifdef LOCAL
    #define dbb(...) debug_out(__VA_ARGS__, 0, __LINE__, __VA_ARGS__)
    #define db(n) cout<<"here "<<n<<"\n";
    #define DB(n) cout << "$|" << n << "|$\n";
#else
    #define dbb(...) ll
    #define db(n) 22
    #define DB(n) 33
#endif

mt19937 rng(chrono::steady_clock::now().time_since_epoch().count());
```

lambdaSort.cpp8 lines

```
int rand(int lo, int hi){if(lo > hi) swap(lo,hi); return lo + rng() % (hi - lo + 1);} //returns in the range [lo, hi]

int main(){
    vector<int>key;
    auto cmp=[key](int a,int b){return key[a]<key[b];};
    vector<int>a;
    sort(all(a),cmp);
    set<int,decltype(cmp)>s(cmp);
    priority_queue<int,vector<int>,decltype(cmp)>pq(cmp);
}

solverX.py11 lines

from sys import setrecursionlimit
import threading # kaizo
setrecursionlimit(10**6+100)

def solve():
    pass

threading.stack_size(10**6)
t=threading.Thread(target=solve)
t.start()
t.join()

troubleshoot.txt52 lines

Pre-submit:
Write a few simple test cases if sample is not enough.
Are time limits close? If so, generate max cases.
Is the memory usage fine?
Could anything overflow?
Make sure to submit the right file.

Wrong answer:
Print your solution! Print debug output, as well.
Are you clearing all data structures between test cases?
Can your algorithm handle the whole range of input?
Read the full problem statement again.
Do you handle all corner cases correctly?
Have you understood the problem correctly?
Any uninitialized variables?
Any overflows?
Confusing N and M, i and j, etc.?
Are you sure your algorithm works?
What special cases have you not thought of?
Are you sure the STL functions you use work as you think?
Add some assertions, maybe resubmit.
Create some testcases to run your algorithm on.
Go through the algorithm for a simple case.
Go through this list again.
Explain your algorithm to a teammate.
Ask the teammate to look at your code.
Go for a small walk, e.g. to the toilet.
Is your output format correct? (including whitespace)
Rewrite your solution from the start or let a teammate do it.

Runtime error:
Have you tested all corner cases locally?
Any uninitialized variables?
Are you reading or writing outside the range of any vector?
Any assertions that might fail?
Any possible division by 0? (mod 0 for example)
Any possible infinite recursion?
Invalidated pointers or iterators?
Are you using too much memory?
```

Debug with resubmits (e.g. remapped signals, see Various).

Time limit exceeded:  
Do you have any possible infinite loops?  
What is the complexity of your algorithm?  
Are you copying a lot of unnecessary data? (References)  
How big is the input and output? (consider scanf)  
Avoid vector, map. (use arrays/unordered\_map)  
What do your teammates think about your algorithm?

Memory limit exceeded:  
What is the max amount of memory your algorithm should need?  
Are you clearing all data structures between test cases?

Mathematics (2)

2.1 Equations

ax^2 + bx + c = 0 \Rightarrow x = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}

The extremum is given by  $x = -b/2a$ .

ax + by = e \quad cx + dy = f \Rightarrow \begin{cases} x = \frac{ed - bf}{ad - bc} \\ y = \frac{af - ec}{ad - bc} \end{cases}

In general, given an equation  $Ax = b$ , the solution to a variable  $x_i$  is given by

x\_i = \frac{\det A'\_i}{\det A}

where  $A'_i$  is  $A$  with the  $i$ 'th column replaced by  $b$ .

2.2 Recurrences

If  $a_n = c_1a_{n-1} + \dots + c_ka_{n-k}$ , and  $r_1, \dots, r_k$  are distinct roots of  $x^k - c_1x^{k-1} - \dots - c_k$ , there are  $d_1, \dots, d_k$  s.t.

a\_n = d\_1r\_1^n + \dots + d\_kr\_k^n.

Non-distinct roots  $r$  become polynomial factors, e.g.  $a_n = (d_1n + d_2)r^n$ .

2.3 Trigonometry

\sin(v + w) = \sin v \cos w + \cos v \sin w \\ \cos(v + w) = \cos v \cos w - \sin v \sin w

\tan(v + w) = \frac{\tan v + \tan w}{1 - \tan v \tan w} \\ \sin v + \sin w = 2 \sin \frac{v + w}{2} \cos \frac{v - w}{2} \\ \cos v + \cos w = 2 \cos \frac{v + w}{2} \cos \frac{v - w}{2}

(V + W) \tan(v - w)/2 = (V - W) \tan(v + w)/2

where  $V, W$  are lengths of sides opposite angles  $v, w$ .

a \cos x + b \sin x = r \cos(x - \phi) \\ a \sin x + b \cos x = r \sin(x + \phi)

where  $r = \sqrt{a^2 + b^2}, \phi = \text{atan2}(b, a)$ .

2.4 Geometry

2.4.1 Triangles

Side lengths:  $a, b, c$

Semiperimeter:  $p = \frac{a + b + c}{2}$

Area:  $A = \sqrt{p(p - a)(p - b)(p - c)}$

Circumradius:  $R = \frac{abc}{4A}$

Inradius:  $r = \frac{A}{p}$

Length of median (divides triangle into two equal-area triangles):

m\_a = \frac{1}{2} \sqrt{2b^2 + 2c^2 - a^2}

Length of bisector (divides angles in two):

s\_a = \sqrt{bc \left[ 1 - \left( \frac{a}{b + c} \right)^2 \right]}

Law of sines: \frac{\sin \alpha}{a} = \frac{\sin \beta}{b} = \frac{\sin \gamma}{c} = \frac{1}{2R}

Law of cosines: a^2 = b^2 + c^2 - 2bc \cos \alpha

Law of tangents: \frac{a + b}{a - b} = \frac{\tan \frac{\alpha + \beta}{2}}{\tan \frac{\alpha - \beta}{2}}


2.4.2 Quadrilaterals

With side lengths  $a, b, c, d$ , diagonals  $e, f$ , diagonals angle  $\theta$ , area  $A$  and magic flux  $F = b^2 + d^2 - a^2 - c^2$ :

4A = 2ef \cdot \sin \theta = F \tan \theta = \sqrt{4e^2f^2 - F^2}

For cyclic quadrilaterals the sum of opposite angles is  $180^\circ$ ,  $ef = ac + bd$ , and  $A = \sqrt{(p - a)(p - b)(p - c)(p - d)}$ .

2.4.3 Spherical coordinates



x = r \sin \theta \cos \phi \quad y = r \sin \theta \sin \phi \quad z = r \cos \theta \\ r = \sqrt{x^2 + y^2 + z^2} \quad \theta = \text{acos}(z / \sqrt{x^2 + y^2 + z^2}) \quad \phi = \text{atan2}(y, x)

2.5 Derivatives/Integrals

\frac{d}{dx} \arcsin x = \frac{1}{\sqrt{1 - x^2}} \quad \frac{d}{dx} \arccos x = -\frac{1}{\sqrt{1 - x^2}} \\ \frac{d}{dx} \tan x = 1 + \tan^2 x \quad \frac{d}{dx} \arctan x = \frac{1}{1 + x^2} \\ \int \tan ax = -\frac{\ln |\cos ax|}{a} \quad \int x \sin ax = \frac{\sin ax - ax \cos ax}{a^2} \\ \int e^{-x^2} = \frac{\sqrt{\pi}}{2} \text{erf}(x) \quad \int x e^{ax} dx = \frac{e^{ax}}{a^2} (ax - 1)

Integration by parts:

\int\_a^b f(x)g(x)dx = [F(x)g(x)]\_a^b - \int\_a^b F(x)g'(x)dx

2.6 Sums

c^a + c^{a+1} + \dots + c^b = \frac{c^{b+1} - c^a}{c - 1}, c \neq 1

1 + 2 + 3 + \dots + n = \frac{n(n + 1)}{2}

1^2 + 2^2 + 3^2 + \dots + n^2 = \frac{n(2n + 1)(n + 1)}{6}

1^3 + 2^3 + 3^3 + \dots + n^3 = \frac{n^2(n + 1)^2}{4}

1^4 + 2^4 + 3^4 + \dots + n^4 = \frac{n(n + 1)(2n + 1)(3n^2 + 3n - 1)}{30}

2.7 Series

e^x = 1 + x + \frac{x^2}{2!} + \frac{x^3}{3!} + \dots, (-\infty < x < \infty)

\ln(1 + x) = x - \frac{x^2}{2} + \frac{x^3}{3} - \frac{x^4}{4} + \dots, (-1 < x \leq 1)

\sqrt{1 + x} = 1 + \frac{x}{2} - \frac{x^2}{8} + \frac{2x^3}{32} - \frac{5x^4}{128} + \dots, (-1 \leq x \leq 1)

\sin x = x - \frac{x^3}{3!} + \frac{x^5}{5!} - \frac{x^7}{7!} + \dots, (-\infty < x < \infty)

\cos x = 1 - \frac{x^2}{2!} + \frac{x^4}{4!} - \frac{x^6}{6!} + \dots, (-\infty < x < \infty)

### 2.8 Probability theory

Let  $X$  be a discrete random variable with probability  $p_X(x)$  of assuming the value  $x$ . It will then have an expected value (mean)  $\mu = \mathbb{E}(X) = \sum_x xp_X(x)$  and variance  $\sigma^2 = V(X) = \mathbb{E}(X^2) - (\mathbb{E}(X))^2 = \sum_x (x - \mathbb{E}(X))^2 p_X(x)$  where  $\sigma$  is the standard deviation. If  $X$  is instead continuous it will have a probability density function  $f_X(x)$  and the sums above will instead be integrals with  $p_X(x)$  replaced by  $f_X(x)$ .

Expectation is linear:

$$\mathbb{E}(aX + bY) = a\mathbb{E}(X) + b\mathbb{E}(Y)$$

For independent  $X$  and  $Y$ ,

$$V(aX + bY) = a^2V(X) + b^2V(Y).$$

#### 2.8.1 Discrete distributions

##### Binomial distribution

The number of successes in  $n$  independent yes/no experiments, each which yields success with probability  $p$  is  $\text{Bin}(n, p)$ ,  $n = 1, 2, \dots$ ,  $0 \leq p \leq 1$ .

$$p(k) = \binom{n}{k} p^k (1 - p)^{n - k}$$

$$\mu = np, \sigma^2 = np(1 - p)$$

$\text{Bin}(n, p)$  is approximately  $\text{Po}(np)$  for small  $p$ .

##### First success distribution

The number of trials needed to get the first success in independent yes/no experiments, each wich yields success with probability  $p$  is  $\text{Fs}(p)$ ,  $0 \leq p \leq 1$ .

$$p(k) = p(1 - p)^{k - 1}, k = 1, 2, \dots$$

$$\mu = \frac{1}{p}, \sigma^2 = \frac{1 - p}{p^2}$$

##### Poisson distribution

The number of events occurring in a fixed period of time  $t$  if these events occur with a known average rate  $\kappa$  and independently of the time since the last event is  $\text{Po}(\lambda)$ ,  $\lambda = t\kappa$ .

$$p(k) = e^{-\lambda} \frac{\lambda^k}{k!}, k = 0, 1, 2, \dots$$

$$\mu = \lambda, \sigma^2 = \lambda$$

#### 2.8.2 Continuous distributions

##### Uniform distribution

If the probability density function is constant between  $a$  and  $b$  and 0 elsewhere it is  $\text{U}(a, b)$ ,  $a < b$ .

$$f(x) = \begin{cases} \frac{1}{b - a} & a < x < b \\ 0 & \text{otherwise} \end{cases}$$

$$\mu = \frac{a + b}{2}, \sigma^2 = \frac{(b - a)^2}{12}$$

##### Exponential distribution

The time between events in a Poisson process is  $\text{Exp}(\lambda)$ ,  $\lambda > 0$ .

$$f(x) = \begin{cases} \lambda e^{-\lambda x} & x \geq 0 \\ 0 & x < 0 \end{cases}$$

$$\mu = \frac{1}{\lambda}, \sigma^2 = \frac{1}{\lambda^2}$$

##### Normal distribution

Most real random values with mean  $\mu$  and variance  $\sigma^2$  are well described by  $\mathcal{N}(\mu, \sigma^2)$ ,  $\sigma > 0$ .

$$f(x) = \frac{1}{\sqrt{2\pi\sigma^2}} e^{-\frac{(x - \mu)^2}{2\sigma^2}}$$

If  $X_1 \sim \mathcal{N}(\mu_1, \sigma_1^2)$  and  $X_2 \sim \mathcal{N}(\mu_2, \sigma_2^2)$  then

$$aX_1 + bX_2 + c \sim \mathcal{N}(\mu_1 + \mu_2 + c, a^2\sigma_1^2 + b^2\sigma_2^2)$$

### 2.9 Markov chains

A *Markov chain* is a discrete random process with the property that the next state depends only on the current state. Let  $X_1, X_2, \dots$  be a sequence of random variables generated by the Markov process. Then there is a transition matrix  $\mathbf{P} = (p_{ij})$ , with  $p_{ij} = \text{Pr}(X_n = i | X_{n - 1} = j)$ , and  $\mathbf{p}^{(n)} = \mathbf{P}^n \mathbf{p}^{(0)}$  is the probability distribution for  $X_n$  (i.e.,  $p_i^{(n)} = \text{Pr}(X_n = i)$ ), where  $\mathbf{p}^{(0)}$  is the initial distribution.

$\pi$  is a stationary distribution if  $\pi = \pi \mathbf{P}$ . If the Markov chain is *irreducible* (it is possible to get to any state from any state), then  $\pi_i = \frac{1}{\mathbb{E}(T_i)}$  where  $\mathbb{E}(T_i)$  is the expected time between two visits in state  $i$ .  $\pi_j / \pi_i$  is the expected number of visits in state  $j$  between two visits in state  $i$ .

For a connected, undirected and non-bipartite graph, where the transition probability is uniform among all neighbors,  $\pi_i$  is proportional to node  $i$ 's degree.

A Markov chain is *ergodic* if the asymptotic distribution is independent of the initial distribution. A finite Markov chain is ergodic iff it is irreducible and *aperiodic* (i.e., the gcd of cycle lengths is 1).  $\lim_{k \rightarrow \infty} \mathbf{P}^k = \mathbf{1}\pi$ .

A Markov chain is an A-chain if the states can be partitioned into two sets  $\mathbf{A}$  and  $\mathbf{G}$ , such that all states in  $\mathbf{A}$  are absorbing ( $p_{ii} = 1$ ), and all states in  $\mathbf{G}$  leads to an absorbing state in  $\mathbf{A}$ . The probability for absorption in state  $i \in \mathbf{A}$ , when the initial state is  $j$ , is  $a_{ij} = p_{ij} + \sum_{k \in \mathbf{G}} a_{ik} p_{kj}$ . The expected time until absorption, when the initial state is  $i$ , is  $t_i = 1 + \sum_{k \in \mathbf{G}} p_{ki} t_k$ .

### Data structures (3)

#### OrderStatisticTree.h

**Description:** A set (not multiset!) with support for finding the n'th element, and finding the index of an element. To get a map, change null\_type. **Time:**  $\mathcal{O}(\log N)$

782797, 16 lines

```
#include <bits/extc++.h>
using namespace __gnu_pbds;

template<class T>
using Tree = tree<T, null_type, less<T>, rb_tree_tag,
    tree_order_statistics_node_update>;

void example() {
    Tree<int> t, t2; t.insert(8);
    auto it = t.insert(10).first;
    assert(it == t.lower_bound(9));
    assert(t.order_of_key(10) == 1);
    assert(t.order_of_key(11) == 2);
    assert(*t.find_by_order(0) == 8);
    t.join(t2); // assuming T< T2 or T> T2, merge t2 into t
}
```

#### HashMap.h

**Description:** Hash map with mostly the same API as unordered\_map, but ~3x faster. Uses 1.5x memory. Initial capacity must be a power of 2 (if provided).

d77092, 7 lines

```
#include <bits/extc++.h>
// To use most bits rather than just the lowest ones:
struct chash { // large odd number for C
    const uint64_t C = 11(4e18 * acos(0)) | 71;
    ll operator() (ll x) const { return __builtin_bswap64(x*C); }
};
__gnu_pbds::gp_hash_table<ll, int, chash> h({}, {}, {}, {}, {1<<16});
```

#### SegmentTree.h

**Description:** One-indexed seg-tree. Bounds are inclusive to the left and right. Can be changed by modifying T, merge.

**Time:**  $\mathcal{O}(\log N)$

fed1bd, 22 lines

```
template<class T>
struct segTree{
    int n; vector<T> t; T init;
    segTree(int _n, T _init){
        n=_n; t.resize(2*n); init=_init; for(auto &tt:t) tt=init;
    } void update(int i, T k){
        i+=n; t[i]=k;
        while(i>1){i>>=1; t[i]=merge(t[i<<1], t[(i<<1)|1]);}
    } T query(int l, int r){
        l+=n; r+=n; T res=init;
        while(l<r){
            if(l&1){res=merge(res, t[l]); l++;}
            if(!(r&1)){res=merge(res, t[r]); r--;}
            l>>=1; r>>=1;
        } if(l==r) res=merge(res, t[l]);
        return res;
    }
```

```
    }T merge(T a,T b){
        T res;
        // merge here
        return res;
    }
};
```

LazySegmentTree.h

**Description:** Segment tree with ability to add or set values of large intervals, and compute max of intervals. Can be changed to other things. Use with a bump allocator for better performance, and SmallPtr or implicit indices to save memory.

**Usage:** Node\* tr = new Node(v, 0, sz(v));

**Time:**  $\mathcal{O}(\log N)$ .

e00909, 36 lines

```
const int N=1000;
const int L=1024;
vector<int>a(L+1);
vector<int>tree(2*L);
vector<int>lazy(2*L);
void update(int l,int r,int k,int u=1,int ul=1,int ur=N){
    tree[u]+=lazy[u]*(ur-ul+1);
    if(ul!=ur){
        lazy[u<<1]+=lazy[u];
        lazy[(u<<1)|1]+=lazy[u];
    }lazy[u]=0;
    if(ur<1 || r<ul) return;
    if(l<=ul && r>=ur){
        tree[u]+=k*(ur-ul+1);
        if(ul!=ur){
            lazy[u<<1]+=k;
            lazy[(u<<1)|1]+=k;
        }return;
    }
    int mid=(ul+ur)/2;
    update(l,r,k,u<<1,ul,mid);
    update(l,r,k,(u<<1)|1,mid+1,ur);
    tree[u]=tree[u<<1]+tree[(u<<1)|1];
}
int query(int l,int r,int u=1,int ul=1,int ur=N){
    tree[u]+=lazy[u]*(ur-ul+1);
    if(ul!=ur){
        lazy[u<<1]+=lazy[u];
        lazy[(u<<1)|1]+=lazy[u];
    }lazy[u]=0;
    if(ur<1 || r<ul) return 0;
    if(l<=ul && r>=ur){
        return tree[u];
    }int mid=(ul+ur)/2;
    return query(l,r,u<<1,ul,mid)+query(l,r,(u<<1)|1,mid+1,ur);
}
```

UnionFind.h

**Description:** Disjoint-set data structure.

**Time:**  $\mathcal{O}(\alpha(N))$

7a1870, 22 lines

```
struct DSU{
    vector<int> P,S;
    DSU(int n){
        P.resize(n+1);S.resize(n+1,1);
        for(int i=0;i<=n;i++)P[i]=i;
    }int find(int u){
        if(u==P[u])return u;
        return P[u]=find(P[u]);
    }void merge(int u,int v){
        u=find(u);
        v=find(v);
        if(u!=v){
            if(S[u]<S[v]){
```

```
                P[u]=v;
                S[v]+=S[u];
            }else{
                P[v]=u;
                S[u]+=S[v];
            }
        }
    };
};
```

UnionFindRollback.h

**Description:** Disjoint-set data structure with undo. If undo is not needed, skip st, time() and rollback().

**Usage:** int t = uf.time(); ...; uf.rollback(t);

**Time:**  $\mathcal{O}(\log(N))$

de4ad0, 21 lines

```
struct RollbackUF {
    vi e; vector<pii> st;
    RollbackUF(int n) : e(n, -1) {}
    int size(int x) { return -e[find(x)]; }
    int find(int x) { return e[x] < 0 ? x : find(e[x]); }
    int time() { return sz(st); }
    void rollback(int t) {
        for (int i = time(); i --> t;)
            e[st[i].first] = st[i].second;
        st.resize(t);
    }
    bool join(int a, int b) {
        a = find(a), b = find(b);
        if (a == b) return false;
        if (e[a] > e[b]) swap(a, b);
        st.push_back({a, e[a]});
        st.push_back({b, e[b]});
        e[a] += e[b]; e[b] = a;
        return true;
    }
};
```

Matrix.h

**Description:** Basic operations on square matrices.

**Usage:** Matrix<int, 3> A;

A.d = {{{{1,2,3}}, {{4,5,6}}, {{7,8,9}}}};

vector<int> vec = {1,2,3};

vec = (A^N) \* vec;

c43c7d, 26 lines

```
template<class T, int N> struct Matrix {
    typedef Matrix M;
    array<array<T, N>, N> d{};
    M operator*(const M& m) const {
        M a;
        rep(i,0,N) rep(j,0,N)
            rep(k,0,N) a.d[i][j] += d[i][k]*m.d[k][j];
        return a;
    }
    vector<T> operator*(const vector<T>& vec) const {
        vector<T> ret(N);
        rep(i,0,N) rep(j,0,N) ret[i] += d[i][j] * vec[j];
        return ret;
    }
    M operator^(ll p) const {
        assert(p >= 0);
        M a, b(*this);
        rep(i,0,N) a.d[i][i] = 1;
        while (p) {
            if (p&1) a = a*b;
            b = b*b;
            p >>= 1;
        }
        return a;
    }
```

```
    }
};
```

LineContainer.h

**Description:** Container where you can add lines of the form  $kx+m$ , and query maximum values at points  $x$ . Useful for dynamic programming (“convex hull trick”).

**Time:**  $\mathcal{O}(\log N)$

Sec1c7, 30 lines

```
struct Line {
    mutable ll k, m, p;
    bool operator<(const Line& o) const { return k < o.k; }
    bool operator<(ll x) const { return p < x; }
};

struct LineContainer : multiset<Line, less<>> {
    // (for doubles, use inf = 1/.0, div(a,b) = a/b)
    static const ll inf = LLONG_MAX;
    ll div(ll a, ll b) { // floored division
        return a / b - ((a ^ b) < 0 && a % b); }
    bool isect(iterator x, iterator y) {
        if (y == end()) return x->p = inf, 0;
        if (x->k == y->k) x->p = x->m > y->m ? inf : -inf;
        else x->p = div(y->m - x->m, x->k - y->k);
        return x->p >= y->p;
    }
    void add(ll k, ll m) {
        auto z = insert({k, m, 0}), y = z++, x = y;
        while (isect(y, z)) z = erase(z);
        if (x != begin() && isect(--x, y)) isect(x, y = erase(y));
        while ((y = x) != begin() && (--x)->p >= y->p)
            isect(x, erase(y));
    }
    ll query(ll x) {
        assert(!empty());
        auto l = *lower_bound(x);
        return l.k * x + l.m;
    }
};
```

Treap.h

**Description:** A short self-balancing tree. It acts as a sequential container with log-time splits/joins, and is easy to augment with additional data.

**Time:**  $\mathcal{O}(\log N)$

9556fc, 55 lines

```
struct Node {
    Node *l = 0, *r = 0;
    int val, y, c = 1;
    Node(int val) : val(val), y(rand()) {}
    void recalc();
};

int cnt(Node* n) { return n ? n->c : 0; }
void Node::recalc() { c = cnt(l) + cnt(r) + 1; }

template<class F> void each(Node* n, F f) {
    if (n) { each(n->l, f); f(n->val); each(n->r, f); }
}

pair<Node*, Node*> split(Node* n, int k) {
    if (!n) return {};
    if (cnt(n->l) >= k) { // "n->val >= k" for lower_bound(k)
        auto pa = split(n->l, k);
        n->l = pa.second;
        n->recalc();
        return {pa.first, n};
    } else {
        auto pa = split(n->r, k - cnt(n->l) - 1); // and just "k"
        n->r = pa.first;
```

```
n->recalc();
    return {n, pa.second};
}
}

Node* merge(Node* l, Node* r) {
    if (!l) return r;
    if (!r) return l;
    if (l->y > r->y) {
        l->r = merge(l->r, r);
        l->recalc();
        return l;
    } else {
        r->l = merge(l, r->l);
        r->recalc();
        return r;
    }
}
```

```
Node* ins(Node* t, Node* n, int pos) {
    auto pa = split(t, pos);
    return merge(merge(pa.first, n), pa.second);
}
```

```
// Example application: move the range [l, r) to index k
void move(Node*& t, int l, int r, int k) {
    Node *a, *b, *c;
    tie(a,b) = split(t, l); tie(b,c) = split(b, r - l);
    if (k <= l) t = merge(ins(a, b, k), c);
    else t = merge(a, ins(c, b, k - r));
}
```

FenwickTree.h  
**Description:** Computes partial sums  $a[0] + a[1] + \dots + a[\text{pos} - 1]$ , and updates single elements  $a[i]$ , taking the difference between the old and new value.  
**Time:** Both operations are  $\mathcal{O}(\log N)$ .

```
template<class T>
struct BIT{
    int n;vector<T>t;
    BIT(int _n){
        n=_n;t.resize(n);
    }void update(int i,T k){
        while(i<n){
            t[i]+=k;
            i+=i&-i;
        }
    }T pref(int i){
        int res=0;
        while(i>0){
            res+=t[i];
            i-=i&-i;
        }return res;
    }T query(int l,int r){
        return pref(r)-pref(l-1);
    }
};
```

FenwickTree2D.h  
**Description:** Computes sums  $a[i,j]$  for all  $i < I, j < J$ , and increases single elements  $a[i,j]$ . Requires that the elements to be updated are known in advance (call fakeUpdate() before init()).  
**Time:**  $\mathcal{O}(\log^2 N)$ . (Use persistent segment trees for  $\mathcal{O}(\log N)$ .)

```
struct FenwickTree2D {
    vector<vector<int>>> bit;
    int n, m;
```

```
// init(...) { ... }

int sum(int x, int y) {
    int ret = 0;
    for (int i = x; i >= 0; i = (i & (i + 1)) - 1)
        for (int j = y; j >= 0; j = (j & (j + 1)) - 1)
            ret += bit[i][j];
    return ret;
}

void add(int x, int y, int delta) {
    for (int i = x; i < n; i = i | (i + 1))
        for (int j = y; j < m; j = j | (j + 1))
            bit[i][j] += delta;
}
};
```

## Numerical (4)

### 4.1 Polynomials and recurrences

Polynomial.h

```
struct Poly {
    vector<double> a;
    double operator()(double x) const {
        double val = 0;
        for (int i = sz(a); i--;) (val *= x) += a[i];
        return val;
    }
    void diff() {
        rep(i,1,sz(a)) a[i-1] = i*a[i];
        a.pop_back();
    }
    void divroot(double x0) {
        double b = a.back(), c; a.back() = 0;
        for(int i=sz(a)-1; i--;) c = a[i], a[i] = a[i+1]*x0+b, b=c;
        a.pop_back();
    }
};
```

PolyRoots.h  
**Description:** Finds the real roots to a polynomial.  
**Usage:** polyRoots({{2,-3,1}},-1e9,1e9) // solve  $x^2-3x+2 = 0$   
**Time:**  $\mathcal{O}(n^2 \log(1/\epsilon))$

```
"Polynomial.h"
vector<double> polyRoots(Poly p, double xmin, double xmax) {
    if (sz(p.a) == 2) { return {-p.a[0]/p.a[1]}; }
    vector<double> ret;
    Poly der = p;
    der.diff();
    auto dr = polyRoots(der, xmin, xmax);
    dr.push_back(xmin-1);
    dr.push_back(xmax+1);
    sort(all(dr));
    rep(i,0,sz(dr)-1) {
        double l = dr[i], h = dr[i+1];
        bool sign = p(l) > 0;
        if (sign ^ (p(h) > 0)) {
            rep(it,0,60) { // while (h - l > 1e-8)
                double m = (l + h) / 2, f = p(m);
                if ((f <= 0) ^ sign) l = m;
                else h = m;
            }
            ret.push_back((l + h) / 2);
        }
    }
    return ret;
};
```

```
}

PolyInterpolate.h
Description: Given  $n$  points  $(x[i], y[i])$ , computes an  $n-1$ -degree polynomial  $p$  that passes through them:  $p(x) = a[0] * x^0 + \dots + a[n-1] * x^{n-1}$ . For numerical precision, pick  $x[k] = c * \cos(k/(n-1) * \pi), k = 0 \dots n-1$ .  
Time:  $\mathcal{O}(n^2)$ 
typedef vector<double> vd;
vd interpolate(vd x, vd y, int n) {
    vd res(n), temp(n);
    rep(k,0,n-1) rep(i,k+1,n)
        y[i] = (y[i] - y[k]) / (x[i] - x[k]);
    double last = 0; temp[0] = 1;
    rep(k,0,n) rep(i,0,n) {
        res[i] += y[k] * temp[i];
        swap(last, temp[i]);
        temp[i] -= last * x[k];
    }
    return res;
}
```

BerlekampMassey.h  
**Description:** Recovers any  $n$ -order linear recurrence relation from the first  $2n$  terms of the recurrence. Useful for guessing linear recurrences after brute-forcing the first terms. Should work on any field, but numerical stability for floats is not guaranteed. Output will have size  $\leq n$ .  
**Usage:** berlekampMassey({0, 1, 1, 3, 5, 11}) // {1, 2}  
**Time:**  $\mathcal{O}(N^2)$

```
"../number-theory/ModPow.h"
vector<ll> berlekampMassey(vector<ll> s) {
    int n = sz(s), L = 0, m = 0;
    vector<ll> C(n), B(n), T;
    C[0] = B[0] = 1;

    ll b = 1;
    rep(i,0,n) { ++m;
        ll d = s[i] % mod;
        rep(j,1,L+1) d = (d + C[j] * s[i - j]) % mod;
        if (!d) continue;
        T = C; ll coef = d * modpow(b, mod-2) % mod;
        rep(j,m,n) C[j] = (C[j] - coef * B[j - m]) % mod;
        if (2 * L > i) continue;
        L = i + 1 - L; B = T; b = d; m = 0;
    }

    C.resize(L + 1); C.erase(C.begin());
    for (ll& x : C) x = (mod - x) % mod;
    return C;
}
```

LinearRecurrence.h  
**Description:** Generates the  $k$ 'th term of an  $n$ -order linear recurrence  $S[i] = \sum_j S[i-j-1]tr[j]$ , given  $S[0 \dots n-1]$  and  $tr[0 \dots n-1]$ . Faster than matrix multiplication. Useful together with Berlekamp-Massey.  
**Usage:** linearRec({0, 1}, {1, 1}, k) //  $k$ 'th Fibonacci number  
**Time:**  $\mathcal{O}(n^2 \log k)$

```
typedef vector<ll> Poly;
ll linearRec(Poly S, Poly tr, ll k) {
    int n = sz(tr);

    auto combine = [&](Poly a, Poly b) {
        Poly res(n * 2 + 1);
        rep(i,0,n+1) rep(j,0,n+1)
            res[i + j] = (res[i + j] + a[i] * b[j]) % mod;
        for (int i = 2 * n; i > n; --i) rep(j,0,n)
            res[i - 1 - j] = (res[i - 1 - j] + res[i] * tr[j]) % mod;
```

```
        res.resize(n + 1);
        return res;
};

Poly pol(n + 1), e(pol);
pol[0] = e[1] = 1;

for (++k; k; k /= 2) {
    if (k % 2) pol = combine(pol, e);
    e = combine(e, e);
}

ll res = 0;
rep(i,0,n) res = (res + pol[i + 1] * S[i]) % mod;
return res;
}
```

## 4.2 Optimization

### Integrate.h

**Description:** Simple integration of a function over an interval using Simpson's rule. The error should be proportional to  $h^4$ , although in practice you will want to verify that the result is stable to desired precision when epsilon changes.

```
template<class F>
double quad(double a, double b, F f, const int n = 1000) {
    double h = (b - a) / 2 / n, v = f(a) + f(b);
    rep(i,1,n*2)
        v += f(a + i*h) * (i&1 ? 4 : 2);
    return v * h / 3;
}
```

## 4.3 Matrices

### Determinant.h

**Description:** Calculates determinant of a matrix. Destroys the matrix.  
**Time:**  $\mathcal{O}(N^3)$

```
double det(vector<vector<double>>& a) {
    int n = sz(a); double res = 1;
    rep(i,0,n) {
        int b = i;
        rep(j,i+1,n) if (fabs(a[j][i]) > fabs(a[b][i])) b = j;
        if (i != b) swap(a[i], a[b]), res *= -1;
        res *= a[i][i];
        if (res == 0) return 0;
        rep(j,i+1,n) {
            double v = a[j][i] / a[i][i];
            if (v != 0) rep(k,i+1,n) a[j][k] -= v * a[i][k];
        }
    }
    return res;
}
```

### IntDeterminant.h

**Description:** Calculates determinant using modular arithmetics. Modulos can also be removed to get a pure-integer version.  
**Time:**  $\mathcal{O}(N^3)$

```
const ll mod = 12345;
ll det(vector<vector<ll>>& a) {
    int n = sz(a); ll ans = 1;
    rep(i,0,n) {
        rep(j,i+1,n) {
            while (a[j][i] != 0) { // gcd step
                ll t = a[i][i] / a[j][i];
                if (t) rep(k,i,n)
                    a[i][k] = (a[i][k] - a[j][k] * t) % mod;
                swap(a[i], a[j]);
            }
        }
    }
}
```

```
        ans *= -1;
    }
}
ans = ans * a[i][i] % mod;
if (!ans) return 0;
}
return (ans + mod) % mod;
}
```

### SolveLinear.h

**Description:** Solves  $A * x = b$ . If there are multiple solutions, an arbitrary one is returned. Returns rank, or -1 if no solutions. Data in  $A$  and  $b$  is lost.  
**Time:**  $\mathcal{O}(n^2m)$

```
typedef vector<double> vd;
const double eps = 1e-12;

int solveLinear(vector<vd>& A, vd& b, vd& x) {
    int n = sz(A), m = sz(x), rank = 0, br, bc;
    if (n) assert(sz(A[0]) == m);
    vi col(m); iota(all(col), 0);

    rep(i,0,n) {
        double v, bv = 0;
        rep(r,i,n) rep(c,i,m)
            if ((v = fabs(A[r][c])) > bv)
                br = r, bc = c, bv = v;
        if (bv <= eps) {
            rep(j,i,n) if (fabs(b[j]) > eps) return -1;
            break;
        }
        swap(A[i], A[br]);
        swap(b[i], b[br]);
        swap(col[i], col[bc]);
        rep(j,0,n) swap(A[j][i], A[j][bc]);
        bv = 1/A[i][i];
        rep(j,i+1,n) {
            double fac = A[j][i] * bv;
            b[j] -= fac * b[i];
            rep(k,i+1,m) A[j][k] -= fac*A[i][k];
        }
        rank++;
    }

    x.assign(m, 0);
    for (int i = rank; i--;) {
        b[i] /= A[i][i];
        x[col[i]] = b[i];
        rep(j,0,i) b[j] -= A[j][i] * b[i];
    }
    return rank; // (multiple solutions if rank < m)
}
```

### SolveLinear2.h

**Description:** To get all uniquely determined values of  $x$  back from SolveLinear, make the following changes:

```
"SolveLinear.h"
08e495, 7 lines

rep(j,0,n) if (j != i) // instead of rep(j,i+1,n)
// ... then at the end:
x.assign(m, undefined);
rep(i,0,rank) {
    rep(j,rank,m) if (fabs(A[i][j]) > eps) goto fail;
    x[col[i]] = b[i] / A[i][i];
fail:; }
```

### SolveLinearBinary.h

**Description:** Solves  $Ax = b$  over  $\mathbb{F}_2$ . If there are multiple solutions, one is returned arbitrarily. Returns rank, or -1 if no solutions. Destroys  $A$  and  $b$ .

```
Time:  $\mathcal{O}(n^2m)$ 
fa2d7a, 34 lines

typedef bitset<1000> bs;

int solveLinear(vector<bs>& A, vi& b, bs& x, int m) {
    int n = sz(A), rank = 0, br;
    assert(m <= sz(x));
    vi col(m); iota(all(col), 0);
    rep(i,0,n) {
        for (br=i; br<n; ++br) if (A[br].any()) break;
        if (br == n) {
            rep(j,i,n) if(b[j]) return -1;
            break;
        }
        int bc = (int)A[br]._Find_next(i-1);
        swap(A[i], A[br]);
        swap(b[i], b[br]);
        swap(col[i], col[bc]);
        rep(j,0,n) if (A[j][i] != A[j][bc]) {
            A[j].flip(i); A[j].flip(bc);
        }
        rep(j,i+1,n) if (A[j][i]) {
            b[j] ^= b[i];
            A[j] ^= A[i];
        }
        rank++;
    }

    x = bs();
    for (int i = rank; i--;) {
        if (!b[i]) continue;
        x[col[i]] = 1;
        rep(j,0,i) b[j] ^= A[j][i];
    }
    return rank; // (multiple solutions if rank < m)
}
```

### MatrixInverse.h

**Description:** Invert matrix  $A$ . Returns rank; result is stored in  $A$  unless singular (rank < n). Can easily be extended to prime moduli; for prime powers, repeatedly set  $A^{-1} = A^{-1}(2I - AA^{-1}) \pmod{p^k}$  where  $A^{-1}$  starts as the inverse of  $A \pmod p$ , and  $k$  is doubled in each step.  
**Time:**  $\mathcal{O}(n^3)$

```
ebfff6, 35 lines

int matInv(vector<vector<double>>& A) {
    int n = sz(A); vi col(n);
    vector<vector<double>> tmp(n, vector<double>(n));
    rep(i,0,n) tmp[i][i] = 1, col[i] = i;

    rep(i,0,n) {
        int r = i, c = i;
        rep(j,i,n) rep(k,i,n)
            if (fabs(A[j][k]) > fabs(A[r][c]))
                r = j, c = k;
        if (fabs(A[r][c]) < 1e-12) return i;
        A[i].swap(A[r]); tmp[i].swap(tmp[r]);
        rep(j,0,n)
            swap(A[j][i], A[j][c]), swap(tmp[j][i], tmp[j][c]);
        swap(col[i], col[c]);
        double v = A[i][i];
        rep(j,i+1,n) {
            double f = A[j][i] / v;
            A[j][i] = 0;
            rep(k,i+1,n) A[j][k] -= f*A[i][k];
            rep(k,0,n) tmp[j][k] -= f*tmp[i][k];
        }
        rep(j,i+1,n) A[i][j] /= v;
        rep(j,0,n) tmp[i][j] /= v;
        A[i][i] = 1;
    }
}
```

```
}

for (int i = n-1; i > 0; --i) rep(j,0,i) {
    double v = A[j][i];
    rep(k,0,n) tmp[j][k] -= v*tmp[i][k];
}

rep(i,0,n) rep(j,0,n) A[col[i]][col[j]] = tmp[i][j];
return n;
}
```

### MatrixInverse-mod.h

**Description:** Invert matrix  $A$  modulo a prime. Returns rank; result is stored in  $A$  unless singular (rank < n). For prime powers, repeatedly set  $A^{-1} = A^{-1}(2I - AA^{-1}) \pmod{p^k}$  where  $A^{-1}$  starts as the inverse of  $A \pmod{p}$ , and  $k$  is doubled in each step.

**Time:**  $\mathcal{O}(n^3)$

"/number-theory/ModPow.h" a6f68f, 36 lines

```
int matInv(vector<vector<ll>>& A) {
    int n = sz(A); vi col(n);
    vector<vector<ll>> tmp(n, vector<ll>(n));
    rep(i,0,n) tmp[i][i] = 1, col[i] = i;

    rep(i,0,n) {
        int r = i, c = i;
        rep(j,i,n) rep(k,i,n) if (A[j][k]) {
            r = j; c = k; goto found;
        }
        return i;
    found:
        A[i].swap(A[r]); tmp[i].swap(tmp[r]);
        rep(j,0,n) swap(A[j][i], A[j][c]), swap(tmp[j][i], tmp[j][c]);
        swap(col[i], col[c]);
        ll v = modpow(A[i][i], mod - 2);
        rep(j,i+1,n) {
            ll f = A[j][i] * v % mod;
            A[j][i] = 0;
            rep(k,i+1,n) A[j][k] = (A[j][k] - f*A[i][k]) % mod;
            rep(k,0,n) tmp[j][k] = (tmp[j][k] - f*tmp[i][k]) % mod;
        }
        rep(j,i+1,n) A[i][j] = A[i][j] * v % mod;
        rep(j,0,n) tmp[i][j] = tmp[i][j] * v % mod;
        A[i][i] = 1;
    }

    for (int i = n-1; i > 0; --i) rep(j,0,i) {
        ll v = A[j][i];
        rep(k,0,n) tmp[j][k] = (tmp[j][k] - v*tmp[i][k]) % mod;
    }

    rep(i,0,n) rep(j,0,n)
        A[col[i]][col[j]] = tmp[i][j] % mod + (tmp[i][j] < 0 ? mod
            : 0);
    return n;
}
```

## 4.4 Fourier transforms

### FastFourierTransform.h

**Description:** fft(a) computes  $\hat{f}(k) = \sum_x a[x] \exp(2\pi i \cdot kx/N)$  for all  $k$ .  $N$  must be a power of 2. Useful for convolution: conv(a, b) = c, where  $c[x] = \sum a[i]b[x-i]$ . For convolution of complex numbers or more than two vectors: FFT, multiply pointwise, divide by n, reverse(start+1, end), FFT back. Rounding is safe if  $(\sum a_i^2 + \sum b_i^2) \log_2 N < 9 \cdot 10^{14}$  (in practice  $10^{16}$ ; higher for random inputs). Otherwise, use NTT/FFTMod.

**Time:**  $\mathcal{O}(N \log N)$  with  $N = |A| + |B|$  ( $\sim 1s$  for  $N = 2^{22}$ )

00ced6, 35 lines

```
typedef complex<double> C;
```

```
typedef vector<double> vd;
void fft(vector<C>& a) {
    int n = sz(a), L = 31 - __builtin_clz(n);
    static vector<complex<long double>> R(2, 1);
    static vector<C> rt(2, 1); // (^ 10% faster if double)
    for (static int k = 2; k < n; k *= 2) {
        R.resize(n); rt.resize(n);
        auto x = polar(1.0L, acos(-1.0L) / k);
        rep(i,k,2*k) rt[i] = R[i] = i&1 ? R[i/2] * x : R[i/2];
    }
    vi rev(n);
    rep(i,0,n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
    rep(i,0,n) if (i < rev[i]) swap(a[i], a[rev[i]]);
    for (int k = 1; k < n; k *= 2)
        for (int i = 0; i < n; i += 2 * k) rep(j,0,k) {
            C z = rt[j+k] * a[i+j+k]; // (25% faster if hand-rolled)
            a[i + j + k] = a[i + j] - z;
            a[i + j] += z;
        }
}

vd conv(const vd& a, const vd& b) {
    if (a.empty() || b.empty()) return {};
    vd res(sz(a) + sz(b) - 1);
    int L = 32 - __builtin_clz(sz(res)), n = 1 << L;
    vector<C> in(n), out(n);
    copy(all(a), begin(in));
    rep(i,0,sz(b)) in[i].imag(b[i]);
    fft(in);
    for (C& x : in) x *= x;
    rep(i,0,n) out[i] = in[-i & (n - 1)] - conj(in[i]);
    fft(out);
    rep(i,0,sz(res)) res[i] = imag(out[i]) / (4 * n);
    return res;
}
```

### FastFourierTransformMod.h

**Description:** Higher precision FFT, can be used for convolutions modulo arbitrary integers as long as  $N \log_2 N \cdot \text{mod} < 8.6 \cdot 10^{14}$  (in practice  $10^{16}$  or higher). Inputs must be in  $[0, \text{mod})$ .

**Time:**  $\mathcal{O}(N \log N)$ , where  $N = |A| + |B|$  (twice as slow as NTT or FFT)

"FastFourierTransform.h" b82773, 22 lines

```
typedef vector<ll> vl;
template<int M> vl convMod(const vl &a, const vl &b) {
    if (a.empty() || b.empty()) return {};
    vl res(sz(a) + sz(b) - 1);
    int B=32-__builtin_clz(sz(res)), n=1<<B, cut=int(sqrt(M));
    vector<C> L(n), R(n), outs(n), outl(n);
    rep(i,0,sz(a)) L[i] = C((int)a[i] / cut, (int)a[i] % cut);
    rep(i,0,sz(b)) R[i] = C((int)b[i] / cut, (int)b[i] % cut);
    fft(L), fft(R);
    rep(i,0,n) {
        int j = -i & (n - 1);
        outl[j] = (L[i] + conj(L[j])) * R[i] / (2.0 * n);
        outs[j] = (L[i] - conj(L[j])) * R[i] / (2.0 * n) / 1i;
    }
    fft(outl), fft(outs);
    rep(i,0,sz(res)) {
        ll av = ll(real(outl[i])+.5), cv = ll(imag(outs[i])+.5);
        ll bv = ll(imag(outl[i])+.5) + ll(real(outs[i])+.5);
        res[i] = ((av % M * cut + bv) % M * cut + cv) % M;
    }
    return res;
}
```

### NumberTheoreticTransform.h

**Description:** ntt(a) computes  $\hat{f}(k) = \sum_x a[x]g^{xk}$  for all  $k$ , where  $g = \text{root}^{(\text{mod}-1)/N}$ .  $N$  must be a power of 2. Useful for convolution modulo specific nice primes of the form  $2^a b + 1$ , where the convolution result has size at most  $2^a$ . For arbitrary modulo, see FFTMod. conv(a, b) = c, where  $c[x] = \sum a[i]b[x-i]$ . For manual convolution: NTT the inputs, multiply pointwise, divide by n, reverse(start+1, end), NTT back. Inputs must be in  $[0, \text{mod})$ .

**Time:**  $\mathcal{O}(N \log N)$

"/number-theory/ModPow.h" ced03d, 33 lines

```
const ll mod = (119 << 23) + 1, root = 62; // = 998244353
// For p < 2^30 there is also e.g. 5 << 25, 7 << 26, 479 << 21
// and 483 << 21 (same root). The last two are > 10^9.
```

```
typedef vector<ll> vl;
void ntt(vl &a) {
    int n = sz(a), L = 31 - __builtin_clz(n);
    static vl rt(2, 1);
    for (static int k = 2, s = 2; k < n; k *= 2, s++) {
        rt.resize(n);
        ll z[] = {1, modpow(root, mod >> s)};
        rep(i,k,2*k) rt[i] = rt[i / 2] * z[i & 1] % mod;
    }
    vi rev(n);
    rep(i,0,n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
    rep(i,0,n) if (i < rev[i]) swap(a[i], a[rev[i]]);
    for (int k = 1; k < n; k *= 2)
        for (int i = 0; i < n; i += 2 * k) rep(j,0,k) {
            ll z = rt[j + k] * a[i + j + k] % mod, &ai = a[i + j];
            a[i + j + k] = ai - z + (z > ai ? mod : 0);
            ai += (ai + z >= mod ? z - mod : z);
        }
}

vl conv(const vl &a, const vl &b) {
    if (a.empty() || b.empty()) return {};
    int s = sz(a) + sz(b) - 1, B = 32 - __builtin_clz(s), n = 1
        << B;
    int inv = modpow(n, mod - 2);
    vl L(a), R(b), out(n);
    L.resize(n), R.resize(n);
    ntt(L), ntt(R);
    rep(i,0,n) out[-i & (n - 1)] = (ll)L[i] * R[i] % mod * inv %
        mod;
    ntt(out);
    return {out.begin(), out.begin() + s};
}
```

### FastSubsetTransform.h

**Description:** Transform to a basis with fast convolutions of the form  $c[z] = \sum_{z=x \oplus y} a[x] \cdot b[y]$ , where  $\oplus$  is one of AND, OR, XOR. The size of  $a$  must be a power of two.

**Time:**  $\mathcal{O}(N \log N)$

464cf3, 16 lines

```
void FST(vi& a, bool inv) {
    for (int n = sz(a), step = 1; step < n; step *= 2) {
        for (int i = 0; i < n; i += 2 * step) rep(j,i,i+step) {
            int &u = a[j], &v = a[j + step]; tie(u, v) =
                inv ? pii(v - u, u) : pii(v, u + v); // AND
                inv ? pii(v, u - v) : pii(u + v, u); // OR
                pii(u + v, u - v); // XOR
        }
    }
    if (inv) for (int& x : a) x /= sz(a); // XOR only
}

vi conv(vi a, vi b) {
    FST(a, 0); FST(b, 0);
    rep(i,0,sz(a)) a[i] *= b[i];
    FST(a, 1); return a;
}
```



## Number theory (5)

### 5.1 Modular arithmetic

ModularArithmetic.h

**Description:** Operators for modular arithmetic. You need to set mod to some number first and then you can use the structure.

"euclid.h"	35bfea, 18 lines
<pre>const ll mod = 17; // change to something else struct Mod {     ll x;     Mod(ll xx) : x(xx) {}     Mod operator+(Mod b) { return Mod((x + b.x) % mod); }     Mod operator-(Mod b) { return Mod((x - b.x + mod) % mod); }     Mod operator*(Mod b) { return Mod((x * b.x) % mod); }     Mod operator/(Mod b) { return *this * invert(b); }     Mod invert(Mod a) {         ll x, y, g = euclid(a.x, mod, x, y);         assert(g == 1); return Mod((x + mod) % mod);     }     Mod operator^(ll e) {         if (!e) return Mod(1);         Mod r = *this ^ (e / 2); r = r * r;         return e&amp;1 ? *this * r : r;     } };</pre>	

ModLog.h

**Description:** Returns the smallest  $x > 0$  s.t.  $a^x = b \pmod m$ , or  $-1$  if no such  $x$  exists. `modLog(a,1,m)` can be used to calculate the order of  $a$ .

<b>Time:</b> $\mathcal{O}(\sqrt{m})$	c040b8, 11 lines
<pre>ll modLog(ll a, ll b, ll m) {     ll n = (ll) sqrt(m) + 1, e = 1, f = 1, j = 1;     unordered_map&lt;ll, ll&gt; A;     while (j &lt;= n &amp;&amp; (e = f = e * a % m) != b % m)         A[e * b % m] = j++;     if (e == b % m) return j;     if (__gcd(m, e) == __gcd(m, b))         rep(i,2,n+2) if (A.count(e = e * f % m))             return n * i - A[e];     return -1; }</pre>	

ModSqrt.h

**Description:** Tonelli-Shanks algorithm for modular square roots. Finds  $x$  s.t.  $x^2 = a \pmod p$  ( $-x$  gives the other solution).

**Time:**  $\mathcal{O}(\log^2 p)$  worst case,  $\mathcal{O}(\log p)$  for most  $p$

"ModPow.h"	19a793, 24 lines
<pre>ll sqrt(ll a, ll p) {     a %= p; if (a &lt; 0) a += p;     if (a == 0) return 0;     assert(modpow(a, (p-1)/2, p) == 1); // else no solution     if (p % 4 == 3) return modpow(a, (p+1)/4, p);     // a^(n+3)/8 or 2^(n+3)/8 * 2^(n-1)/4 works if p % 8 == 5     ll s = p - 1, n = 2;     int r = 0, m;     while (s % 2 == 0)         ++r, s /= 2;     while (modpow(n, (p - 1) / 2, p) != p - 1) ++n;     ll x = modpow(a, (s + 1) / 2, p);     ll b = modpow(a, s, p), g = modpow(n, s, p);     for (; r = m) {         ll t = b;         for (m = 0; m &lt; r &amp;&amp; t != 1; ++m)             t = t * t % p;         if (m == 0) return x;         ll gs = modpow(g, 1LL &lt;&lt; (r - m - 1), p);</pre>	

<pre>        g = gs * gs % p;         x = x * gs % p;         b = b * g % p;     } }</pre>	
--	--

### 5.2 Primality

FastEratosthenes.h

**Description:** Prime sieve for generating all primes smaller than LIM.

<b>Time:</b> LIM=1e9 $\approx$ 1.5s	6b2912, 20 lines
<pre>const int LIM = 1e6; bitset&lt;LIM&gt; isPrime; vi eratosthenes() {     const int S = (int)round(sqrt(LIM)), R = LIM / 2;     vi pr = {2}, sieve(S+1); pr.reserve((int)(LIM/log(LIM)*1.1));     vector&lt;pii&gt; cp;     for (int i = 3; i &lt;= S; i += 2) if (!sieve[i]) {         cp.push_back({i, i * i / 2});         for (int j = i * i; j &lt;= S; j += 2 * i) sieve[j] = 1;     }     for (int L = 1; L &lt;= R; L += S) {         array&lt;bool, S&gt; block{};         for (auto &amp;[p, idx] : cp)             for (int i=idx; i &lt; S+L; idx = (i+=p)) block[i-L] = 1;         rep(i,0,min(S, R - L))             if (!block[i]) pr.push_back((L + i) * 2 + 1);     }     for (int i : pr) isPrime[i] = 1;     return pr; }</pre>	

MillerRabin.h

**Description:** Deterministic Miller-Rabin primality test. Guaranteed to work for numbers up to  $7 \cdot 10^{18}$ ; for larger numbers, use Python and extend A randomly.

**Time:** 7 times the complexity of  $a^b \pmod c$ .

"ModMulLL.h"	60dcd1, 12 lines
<pre>bool isPrime(ull n) {     if (n &lt; 2    n % 6 % 4 != 1) return (n   1) == 3;     ull A[] = {2, 325, 9375, 28178, 450775, 9780504, 1795265022},         s = __builtin_ctzll(n-1), d = n &gt;&gt; s;     for (ull a : A) { // ^ count trailing zeroes         ull p = modpow(a%n, d, n), i = s;         while (p != 1 &amp;&amp; p != n - 1 &amp;&amp; a % n &amp;&amp; i--)             p = modmul(p, p, n);         if (p != n-1 &amp;&amp; i != s) return 0;     }     return 1; }</pre>	

Factor.h

**Description:** Pollard-rho randomized factorization algorithm. Returns prime factors of a number, in arbitrary order (e.g. 2299 -> {11, 19, 11}).

**Time:**  $\mathcal{O}\left(n^{1/4}\right)$ , less for numbers with small factors.

"ModMulLL.h", "MillerRabin.h"	a33cf6, 18 lines
<pre>ull pollard(ull n) {     auto f = [n](ull x) { return modmul(x, x, n) + 1; };     ull x = 0, y = 0, t = 30, prd = 2, i = 1, q;     while (t++ % 40    __gcd(prd, n) == 1) {         if (x == y) x = ++i, y = f(x);         if ((q = modmul(prd, max(x,y) - min(x,y), n))) prd = q;         x = f(x), y = f(f(y));     }     return __gcd(prd, n); } vector&lt;ull&gt; factor(ull n) {</pre>	

<pre>    if (n == 1) return {};</pre>	
<pre>    if (isPrime(n)) return {n};</pre>	
<pre>    ull x = pollard(n);</pre>	
<pre>    auto l = factor(x), r = factor(n / x);</pre>	
<pre>    l.insert(l.end(), all(r));</pre>	
<pre>    return l;</pre>	
<pre>}</pre>	

### 5.3 Divisibility

gcdFast.h

**Description:** Faster gcd

<b>Time:</b> $\mathcal{O}(\log N)$	737641, 16 lines
<pre>int gcd(int u, int v) {     int shift;     if (u == 0) return v;     if (v == 0) return u;     shift = __builtin_ctz(u   v);     u &gt;&gt;= __builtin_ctz(u);     do{         int m;         v &gt;&gt;= __builtin_ctz(v);         v -= u;         m = v &gt;&gt; 31;         u += v &amp; m;         v = (v + m) ^ m;     } while (v != 0);     return u &lt;&lt; shift; }</pre>	

euclid.h

**Description:** Finds two integers  $x$  and  $y$ , such that  $ax + by = \gcd(a, b)$ . If you just need gcd, use the built in `__gcd` instead. If  $a$  and  $b$  are coprime, then  $x$  is the inverse of  $a \pmod b$ .

```
ll euclid(ll a, ll b, ll &x, ll &y) {
    if (!b) return x = 1, y = 0, a;
    ll d = euclid(b, a % b, y, x);
    return y -= a/b * x, d;
}
```

CRT.h

**Description:** Chinese Remainder Theorem.

`crt(a, m, b, n)` computes  $x$  such that  $x \equiv a \pmod m, x \equiv b \pmod n$ . If  $|a| < m$  and  $|b| < n$ ,  $x$  will obey  $0 \leq x < \text{lcm}(m, n)$ . Assumes  $mn < 2^{62}$ .

**Time:**  $\log(n)$

"euclid.h"	04d93a, 7 lines
<pre>ll crt(ll a, ll m, ll b, ll n) {     if (n &gt; m) swap(a, b), swap(m, n);     ll x, y, g = euclid(m, n, x, y);     assert((a - b) % g == 0); // else no solution     x = (b - a) % n * x % n / g * m + a;     return x &lt; 0 ? x + m*n/g : x; }</pre>	

#### 5.3.1 Bézout's identity

For  $a \neq 0, b \neq 0$ , then  $d = \gcd(a, b)$  is the smallest positive integer

for which there are integer solutions to

$$ax + by = d$$

If  $(x, y)$  is one solution, then all solutions are given by

$$\left(x + \frac{kb}{\gcd(a,b)}, y - \frac{ka}{\gcd(a,b)}\right), \quad k \in \mathbb{Z}$$

phiFunction.h

**Description:** *Euler's*  $\phi$  function is defined as  $\phi(n) := \#$  of positive integers  $\leq n$  that are coprime with  $n$ .  $\phi(1) = 1$ ,  $p$  prime  $\Rightarrow \phi(p^k) = (p - 1)p^{k-1}$ ,  $m, n$  coprime  $\Rightarrow \phi(mn) = \phi(m)\phi(n)$ . If  $n = p_1^{k_1}p_2^{k_2}...p_r^{k_r}$  then  $\phi(n) = (p_1 - 1)p_1^{k_1-1}...(p_r - 1)p_r^{k_r-1}$ .  $\phi(n) = n \cdot \prod_{p|n}(1 - 1/p)$ .  $\sum_{d|n} \phi(d) = n$ ,  $\sum_{1 \leq k \leq n, \gcd(k,n)=1} k = n\phi(n)/2, n > 1$   
**Euler's thm:**  $a, n$  coprime  $\Rightarrow a^{\phi(n)} \equiv 1 \pmod n$ .  
**Fermat's little thm:**  $p$  prime  $\Rightarrow a^{p-1} \equiv 1 \pmod p \ \forall a$ .

```
const int LIM = 5000000;
int phi[LIM];

void calculatePhi() {
    rep(i,0,LIM) phi[i] = i&1 ? i : i/2;
    for (int i = 3; i < LIM; i += 2) if(phi[i] == i)
        for (int j = i; j < LIM; j += i) phi[j] -= phi[j] / i;
}
```

5.4 Pythagorean Triples

The Pythagorean triples are uniquely generated by

$a = k \cdot (m^2 - n^2), \ b = k \cdot (2mn), \ c = k \cdot (m^2 + n^2),$

with  $m > n > 0, k > 0, m \perp n$ , and either  $m$  or  $n$  even.

5.5 Primes

$p = 962592769$  is such that  $2^{21} \mid p - 1$ , which may be useful. For hashing use 970592641 (31-bit number), 31443539979727 (45-bit), 3006703054056749 (52-bit). There are 78498 primes less than 1 000 000.

Primitive roots exist modulo any prime power  $p^a$ , except for  $p = 2, a > 2$ , and there are  $\phi(\phi(p^a))$  many. For  $p = 2, a > 2$ , the group  $\mathbb{Z}_{2^a}^\times$  is instead isomorphic to  $\mathbb{Z}_2 \times \mathbb{Z}_{2^{a-2}}$ .

5.6 Estimates

$\sum_{d|n} d = O(n \log \log n)$ .

The number of divisors of  $n$  is at most around 100 for  $n < 5e4$ , 500 for  $n < 1e7$ , 2000 for  $n < 1e10$ , 200 000 for  $n < 1e19$ .

5.7 Mobius Function

$$\mu(n) = \begin{cases} 0 & n \text{ is not square free} \\ 1 & n \text{ has even number of prime factors} \\ -1 & n \text{ has odd number of prime factors} \end{cases}$$

Mobius Inversion:

$$g(n) = \sum_{d|n} f(d) \Leftrightarrow f(n) = \sum_{d|n} \mu(d)g(n/d)$$

Other useful formulas/forms:

$\sum_{d|n} \mu(d) = [n = 1]$  (very useful)

$g(n) = \sum_{n|d} f(d) \Leftrightarrow f(n) = \sum_{n|d} \mu(d/n)g(d)$

$g(n) = \sum_{1 \leq m \leq n} f(\lfloor \frac{n}{m} \rfloor) \Leftrightarrow f(n) = \sum_{1 \leq m \leq n} \mu(m)g(\lfloor \frac{n}{m} \rfloor)$

Combinatorial (6)

6.1 Permutations

6.1.1 Factorial

$n$	1	2	3	4	5	6	7	8	9	10
$n!$	1	2	6	24	120	720	5040	40320	362880	3628800
$n$	11	12	13	14	15	16	17			
$n!$	4.0e7	4.8e8	6.2e9	8.7e10	1.3e12	2.1e13	3.6e14			
$n$	20	25	30	40	50	100	150	171		
$n!$	2e18	2e25	3e32	8e47	3e64	9e157	6e262	>DBL.MAX		

6.1.2 Cycles

Let  $g_S(n)$  be the number of  $n$ -permutations whose cycle lengths all belong to the set  $S$ . Then

$$\sum_{n=0}^{\infty} g_S(n) \frac{x^n}{n!} = \exp \left( \sum_{n \in S} \frac{x^n}{n} \right)$$

6.1.3 Derangements

Permutations of a set such that none of the elements appear in their original position.

$$D(n) = (n - 1)(D(n - 1) + D(n - 2)) = nD(n - 1) + (-1)^n = \left\lfloor \frac{n!}{e} \right\rfloor$$

6.2 Partitions and subsets

6.2.1 Partition function

Number of ways of writing  $n$  as a sum of positive integers, disregarding the order of the summands.

$$p(0) = 1, \ p(n) = \sum_{k \in \mathbb{Z} \setminus \{0\}} (-1)^{k+1} p(n - k(3k - 1)/2)$$

$$p(n) \sim 0.145/n \cdot \exp(2.56\sqrt{n})$$

$n$	0	1	2	3	4	5	6	7	8	9	20	50	100
$p(n)$	1	1	2	3	5	7	11	15	22	30	627	~2e5	~2e8

6.2.2 Lucas' Theorem

Let  $n, m$  be non-negative integers and  $p$  a prime. Write  $n = n_kp^k + ... + n_1p + n_0$  and  $m = m_kp^k + ... + m_1p + m_0$ . Then  $\binom{n}{m} \equiv \prod_{i=0}^k \binom{n_i}{m_i} \pmod p$ .

6.2.3 Binomials

multinomial.h

**Description:** Computes  $\binom{k_1 + \dots + k_n}{k_1, k_2, \dots, k_n} = \frac{(\sum k_i)!}{k_1!k_2!...k_n!}$ .a0a312, 6 lines

```
ll multinomial(vi& v) {
    ll c = 1, m = v.empty() ? 1 : v[0];
    rep(i,1,sz(v)) rep(j,0,v[i])
        c = c * ++m / (j+1);
    return c;
}
```

6.3 General purpose numbers

6.3.1 Stirling numbers of the first kind

Number of permutations on  $n$  items with  $k$  cycles.

$$c(n, k) = c(n - 1, k - 1) + (n - 1)c(n - 1, k), \ c(0, 0) = 1$$
$$\sum_{k=0}^n c(n, k)x^k = x(x + 1) \dots (x + n - 1)$$

$$c(8, k) = 8, 0, 5040, 13068, 13132, 6769, 1960, 322, 28, 1$$
$$c(n, 2) = 0, 0, 1, 3, 11, 50, 274, 1764, 13068, 109584, \dots$$

6.3.2 Eulerian numbers

Number of permutations  $\pi \in S_n$  in which exactly  $k$  elements are greater than the previous element.  $k$   $j$ :s s.t.  $\pi(j) > \pi(j + 1)$ ,  $k + 1$   $j$ :s s.t.  $\pi(j) \geq j$ ,  $k$   $j$ :s s.t.  $\pi(j) > j$ .

$$E(n, k) = (n - k)E(n - 1, k - 1) + (k + 1)E(n - 1, k)$$

$$E(n, 0) = E(n, n - 1) = 1$$

$$E(n, k) = \sum_{j=0}^k (-1)^j \binom{n+1}{j} (k+1-j)^n$$

6.3.3 Stirling numbers of the second kind

Partitions of  $n$  distinct elements into exactly  $k$  groups.

$$S(n, k) = S(n - 1, k - 1) + kS(n - 1, k)$$

$$S(n, 1) = S(n, n) = 1$$

$$S(n, k) = \frac{1}{k!} \sum_{j=0}^k (-1)^{k-j} \binom{k}{j} j^n$$

6.3.4 Bell numbers

Total number of partitions of  $n$  distinct elements.  $B(n) = 1, 1, 2, 5, 15, 52, 203, 877, 4140, 21147, \dots$ . For  $p$  prime,

$$B(p^m + n) \equiv mB(n) + B(n + 1) \pmod p$$

6.3.5 Labeled unrooted trees

# on  $n$  vertices:  $n^{n-2}$   
# on  $k$  existing trees of size  $n_i$ :  $n_1n_2 \dots n_k n^{k-2}$   
# with degrees  $d_i$ :  $(n - 2)! / ((d_1 - 1)! \dots (d_n - 1)!)$

### 6.3.6 Catalan numbers

$$C_n = \frac{1}{n+1} \binom{2n}{n} = \binom{2n}{n} - \binom{2n}{n+1} = \frac{(2n)!}{(n+1)!n!}$$
$$C_0 = 1, \; C_{n+1} = \frac{2(2n+1)}{n+2} C_n, \; C_{n+1} = \sum C_i C_{n-i}$$
$$C_n = 1, 1, 2, 5, 14, 42, 132, 429, 1430, 4862, 16796, 58786, \dots$$

- sub-diagonal monotone paths in an  $n \times n$  grid.
- strings with  $n$  pairs of parenthesis, correctly nested.
- binary trees with with  $n + 1$  leaves (0 or 2 children).
- ordered trees with  $n + 1$  vertices.
- ways a convex polygon with  $n + 2$  sides can be cut into triangles by connecting vertices with straight lines.
- permutations of  $[n]$  with no 3-term increasing subseq.

## Graph (7)

### 7.1 Fundamentals

BellmanFord.h

**Description:** Calculates shortest paths from  $s$  in a graph that might have negative edge weights. Unreachable nodes get  $\text{dist} = \text{inf}$ ; nodes reachable through negative-weight cycles get  $\text{dist} = -\text{inf}$ . Assumes  $V^2 \max |w_i| < \sim 2^{63}$ .  
**Time:**  $\mathcal{O}(VE)$

```
const ll inf = LLONG_MAX;
struct Ed { int a, b, w, s() { return a < b ? a : -a; }};
struct Node { ll dist = inf; int prev = -1; };

void bellmanFord(vector<Node>& nodes, vector<Ed>& eds, int s) {
    nodes[s].dist = 0;
    sort(all(eds), [](Ed a, Ed b) { return a.s() < b.s(); });

    int lim = sz(nodes) / 2 + 2; // /3+100 with shuffled vertices
    rep(i,0,lim) for (Ed ed : eds) {
        Node cur = nodes[ed.a], &dest = nodes[ed.b];
        if (abs(cur.dist) == inf) continue;
        ll d = cur.dist + ed.w;
        if (d < dest.dist) {
            dest.prev = ed.a;
            dest.dist = (i < lim-1 ? d : -inf);
        }
    }
    rep(i,0,lim) for (Ed e : eds) {
        if (nodes[e.a].dist == -inf)
            nodes[e.b].dist = -inf;
    }
}
```

FloydWarshall.h

**Description:** Calculates all-pairs shortest path in a directed graph that might have negative edge weights. Input is an distance matrix  $m$ , where  $m[i][j] = \text{inf}$  if  $i$  and  $j$  are not adjacent. As output,  $m[i][j]$  is set to the shortest distance between  $i$  and  $j$ ,  $\text{inf}$  if no path, or  $-\text{inf}$  if the path goes through a negative-weight cycle.  
**Time:**  $\mathcal{O}(N^3)$

```
const ll inf = 1LL << 62;
void floydWarshall(vector<vector<ll>>& m) {
    int n = sz(m);
    rep(i,0,n) m[i][i] = min(m[i][i], 0LL);
    rep(k,0,n) rep(i,0,n) rep(j,0,n)
```

```
    if (m[i][k] != inf && m[k][j] != inf) {
        auto newDist = max(m[i][k] + m[k][j], -inf);
        m[i][j] = min(m[i][j], newDist);
    }
    rep(k,0,n) if (m[k][k] < 0) rep(i,0,n) rep(j,0,n)
        if (m[i][k] != inf && m[k][j] != inf) m[i][j] = -inf;
}
```

TopoSort.h

**Description:** Topological sorting. Given is an oriented graph. Output is an ordering of vertices, such that there are edges only from left to right. If there are cycles, the returned list will have size smaller than  $n$  – nodes reachable from cycles will not be returned.  
**Time:**  $\mathcal{O}(|V| + |E|)$

```
vi topoSort(const vector<vi>& gr) {
    vi indeg(sz(gr)), ret;
    for (auto& li : gr) for (int x : li) indeg[x]++;
    queue<int> q; // use priority-queue for lexic. largest ans.
    rep(i,0,sz(gr)) if (indeg[i] == 0) q.push(i);
    while (!q.empty()) {
        int i = q.front(); // top() for priority queue
        ret.push_back(i);
        q.pop();
        for (int x : gr[i])
            if (--indeg[x] == 0) q.push(x);
    }
    return ret;
}
```

### 7.2 Network flow

PushRelabel.h

**Description:** Push-relabel using the highest label selection rule and the gap heuristic. Quite fast in practice. To obtain the actual flow, look at positive values only.  
**Time:**  $\mathcal{O}(V^2\sqrt{E})$

```
struct PushRelabel {
    struct Edge {
        int dest, back;
        ll f, c;
    };
    vector<vector<Edge>> g;
    vector<ll> ec;
    vector<Edge*> cur;
    vector<vi> hs; vi H;
    PushRelabel(int n) : g(n), ec(n), cur(n), hs(2*n), H(n) {}

    void addEdge(int s, int t, ll cap, ll rcap=0) {
        if (s == t) return;
        g[s].push_back({t, sz(g[t]), 0, cap});
        g[t].push_back({s, sz(g[s])-1, 0, rcap});
    }

    void addFlow(Edge& e, ll f) {
        Edge &back = g[e.dest][e.back];
        if (!ec[e.dest] && f) hs[H[e.dest]].push_back(e.dest);
        e.f += f; e.c -= f; ec[e.dest] += f;
        back.f -= f; back.c += f; ec[back.dest] -= f;
    }

    ll calc(int s, int t) {
        int v = sz(g); H[s] = v; ec[t] = 1;
        vi co(2*v); co[0] = v-1;
        rep(i,0,v) cur[i] = g[i].data();
        for (Edge& e : g[s]) addFlow(e, e.c);

        for (int hi = 0;;) {
            while (hs[hi].empty()) if (!hi--) return -ec[s];
```

```
int u = hs[hi].back(); hs[hi].pop_back();
while (ec[u] > 0) // discharge u
    if (cur[u] == g[u].data() + sz(g[u])) {
        H[u] = 1e9;
        for (Edge& e : g[u]) if (e.c && H[u] > H[e.dest]+1)
            H[u] = H[e.dest]+1, cur[u] = &e;
        if (++co[H[u]], !--co[hi] && hi < v)
            rep(i,0,v) if (hi < H[i] && H[i] < v)
                --co[H[i]], H[i] = v + 1;
        hi = H[u];
    } else if (cur[u]->c && H[u] == H[cur[u]->dest]+1)
        addFlow(*cur[u], min(ec[u], cur[u]->c));
    else ++cur[u];
}
}
bool leftOfMinCut(int a) { return H[a] >= sz(g); }
```

MinCostMaxFlow.h

**Description:** Min-cost max-flow.  $\text{cap}[i][j] \neq \text{cap}[j][i]$  is allowed; double edges are not. If costs can be negative, call  $\text{setpi}$  before  $\text{maxflow}$ , but note that negative cost cycles are not supported. To obtain the actual flow, look at positive values only.  
**Time:** Approximately  $\mathcal{O}(E^2)$

```
#include <bits/extc++.h>

const ll INF = numeric_limits<ll>::max() / 4;
typedef vector<ll> VL;

struct MCMF {
    int N;
    vector<vi> ed, red;
    vector<VL> cap, flow, cost;
    vi seen;
    VL dist, pi;
    vector<pii> par;

    MCMF(int N) :
        N(N), ed(N), red(N), cap(N, VL(N)), flow(cap), cost(cap),
        seen(N), dist(N), pi(N), par(N) {}

    void addEdge(int from, int to, ll cap, ll cost) {
        this->cap[from][to] = cap;
        this->cost[from][to] = cost;
        ed[from].push_back(to);
        red[to].push_back(from);
    }

    void path(int s) {
        fill(all(seen), 0);
        fill(all(dist), INF);
        dist[s] = 0; ll di;

        __gnu_pbds::priority_queue<pair<ll, int>> q;
        vector<decltype(q)::point_iterator> its(N);
        q.push({0, s});

        auto relax = [&](int i, ll cap, ll cost, int dir) {
            ll val = di - pi[i] + cost;
            if (cap && val < dist[i]) {
                dist[i] = val;
                par[i] = {s, dir};
                if (its[i] == q.end()) its[i] = q.push({-dist[i], i});
                else q.modify(its[i], {-dist[i], i});
            }
        };

        while (!q.empty()) {
```

```
s = q.top().second; q.pop();
seen[s] = 1; di = dist[s] + pi[s];
for (int i : ed[s]) if (!seen[i])
    relax(i, cap[s][i] - flow[s][i], cost[s][i], 1);
for (int i : red[s]) if (!seen[i])
    relax(i, flow[i][s], -cost[i][s], 0);
}
rep(i,0,N) pi[i] = min(pi[i] + dist[i], INF);
}

pair<ll, ll> maxflow(int s, int t) {
    ll totflow = 0, totcost = 0;
    while (path(s), seen[t]) {
        ll fl = INF;
        for (int p,r,x = t; tie(p,r) = par[x], x != s; x = p)
            fl = min(fl, r ? cap[p][x] - flow[p][x] : flow[x][p]);
        totflow += fl;
        for (int p,r,x = t; tie(p,r) = par[x], x != s; x = p)
            if (r) flow[p][x] += fl;
            else flow[x][p] -= fl;
    }
    rep(i,0,N) rep(j,0,N) totcost += cost[i][j] * flow[i][j];
    return {totflow, totcost};
}

// If some costs can be negative, call this before maxflow:
void setpi(int s) { // (otherwise, leave this out)
    fill(all(pi), INF); pi[s] = 0;
    int it = N, ch = 1; ll v;
    while (ch-- && it--)
        rep(i,0,N) if (pi[i] != INF)
            for (int to : ed[i]) if (cap[i][to])
                if ((v = pi[i] + cost[i][to]) < pi[to])
                    pi[to] = v, ch = 1;
    assert(it >= 0); // negative cost cycle
}
};
```

EdmondsKarp.h

**Description:** Flow algorithm with guaranteed complexity  $O(VE^2)$ . To get edge flow values, compare capacities before and after, and take the positive values only.

482fe0, 35 lines

```
template<class T> T edmondsKarp(vector<unordered_map<int, T>&&
    graph, int source, int sink) {
    assert(source != sink);
    T flow = 0;
    vi par(sz(graph)), q = par;

    for (;;) {
        fill(all(par), -1);
        par[source] = 0;
        int ptr = 1;
        q[0] = source;

        rep(i,0,ptr) {
            int x = q[i];
            for (auto e : graph[x]) {
                if (par[e.first] == -1 && e.second > 0) {
                    par[e.first] = x;
                    q[ptr++] = e.first;
                    if (e.first == sink) goto out;
                }
            }
        }
        return flow;
    out:
        T inc = numeric_limits<T>::max();
        for (int y = sink; y != source; y = par[y])
```

```
        inc = min(inc, graph[par[y]][y]);

        flow += inc;
        for (int y = sink; y != source; y = par[y]) {
            int p = par[y];
            if ((graph[p][y] -= inc) <= 0) graph[p].erase(y);
            graph[y][p] += inc;
        }
    }
}
```

MinCut.h

**Description:** After running max-flow, the left side of a min-cut from  $s$  to  $t$  is given by all vertices reachable from  $s$ , only traversing edges with positive residual capacity.

GlobalMinCut.h

**Description:** Find a global minimum cut in an undirected graph, as represented by an adjacency matrix.

**Time:**  $\mathcal{O}(V^3)$

8b0e19, 21 lines

```
pair<int, vi> globalMinCut(vector<vi> mat) {
    pair<int, vi> best = {INT_MAX, {}};
    int n = sz(mat);
    vector<vi> co(n);
    rep(i,0,n) co[i] = {i};
    rep(ph,1,n) {
        vi w = mat[0];
        size_t s = 0, t = 0;
        rep(it,0,n-ph) { //  $O(V^2) \rightarrow O(E \log V)$  with prio. queue
            w[t] = INT_MIN;
            s = t, t = max_element(all(w)) - w.begin();
            rep(i,0,n) w[i] += mat[t][i];
        }
        best = min(best, {w[t] - mat[t][t], co[t]});
        co[s].insert(co[s].end(), all(co[t]));
        rep(i,0,n) mat[s][i] += mat[t][i];
        rep(i,0,n) mat[i][s] = mat[s][i];
        mat[0][t] = INT_MIN;
    }
    return best;
}
```

GomoryHu.h

**Description:** Given a list of edges representing an undirected flow graph, returns edges of the Gomory-Hu tree. The max flow between any pair of vertices is given by minimum edge weight along the Gomory-Hu tree path.

**Time:**  $\mathcal{O}(V)$  Flow Computations

"PushRelabel.h"

0418b3, 13 lines

```
typedef array<ll, 3> Edge;
vector<Edge> gomoryHu(int N, vector<Edge> ed) {
    vector<Edge> tree;
    vi par(N);
    rep(i,1,N) {
        PushRelabel D(N); // Dinic also works
        for (Edge t : ed) D.addEdge(t[0], t[1], t[2], t[2]);
        tree.push_back({i, par[i], D.calc(i, par[i])});
        rep(j,i+1,N)
            if (par[j] == par[i] && D.leftOfMinCut(j)) par[j] = i;
    }
    return tree;
}
```

7.3 Matching

hopcroftKarp.h

**Description:** Fast bipartite matching algorithm. Graph  $g$  should be a list of neighbors of the left partition, and  $btoa$  should be a vector full of -1's of the same size as the right partition. Returns the size of the matching.  $btoa[i]$  will be the match for vertex  $i$  on the right side, or  $-1$  if it's not matched.

**Usage:** vi btoa(m, -1); hopcroftKarp(g, btoa);

**Time:**  $\mathcal{O}(\sqrt{VE})$

f612e4, 42 lines

```
bool dfs(int a, int L, vector<vi>& g, vi& btoa, vi& A, vi& B) {
    if (A[a] != L) return 0;
    A[a] = -1;
    for (int b : g[a]) if (B[b] == L + 1) {
        B[b] = 0;
        if (btoa[b] == -1 || dfs(btoa[b], L + 1, g, btoa, A, B))
            return btoa[b] = a, 1;
    }
    return 0;
}

int hopcroftKarp(vector<vi>& g, vi& btoa) {
    int res = 0;
    vi A(g.size()), B(btoa.size()), cur, next;
    for (;;) {
        fill(all(A), 0);
        fill(all(B), 0);
        cur.clear();
        for (int a : btoa) if (a != -1) A[a] = -1;
        rep(a,0,sz(g)) if (A[a] == 0) cur.push_back(a);
        for (int lay = 1;; lay++) {
            bool islast = 0;
            next.clear();
            for (int a : cur) for (int b : g[a]) {
                if (btoa[b] == -1) {
                    B[b] = lay;
                    islast = 1;
                }
                else if (btoa[b] != a && !B[b]) {
                    B[b] = lay;
                    next.push_back(btoa[b]);
                }
            }
            if (islast) break;
            if (next.empty()) return res;
            for (int a : next) A[a] = lay;
            cur.swap(next);
        }
        rep(a,0,sz(g))
            res += dfs(a, 0, g, btoa, A, B);
    }
}
```

DFSMatching.h

**Description:** Simple bipartite matching algorithm. Graph  $g$  should be a list of neighbors of the left partition, and  $btoa$  should be a vector full of -1's of the same size as the right partition. Returns the size of the matching.  $btoa[i]$  will be the match for vertex  $i$  on the right side, or  $-1$  if it's not matched.

**Usage:** vi btoa(m, -1); dfsMatching(g, btoa);

**Time:**  $\mathcal{O}(VE)$

522b98, 22 lines

```
bool find(int j, vector<vi>& g, vi& btoa, vi& vis) {
    if (btoa[j] == -1) return 1;
    vis[j] = 1; int di = btoa[j];
    for (int e : g[di])
        if (!vis[e] && find(e, g, btoa, vis)) {
            btoa[e] = di;
            return 1;
        }
    return 0;
}
```

```
}
int dfsMatching(vector<vi>& g, vi& btoa) {
    vi vis;
    rep(i,0,sz(g)) {
        vis.assign(sz(btoa), 0);
        for (int j : g[i])
            if (find(j, g, btoa, vis)) {
                btoa[j] = i;
                break;
            }
    }
    return sz(btoa) - (int)count(all(btoa), -1);
}
```

### MinimumVertexCover.h

**Description:** Finds a minimum vertex cover in a bipartite graph. The size is the same as the size of a maximum matching, and the complement is a maximum independent set.

"DFSMatching.h"da4196, 20 lines

```
vi cover(vector<vi>& g, int n, int m) {
    vi match(m, -1);
    int res = dfsMatching(g, match);
    vector<bool> lfound(n, true), seen(m);
    for (int it : match) if (it != -1) lfound[it] = false;
    vi g, cover;
    rep(i,0,n) if (lfound[i]) q.push_back(i);
    while (!q.empty()) {
        int i = q.back(); q.pop_back();
        lfound[i] = 1;
        for (int e : g[i]) if (!seen[e] && match[e] != -1) {
            seen[e] = true;
            q.push_back(match[e]);
        }
    }
    rep(i,0,n) if (!lfound[i]) cover.push_back(i);
    rep(i,0,m) if (seen[i]) cover.push_back(n+i);
    assert(sz(cover) == res);
    return cover;
}
```

### WeightedMatching.h

**Description:** Given a weighted bipartite graph, matches every node on the left with a node on the right such that no nodes are in two matchings and the sum of the edge weights is minimal. Takes cost[N][M], where cost[i][j] = cost for L[i] to be matched with R[j] and returns (min cost, match), where L[i] is matched with R[match[i]]. Negate costs for max cost. Requires  $N \leq M$ .  
**Time:**  $\mathcal{O}(N^2M)$

1e0fe9, 31 lines

```
pair<int, vi> hungarian(const vector<vi> &a) {
    if (a.empty()) return {0, {}};
    int n = sz(a) + 1, m = sz(a[0]) + 1;
    vi u(n), v(m), p(m), ans(n - 1);
    rep(i,1,n) {
        p[0] = i;
        int j0 = 0; // add "dummy" worker 0
        vi dist(m, INT_MAX), pre(m, -1);
        vector<bool> done(m + 1);
        do { // dijkstra
            done[j0] = true;
            int i0 = p[j0], j1, delta = INT_MAX;
            rep(j,1,m) if (!done[j]) {
                auto cur = a[i0 - 1][j - 1] - u[i0] - v[j];
                if (cur < dist[j]) dist[j] = cur, pre[j] = j0;
                if (dist[j] < delta) delta = dist[j], j1 = j;
            }
            rep(j,0,m) {
                if (done[j]) u[p[j]] += delta, v[j] -= delta;
                else dist[j] -= delta;
            }
        }
    }
```

```
    j0 = j1;
    } while (p[j0]);
    while (j0) { // update alternating path
        int j1 = pre[j0];
        p[j0] = p[j1], j0 = j1;
    }
    rep(j,1,m) if (p[j]) ans[p[j] - 1] = j - 1;
    return {-v[0], ans}; // min cost
}
```

### GeneralMatching.h

**Description:** Matching for general graphs. Fails with probability  $N/mod$ .  
**Time:**  $\mathcal{O}(N^3)$

"../numerical/MatrixInverse-mod.h"cb1912, 40 lines

```
vector<pii> generalMatching(int N, vector<pii>& ed) {
    vector<vector<ll>> mat(N, vector<ll>(N)), A;
    for (pii pa : ed) {
        int a = pa.first, b = pa.second, r = rand() % mod;
        mat[a][b] = r, mat[b][a] = (mod - r) % mod;
    }

    int r = matInv(A = mat), M = 2*N - r, fi, fj;
    assert(r % 2 == 0);

    if (M != N) do {
        mat.resize(M, vector<ll>(M));
        rep(i,0,N) {
            mat[i].resize(M);
            rep(j,N,M) {
                int r = rand() % mod;
                mat[i][j] = r, mat[j][i] = (mod - r) % mod;
            }
        }
    } while (matInv(A = mat) != M);

    vi has(M, 1); vector<pii> ret;
    rep(it,0,M/2) {
        rep(i,0,M) if (has[i])
            rep(j,i+1,M) if (A[i][j] && mat[i][j]) {
                fi = i; fj = j; goto done;
            } assert(0); done:
        if (fj < N) ret.emplace_back(fi, fj);
        has[fi] = has[fj] = 0;
        rep(sw,0,2) {
            ll a = modpow(A[fi][fj], mod-2);
            rep(i,0,M) if (has[i] && A[i][fj]) {
                ll b = A[i][fj] * a % mod;
                rep(j,0,M) A[i][j] = (A[i][j] - A[fi][j] * b) % mod;
            }
            swap(fi,fj);
        }
    }
    return ret;
}
```

## 7.4 DFS algorithms

### SCC.h

**Description:** Finds strongly connected components in a directed graph. If vertices  $u, v$  belong to the same component, we can reach  $u$  from  $v$  and vice versa.  
**Usage:** scc(graph, [&](vi& v) { ... }) visits all components in reverse topological order. comp[i] holds the component index of a node (a component only has edges to components with lower index). ncomps will contain the number of components.  
**Time:**  $\mathcal{O}(E + V)$

76b5c9, 24 lines

```
vi val, comp, z, cont;
```

```
int Time, ncomps;
template<class G, class F> int dfs(int j, G& g, F& f) {
    int low = val[j] = ++Time, x; z.push_back(j);
    for (auto e : g[j]) if (comp[e] < 0)
        low = min(low, val[e] ?: dfs(e,g,f));

    if (low == val[j]) {
        do {
            x = z.back(); z.pop_back();
            comp[x] = ncomps;
            cont.push_back(x);
        } while (x != j);
        f(cont); cont.clear();
        ncomps++;
    }
    return val[j] = low;
}

template<class G, class F> void scc(G& g, F f) {
    int n = sz(g);
    val.assign(n, 0); comp.assign(n, -1);
    Time = ncomps = 0;
    rep(i,0,n) if (comp[i] < 0) dfs(i, g, f);
}
```

### Articulation-Bridges.h

**Description:** get all articulation points/bridges, 0-based  
**Time:**  $\mathcal{O}(V + E)$

e0548e, 36 lines

```
vector<bool> visited;
vector<int> tin, low;
int timer;

void dfs(int v, int p = -1) {
    visited[v] = true;
    tin[v] = low[v] = timer++;
    int children=0;
    for (int to : adj[v]) {
        if (to == p) continue;
        if (visited[to]) {
            low[v] = min(low[v], tin[to]);
        } else {
            dfs(to, v);
            low[v] = min(low[v], low[to]);
            ++children;
            if (low[to] >= tin[v] && p!=-1)
                IS_CUTPOINT(v);
            if (low[to] > tin[v])
                IS_BRIDGE(v, to);
        }
    }
    if(p == -1 && children > 1)
        IS_CUTPOINT(v);
}

void find() {
    timer = 0;
    visited.assign(n, false);
    tin.assign(n, -1);
    low.assign(n, -1);
    for (int i = 0; i < n; ++i) {
        if (!visited[i])
            dfs (i);
    }
}
```

EulerWalk.h  
**Description:** Eulerian undirected/directed path/cycle algorithm. Input should be a vector of (dest, global edge index), where for undirected graphs, forward/backward edges have the same index. Returns a list of nodes in the Eulerian path/cycle with src at both start and end, or empty list if no cycle/path exists. To get edge indices back, add .second to s and ret.  
**Time:**  $\mathcal{O}(V + E)$

```
65897d, 16 lines
vector<pii> eulerWalk(vector<vector<pii>>& gr, int nedges, int src=0) {
    int n = sz(gr);
    vi D(n), its(n), eu(nedges);
    vector<pii> ret, s = {{src,0}};
    D[src]++; // to allow Euler paths, not just cycles
    while (!s.empty()) {
        int x = s.back().first,id=s.back().second,y, e, &it = its[x], end = sz(gr[x]);
        if (it == end){ ret.push_back({x,id}); s.pop_back(); continue; }
        tie(y, e) = gr[x][it++];
        if (!eu[e]) {
            D[x]--, D[y]++;
            eu[e] = 1; s.push_back({y,e});
        }
    }
    for (int x : D) if (x < 0 || sz(ret) != nedges+1) return {} ;
    return {ret.rbegin(), ret.rend()};
}
```

## 7.5 Coloring

EdgeColoring.h  
**Description:** Given a simple, undirected graph with max degree  $D$ , computes a  $(D + 1)$ -coloring of the edges such that no neighboring edges share a color. ( $D$ -coloring is NP-hard, but can be done for bipartite graphs by repeated matchings of max-degree nodes.)  
**Time:**  $\mathcal{O}(NM)$

```
e210e2, 31 lines
vi edgeColoring(int N, vector<pii> eds) {
    vi cc(N + 1), ret(sz(eds)), fan(N), free(N), loc;
    for (pii e : eds) ++cc[e.first], ++cc[e.second];
    int u, v, ncols = *max_element(all(cc)) + 1;
    vector<vi> adj(N, vi(ncols, -1));
    for (pii e : eds) {
        tie(u, v) = e;
        fan[0] = v;
        loc.assign(ncols, 0);
        int at = u, end = u, d, c = free[u], ind = 0, i = 0;
        while (d = free[v], !loc[d] && (v = adj[u][d]) != -1)
            loc[d] = ++ind, cc[ind] = d, fan[ind] = v;
        cc[loc[d]] = c;
        for (int cd = d; at != -1; cd ^= c ^ d, at = adj[at][cd])
            swap(adj[at][cd], adj[end = at][cd ^ c ^ d]);
        while (adj[fan[i]][d] != -1) {
            int left = fan[i], right = fan[++i], e = cc[i];
            adj[u][e] = left;
            adj[left][e] = u;
            adj[right][e] = -1;
            free[right] = e;
        }
        adj[u][d] = fan[i];
        adj[fan[i]][d] = u;
        for (int y : {fan[0], u, end})
            for (int& z = free[y] = 0; adj[y][z] != -1; z++);
    }
    rep(i,0,sz(eds))
        for (tie(u, v) = eds[i]; adj[u][ret[i]] != v;) ++ret[i];
    return ret;
}
```

## 7.6 Heuristics

MaximalCliques.h  
**Description:** Runs a callback for all maximal cliques in a graph (given as a symmetric bitset matrix; self-edges not allowed). Callback is given a bitset representing the maximal clique.  
**Time:**  $\mathcal{O}\left(3^{n/3}\right)$ , much faster for sparse graphs

```
b0d5b1, 12 lines
typedef bitset<128> B;
template<class F>
void cliques(vector<B>& eds, F f, B P = ~B(), B X={}, B R={}) {
    if (!P.any()) { if (!X.any()) f(R); return; }
    auto q = (P | X)._Find_first();
    auto cands = P & ~eds[q];
    rep(i,0,sz(eds)) if (cands[i]) {
        R[i] = 1;
        cliques(eds, f, P & eds[i], X & eds[i], R);
        R[i] = P[i] = 0; X[i] = 1;
    }
}
```

MaximumClique.h  
**Description:** Quickly finds a maximum clique of a graph (given as symmetric bitset matrix; self-edges not allowed). Can be used to find a maximum independent set by finding a clique of the complement graph.  
**Time:** Runs in about 1s for n=155 and worst case random graphs (p=.90). Runs faster for sparse graphs.

```
f7c0bc, 49 lines
typedef vector<bitset<200>> vb;
struct Maxclique {
    double limit=0.025, pk=0;
    struct Vertex { int i, d=0; };
    typedef vector<Vertex> vv;
    vb e;
    vv V;
    vector<vi> C;
    vi qmax, q, S, old;
    void init(vv& r) {
        for (auto& v : r) v.d = 0;
        for (auto& v : r) for (auto j : r) v.d += e[v.i][j.i];
        sort(all(r), [](auto a, auto b) { return a.d > b.d; });
        int mxD = r[0].d;
        rep(i,0,sz(r)) r[i].d = min(i, mxD) + 1;
    }
    void expand(vv& R, int lev = 1) {
        S[lev] += S[lev - 1] - old[lev];
        old[lev] = S[lev - 1];
        while (sz(R)) {
            if (sz(q) + R.back().d <= sz(qmax)) return;
            q.push_back(R.back().i);
            vv T;
            for(auto v:R) if (e[R.back().i][v.i]) T.push_back({v.i});
            if (sz(T)) {
                if (S[lev]++ / ++pk < limit) init(T);
                int j = 0, mxk = 1, mnk = max(sz(qmax) - sz(q) + 1, 1);
                C[1].clear(), C[2].clear();
                for (auto v : T) {
                    int k = 1;
                    auto f = [&](int i) { return e[v.i][i]; };
                    while (any_of(all(C[k]), f)) k++;
                    if (k > mxk) mxk = k, C[mxk + 1].clear();
                    if (k < mnk) T[j++].i = v.i;
                    C[k].push_back(v.i);
                }
                if (j > 0) T[j - 1].d = 0;
                rep(k,mnk,mxk + 1) for (int i : C[k])
                    T[j].i = i, T[j++].d = k;
                expand(T, lev + 1);
            } else if (sz(q) > sz(qmax)) qmax = q;
        }
        q.pop_back(), R.pop_back();
    }
}
```

```

    }
}
vi maxClique() { init(V), expand(V); return qmax; }
Maxclique(vb conn) : e(conn), C(sz(e)+1), S(sz(C)), old(S) {
    rep(i,0,sz(e)) V.push_back({i});
}
};
```

MaximumIndependentSet.h  
**Description:** To obtain a maximum independent set of a graph, find a max clique of the complement. If the graph is bipartite, see MinimumVertex-Cover.

## 7.7 Trees

LinkCutTree.h  
**Description:** Represents a forest of unrooted trees. You can add and remove edges (as long as the result is still a forest), and check whether two nodes are in the same tree.  
**Time:** All operations take amortized  $\mathcal{O}(\log N)$ .

```
5909e2, 90 lines
struct Node { // Splay tree. Root's pp contains tree's parent.
    Node *p = 0, *pp = 0, *c[2];
    bool flip = 0;
    Node() { c[0] = c[1] = 0; fix(); }
    void fix() {
        if (c[0]) c[0]->p = this;
        if (c[1]) c[1]->p = this;
        // (+ update sum of subtree elements etc. if wanted)
    }
    void pushFlip() {
        if (!flip) return;
        flip = 0; swap(c[0], c[1]);
        if (c[0]) c[0]->flip ^= 1;
        if (c[1]) c[1]->flip ^= 1;
    }
    int up() { return p ? p->c[1] == this : -1; }
    void rot(int i, int b) {
        int h = i ^ b;
        Node *x = c[i], *y = b == 2 ? x : x->c[h], *z = b ? y : x;
        if ((y->p = p)) p->c[up()] = y;
        c[i] = z->c[i ^ 1];
        if (b < 2) {
            x->c[h] = y->c[h ^ 1];
            z->c[h ^ 1] = b ? x : this;
        }
        y->c[i ^ 1] = b ? this : x;
        fix(); x->fix(); y->fix();
        if (p) p->fix();
        swap(pp, y->pp);
    }
    void splay() {
        for (pushFlip(); p; ) {
            if (p->p) p->p->pushFlip();
            p->pushFlip(); pushFlip();
            int c1 = up(), c2 = p->up();
            if (c2 == -1) p->rot(c1, 2);
            else p->p->rot(c2, c1 != c2);
        }
    }
    Node* first() {
        pushFlip();
        return c[0] ? c[0]->first() : (splay(), this);
    }
};

struct LinkCut {
    vector<Node> node;
    LinkCut(int N) : node(N) {}
}
```

```
void link(int u, int v) { // add an edge (u, v)
    assert(!connected(u, v));
    makeRoot(&node[u]);
    node[u].pp = &node[v];
}

void cut(int u, int v) { // remove an edge (u, v)
    Node *x = &node[u], *top = &node[v];
    makeRoot(top); x->splay();
    assert(top == (x->pp ? x->c[0]));
    if (x->pp) x->pp = 0;
    else {
        x->c[0] = top->p = 0;
        x->fix();
    }
}

bool connected(int u, int v) { // are u, v in the same tree?
    Node* nu = access(&node[u])->first();
    return nu == access(&node[v])->first();
}

void makeRoot(Node* u) {
    access(u);
    u->splay();
    if (u->c[0]) {
        u->c[0]->p = 0;
        u->c[0]->flip ^= 1;
        u->c[0]->pp = u;
        u->c[0] = 0;
        u->fix();
    }
}

Node* access(Node* u) {
    u->splay();
    while (Node* pp = u->pp) {
        pp->splay(); u->pp = 0;
        if (pp->c[1]) {
            pp->c[1]->p = 0; pp->c[1]->pp = pp; }
        pp->c[1] = u; pp->fix(); u = pp;
    }
    return u;
}
};
```

DirectedMST.h

**Description:** Finds a minimum spanning tree/arborescence of a directed graph, given a root node. If no MST exists, returns -1.  
**Time:**  $\mathcal{O}(E \log V)$

```
"/data-structures/UnionFindRollback.h" 39e620, 60 lines

struct Edge { int a, b; ll w; };
struct Node {
    Edge key;
    Node *l, *r;
    ll delta;
    void prop() {
        key.w += delta;
        if (l) l->delta += delta;
        if (r) r->delta += delta;
        delta = 0;
    }
    Edge top() { prop(); return key; }
};

Node *merge(Node *a, Node *b) {
    if (!a || !b) return a ? b;
    a->prop(), b->prop();
    if (a->key.w > b->key.w) swap(a, b);
    swap(a->l, (a->r = merge(b, a->r)));
    return a;
}

void pop(Node*& a) { a->prop(); a = merge(a->l, a->r); }
```

```
pair<ll, vi> dmst(int n, int r, vector<Edge>& g) {
    RollbackUF uf(n);
    vector<Node*> heap(n);
    for (Edge e : g) heap[e.b] = merge(heap[e.b], new Node{e});
    ll res = 0;
    vi seen(n, -1), path(n), par(n);
    seen[r] = r;
    vector<Edge> Q(n), in(n, {-1,-1}), comp;
    deque<tuple<int, int, vector<Edge>>> cycs;
    rep(s,0,n) {
        int u = s, qi = 0, w;
        while (seen[u] < 0) {
            if (!heap[u]) return {-1,{};};
            Edge e = heap[u]->top();
            heap[u]->delta -= e.w, pop(heap[u]);
            Q[qi] = e, path[qi++] = u, seen[u] = s;
            res += e.w, u = uf.find(e.a);
            if (seen[u] == s) {
                Node* cyc = 0;
                int end = qi, time = uf.time();
                do cyc = merge(cyc, heap[w = path[--qi]]);
                while (uf.join(u, w));
                u = uf.find(u), heap[u] = cyc, seen[u] = -1;
                cycs.push_front({u, time, {&Q[qi], &Q[end]}));
            }
        }
        rep(i,0,qi) in[uf.find(Q[i].b)] = Q[i];
    }

    for (auto& [u,t,comp] : cycs) { // restore sol (optional)
        uf.rollback(t);
        Edge inEdge = in[u];
        for (auto& e : comp) in[uf.find(e.b)] = e;
        in[uf.find(inEdge.b)] = inEdge;
    }
    rep(i,0,n) par[i] = in[i].a;
    return {res, par};
}
```

7.8 Math

7.8.1 Number of Spanning Trees

Create an  $N \times N$  matrix mat, and for each edge  $a \rightarrow b \in G$ , do mat[a][b]--, mat[b][b]++ (and mat[b][a]--, mat[a][a]++ if  $G$  is undirected). Remove the  $i$ th row and column and take the determinant; this yields the number of directed spanning trees rooted at  $i$  (if  $G$  is undirected, remove any row/column).

7.8.2 Erdős–Gallai theorem

A simple graph with node degrees  $d_1 \geq \dots \geq d_n$  exists iff  $d_1 + \dots + d_n$  is even and for every  $k = 1 \dots n$ ,

$$\sum_{i=1}^k d_i \leq k(k-1) + \sum_{i=k+1}^n \min(d_i, k).$$

Geometry (8)

8.1 Geometric primitives

Point.h


**Description:** Class to handle points in the plane. T can be e.g. double or long long. (Avoid int.)

```
47ec0a, 28 lines

template <class T> int sgn(T x) { return (x > 0) - (x < 0); }
template<class T>
struct Point {
    typedef Point P;
    T x, y;
    explicit Point(T x=0, T y=0) : x(x), y(y) {}
    bool operator<(P p) const { return tie(x,y) < tie(p.x,p.y); }
    bool operator==(P p) const { return tie(x,y)==tie(p.x,p.y); }
    P operator+(P p) const { return P(x+p.x, y+p.y); }
    P operator-(P p) const { return P(x-p.x, y-p.y); }
    P operator*(T d) const { return P(x*d, y*d); }
    P operator/(T d) const { return P(x/d, y/d); }
    T dot(P p) const { return x*p.x + y*p.y; }
    T cross(P p) const { return x*p.y - y*p.x; }
    T cross(P a, P b) const { return (a-*this).cross(b-*this); }
    T dist2() const { return x*x + y*y; }
    double dist() const { return sqrt((double)dist2()); }
    // angle to x-axis in interval [-pi, pi]
    double angle() const { return atan2(y, x); }
    P unit() const { return *this/dist(); } // makes dist()==1
    P perp() const { return P(-y, x); } // rotates +90 degrees
    P normal() const { return perp().unit(); }
    // returns point rotated 'a' radians ccw around the origin
    P rotate(double a) const {
        return P(x*cos(a)-y*sin(a),x*sin(a)+y*cos(a)); }
    friend ostream& operator<<(ostream& os, P p) {
        return os << "(" << p.x << ", " << p.y << ")"; }
};
```

lineDistance.h

**Description:**  
Returns the signed distance between point p and the line containing points a and b. Positive value on left side and negative on right as seen from a towards b. a==b gives nan. P is supposed to be Point<T> or Point3D<T> where T is e.g. double or long long. It uses products in intermediate steps so watch out for overflow if using int or long long. Using Point3D will always give a non-negative distance. For Point3D, call .dist on the result of the cross product.




```
"Point.h" f6bf6b, 4 lines

template<class P>
double lineDist(const P& a, const P& b, const P& p) {
    return (double) (b-a).cross(p-a) / (b-a).dist();
}

SegmentDistance.h
Description:
Returns the shortest distance between point p and the line segment from point s to e.
Usage: Point<double> a, b(2,2), p(1,1);
bool onSegment = segDist(a,b,p) < 1e-10;


5c88f4, 6 lines

typedef Point<double> P;
double segDist(P& s, P& e, P& p) {
    if (s==e) return (p-s).dist();
    auto d = (e-s).dist2(), t = min(d,max(.0, (p-s).dot(e-s)));
    return ((p-s)*d-(e-s)*t).dist()/d;
}
```



### SegmentIntersection.h


**Description:**  
If a unique intersection point between the line segments going from s1 to e1 and from s2 to e2 exists then it is returned. If no intersection point exists an empty vector is returned. If infinitely many exist a vector with 2 elements is returned, containing the endpoints of the common line segment. The wrong position will be returned if P is Point<ll> and the intersection point does not have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow if using int or long long.  
**Usage:** vector<P> inter = segInter(s1,e1,s2,e2);  
if (sz(inter)==1)  
cout << "segments intersect at " << inter[0] << endl;  
"Point.h", "OnSegment.h" 9d57f2, 13 lines



```
template<class P> vector<P> segInter(P a, P b, P c, P d) {
    auto oa = c.cross(d, a), ob = c.cross(d, b),
        oc = a.cross(b, c), od = a.cross(b, d);
    // Checks if intersection is single non-endpoint point.
    if (sgn(oa) * sgn(ob) < 0 && sgn(oc) * sgn(od) < 0)
        return {(a * ob - b * oa) / (ob - oa)};
    set<P> s;
    if (onSegment(c, d, a)) s.insert(a);
    if (onSegment(c, d, b)) s.insert(b);
    if (onSegment(a, b, c)) s.insert(c);
    if (onSegment(a, b, d)) s.insert(d);
    return {all(s)};
}
```

### lineIntersection.h

**Description:**  
If a unique intersection point of the lines going through s1,e1 and s2,e2 exists {1, point} is returned. If no intersection point exists {0, (0,0)} is returned and if infinitely many exists {-1, (0,0)} is returned. The wrong position will be returned if P is Point<ll> and the intersection point does not have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow if using int or ll.  
**Usage:** auto res = lineInter(s1,e1,s2,e2);  
if (res.first == 1)  
cout << "intersection point at " << res.second << endl;  
"Point.h" a01f81, 8 lines



```
template<class P>
pair<int, P> lineInter(P s1, P e1, P s2, P e2) {
    auto d = (e1 - s1).cross(e2 - s2);
    if (d == 0) // if parallel
        return {-(s1.cross(e1, s2) == 0), P(0, 0)};
    auto p = s2.cross(e1, e2), q = s2.cross(e2, s1);
    return {1, (s1 * p + e1 * q) / d};
}
```

### sideOf.h

**Description:** Returns where *p* is as seen from *s* towards *e*. 1/0/-1 ⇔ left/on line/right. If the optional argument *eps* is given 0 is returned if *p* is within distance *eps* from the line. P is supposed to be Point<T> where T is e.g. double or long long. It uses products in intermediate steps so watch out for overflow if using int or long long.  
**Usage:** bool left = sideOf(p1,p2,q)==1;  
"Point.h" 3af81c, 9 lines

```
template<class P>
int sideOf(P s, P e, P p) { return sgn(s.cross(e, p)); }
```


  

```
template<class P>
int sideOf(const P& s, const P& e, const P& p, double eps) {
    auto a = (e-s).cross(p-s);
    double l = (e-s).dist()*eps;
    return (a > l) - (a < -l);
}
```

### OnSegment.h

**Description:** Returns true iff p lies on the line segment from s to e. Use (segDist(s,e,p)<=epsilon) instead when using Point<double>.  
"Point.h" c597e8, 3 lines

```
template<class P> bool onSegment(P s, P e, P p) {
    return p.cross(s, e) == 0 && (s - p).dot(e - p) <= 0;
}
```



**linearTransformation.h**  
**Description:**  
Apply the linear transformation (translation, rotation and scaling) which takes line p0-p1 to line q0-q1 to point r.  
"Point.h" 03a306, 6 lines

```
typedef Point<double> P;
P linearTransformation(const P& p0, const P& p1,
    const P& q0, const P& q1, const P& r) {
    P dp = p1-p0, dq = q1-q0, num(dp.cross(dq), dp.dot(dq));
    return q0 + P((r-p0).cross(num), (r-p0).dot(num))/dp.dist2();
}
```

### Angle.h

**Description:** A class for ordering angles (as represented by int points and a number of rotations around the origin). Useful for rotational sweeping. Sometimes also represents points or vectors.  
**Usage:** vector<Angle> v = {w[0], w[0].t360() ...}; // sorted  
int j = 0; rep(i,0,n) { while (v[j] < v[i].t180()) ++j; }  
// sweeps j such that (j-i) represents the number of positively oriented triangles with vertices at 0 and i  
0f0602, 35 lines

```
struct Angle {
    int x, y;
    int t;
    Angle(int x, int y, int t=0) : x(x), y(y), t(t) {}
    Angle operator-(Angle b) const { return {x-b.x, y-b.y, t}; }
    int half() const {
        assert(x || y);
        return y < 0 || (y == 0 && x < 0);
    }
    Angle t90() const { return {-y, x, t + (half() && x >= 0)}; }
    Angle t180() const { return {-x, -y, t + half()}; }
    Angle t360() const { return {x, y, t + 1}; }
};
bool operator<(Angle a, Angle b) {
    // add a.dist2() and b.dist2() to also compare distances
    return make_tuple(a.t, a.half(), a.y * (1l)b.x) <
        make_tuple(b.t, b.half(), a.x * (1l)b.y);
}
```

*// Given two points, this calculates the smallest angle between them, i.e., the angle that covers the defined line segment.*  
pair<Angle, Angle> segmentAngles(Angle a, Angle b) {  
 if (b < a) swap(a, b);  
 return (b < a.t180() ?  
 make\_pair(a, b) : make\_pair(b, a.t360()));  
}  
Angle operator+(Angle a, Angle b) { // point a + vector b  
 Angle r(a.x + b.x, a.y + b.y, a.t);  
 if (a.t180() < r) r.t--;  
 return r.t180() < a ? r.t360() : r;  
}  
Angle angleDiff(Angle a, Angle b) { // angle b - angle a  
 int tu = b.t - a.t; a.t = b.t;  
 return {a.x\*b.x + a.y\*b.y, a.x\*b.y - a.y\*b.x, tu - (b < a)};  
}

## 8.2 Circles

### CircleIntersection.h

**Description:** Computes the pair of points at which two circles intersect. Returns false in case of no intersection.  
"Point.h" 84d6d3, 11 lines

```
typedef Point<double> P;
bool circleInter(P a,P b,double r1,double r2,pair<P, P>* out) {
    if (a == b) { assert(r1 != r2); return false; }
    P vec = b - a;
    double d2 = vec.dist2(), sum = r1+r2, dif = r1-r2,
        p = (d2 + r1*r1 - r2*r2)/(d2*2), h2 = r1*r1 - p*p*d2;
    if (sum*sum < d2 || dif*dif > d2) return false;
    P mid = a + vec*p, per = vec.perp() * sqrt(fmax(0, h2) / d2);
    *out = {mid + per, mid - per};
    return true;
}
```

### CircleTangents.h

**Description:** Finds the external tangents of two circles, or internal if r2 is negated. Can return 0, 1, or 2 tangents – 0 if one circle contains the other (or overlaps it, in the internal case, or if the circles are the same); 1 if the circles are tangent to each other (in which case .first = .second and the tangent line is perpendicular to the line between the centers). .first and .second give the tangency points at circle 1 and 2 respectively. To find the tangents of a circle with a point set r2 to 0.  
"Point.h" b0153d, 13 lines

```
template<class P>
vector<pair<P, P>> tangents(P c1, double r1, P c2, double r2) {
    P d = c2 - c1;
    double dr = r1 - r2, d2 = d.dist2(), h2 = d2 - dr * dr;
    if (d2 == 0 || h2 < 0) return {};
    vector<pair<P, P>> out;
    for (double sign : {-1, 1}) {
        P v = (d * dr + d.perp() * sqrt(h2) * sign) / d2;
        out.push_back({c1 + v * r1, c2 + v * r2});
    }
    if (h2 == 0) out.pop_back();
    return out;
}
```


### CirclePolygonIntersection.h

**Description:** Returns the area of the intersection of a circle with a ccw polygon.  
**Time:**  $\mathcal{O}(n)$   
"../../content/geometry/Point.h" aleec63, 19 lines

```
typedef Point<double> P;
#define arg(p, q) atan2(p.cross(q), p.dot(q))
double circlePoly(P c, double r, vector<P> ps) {
    auto tri = [&](P p, P q) {
        auto r2 = r * r / 2;
        P d = q - p;
        auto a = d.dot(p)/d.dist2(), b = (p.dist2()-r*r)/d.dist2();
        auto det = a * a - b;
        if (det <= 0) return arg(p, q) * r2;
        auto s = max(0., -a-sqrt(det)), t = min(1., -a+sqrt(det));
        if (t < 0 || 1 <= s) return arg(p, q) * r2;
        P u = p + d * s, v = p + d * t;
        return arg(p,u) * r2 + u.cross(v)/2 + arg(v,q) * r2;
    };
    auto sum = 0.0;
    rep(i,0,sz(ps))
        sum += tri[ps[i] - c, ps[(i + 1) % sz(ps)] - c];
    return sum;
}
```



circumcircle.h  
**Description:** The circumcircle of a triangle is the circle intersecting all three vertices. ccRadius returns the radius of the circle going through points A, B and C and ccCenter returns the center of the same circle.



```
"Point.h"1caa3a, 9 lines

typedef Point<double> P;
double ccRadius(const P& A, const P& B, const P& C) {
    return (B-A).dist()*(C-B).dist()*(A-C).dist() /
        abs((B-A).cross(C-A))/2;
}
P ccCenter(const P& A, const P& B, const P& C) {
    P b = C-A, c = B-A;
    return A + (b*c.dist2()-c*b.dist2()).perp()/b.cross(c)/2;
}
```

MinimumEnclosingCircle.h  
**Description:** Computes the minimum circle that encloses a set of points.  
**Time:** expected  $\mathcal{O}(n)$

```
"circumcircle.h"09dd0a, 17 lines

pair<P, double> mec(vector<P> ps) {
    shuffle(all(ps), mt19937(time(0)));
    P o = ps[0];
    double r = 0, EPS = 1 + 1e-8;
    rep(i,0,sz(ps)) if ((o - ps[i]).dist() > r * EPS) {
        o = ps[i], r = 0;
        rep(j,0,i) if ((o - ps[j]).dist() > r * EPS) {
            o = (ps[i] + ps[j]) / 2;
            r = (o - ps[i]).dist();
            rep(k,0,j) if ((o - ps[k]).dist() > r * EPS) {
                o = ccCenter(ps[i], ps[j], ps[k]);
                r = (o - ps[i]).dist();
            }
        }
    }
    return {o, r};
}
```

### 8.3 Polygons

InsidePolygon.h  
**Description:** Returns true if p lies within the polygon. If strict is true, it returns false for points on the boundary. The algorithm uses products in intermediate steps so watch out for overflow.  
**Usage:** vector<P> v = {P{4,4}, P{1,2}, P{2,1}};  
bool in = inPolygon(v, P{3, 3}, false);  
**Time:**  $\mathcal{O}(n)$

```
"Point.h", "OnSegment.h", "SegmentDistance.h"2bf504, 11 lines

template<class P>
bool inPolygon(vector<P> &p, P a, bool strict = true) {
    int cnt = 0, n = sz(p);
    rep(i,0,n) {
        P q = p[(i + 1) % n];
        if (onSegment(p[i], q, a)) return !strict;
        //or: if (segDist(p[i], q, a) <= eps) return !strict;
        cnt ^= ((a.y<p[i].y) - (a.y<q.y)) * a.cross(p[i], q) > 0;
    }
    return cnt;
}
```

PolygonArea.h  
**Description:** Returns twice the signed area of a polygon. Clockwise enumeration gives negative area. Watch out for overflow if using int as T!  
**Time:**  $\mathcal{O}(n)$

```
"Point.h"fl2300, 6 lines

template<class T>
T polygonArea2(vector<Point<T>>& v) {
```


```
T a = v.back().cross(v[0]);
rep(i,0,sz(v)-1) a += v[i].cross(v[i+1]);
return a;
}
```

PolygonCenter.h  
**Description:** Returns the center of mass for a polygon.  
**Time:**  $\mathcal{O}(n)$

```
"Point.h"9706dc, 9 lines

typedef Point<double> P;
P polygonCenter(const vector<P>& v) {
    P res(0, 0); double A = 0;
    for (int i = 0, j = sz(v) - 1; i < sz(v); j = i++) {
        res = res + (v[i] + v[j]) * v[j].cross(v[i]);
        A += v[j].cross(v[i]);
    }
    return res / A / 3;
}
```

PolygonCut.h  
**Description:** Returns a vector with the vertices of a polygon with everything to the left of the line going from s to e cut away.  
**Usage:** vector<P> p = ...;  
p = polygonCut(p, P(0,0), P(1,0));



```
"Point.h", "LineIntersection.h"f2b7d4, 13 lines

typedef Point<double> P;
vector<P> polygonCut(const vector<P>& poly, P s, P e) {
    vector<P> res;
    rep(i,0,sz(poly)) {
        P cur = poly[i], prev = i ? poly[i-1] : poly.back();
        bool side = s.cross(e, cur) < 0;
        if (side != (s.cross(e, prev) < 0))
            res.push_back(lineInter(s, e, cur, prev).second);
        if (side)
            res.push_back(cur);
    }
    return res;
}
```

ConvexHull.h  
**Description:** Returns a vector of the points of the convex hull in counter-clockwise order. Points on the edge of the hull between two other points are not considered part of the hull.  
**Time:**  $\mathcal{O}(n \log n)$



```
"Point.h"310954, 13 lines

typedef Point<ll> P;
vector<P> convexHull(vector<P> pts) {
    if (sz(pts) <= 1) return pts;
    sort(all(pts));
    vector<P> h(sz(pts)+1);
    int s = 0, t = 0;
    for (int it = 2; it--; s = --t, reverse(all(pts)))
        for (P p : pts) {
            while (t >= s + 2 && h[t-2].cross(h[t-1], p) <= 0) t--;
            h[t++] = p;
        }
    return {h.begin(), h.begin() + t - (t == 2 && h[0] == h[1])};
}
```

HullDiameter.h  
**Description:** Returns the two points with max distance on a convex hull (ccw, no duplicate/collinear points).  
**Time:**  $\mathcal{O}(n)$

```
"Point.h"c571b8, 12 lines

typedef Point<ll> P;
```

```
array<P, 2> hullDiameter(vector<P> S) {
    int n = sz(S), j = n < 2 ? 0 : 1;
    pair<ll, array<P, 2>> res({0, {S[0], S[0]}});
    rep(i,0,j)
        for (;; j = (j + 1) % n) {
            res = max(res, {(S[i] - S[j]).dist2(), {S[i], S[j]}});
            if ((S[(j + 1) % n] - S[j]).cross(S[i + 1] - S[i]) >= 0)
                break;
        }
    return res.second;
}
```

PointInsideHull.h  
**Description:** Determine whether a point t lies inside a convex hull (CCW order, with no collinear points). Returns true if point lies within the hull. If strict is true, points on the boundary aren't included.  
**Time:**  $\mathcal{O}(\log N)$

```
"Point.h", "sideOf.h", "OnSegment.h"71446b, 14 lines

typedef Point<ll> P;
```

```
bool inHull(const vector<P>& l, P p, bool strict = true) {
    int a = 1, b = sz(l) - 1, r = !strict;
    if (sz(l) < 3) return r && onSegment(l[0], l.back(), p);
    if (sideOf(l[0], l[a], l[b]) > 0) swap(a, b);
    if (sideOf(l[0], l[a], p) >= r || sideOf(l[0], l[b], p) <= -r)
        return false;
    while (abs(a - b) > 1) {
        int c = (a + b) / 2;
        (sideOf(l[0], l[c], p) > 0 ? b : a) = c;
    }
    return sgn(l[a].cross(l[b], p)) < r;
}
```

LineHullIntersection.h  
**Description:** Line-convex polygon intersection. The polygon must be ccw and have no collinear points. lineHull(line, poly) returns a pair describing the intersection of a line with the polygon:  $\bullet(-1, -1)$  if no collision,  $\bullet(i, -1)$  if touching the corner  $i$ ,  $\bullet(i, i)$  if along side  $(i, i + 1)$ ,  $\bullet(i, j)$  if crossing sides  $(i, i + 1)$  and  $(j, j + 1)$ . In the last case, if a corner  $i$  is crossed, this is treated as happening on side  $(i, i + 1)$ . The points are returned in the same order as the line hits the polygon. extrVertex returns the point of a hull with the max projection onto a line.  
**Time:**  $\mathcal{O}(\log n)$

```
"Point.h"7cf45b, 39 lines

#define cmp(i,j) sgn(dir.perp().cross(poly[(i)%n]-poly[(j)%n]))
#define extr(i) cmp(i + 1, i) >= 0 && cmp(i, i - 1 + n) < 0
template <class P> int extrVertex(vector<P>& poly, P dir) {
    int n = sz(poly), lo = 0, hi = n;
    if (extr(0)) return 0;
    while (lo + 1 < hi) {
        int m = (lo + hi) / 2;
        if (extr(m)) return m;
        int ls = cmp(lo + 1, lo), ms = cmp(m + 1, m);
        (ls < ms || (ls == ms && ls == cmp(lo, m)) ? hi : lo) = m;
    }
    return lo;
}
```

```
#define cmpL(i) sgn(a.cross(poly[i], b))
template <class P>
array<int, 2> lineHull(P a, P b, vector<P>& poly) {
    int endA = extrVertex(poly, (a - b).perp());
    int endB = extrVertex(poly, (b - a).perp());
    if (cmpL(endA) < 0 || cmpL(endB) > 0)
        return {-1, -1};
    array<int, 2> res;
    rep(i,0,2) {
        int lo = endB, hi = endA, n = sz(poly);
```

```

while ((lo + 1) % n != hi) {
    int m = ((lo + hi + (lo < hi ? 0 : n)) / 2) % n;
    (cmpL(m) == cmpL(endB) ? lo : hi) = m;
}
res[i] = (lo + !cmpL(hi)) % n;
swap(endA, endB);
}
if (res[0] == res[1]) return {res[0], -1};
if (!cmpL(res[0]) && !cmpL(res[1]))
    switch ((res[0] - res[1] + sz(poly) + 1) % sz(poly)) {
        case 0: return {res[0], res[0]};
        case 2: return {res[1], res[1]};
    }
return res;
}
}

```

## 8.4 Misc. Point Set Problems

### ClosestPair.h

**Description:** Finds the closest pair of points.

**Time:**  $O(n \log n)$

"Point.h" ac41a6, 17 lines

```

typedef Point<ll> P;
pair<P, P> closest(vector<P> v) {
    assert(sz(v) > 1);
    set<P> S;
    sort(all(v), [](P a, P b) { return a.y < b.y; });
    pair<ll, pair<P, P>> ret{LLONG_MAX, {P(), P()}};
    int j = 0;
    for (P p : v) {
        P d{1 + (ll)sqrt(ret.first), 0};
        while (v[j].y <= p.y - d.x) S.erase(v[j++]);
        auto lo = S.lower_bound(p - d), hi = S.upper_bound(p + d);
        for (; lo != hi; ++lo)
            ret = min(ret, {(ll)lo - p).dist2(), {(ll)lo, p}});
        S.insert(p);
    }
    return ret.second;
}

```

### kdTree.h

**Description:** KD-tree (2d, can be extended to 3d)

"Point.h" bac5b0, 63 lines

```

typedef long long T;
typedef Point<T> P;
const T INF = numeric_limits<T>::max();

```

```

bool on_x(const P& a, const P& b) { return a.x < b.x; }
bool on_y(const P& a, const P& b) { return a.y < b.y; }

```

```

struct Node {
    P pt; // if this is a leaf, the single point in it
    T x0 = INF, x1 = -INF, y0 = INF, y1 = -INF; // bounds
    Node *first = 0, *second = 0;

    T distance(const P& p) { // min squared distance to a point
        T x = (p.x < x0 ? x0 : p.x > x1 ? x1 : p.x);
        T y = (p.y < y0 ? y0 : p.y > y1 ? y1 : p.y);
        return (P(x,y) - p).dist2();
    }
}

```

```

Node(vector<P>&& vp) : pt(vp[0]) {
    for (P p : vp) {
        x0 = min(x0, p.x); x1 = max(x1, p.x);
        y0 = min(y0, p.y); y1 = max(y1, p.y);
    }
    if (vp.size() > 1) {
        // split on x if width >= height (not ideal...)
        sort(all(vp), x1 - x0 >= y1 - y0 ? on_x : on_y);
    }
}

```

```

// divide by taking half the array for each child (not
// best performance with many duplicates in the middle)
int half = sz(vp)/2;
first = new Node({vp.begin(), vp.begin() + half});
second = new Node({vp.begin() + half, vp.end()});
}
}
};

```

```

struct KDTree {
    Node* root;
    KDTree(const vector<P>& vp) : root(new Node({all(vp)})) {}
}

```

```

pair<T, P> search(Node *node, const P& p) {
    if (!node->first) {
        // uncomment if we should not find the point itself:
        // if (p == node->pt) return {INF, P()};
        return make_pair((p - node->pt).dist2(), node->pt);
    }
}

```

```

Node *f = node->first, *s = node->second;
T bfirst = f->distance(p), bsec = s->distance(p);
if (bfirst > bsec) swap(bsec, bfirst), swap(f, s);

```

```

// search closest side first, other side if needed
auto best = search(f, p);
if (bsec < best.first)
    best = min(best, search(s, p));
return best;
}

```

```

// find nearest point to a point, and its squared distance
// (requires an arbitrary operator< for Point)
pair<T, P> nearest(const P& p) {
    return search(root, p);
}
}

```

### FastDelaunay.h

**Description:** Fast Delaunay triangulation. Each circumcircle contains none of the input points. There must be no duplicate points. If all points are on a line, no triangles will be returned. Should work for doubles as well, though there may be precision issues in 'circ'. Returns triangles in order {t[0][0], t[0][1], t[0][2], t[1][0], ...}, all counter-clockwise.

**Time:**  $O(n \log n)$

"Point.h" eefdf5, 88 lines

```

typedef Point<ll> P;
typedef struct Quad* Q;
typedef __int128_t lll; // (can be ll if coords are < 2e4)
P arb(LLONG_MAX, LLONG_MAX); // not equal to any other point

```

```

struct Quad {
    Q rot, o; P p = arb; bool mark;
    P& F() { return r()->p; }
    Q& r() { return rot->rot; }
    Q prev() { return rot->o->rot; }
    Q next() { return r()->prev(); }
} *H;

```

```

bool circ(P p, P a, P b, P c) { // is p in the circumcircle?
    lll p2 = p.dist2(), A = a.dist2()-p2,
        B = b.dist2()-p2, C = c.dist2()-p2;
    return p.cross(a,b)*C + p.cross(b,c)*A + p.cross(c,a)*B > 0;
}
Q makeEdge(P orig, P dest) {
    Q r = H ? H : new Quad(new Quad{new Quad{new Quad{0}}});
    H = r->o; r->r()->r() = r;
    rep(i,0,4) r = r->rot, r->p = arb, r->o = i & 1 ? r : r->r();
    r->p = orig; r->F() = dest;
}

```

```

return r;
}
void splice(Q a, Q b) {
    swap(a->o->rot->o, b->o->rot->o); swap(a->o, b->o);
}
Q connect(Q a, Q b) {
    Q q = makeEdge(a->F(), b->p);
    splice(q, a->next());
    splice(q->r(), b);
    return q;
}

```

```

pair<Q,Q> rec(const vector<P>& s) {
    if (sz(s) <= 3) {
        Q a = makeEdge(s[0], s[1]), b = makeEdge(s[1], s.back());
        if (sz(s) == 2) return { a, a->r() };
        splice(a->r(), b);
        auto side = s[0].cross(s[1], s[2]);
        Q c = side ? connect(b, a) : 0;
        return {side < 0 ? c->r() : a, side < 0 ? c : b->r() };
    }
}

```

```

#define H(e) e->F(), e->p
#define valid(e) (e->F().cross(H(base)) > 0)
Q A, B, ra, rb;
int half = sz(s) / 2;
tie(ra, A) = rec({all(s) - half});
tie(B, rb) = rec({sz(s) - half + all(s)});
while ((B->p.cross(H(A)) < 0 && (A = A->next())) ||
        (A->p.cross(H(B)) > 0 && (B = B->r()->o)));
Q base = connect(B->r(), A);
if (A->p == ra->p) ra = base->r();
if (B->p == rb->p) rb = base;

```

```

#define DEL(e, init, dir) Q e = init->dir; if (valid(e)) \
    while (circ(e->dir->F(), H(base), e->F())) { \
        Q t = e->dir; \
        splice(e, e->prev()); \
        splice(e->r(), e->r()->prev()); \
        e->o = H; H = e; e = t; \
    }
for (;;) {
    DEL(LC, base->r(), o); DEL(RC, base, prev());
    if (!valid(LC) && !valid(RC)) break;
    if (!valid(LC) || (valid(RC) && circ(H(RC), H(LC))))
        base = connect(RC, base->r());
    else
        base = connect(base->r(), LC->r());
}
return { ra, rb };
}

```

```

vector<P> triangulate(vector<P> pts) {
    sort(all(pts)); assert(unique(all(pts)) == pts.end());
    if (sz(pts) < 2) return {};
    Q e = rec(pts).first;
    vector<Q> q = {e};
    int qi = 0;
    while (e->o->F().cross(e->F(), e->p) < 0) e = e->o;
    #define ADD { Q c = e; do { c->mark = 1; pts.push_back(c->p); \
        q.push_back(c->r()); c = c->next(); } while (c != e); }
    ADD; pts.clear();
    while (qi < sz(q)) if (!(e = q[qi++])->mark) ADD;
    return pts;
}

```

## 8.5 3D

### PolyhedronVolume.h

**Description:** Magic formula for the volume of a polyhedron. Faces should point outwards.

```
3058c3, 6 lines
template<class V, class L>
double signedPolyVolume(const V& p, const L& trilst) {
    double v = 0;
    for (auto i : trilst) v += p[i.a].cross(p[i.b]).dot(p[i.c]);
    return v / 6;
}
```

### Point3D.h

**Description:** Class to handle points in 3D space. T can be e.g. double or long long.

```
8058ae, 32 lines
template<class T> struct Point3D {
    typedef Point3D P;
    typedef const P& R;
    T x, y, z;
    explicit Point3D(T x=0, T y=0, T z=0) : x(x), y(y), z(z) {}
    bool operator<(R p) const {
        return tie(x, y, z) < tie(p.x, p.y, p.z); }
    bool operator==(R p) const {
        return tie(x, y, z) == tie(p.x, p.y, p.z); }
    P operator+(R p) const { return P(x+p.x, y+p.y, z+p.z); }
    P operator-(R p) const { return P(x-p.x, y-p.y, z-p.z); }
    P operator*(T d) const { return P(x*d, y*d, z*d); }
    P operator/(T d) const { return P(x/d, y/d, z/d); }
    T dot(R p) const { return x*p.x + y*p.y + z*p.z; }
    P cross(R p) const {
        return P(y*p.z - z*p.y, z*p.x - x*p.z, x*p.y - y*p.x);
    }
    T dist2() const { return x*x + y*y + z*z; }
    double dist() const { return sqrt((double)dist2()); }
    //Azimuthal angle (longitude) to x-axis in interval [-pi, pi]
    double phi() const { return atan2(y, x); }
    //Zenith angle (latitude) to the z-axis in interval [0, pi]
    double theta() const { return atan2(sqrt(x*x+y*y),z); }
    P unit() const { return *this/(T)dist(); } //makes dist()==1
    //returns unit vector normal to *this and p
    P normal(P p) const { return cross(p).unit(); }
    //returns point rotated 'angle' radians ccw around axis
    P rotate(double angle, P axis) const {
        double s = sin(angle), c = cos(angle); P u = axis.unit();
        return u*dot(u)*(1-c) + (*this)*c - cross(u)*s;
    }
};
```

### 3dHull.h

**Description:** Computes all faces of the 3-dimension hull of a point set. \*No four points must be coplanar\*, or else random results will be returned. All faces will point outwards.

**Time:**  $\mathcal{O}(n^2)$

```
"Point3D.h"
5b45fc, 49 lines
typedef Point3D<double> P3;

struct PR {
    void ins(int x) { (a == -1 ? a : b) = x; }
    void rem(int x) { (a == x ? a : b) = -1; }
    int cnt() { return (a != -1) + (b != -1); }
    int a, b;
};

struct F { P3 q; int a, b, c; };

vector<F> hull3d(const vector<P3>& A) {
    assert(sz(A) >= 4);
```

```
vector<vector<PR>> E(sz(A), vector<PR>(sz(A), {-1, -1}));
#define E(x,y) E[f.x][f.y]
vector<F> FS;
auto mf = [&](int i, int j, int k, int l) {
    P3 q = (A[j] - A[i]).cross((A[k] - A[i]));
    if (q.dot(A[l]) > q.dot(A[i]))
        q = q * -1;
    F f{q, i, j, k};
    E(a,b).ins(k); E(a,c).ins(j); E(b,c).ins(i);
    FS.push_back(f);
};
rep(i,0,4) rep(j,i+1,4) rep(k,j+1,4)
    mf(i, j, k, 6 - i - j - k);

rep(i,4,sz(A)) {
    rep(j,0,sz(FS)) {
        F f = FS[j];
        if (f.q.dot(A[i]) > f.q.dot(A[f.a])) {
            E(a,b).rem(f.c);
            E(a,c).rem(f.b);
            E(b,c).rem(f.a);
            swap(FS[j--], FS.back());
            FS.pop_back();
        }
    }
    int nw = sz(FS);
    rep(j,0,nw) {
        F f = FS[j];
#define C(a, b, c) if (E(a,b).cnt() != 2) mf(f.a, f.b, i, f.c);
        C(a, b, c); C(a, c, b); C(b, c, a);
    }
    for (F& it : FS) if ((A[it.b] - A[it.a]).cross(
        A[it.c] - A[it.a]).dot(it.q) <= 0) swap(it.c, it.b);
    return FS;
};
```

### sphericalDistance.h

**Description:** Returns the shortest distance on the sphere with radius  $r$ adius between the points with azimuthal angles (longitude)  $f_1$  ( $\phi_1$ ) and  $f_2$  ( $\phi_2$ ) from  $x$  axis and zenith angles (latitude)  $t_1$  ( $\theta_1$ ) and  $t_2$  ( $\theta_2$ ) from  $z$  axis ( $0 =$  north pole). All angles measured in radians. The algorithm starts by converting the spherical coordinates to cartesian coordinates so if that is what you have you can use only the two last rows.  $dx*$ radius is then the difference between the two points in the  $x$  direction and  $d*$ radius is the total distance between the points.

```
611f07, 8 lines
double sphericalDistance(double f1, double t1,
    double f2, double t2, double radius) {
    double dx = sin(t2)*cos(f2) - sin(t1)*cos(f1);
    double dy = sin(t2)*sin(f2) - sin(t1)*sin(f1);
    double dz = cos(t2) - cos(t1);
    double d = sqrt(dx*dx + dy*dy + dz*dz);
    return radius*2*asin(d/2);
}
```

## Strings (9)

### KMP.h

**Description:**  $pi[x]$  computes the length of the longest prefix of  $s$  that ends at  $x$ , other than  $s[0..x]$  itself (abacaba -> 0010123). Can be used to find all occurrences of a string.

**Time:**  $\mathcal{O}(n)$

```
d4375c, 16 lines
vi pi(const string& s) {
    vi p(sz(s));
    rep(i,1,sz(s)) {
        int g = p[i-1];
```

```
        while (g && s[i] != s[g]) g = p[g-1];
        p[i] = g + (s[i] == s[g]);
    }
    return p;
}

vi match(const string& s, const string& pat) {
    vi p = pi(pat + '\0' + s), res;
    rep(i,sz(p)-sz(s),sz(p))
        if (p[i] == sz(pat)) res.push_back(i - 2 * sz(pat));
    return res;
}
```

### Zfunc.h

**Description:**  $z[x]$  computes the length of the longest common prefix of  $s[i:]$  and  $s$ , except  $z[0] = 0$ . (abacaba -> 0010301)

**Time:**  $\mathcal{O}(n)$

```
e09e2, 12 lines
vi Z(const string& S) {
    vi z(sz(S));
    int l = -1, r = -1;
    rep(i,1,sz(S)) {
        z[i] = i >= r ? 0 : min(r - i, z[i - l]);
        while (i + z[i] < sz(S) && S[i + z[i]] == S[z[i]])
            z[i]++;
        if (i + z[i] > r)
            l = i, r = i + z[i];
    }
    return z;
}
```

### Manacher.h

**Description:** For each position in a string, computes  $p[0][i] =$  half length of longest even palindrome around pos  $i$ ,  $p[1][i] =$  longest odd (half rounded down).

**Time:**  $\mathcal{O}(N)$

```
e7ad79, 13 lines
array<vi, 2> manacher(const string& s) {
    int n = sz(s);
    array<vi,2> p = {vi(n+1), vi(n)};
    rep(z,0,2) for (int i=0,l=0,r=0; i < n; i++) {
        int t = r-i+!z;
        if (i<r) p[z][i] = min(t, p[z][l+t]);
        int L = i-p[z][i], R = i+p[z][i]-!z;
        while (L>=1 && R+1<n && s[L-1] == s[R+1])
            p[z][i]++, L--, R++;
        if (R>r) l=L, r=R;
    }
    return p;
}
```

### MinRotation.h

**Description:** Finds the lexicographically smallest rotation of a string.

**Usage:** rotate(v.begin(), v.begin()+minRotation(v), v.end());

**Time:**  $\mathcal{O}(N)$

```
d07a42, 8 lines
int minRotation(string s) {
    int a=0, N=sz(s); s += s;
    rep(b,0,N) rep(k,0,N) {
        if (a+k == b || s[a+k] < s[b+k]) {b += max(0, k-1); break;}
        if (s[a+k] > s[b+k]) { a = b; break; }
    }
    return a;
}
```

### SuffixArray.h

**Description:** Builds suffix array for a string. `sa[i]` is the starting index of the suffix which is *i*'th in the sorted suffix array. The returned vector is of size  $n + 1$ , and `sa[0] = n`. The lcp array contains longest common prefixes for neighbouring strings in the suffix array: `lcp[i] = lcp(sa[i], sa[i-1])`, `lcp[0] = 0`. The input string must not contain any zero bytes.  
**Time:**  $\mathcal{O}(n \log n)$

38db9f, 23 lines

```
struct SuffixArray {
    vi sa, lcp;
    SuffixArray(string& s, int lim=256) { // or basic_string<int>
        int n = sz(s) + 1, k = 0, a, b;
        vi x(all(s)+1), y(n), ws(max(n, lim)), rank(n);
        sa = lcp = y, iota(all(sa), 0);
        for (int j = 0, p = 0; p < n; j = max(1, j * 2), lim = p) {
            p = j, iota(all(y), n - j);
            rep(i,0,n) if (sa[i] >= j) y[p++] = sa[i] - j;
            fill(all(ws), 0);
            rep(i,0,n) ws[x[i]]++;
            rep(i,1,lim) ws[i] += ws[i - 1];
            for (int i = n; i--;) sa[--ws[x[i]]] = y[i];
            swap(x, y), p = 1, x[sa[0]] = 0;
            rep(i,1,n) a = sa[i - 1], b = sa[i], x[b] =
                (y[a] == y[b] && y[a + j] == y[b + j]) ? p - 1 : p++;
        }
        rep(i,1,n) rank[sa[i]] = i;
        for (int i = 0, j; i < n - 1; lcp[rank[i++]] = k)
            for (k && k--, j = sa[rank[i] - 1];
                s[i + k] == s[j + k]; k++);
    }
};
```

## SuffixTree.h

**Description:** Ukkonen's algorithm for online suffix tree construction. Each node contains indices `[l, r]` into the string, and a list of child nodes. Suffixes are given by traversals of this tree, joining `[l, r]` substrings. The root is 0 (has `l = -1, r = 0`), non-existent children are -1. To get a complete tree, append a dummy symbol – otherwise it may contain an incomplete path (still useful for substring matching, though).

**Time:**  $\mathcal{O}(26N)$

aac0b8, 50 lines

```
struct SuffixTree {
    enum { N = 200010, ALPHA = 26 }; // N ~ 2*maxlen+10
    int toi(char c) { return c - 'a'; }
    string a; // v = cur node, q = cur position
    int t[N][ALPHA], l[N], r[N], p[N], s[N], v=0, q=0, m=2;

    void ukkadd(int i, int c) { suff:
        if (r[v]<=q) {
            if (t[v][c]==-1) { t[v][c]=m; l[m]=i;
                p[m++]=v; v=s[v]; q=r[v]; goto suff; }
            v=t[v][c]; q=l[v];
        }
        if (q==-1 || c==toi(a[q])) q++; else {
            l[m+1]=i; p[m+1]=m; l[m]=l[v]; r[m]=q;
            p[m]=p[v]; t[m][c]=m+1; t[m][toi(a[q])]=v;
            l[v]=q; p[v]=m; t[p[m]][toi(a[l[m])]]=m;
            v=s[p[m]]; q=l[m];
            while (q<r[m]) { v=t[v][toi(a[q])]; q+=r[v]-l[v]; }
            if (q==r[m]) s[m]=v; else s[m]=m+2;
            q=r[v]-(q-r[m]); m+=2; goto suff;
        }
    }
};
```

```
SuffixTree(string a) : a(a) {
    fill(r,r+N,sz(a));
    memset(s, 0, sizeof s);
    memset(t, -1, sizeof t);
    fill(t[1],t[1]+ALPHA,0);
    s[0] = 1; l[0] = l[1] = -1; r[0] = r[1] = p[0] = p[1] = 0;
    rep(i,0,sz(a)) ukkadd(i, toi(a[i]));
}
```

```
}

// example: find longest common substring (uses ALPHA = 28)
pii best;
int lcs(int node, int i1, int i2, int olen) {
    if (l[node] <= i1 && i1 < r[node]) return 1;
    if (l[node] <= i2 && i2 < r[node]) return 2;
    int mask = 0, len = node ? olen + (r[node] - l[node]) : 0;
    rep(c,0,ALPHA) if (t[node][c] != -1)
        mask |= lcs(t[node][c], i1, i2, len);
    if (mask == 3)
        best = max(best, {len, r[node] - len});
    return mask;
}

static pii LCS(string s, string t) {
    SuffixTree st(s + (char)('z' + 1) + t + (char)('z' + 2));
    st.lcs(0, sz(s), sz(s) + 1 + sz(t), 0);
    return st.best;
}
};
```

## Hashing.h

**Description:** Self-explanatory methods for string hashing.

2d2a67, 44 lines

```
// Arithmetic mod 2^64-1. 2x slower than mod 2^64 and more
// code, but works on evil test data (e.g. Thue-Morse, where
// ABBA... and BAAB... of length 2^10 hash the same mod 2^64).
// "typedef ull H;" instead if you think test data is random,
// or work mod 10^9+7 if the Birthday paradox is not a problem.
typedef uint64_t ull;
struct H {
    ull x; H(ull x=0) : x(x) {}
    H operator+(H o) { return x + o.x + (x + o.x < x); }
    H operator-(H o) { return *this + ~o.x; }
    H operator*(H o) { auto m = (uint128_t)x * o.x;
        return H((ull)m) + (ull)(m >> 64); }
    ull get() const { return x + !~x; }
    bool operator==(H o) const { return get() == o.get(); }
    bool operator<(H o) const { return get() < o.get(); }
};

static const H C = (1ll)1e11+3; // (order ~ 3e9; random also ok)
```

```
struct HashInterval {
    vector<H> ha, pw;
    HashInterval(string& str) : ha(sz(str)+1), pw(ha) {
        pw[0] = 1;
        rep(i,0,sz(str))
            ha[i+1] = ha[i] * C + str[i],
            pw[i+1] = pw[i] * C;
    }
    H hashInterval(int a, int b) { // hash [a, b)
        return ha[b] - ha[a] * pw[b - a];
    }
};
```

```
vector<H> getHashes(string& str, int length) {
    if (sz(str) < length) return {};
    H h = 0, pw = 1;
    rep(i,0,length)
        h = h * C + str[i], pw = pw * C;
    vector<H> ret = {h};
    rep(i,length,sz(str)) {
        ret.push_back(h = h * C + str[i] - pw * str[i-length]);
    }
    return ret;
}
```

H hashString(string& s){H h{}; for(char c:s) h=h\*C+c;return h;}

## AhoCorasick.h

**Description:** Aho-Corasick automaton, used for multiple pattern matching. Initialize with AhoCorasick `ac(patterns)`; the automaton start node will be at index 0. `find(word)` returns for each position the index of the longest word that ends there, or -1 if none. `findAll(–, word)` finds all words (up to  $N\sqrt{N}$  many if no duplicate patterns) that start at each position (shortest first). Duplicate patterns are allowed; empty patterns are not. To find the longest words that start at each position, reverse all input. For large alphabets, split each symbol into chunks, with sentinel bits for symbol boundaries.

**Time:** construction takes  $\mathcal{O}(26N)$ , where  $N$  = sum of length of patterns. `find(x)` is  $\mathcal{O}(N)$ , where  $N$  = length of `x`. `findAll` is  $\mathcal{O}(NM)$ .

f35677, 66 lines

```
struct AhoCorasick {
    enum {alpha = 26, first = 'A'}; // change this!
    struct Node {
        // (nmatches is optional)
        int back, next[alpha], start = -1, end = -1, nmatches = 0;
        Node(int v) { memset(next, v, sizeof(next)); }
    };
    vector<Node> N;
    vi backp;
    void insert(string& s, int j) {
        assert(!s.empty());
        int n = 0;
        for (char c : s) {
            int& m = N[n].next[c - first];
            if (m == -1) { n = m = sz(N); N.emplace_back(-1); }
            else n = m;
        }
        if (N[n].end == -1) N[n].start = j;
        backp.push_back(N[n].end);
        N[n].end = j;
        N[n].nmatches++;
    }
    AhoCorasick(vector<string>& pat) : N(1, -1) {
        rep(i,0,sz(pat)) insert(pat[i], i);
        N[0].back = sz(N);
        N.emplace_back(0);

        queue<int> q;
        for (q.push(0); !q.empty(); q.pop()) {
            int n = q.front(), prev = N[n].back;
            rep(i,0,alpha) {
                int &ed = N[n].next[i], y = N[prev].next[i];
                if (ed == -1) ed = y;
                else {
                    N[ed].back = y;
                    (N[ed].end == -1 ? N[ed].end : backp[N[ed].start])
                        = N[y].end;
                    N[ed].nmatches += N[y].nmatches;
                    q.push(ed);
                }
            }
        }
    }
    vi find(string word) {
        int n = 0;
        vi res; // ll count = 0;
        for (char c : word) {
            n = N[n].next[c - first];
            res.push_back(N[n].end);
            // count += N[n].nmatches;
        }
        return res;
    }
    vector<vi> findAll(vector<string>& pat, string word) {
        vi r = find(word);
        vector<vi> res(sz(word));
        rep(i,0,sz(word)) {
```

```
int ind = r[i];
while (ind != -1) {
    res[i - sz(pat[ind]) + 1].push_back(ind);
    ind = backp[ind];
}
}
return res;
}
};
```

## Various (10)

### 10.1 Intervals

**IntervalContainer.h**  
**Description:** Add and remove intervals from a set of disjoint intervals. Will merge the added interval with any overlapping intervals in the set when adding. Intervals are [inclusive, exclusive).  
**Time:**  $\mathcal{O}(\log N)$

```
set<pii>::iterator addInterval(set<pii>& is, int L, int R) {
    if (L == R) return is.end();
    auto it = is.lower_bound({L, R}), before = it;
    while (it != is.end() && it->first <= R) {
        R = max(R, it->second);
        before = it = is.erase(it);
    }
    if (it != is.begin() && (--it)->second >= L) {
        L = min(L, it->first);
        R = max(R, it->second);
        is.erase(it);
    }
    return is.insert(before, {L,R});
}
```

```
void removeInterval(set<pii>& is, int L, int R) {
    if (L == R) return;
    auto it = addInterval(is, L, R);
    auto r2 = it->second;
    if (it->first == L) is.erase(it);
    else (int&)it->second = L;
    if (R != r2) is.emplace(R, r2);
}
```

**IntervalCover.h**  
**Description:** Compute indices of smallest set of intervals covering another interval. Intervals should be [inclusive, exclusive). To support [inclusive, inclusive], change (A) to add || R.empty(). Returns empty set on failure (or if G is empty).  
**Time:**  $\mathcal{O}(N \log N)$

```
template<class T>
vi cover(pair<T, T> G, vector<pair<T, T>> I) {
    vi S(sz(I)), R;
    iota(all(S), 0);
    sort(all(S), [&](int a, int b) { return I[a] < I[b]; });
    T cur = G.first;
    int at = 0;
    while (cur < G.second) { //(A)
        pair<T, int> mx = make_pair(cur, -1);
        while (at < sz(I) && I[S[at]].first <= cur) {
            mx = max(mx, make_pair(I[S[at]].second, S[at]));
            at++;
        }
        if (mx.second == -1) return {};
        cur = mx.first;
        R.push_back(mx.second);
    }
}
```

```
return R;
}
```

**ConstantIntervals.h**  
**Description:** Split a monotone function on [from, to) into a minimal set of half-open intervals on which it has the same value. Runs a callback g for each such interval.  
**Usage:** constantIntervals(0, sz(v), [&](int x){return v[x];}, [&](int lo, int hi, T val){...});  
**Time:**  $\mathcal{O}(k \log \frac{n}{k})$

```
template<class F, class G, class T>
void rec(int from, int to, F& f, G& g, int& i, T& p, T q) {
    if (p == q) return;
    if (from == to) {
        g(i, to, p);
        i = to; p = q;
    } else {
        int mid = (from + to) >> 1;
        rec(from, mid, f, g, i, p, f(mid));
        rec(mid+1, to, f, g, i, p, q);
    }
}
template<class F, class G>
void constantIntervals(int from, int to, F f, G g) {
    if (to <= from) return;
    int i = from; auto p = f(i), q = f(to-1);
    rec(from, to-1, f, g, i, p, q);
    g(i, to, q);
}
```

### 10.2 Misc. algorithms

**LIS.h**  
**Description:** Compute indices for the longest increasing subsequence.  
**Time:**  $\mathcal{O}(N \log N)$

```
template<class I> vi lis(const vector<I>& S) {
    if (S.empty()) return {};
    vi prev(sz(S));
    typedef pair<I, int> p;
    vector<p> res;
    rep(i,0,sz(S)) {
        // change 0 -> i for longest non-decreasing subsequence
        auto it = lower_bound(all(res), p{S[i], 0});
        if (it == res.end()) res.emplace_back(), it = res.end()-1;
        *it = {S[i], i};
        prev[i] = it == res.begin() ? 0 : (it-1)->second;
    }
    int L = sz(res), cur = res.back().second;
    vi ans(L);
    while (L--) ans[L] = cur, cur = prev[cur];
    return ans;
}
```

**FastKnapsack.h**  
**Description:** Given N non-negative integer weights w and a non-negative target t, computes the maximum S <= t such that S is the sum of some subset of the weights.  
**Time:**  $\mathcal{O}(N \max(w_i))$

```
int knapsack(vi w, int t) {
    int a = 0, b = 0, x;
    while (b < sz(w) && a + w[b] <= t) a += w[b++];
    if (b == sz(w)) return a;
    int m = *max_element(all(w));
    vi u, v(2*m, -1);
    v[a+m-t] = b;
    rep(i,b,sz(w)) {
        u = v;
```

```
rep(x,0,m) v[x+w[i]] = max(v[x+w[i]], u[x]);
for (x = 2*m; --x > m;) rep(j, max(0,u[x]), v[x])
    v[x-w[j]] = max(v[x-w[j]], j);
}
for (a = t; v[a+m-t] < 0; a--);
return a;
}
```

### 10.3 Dynamic programming

**KnuthDP.h**  
**Description:** When doing DP on intervals:  $a[i][j] = \min_{i < k < j} (a[i][k] + a[k][j]) + f(i, j)$ , where the (minimal) optimal  $k$  increases with both  $i$  and  $j$ , one can solve intervals in increasing order of length, and search  $k = p[i][j]$  for  $a[i][j]$  only between  $p[i][j - 1]$  and  $p[i + 1][j]$ . This is known as Knuth DP. Sufficient criteria for this are if  $f(b, c) \leq f(a, d)$  and  $f(a, c) + f(b, d) \leq f(a, d) + f(b, c)$  for all  $a \leq b \leq c \leq d$ . Consider also: LineContainer (ch. Data structures), monotone queues, ternary search.  
**Time:**  $\mathcal{O}(N^2)$

**DivideAndConquerDP.h**  
**Description:** Given  $a[i] = \min_{lo(i) \leq k < hi(i)} (f(i, k))$  where the (minimal) optimal  $k$  increases with  $i$ , computes  $a[i]$  for  $i = L..R - 1$ .  
**Time:**  $\mathcal{O}((N + (hi - lo)) \log N)$

```
struct DP { // Modify at will:
    int lo(int ind) { return 0; }
    int hi(int ind) { return ind; }
    ll f(int ind, int k) { return dp[ind][k]; }
    void store(int ind, int k, ll v) { res[ind] = pii(k, v); }

    void rec(int L, int R, int LO, int HI) {
        if (L >= R) return;
        int mid = (L + R) >> 1;
        pair<ll, int> best (LLONG_MAX, LO);
        rep(k, max(LO, lo(mid)), min(HI, hi(mid)))
            best = min(best, make_pair(f(mid, k), k));
        store(mid, best.second, best.first);
        rec(L, mid, LO, best.second+1);
        rec(mid+1, R, best.second, HI);
    }
    void solve(int L, int R) { rec(L, R, INT_MIN, INT_MAX); }
};
```

### 10.4 Debugging tricks

- signal(SIGSEGV, [](int) { \_Exit(0); }); converts segfaults into Wrong Answers. Similarly one can catch SIGABRT (assertion failures) and SIGFPE (zero divisions). \_GLIBCXX\_DEBUG failures generate SIGABRT (or SIGSEGV on gcc 5.4.0 apparently).
- feenableexcept(29); kills the program on NaNs (1), 0-divs (4), infinities (8) and denormals (16).

### 10.5 Optimization tricks

\_\_builtin\_ia32\_ldmxcsr(40896); disables denormals (which make floats 20x slower near their minimum value).

#### 10.5.1 Bit hacks

- x & -x is the least bit in x.
- for (int x = m; x; ) { --x &= m; ... } loops over all subset masks of m (except m itself).

- `c = x&-x, r = x+c; (((r^x) >> 2)/c) | r` is the next number after `x` with the same number of bits set.
- `rep(b,0,K) rep(i,0,(1 << K))`  
if `(i & 1 << b) D[i] += D[i^(1 << b)];`  
computes all sums of subsets.

### 10.5.2 Pragma

- **#pragma** `GCC optimize ("Ofast")` will make GCC auto-vectorize loops and optimizes floating points better.
- **#pragma** `GCC target ("avx2")` can double performance of vectorized code, but causes crashes on old machines.
- **#pragma** `GCC optimize ("trapv")` kills the program on integer overflows (but is really slow).

# Techniques (A)

techniques.txt

159 lines

Recursion

Divide and conquer

Finding interesting points in N log N

Algorithm analysis

Master theorem

Amortized time complexity

Greedy algorithm

Scheduling

Max contiguous subvector sum

Invariants

Huffman encoding

Graph theory

Dynamic graphs (extra book-keeping)

Breadth first search

Depth first search

\* Normal trees / DFS trees

Dijkstra’s algorithm

MST: Prim’s algorithm

Bellman-Ford

Konig’s theorem and vertex cover

Min-cost max flow

Lovasz toggle

Matrix tree theorem

Maximal matching, general graphs

Hopcroft-Karp

Hall’s marriage theorem

Graphical sequences

Floyd-Warshall

Euler cycles

Flow networks

\* Augmenting paths

\* Edmonds-Karp

Bipartite matching

Min. path cover

Topological sorting

Strongly connected components

2-SAT

Cut vertices, cut-edges and biconnected components

Edge coloring

\* Trees

Vertex coloring

\* Bipartite graphs (=> trees)

\* 3^n (special case of set cover)

Diameter and centroid

K’t h shortest path

Shortest cycle

Dynamic programming

Knapsack

Coin change

Longest common subsequence

Longest increasing subsequence

Number of paths in a dag

Shortest path in a dag

Dynprog over intervals

Dynprog over subsets

Dynprog over probabilities

Dynprog over trees

3^n set cover

Divide and conquer

Knuth optimization

Convex hull optimizations

RMQ (sparse table a.k.a 2^k-jumps)

Bitonic cycle

Log partitioning (loop over most restricted)

Combinatorics

Computation of binomial coefficients

Pigeon-hole principle

Inclusion/exclusion

Catalan number

Pick’s theorem

Number theory

Integer parts

Divisibility

Euclidean algorithm

Modular arithmetic

\* Modular multiplication

\* Modular inverses

\* Modular exponentiation by squaring

Chinese remainder theorem

Fermat’s little theorem

Euler’s theorem

Phi function

Frobenius number

Quadratic reciprocity

Pollard-Rho

Miller-Rabin

Hensel lifting

Vieta root jumping

Game theory

Combinatorial games

Game trees

Mini-max

Nim

Games on graphs

Games on graphs with loops

Grundy numbers

Bipartite games without repetition

General games without repetition

Alpha-beta pruning

Probability theory

Optimization

Binary search

Ternary search

Unimodality and convex functions

Binary search on derivative

Numerical methods

Numeric integration

Newton’s method

Root-finding with binary/ternary search

Golden section search

Matrices

Gaussian elimination

Exponentiation by squaring

Sorting

Radix sort

Geometry

Coordinates and vectors

\* Cross product

\* Scalar product

Convex hull

Polygon cut

Closest pair

Coordinate-compression

Quadtrees

KD-trees

All segment-segment intersection

Sweeping

Discretization (convert to events and sweep)

Angle sweeping

Line sweeping

Discrete second derivatives

Strings

Longest common substring

Palindrome subsequences

Knuth-Morris-Pratt

Tries

Rolling polynomial hashes

Suffix array

Suffix tree

Aho-Corasick

Manacher’s algorithm

Letter position lists

Combinatorial search

Meet in the middle

Brute-force with pruning

Best-first (A\*)

Bidirectional search

Iterative deepening DFS / A\*

Data structures

LCA (2^k-jumps in trees in general)

Pull/push-technique on trees

Heavy-light decomposition

Centroid decomposition

Lazy propagation

Self-balancing trees

Convex hull trick (wcipeg.com/wiki/Convex\_hull\_trick)

Monotone queues / monotone stacks / sliding queues

Sliding queue using 2 stacks

Persistent segment tree