

Polyspace Bug Finder

Detailed Report for Project: lan8720

Report Author: LibDriver

Polyspace Bug Finder: Detailed Report for Project: lan8720

by Report Author: LibDriver

Published 12-Aug-2023 17:16:34

Analysis Author(s): libdriver

Polyspace Version(s): Polyspace Bug Finder 3.2 (R2020a)

Project Version(s): 1.0

Result Folder(s):

E:\Polyspace\lan8720\Module\BF_Result

Table of Contents

Chapter 1. Polyspace Bug Finder Summary.....	1
Chapter 2. MISRA C:2012 Guidelines.....	2
MISRA C:2012 Guidelines Summary - Violations by File	2
MISRA C:2012 Guidelines Violations	2
Chapter 3. Defects	114
Defects	114
Chapter 4. Appendix 1 - Configuration Settings.....	115
Polyspace Settings	115
Coding Standard Configuration	116
Chapter 5. Appendix 2 - Definitions.....	124

Chapter 1. Polyspace Bug Finder Summary

Table 1.1. Project Summary

	Count	Reviewed	Unreviewed	Pass/Fail
MISRA C:2012 Guidelines	536	536	0	Pass
Defects	0	0	0	Pass
Total	536	536	0	Pass

Table 1.2. Summary By File

File	Defects (Reviewed)	MISRA C:2012 Guidelines (Reviewed)
E:\Github\lan8720\src\driver_lan8720.c	0 (0)	536 (536)
E:\Github\lan8720\src\driver_lan8720.h	0 (0)	0 (0)

Chapter 2. MISRA C:2012 Guidelines

MISRA C:2012 Guidelines Summary - Violations by File

File	Total
E:\Github\lan8720\src\driver_lan8720.c	536
Total	536

MISRA C:2012 Guidelines Violations

Table 2.1. E:\Github\lan8720\src\driver_lan8720.c

ID	Guideline	Message	Function	Severity	Status	Comment
381	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_set_address()	Low	Justified	(handle == NULL)checked.
382	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_set_address()	Low	Justified	(handle == NULL)checked.
383	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_address()	Low	Justified	(handle == NULL)checked.
384	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_address()	Low	Justified	(handle == NULL)checked.
385	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_init()	Low	Justified	(handle == NULL)checked.

45	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	lan8720_init()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
7	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	lan8720_init()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
1	12.2	The right hand operand of a shift operator shall lie in the range zero to one less than the width in bits of the essential type of the left hand operand.	lan8720_init()	Low	Justified	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
4	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	lan8720_init()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
29	10.1	Operands shall not be of an inappropriate essential type. The right operand of the = operator is of an inappropriate essential type category signed.	lan8720_init()	Low	Not a defect	Embedded drivers need this method

						to set or clear some bits and drivers guarantee the safety of the operation.
30	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	lan8720_init()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
18	12.2	The right hand operand of a shift operator shall lie in the range zero to one less than the width in bits of the essential type of the left hand operand.	lan8720_init()	Low	Justified	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
23	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	lan8720_init()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
37	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the & operator has essentially unsigned type while the right operand has essentially signed type.	lan8720_init()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers

						guarantee the safety of the operation.
63	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_init()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
25 2	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	lan8720_init()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
29 6	12.2	The right hand operand of a shift operator shall lie in the range zero to one less than the width in bits of the essential type of the left hand operand.	lan8720_init()	Low	Justified	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
38 6	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_deinit()	Low	Justified	(handle == NULL)checked.
25	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	lan8720_deinit()	Low	Not a defect	Embedded drivers need this method to set or clear some bits

						and drivers guarantee the safety of the operation.
41	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	lan8720_deinit()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
14	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	lan8720_deinit()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
20	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	lan8720_deinit()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
16 6	12.2	The right hand operand of a shift operator shall lie in the range zero to one less than the width in bits of the essential type of the left hand operand.	lan8720_deinit()	Low	Justified	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the

						operation.
53	10.1	Operands shall not be of an inappropriate essential type. The right operand of the = operator is of an inappropriate essential type category signed.	lan8720_deinit()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
42	12.2	The right hand operand of a shift operator shall lie in the range zero to one less than the width in bits of the essential type of the left hand operand.	lan8720_deinit()	Low	Justified	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
44	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	lan8720_deinit()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
38 7	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_set_soft_reset()	Low	Justified	(handle == NULL)checked.
17 0	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	lan8720_set_soft_reset()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the

						safety of the operation.
60	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	lan8720_set_soft_reset()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
50	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	lan8720_set_soft_reset()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
58	12.2	The right hand operand of a shift operator shall lie in the range zero to one less than the width in bits of the essential type of the left hand operand.	lan8720_set_soft_reset()	Low	Justified	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
2	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the = operator has essentially unsigned type while the right operand has essentially enum type.	lan8720_set_soft_reset()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.

59	10.1	Operands shall not be of an inappropriate essential type. The right operand of the = operator is of an inappropriate essential type category enum.	lan8720_set_soft_reset()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
163	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	lan8720_set_soft_reset()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
239	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	lan8720_set_soft_reset()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
388	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_soft_reset()	Low	Justified	(handle == NULL)checked.
389	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_soft_reset()	Low	Justified	(handle == NULL)checked.
24	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category	lan8720_get_soft_reset()	Low	Not a defect	We use enumeration to define

		unsigned shall not be cast to the different essential type category enum.				driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
11	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_soft_reset()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
390	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_set_loop_back()	Low	Justified	(handle == NULL)checked.
181	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	lan8720_set_loop_back()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
205	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	lan8720_set_loop_back()	Low	Not a defect	Embedded drivers need this method to set or clear some bits

						and drivers guarantee the safety of the operation.
64	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	lan8720_set_loop_back()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
34	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	lan8720_set_loop_back()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
31 7	12.2	The right hand operand of a shift operator shall lie in the range zero to one less than the width in bits of the essential type of the left hand operand.	lan8720_set_loop_back()	Low	Justified	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
9	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the = operator has essentially unsigned type while the right operand has essentially enum type.	lan8720_set_loop_back()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the

						operation.
35	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	lan8720_set_loop_back()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
22 3	10.1	Operands shall not be of an inappropriate essential type. The right operand of the = operator is of an inappropriate essential type category enum.	lan8720_set_loop_back()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
49	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	lan8720_set_loop_back()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
39 1	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_loop_back()	Low	Justified	(handle == NULL)checked.
39 2	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_loop_back()	Low	Justified	(handle == NULL)checked.
68	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type.	lan8720_get_loop_back()	Low	Not a defect	We use enumeration

		The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.				to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
32 2	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_loop_back()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
39 3	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_set_speed_select()	Low	Justified	(handle == NULL)checked.
31	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	lan8720_set_speed_select()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
52	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	lan8720_set_speed_select()	Low	Not a defect	Embedded drivers need this method to set or clear

						some bits and drivers guarantee the safety of the operation.
69	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	lan8720_set_speed_select()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
6	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	lan8720_set_speed_select()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
107	12.2	The right hand operand of a shift operator shall lie in the range zero to one less than the width in bits of the essential type of the left hand operand.	lan8720_set_speed_select()	Low	Justified	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
71	10.1	Operands shall not be of an inappropriate essential type. The right operand of the = operator is of an inappropriate essential type category enum.	lan8720_set_speed_select()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the

						safety of the operation.
110	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	lan8720_set_speed_select()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
215	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the = operator has essentially unsigned type while the right operand has essentially enum type.	lan8720_set_speed_select()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
341	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	lan8720_set_speed_select()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
394	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_speed_select()	Low	Justified	(handle == NULL)checked.
395	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_speed_select()	Low	Justified	(handle == NULL)checked.
25	10.8	The value of a composite expression shall not be cast to a different	lan8720_get_speed_select()	Low	Not a	We use

6		essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.			defect	enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
193	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_speed_select()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
396	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_set_auto_negotiation()	Low	Justified	(handle == NULL)checked.
57	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	lan8720_set_auto_negotiation()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
76	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	lan8720_set_auto_negotiation()	Low	Not a defect	Embedded drivers need this method

						to set or clear some bits and drivers guarantee the safety of the operation.
56	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	lan8720_set_auto_negotiation()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
116	12.2	The right hand operand of a shift operator shall lie in the range zero to one less than the width in bits of the essential type of the left hand operand.	lan8720_set_auto_negotiation()	Low	Justified	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
352	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	lan8720_set_auto_negotiation()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
27	10.1	Operands shall not be of an inappropriate essential type. The right operand of the = operator is of an inappropriate essential type category enum.	lan8720_set_auto_negotiation()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers

						guarantee the safety of the operation.
36	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	lan8720_set_auto_negotiation()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
114	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the = operator has essentially unsigned type while the right operand has essentially enum type.	lan8720_set_auto_negotiation()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
195	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	lan8720_set_auto_negotiation()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
397	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation()	Low	Justified	(handle == NULL)checked.
398	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation()	Low	Justified	(handle == NULL)checked.

22	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_auto_negotiation()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
15 5	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_auto_negotiation()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
39 9	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_set_power_down()	Low	Justified	(handle == NULL)checked.
79	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	lan8720_set_power_down()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
80	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category.	lan8720_set_power_down()	Low	Not a defect	Embedded drivers need

		The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)				this method to set or clear some bits and drivers guarantee the safety of the operation.
101	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	lan8720_set_power_down()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
78	12.2	The right hand operand of a shift operator shall lie in the range zero to one less than the width in bits of the essential type of the left hand operand.	lan8720_set_power_down()	Low	Justified	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
165	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	lan8720_set_power_down()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
15	10.1	Operands shall not be of an inappropriate essential type. The right operand of the = operator is of an inappropriate essential type category enum.	lan8720_set_power_down()	Low	Not a defect	Embedded drivers need this method to set or clear some bits

						and drivers guarantee the safety of the operation.
81	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	lan8720_set_power_down()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
157	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the = operator has essentially unsigned type while the right operand has essentially enum type.	lan8720_set_power_down()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
206	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	lan8720_set_power_down()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
400	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_power_down()	Low	Justified	(handle == NULL)checked.
401	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source.	lan8720_get_power_down()	Low	Justified	(handle == NULL)checked.

		Pointer may be NULL or may point to unknown memory.				
32 6	10.8	<p>The value of a composite expression shall not be cast to a different essential type category or a wider essential type.</p> <p>The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.</p>	lan8720_get_power_down()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
13 6	10.1	<p>Operands shall not be of an inappropriate essential type.</p> <p>The right operand of the & operator is of an inappropriate essential type category signed.</p>	lan8720_get_power_down()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
40 2	D4.14	<p>The validity of values received from external sources shall be checked.</p> <p>Dereferenced pointer is from an unsecure source.</p> <p>Pointer may be NULL or may point to unknown memory.</p>	lan8720_set_electrical_isolation()	Low	Justified	(handle == NULL)checked.
86	10.1	<p>Operands shall not be of an inappropriate essential type.</p> <p>The right operand of the &= operator is of an inappropriate essential type category signed.</p>	lan8720_set_electrical_isolation()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.

88	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	lan8720_set_electrical_isolation()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
85	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	lan8720_set_electrical_isolation()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
8	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	lan8720_set_electrical_isolation()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
19	12.2	The right hand operand of a shift operator shall lie in the range zero to one less than the width in bits of the essential type of the left hand operand.	lan8720_set_electrical_isolation()	Low	Justified	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
72	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category.	lan8720_set_electrical_isolation()	Low	Not a defect	Embedded drivers need this method

		The left operand of the = operator has essentially unsigned type while the right operand has essentially enum type.				to set or clear some bits and drivers guarantee the safety of the operation.
89	10.1	Operands shall not be of an inappropriate essential type. The right operand of the = operator is of an inappropriate essential type category enum.	lan8720_set_electrical_isolation()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
27 6	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	lan8720_set_electrical_isolation()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
17	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	lan8720_set_electrical_isolation()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
40 3	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_electrical_isolation()	Low	Justified	(handle == NULL)checked.
40	D4.14	The validity of values received from external sources shall be checked.	lan8720_get_electrical_isolation()	Low	Justified	(handle == NULL)checked.

4		Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.			d	d.
32 7	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_electrical_isolation()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
30 4	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_electrical_isolation()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
40 5	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_set_restart_auto_negotiate()	Low	Justified	(handle == NULL)checked.
14 9	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	lan8720_set_restart_auto_negotiate()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.

236	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	lan8720_set_restart_auto_negotiate()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
95	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	lan8720_set_restart_auto_negotiate()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
92	12.2	The right hand operand of a shift operator shall lie in the range zero to one less than the width in bits of the essential type of the left hand operand.	lan8720_set_restart_auto_negotiate()	Low	Justified	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
93	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	lan8720_set_restart_auto_negotiate()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
40	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an	lan8720_set_restart_auto_negotiate()	Low	Not a defect	Embedded drivers need this method

		object with a different essential type category (unsigned)				to set or clear some bits and drivers guarantee the safety of the operation.
91	10.1	Operands shall not be of an inappropriate essential type. The right operand of the = operator is of an inappropriate essential type category enum.	lan8720_set_restart_auto_negotiate()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
24 7	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the = operator has essentially unsigned type while the right operand has essentially enum type.	lan8720_set_restart_auto_negotiate()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
75	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	lan8720_set_restart_auto_negotiate()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
40 6	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_restart_auto_negotiate()	Low	Justified	(handle == NULL)checked.
40	D4.14	The validity of values received from external sources shall be checked.	lan8720_get_restart_auto_negotiate()	Low	Justified	(handle == NULL)checked.

7		Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.			d	d.
96	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_restart_auto_negotiate()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
22 5	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_restart_auto_negotiate()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
40 8	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_set_duplex_mode()	Low	Justified	(handle == NULL)checked.
16	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	lan8720_set_duplex_mode()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.

260	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	lan8720_set_duplex_mode()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
168	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	lan8720_set_duplex_mode()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
55	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	lan8720_set_duplex_mode()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
105	12.2	The right hand operand of a shift operator shall lie in the range zero to one less than the width in bits of the essential type of the left hand operand.	lan8720_set_duplex_mode()	Low	Justified	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
32	10.1	Operands shall not be of an inappropriate essential type. The right operand of the = operator is of an inappropriate essential type category enum.	lan8720_set_duplex_mode()	Low	Not a defect	Embedded drivers need this method

						to set or clear some bits and drivers guarantee the safety of the operation.
73	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the = operator has essentially unsigned type while the right operand has essentially enum type.	lan8720_set_duplex_mode()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
120	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	lan8720_set_duplex_mode()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
87	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	lan8720_set_duplex_mode()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
409	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_duplex_mode()	Low	Justified	(handle == NULL)checked.
41	D4.14	The validity of values received from external sources shall be checked.	lan8720_get_duplex_mode()	Low	Justified	(handle == NULL)checked.

0		Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.			d	d.
16 0	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_duplex_mode()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
61	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_duplex_mode()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
41 1	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_100base_t4()	Low	Justified	(handle == NULL)checked.
41 2	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_100base_t4()	Low	Justified	(handle == NULL)checked.
32 4	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category	lan8720_get_100base_t4()	Low	Not a defect	We use enumeration to define driver configuration,

		enum.				which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
128	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_100base_t4()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
413	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_100base_tx_full_duplex()	Low	Justified	(handle == NULL)checked.
414	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_100base_tx_full_duplex()	Low	Justified	(handle == NULL)checked.
335	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_100base_tx_full_duplex()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers

						guarantee the safety of the operation.
109	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_100base_tx_full_duplex()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
415	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_100base_tx_half_duplex()	Low	Justified	(handle == NULL)checked.
416	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_100base_tx_half_duplex()	Low	Justified	(handle == NULL)checked.
250	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_100base_tx_half_duplex()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
10	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_100base_tx_half_duplex()	Low	Not a defect	Embedded drivers need this method to set or clear

						some bits and drivers guarantee the safety of the operation.
417	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_10base_t_full_duplex()	Low	Justified	(handle == NULL)checked.
418	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_10base_t_full_duplex()	Low	Justified	(handle == NULL)checked.
243	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_10base_t_full_duplex()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
5	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_10base_t_full_duplex()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
41	D4.14	The validity of values received from external sources shall be checked.	lan8720_get_10base_t_half_duplex()	Low	Justified	(handle == NULL)checked.

9		Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.			d	d.
420	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_10base_t_half_duplex()	Low	Justified	(handle == NULL)checked.
70	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_10base_t_half_duplex()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
294	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_10base_t_half_duplex()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
421	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_100base_t2_full_duplex()	Low	Justified	(handle == NULL)checked.
422	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_100base_t2_full_duplex()	Low	Justified	(handle == NULL)checked.

97	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_100base_t2_full_duplex()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
34 3	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_100base_t2_full_duplex()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
42 3	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_100base_t2_half_duplex()	Low	Justified	(handle == NULL)checked.
42 4	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_100base_t2_half_duplex()	Low	Justified	(handle == NULL)checked.
28 7	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_100base_t2_half_duplex()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly

						programming method and should be accepted and drivers guarantee the safety of the operation.
29 5	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_100base_t2_half_duplex()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
42 5	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_extended_status_information()	Low	Justified	(handle == NULL)checked.
42 6	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_extended_status_information()	Low	Justified	(handle == NULL)checked.
34 7	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_extended_status_information()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the

						operation.
17 2	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_extended_status_information()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
42 7	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiate_complete()	Low	Justified	(handle == NULL)checked.
42 8	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiate_complete()	Low	Justified	(handle == NULL)checked.
16 4	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_auto_negotiate_complete()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
28 0	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_auto_negotiate_complete()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers

						guarantee the safety of the operation.
429	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_remote_fault()	Low	Justified	(handle == NULL)checked.
430	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_remote_fault()	Low	Justified	(handle == NULL)checked.
108	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_remote_fault()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
104	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_remote_fault()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
431	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source.	lan8720_get_auto_negotiate_ability()	Low	Justified	(handle == NULL)checked.

		Pointer may be NULL or may point to unknown memory.				
43 2	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiate_ability()	Low	Justified	(handle == NULL)checked.
21	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_auto_negotiate_ability()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
11 1	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_auto_negotiate_ability()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
43 3	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_link_status()	Low	Justified	(handle == NULL)checked.
43 4	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_link_status()	Low	Justified	(handle == NULL)checked.
14	10.8	The value of a composite expression shall not be cast to a different	lan8720_get_link_status()	Low	Not a	We use

7		essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.			defect	enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
21 2	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_link_status()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
43 5	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_jabber_detect()	Low	Justified	(handle == NULL)checked.
43 6	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_jabber_detect()	Low	Justified	(handle == NULL)checked.
24 8	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_jabber_detect()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming

						method and should be accepted and drivers guarantee the safety of the operation.
24 2	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_jabber_detect()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
43 7	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_extended_capabilities()	Low	Justified	(handle == NULL)checked.
43 8	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_extended_capabilities()	Low	Justified	(handle == NULL)checked.
11 2	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_extended_capabilities()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.

10 6	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_extended_capabilities()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
43 9	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_set_identifier()	Low	Justified	(handle == NULL)checked.
62	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type unsigned on 32 bits) is assigned to an object with a narrower essential type (unsigned on 16 bits)	lan8720_set_identifier()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
11 7	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_set_identifier()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
12 7	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type unsigned on 32 bits) is assigned to an object with a narrower essential type (unsigned on 16 bits)	lan8720_set_identifier()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the

						operation.
12 1	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_set_identifier()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
74	10.7	If a composite expression is used as one operand of an operator in which the usual arithmetic conversions are performed then the other operand shall not have wider essential type. The left operand of the operator shall not have wider essential type (unsigned on 32 bits) than the right operand (unsigned on 8 bits) which is a composite expression	lan8720_set_identifier()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
12 2	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_set_identifier()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
12 6	10.7	If a composite expression is used as one operand of an operator in which the usual arithmetic conversions are performed then the other operand shall not have wider essential type. The left operand of the operator shall not have wider essential type (unsigned on 32 bits) than the right operand (unsigned on 8 bits) which is a composite expression	lan8720_set_identifier()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
12	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential	lan8720_set_identifier()	Low	Not a	Embedded drivers need

5		type category signed.			defect	this method to set or clear some bits and drivers guarantee the safety of the operation.
440	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_identifier()	Low	Justified	(handle == NULL)checked.
441	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_identifier()	Low	Justified	(handle == NULL)checked.
156	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type uint16_t shall not be cast to the wider essential type uint32_t.	lan8720_get_identifier()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
130	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_identifier()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.

44 2	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_identifier()	Low	Justified	(handle == NULL)checked.
10 3	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type unsigned on 16 bits) is assigned to an object with a narrower essential type (unsigned on 8 bits)	lan8720_get_identifier()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
31 9	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_identifier()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
44 3	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_identifier()	Low	Justified	(handle == NULL)checked.
22 8	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type unsigned on 16 bits) is assigned to an object with a narrower essential type (unsigned on 8 bits)	lan8720_get_identifier()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
17 5	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_identifier()	Low	Not a defect	Embedded drivers need this method

						to set or clear some bits and drivers guarantee the safety of the operation.
44 4	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_set_auto_negotiation_advertisement_remote_fault()	Low	Justified	(handle == NULL)checked.
51	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	lan8720_set_auto_negotiation_advertisement_remote_fault()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
13 8	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	lan8720_set_auto_negotiation_advertisement_remote_fault()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
13 7	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	lan8720_set_auto_negotiation_advertisement_remote_fault()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
14	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential	lan8720_set_auto_negotiation_advertisement_remote_fault()	Low	Not a	Embedded drivers need

2		type category signed.			defect	this method to set or clear some bits and drivers guarantee the safety of the operation.
229	12.2	The right hand operand of a shift operator shall lie in the range zero to one less than the width in bits of the essential type of the left hand operand.	lan8720_set_auto_negotiation_advertisement_remote_fault()	Low	Justified	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
115	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	lan8720_set_auto_negotiation_advertisement_remote_fault()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
135	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the = operator has essentially unsigned type while the right operand has essentially enum type.	lan8720_set_auto_negotiation_advertisement_remote_fault()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
342	10.1	Operands shall not be of an inappropriate essential type. The right operand of the = operator is of an inappropriate essential type category enum.	lan8720_set_auto_negotiation_advertisement_remote_fault()	Low	Not a defect	Embedded drivers need this method to set or clear some bits

						and drivers guarantee the safety of the operation.
314	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	lan8720_set_auto_negotiation_advertisement_remote_fault()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
445	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_advertisement_remote_fault()	Low	Justified	(handle == NULL)checked.
446	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_advertisement_remote_fault()	Low	Justified	(handle == NULL)checked.
140	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_auto_negotiation_advertisement_remote_fault()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
233	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential	lan8720_get_auto_negotiation_advertisement_remote_fault()	Low	Not a defect	Embedded drivers need this method

		type category signed.				to set or clear some bits and drivers guarantee the safety of the operation.
36 7	5.1	External identifiers shall be distinct. External function lan8720_set_auto_negotiation_advertisement_pause conflicts with the external identifier lan8720_set_auto_negotiation_advertisement_remote_fault (driver_lan8720.c line 1664).	File Scope	Low	Justified	Distinct.
44 7	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_set_auto_negotiation_advertisement_pause()	Low	Justified	(handle == NULL)checked.
12 9	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	lan8720_set_auto_negotiation_advertisement_pause()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
20 8	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	lan8720_set_auto_negotiation_advertisement_pause()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
94	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	lan8720_set_auto_negotiation_advertisement_pause()	Low	Not a defect	Embedded drivers need this method to set or clear some bits

						and drivers guarantee the safety of the operation.
185	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	lan8720_set_auto_negotiation_advertisement_pause()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
255	12.2	The right hand operand of a shift operator shall lie in the range zero to one less than the width in bits of the essential type of the left hand operand.	lan8720_set_auto_negotiation_advertisement_pause()	Low	Justified	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
90	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the = operator has essentially unsigned type while the right operand has essentially enum type.	lan8720_set_auto_negotiation_advertisement_pause()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
152	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	lan8720_set_auto_negotiation_advertisement_pause()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the

						operation.
29 2	10.1	Operands shall not be of an inappropriate essential type. The right operand of the = operator is of an inappropriate essential type category enum.	lan8720_set_auto_negotiation_advertisement_pause()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
14 1	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	lan8720_set_auto_negotiation_advertisement_pause()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
36 4	5.1	External identifiers shall be distinct. External function lan8720_get_auto_negotiation_advertisement_pause conflicts with the external identifier lan8720_get_auto_negotiation_advertisement_remote_fault (driver_lan8720.c line 1709).	File Scope	Low	Justified	Distinct.
44 8	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_advertisement_pause()	Low	Justified	(handle == NULL)checked.
44 9	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_advertisement_pause()	Low	Justified	(handle == NULL)checked.
21 7	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_auto_negotiation_advertisement_pause()	Low	Not a defect	We use enumeration to define driver configuration,

						which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
145	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_auto_negotiation_advertisement_pause()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
368	5.1	External identifiers shall be distinct. External function lan8720_set_auto_negotiation_advertisement_100base_tx_full_duplex conflicts with the external identifier lan8720_set_auto_negotiation_advertisement_remote_fault (driver_lan8720.c line 1664).	File Scope	Low	Justified	Distinct.
450	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_set_auto_negotiation_advertisement_100base_tx_full_duplex()	Low	Justified	(handle == NULL)checked.
38	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	lan8720_set_auto_negotiation_advertisement_100base_tx_full_duplex()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.

23 5	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	lan8720_set_auto_negotiation_advertisement_100base_tx_full_duplex()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
22 2	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	lan8720_set_auto_negotiation_advertisement_100base_tx_full_duplex()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
14 8	12.2	The right hand operand of a shift operator shall lie in the range zero to one less than the width in bits of the essential type of the left hand operand.	lan8720_set_auto_negotiation_advertisement_100base_tx_full_duplex()	Low	Justified	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
27 8	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	lan8720_set_auto_negotiation_advertisement_100base_tx_full_duplex()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
15 3	10.1	Operands shall not be of an inappropriate essential type. The right operand of the = operator is of an inappropriate essential type category enum.	lan8720_set_auto_negotiation_advertisement_100base_tx_full_duplex()	Low	Not a defect	Embedded drivers need this method

						to set or clear some bits and drivers guarantee the safety of the operation.
230	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	lan8720_set_auto_negotiation_advertisement_100base_tx_full_duplex()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
309	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the = operator has essentially unsigned type while the right operand has essentially enum type.	lan8720_set_auto_negotiation_advertisement_100base_tx_full_duplex()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
158	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	lan8720_set_auto_negotiation_advertisement_100base_tx_full_duplex()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
378	5.1	External identifiers shall be distinct. External function lan8720_get_auto_negotiation_advertisement_100base_tx_full_duplex conflicts with the external identifier lan8720_get_auto_negotiation_advertisement_remote_fault (driver_lan8720.c line 1709).	File Scope	Low	Justified	Distinct.

45 1	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_advertisement_100base_tx_full_duplex()	Low	Justified	(handle == NULL)checked.
45 2	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_advertisement_100base_tx_full_duplex()	Low	Justified	(handle == NULL)checked.
16 1	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_auto_negotiation_advertisement_100base_tx_full_duplex()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
12	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_auto_negotiation_advertisement_100base_tx_full_duplex()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
36 2	5.1	External identifiers shall be distinct. External function lan8720_set_auto_negotiation_advertisement_100base_tx conflicts with the external identifier lan8720_set_auto_negotiation_advertisement_remote_fault (driver_lan8720.c line 1664).	File Scope	Low	Justified	Distinct.

453	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_set_auto_negotiation_advertisement_100base_tx()	Low	Justified	(handle == NULL)checked.
273	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	lan8720_set_auto_negotiation_advertisement_100base_tx()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
288	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	lan8720_set_auto_negotiation_advertisement_100base_tx()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
162	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	lan8720_set_auto_negotiation_advertisement_100base_tx()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
26	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	lan8720_set_auto_negotiation_advertisement_100base_tx()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the

						operation.
43	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	lan8720_set_auto_negotiation_advertisement_100base_tx()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
17 4	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the = operator has essentially unsigned type while the right operand has essentially enum type.	lan8720_set_auto_negotiation_advertisement_100base_tx()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
26 6	10.1	Operands shall not be of an inappropriate essential type. The right operand of the = operator is of an inappropriate essential type category enum.	lan8720_set_auto_negotiation_advertisement_100base_tx()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
26 9	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	lan8720_set_auto_negotiation_advertisement_100base_tx()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
36	5.1	External identifiers shall be distinct. External function	File Scope	Low	Justifie	Distinct.

9		lan8720_get_auto_negotiation_advertisement_100base_tx conflicts with the external identifier lan8720_get_auto_negotiation_advertisement_remote_fault (driver_lan8720.c line 1709).			d	
454	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_advertisement_100base_tx()	Low	Justified	(handle == NULL)checked.
455	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_advertisement_100base_tx()	Low	Justified	(handle == NULL)checked.
176	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_auto_negotiation_advertisement_100base_tx()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
28	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_auto_negotiation_advertisement_100base_tx()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
370	5.1	External identifiers shall be distinct. External function lan8720_set_auto_negotiation_advertisement_10base_t_full_duplex	File Scope	Low	Justified	Distinct.

		conflicts with the external identifier lan8720_set_auto_negotiation_advertisement_remote_fault (driver_lan8720.c line 1664).				
456	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_set_auto_negotiation_advertisement_10base_t_full_duplex()	Low	Justified	(handle == NULL)checked.
178	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	lan8720_set_auto_negotiation_advertisement_10base_t_full_duplex()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
204	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	lan8720_set_auto_negotiation_advertisement_10base_t_full_duplex()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
308	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	lan8720_set_auto_negotiation_advertisement_10base_t_full_duplex()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
198	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	lan8720_set_auto_negotiation_advertisement_10base_t_full_duplex()	Low	Not a defect	Embedded drivers need this method to set or clear some bits

						and drivers guarantee the safety of the operation.
83	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	lan8720_set_auto_negotiation_advertisement_10base_t_full_duplex()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
13 2	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the = operator has essentially unsigned type while the right operand has essentially enum type.	lan8720_set_auto_negotiation_advertisement_10base_t_full_duplex()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
17 9	10.1	Operands shall not be of an inappropriate essential type. The right operand of the = operator is of an inappropriate essential type category enum.	lan8720_set_auto_negotiation_advertisement_10base_t_full_duplex()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
19 0	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	lan8720_set_auto_negotiation_advertisement_10base_t_full_duplex()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the

						operation.
36 3	5.1	External identifiers shall be distinct. External function lan8720_get_auto_negotiation_advertisement_10base_t_full_duplex conflicts with the external identifier lan8720_get_auto_negotiation_advertisement_remote_fault (driver_lan8720.c line 1709).	File Scope	Low	Justified	Distinct.
45 7	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_advertisement_10base_t_full_duplex()	Low	Justified	(handle == NULL)checked.
45 8	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_advertisement_10base_t_full_duplex()	Low	Justified	(handle == NULL)checked.
18 7	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_auto_negotiation_advertisement_10base_t_full_duplex()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
18 4	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_auto_negotiation_advertisement_10base_t_full_duplex()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the

						operation.
36 5	5.1	External identifiers shall be distinct. External function lan8720_set_auto_negotiation_advertisement_10base_t conflicts with the external identifier lan8720_set_auto_negotiation_advertisement_remote_fault (driver_lan8720.c line 1664).	File Scope	Low	Justified	Distinct.
45 9	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_set_auto_negotiation_advertisement_10base_t()	Low	Justified	(handle == NULL)checked.
19 2	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	lan8720_set_auto_negotiation_advertisement_10base_t()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
31 5	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	lan8720_set_auto_negotiation_advertisement_10base_t()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
19 1	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	lan8720_set_auto_negotiation_advertisement_10base_t()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.

14 6	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	lan8720_set_auto_negotiation_advertisement_10base_t()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
19 4	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	lan8720_set_auto_negotiation_advertisement_10base_t()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
27 1	10.1	Operands shall not be of an inappropriate essential type. The right operand of the = operator is of an inappropriate essential type category enum.	lan8720_set_auto_negotiation_advertisement_10base_t()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
35 1	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the = operator has essentially unsigned type while the right operand has essentially enum type.	lan8720_set_auto_negotiation_advertisement_10base_t()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
99	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	lan8720_set_auto_negotiation_advertisement_10base_t()	Low	Not a defect	Embedded drivers need this method

						to set or clear some bits and drivers guarantee the safety of the operation.
379	5.1	External identifiers shall be distinct. External function lan8720_get_auto_negotiation_advertisement_10base_t conflicts with the external identifier lan8720_get_auto_negotiation_advertisement_remote_fault (driver_lan8720.c line 1709).	File Scope	Low	Justified	Distinct.
460	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_advertisement_10base_t()	Low	Justified	(handle == NULL)checked.
461	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_advertisement_10base_t()	Low	Justified	(handle == NULL)checked.
199	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_auto_negotiation_advertisement_10base_t()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
65	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_auto_negotiation_advertisement_10base_t()	Low	Not a defect	Embedded drivers need this method to set or clear

						some bits and drivers guarantee the safety of the operation.
357	5.1	External identifiers shall be distinct. External function lan8720_set_auto_negotiation_advertisement_selector_field conflicts with the external identifier lan8720_set_auto_negotiation_advertisement_remote_fault (driver_lan8720.c line 1664).	File Scope	Low	Justified	Distinct.
462	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_set_auto_negotiation_advertisement_selector_field()	Low	Justified	(handle == NULL)checked.
240	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	lan8720_set_auto_negotiation_advertisement_selector_field()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
246	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	lan8720_set_auto_negotiation_advertisement_selector_field()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
201	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	lan8720_set_auto_negotiation_advertisement_selector_field()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers

						guarantee the safety of the operation.
119	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	lan8720_set_auto_negotiation_advertisement_selector_field()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
180	10.7	If a composite expression is used as one operand of an operator in which the usual arithmetic conversions are performed then the other operand shall not have wider essential type. The left operand of the = operator shall not have wider essential type (unsigned on 16 bits) than the right operand (unsigned on 8 bits) which is a composite expression	lan8720_set_auto_negotiation_advertisement_selector_field()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
300	10.6	The value of a composite expression shall not be assigned to an object with wider essential type. The composite expression (of essential type unsigned on 8 bits) is assigned to an object with a wider essential type (unsigned on 16 bits)	lan8720_set_auto_negotiation_advertisement_selector_field()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
375	5.1	External identifiers shall be distinct. External function lan8720_get_auto_negotiation_advertisement_selector_field conflicts with the external identifier lan8720_get_auto_negotiation_advertisement_remote_fault (driver_lan8720.c line 1709).	File Scope	Low	Justified	Distinct.
463	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source.	lan8720_get_auto_negotiation_advertisement_selector_field()	Low	Justified	(handle == NULL)checke

		Pointer may be NULL or may point to unknown memory.				d.
46 4	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_advertisement_selector_field()	Low	Justified	(handle == NULL)checked.
19 7	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type unsigned on 16 bits) is assigned to an object with a narrower essential type (unsigned on 8 bits)	lan8720_get_auto_negotiation_advertisement_selector_field()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
17 1	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_auto_negotiation_advertisement_selector_field()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
46 5	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_link_partner_ability_next_page()	Low	Justified	(handle == NULL)checked.
46 6	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_link_partner_ability_next_page()	Low	Justified	(handle == NULL)checked.
77	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_auto_negotiation_link_partner_ability_next_page()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly

						programming method and should be accepted and drivers guarantee the safety of the operation.
20 2	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_auto_negotiation_link_partner_ability_next_page()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
35 8	5.1	External identifiers shall be distinct. External function lan8720_get_auto_negotiation_link_partner_ability_acknowledge conflicts with the external identifier lan8720_get_auto_negotiation_link_partner_ability_next_page (driver_lan8720.c line 2245).	File Scope	Low	Justified	Distinct.
46 7	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_link_partner_ability_acknowledge()	Low	Justified	(handle == NULL)checked.
46 8	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_link_partner_ability_acknowledge()	Low	Justified	(handle == NULL)checked.
14 4	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_auto_negotiation_link_partner_ability_acknowledge()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming

						method and should be accepted and drivers guarantee the safety of the operation.
54	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_auto_negotiation_link_partner_ability_acknowledge()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
374	5.1	External identifiers shall be distinct. External function lan8720_get_auto_negotiation_link_partner_ability_remote_fault conflicts with the external identifier lan8720_get_auto_negotiation_link_partner_ability_next_page (driver_lan8720.c line 2245).	File Scope	Low	Justified	Distinct.
469	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_link_partner_ability_remote_fault()	Low	Justified	(handle == NULL)checked.
470	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_link_partner_ability_remote_fault()	Low	Justified	(handle == NULL)checked.
245	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_auto_negotiation_link_partner_ability_remote_fault()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and

						should be accepted and drivers guarantee the safety of the operation.
203	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_auto_negotiation_link_partner_ability_remote_fault()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
377	5.1	External identifiers shall be distinct. External function lan8720_get_auto_negotiation_link_partner_ability_pause conflicts with the external identifier lan8720_get_auto_negotiation_link_partner_ability_next_page (driver_lan8720.c line 2245).	File Scope	Low	Justified	Distinct.
471	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_link_partner_ability_pause()	Low	Justified	(handle == NULL)checked.
472	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_link_partner_ability_pause()	Low	Justified	(handle == NULL)checked.
282	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_auto_negotiation_link_partner_ability_pause()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be

						accepted and drivers guarantee the safety of the operation.
299	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_auto_negotiation_link_partner_ability_pause()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
361	5.1	External identifiers shall be distinct. External function lan8720_get_auto_negotiation_link_partner_ability_100base_t4 conflicts with the external identifier lan8720_get_auto_negotiation_link_partner_ability_next_page (driver_lan8720.c line 2245).	File Scope	Low	Justified	Distinct.
473	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_link_partner_ability_100base_t4()	Low	Justified	(handle == NULL)checked.
474	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_link_partner_ability_100base_t4()	Low	Justified	(handle == NULL)checked.
177	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_auto_negotiation_link_partner_ability_100base_t4()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and

						drivers guarantee the safety of the operation.
123	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_auto_negotiation_link_partner_ability_100base_t4()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
380	5.1	External identifiers shall be distinct. External function lan8720_get_auto_negotiation_link_partner_ability_100base_tx_full_duplex conflicts with the external identifier lan8720_get_auto_negotiation_link_partner_ability_next_page (driver_lan8720.c line 2245).	File Scope	Low	Justified	Distinct.
475	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_link_partner_ability_100base_tx_full_duplex()	Low	Justified	(handle == NULL)checked.
476	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_link_partner_ability_100base_tx_full_duplex()	Low	Justified	(handle == NULL)checked.
320	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_auto_negotiation_link_partner_ability_100base_tx_full_duplex()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers

						guarantee the safety of the operation.
183	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_auto_negotiation_link_partner_ability_100base_tx_full_duplex()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
373	5.1	External identifiers shall be distinct. External function lan8720_get_auto_negotiation_link_partner_ability_100base_tx conflicts with the external identifier lan8720_get_auto_negotiation_link_partner_ability_next_page (driver_lan8720.c line 2245).	File Scope	Low	Justified	Distinct.
477	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_link_partner_ability_100base_tx()	Low	Justified	(handle == NULL)checked.
478	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_link_partner_ability_100base_tx()	Low	Justified	(handle == NULL)checked.
277	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_auto_negotiation_link_partner_ability_100base_tx()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the

						safety of the operation.
48	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_auto_negotiation_link_partner_ability_100base_tx()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
35 6	5.1	External identifiers shall be distinct. External function lan8720_get_auto_negotiation_link_partner_ability_10base_t_full_duplex conflicts with the external identifier lan8720_get_auto_negotiation_link_partner_ability_next_page (driver_lan8720.c line 2245).	File Scope	Low	Justified	Distinct.
47 9	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_link_partner_ability_10base_t_full_duplex()	Low	Justified	(handle == NULL)checked.
48 0	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_link_partner_ability_10base_t_full_duplex()	Low	Justified	(handle == NULL)checked.
23 4	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_auto_negotiation_link_partner_ability_10base_t_full_duplex()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the

						operation.
210	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_auto_negotiation_link_partner_ability_10base_t_full_duplex()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
360	5.1	External identifiers shall be distinct. External function lan8720_get_auto_negotiation_link_partner_ability_10base_t conflicts with the external identifier lan8720_get_auto_negotiation_link_partner_ability_next_page (driver_lan8720.c line 2245).	File Scope	Low	Justified	Distinct.
481	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_link_partner_ability_10base_t()	Low	Justified	(handle == NULL)checked.
482	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_link_partner_ability_10base_t()	Low	Justified	(handle == NULL)checked.
306	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_auto_negotiation_link_partner_ability_10base_t()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the

						operation.
209	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_auto_negotiation_link_partner_ability_10base_t()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
359	5.1	External identifiers shall be distinct. External function lan8720_get_auto_negotiation_link_partner_ability_selector_field conflicts with the external identifier lan8720_get_auto_negotiation_link_partner_ability_next_page (driver_lan8720.c line 2245).	File Scope	Low	Justified	Distinct.
483	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_link_partner_ability_selector_field()	Low	Justified	(handle == NULL)checked.
484	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_link_partner_ability_selector_field()	Low	Justified	(handle == NULL)checked.
139	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type unsigned on 16 bits) is assigned to an object with a narrower essential type (unsigned on 8 bits)	lan8720_get_auto_negotiation_link_partner_ability_selector_field()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
196	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_auto_negotiation_link_partner_ability_selector_field()	Low	Not a defect	Embedded drivers need this method to set or clear some bits

						and drivers guarantee the safety of the operation.
485	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_expansion_parallel_detection_fault()	Low	Justified	(handle == NULL)checked.
486	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_expansion_parallel_detection_fault()	Low	Justified	(handle == NULL)checked.
211	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_auto_negotiation_expansion_parallel_detection_fault()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
66	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_auto_negotiation_expansion_parallel_detection_fault()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
376	5.1	External identifiers shall be distinct. External function lan8720_get_auto_negotiation_expansion_link_partner_next_page_a	File Scope	Low	Justified	Distinct.

		ble conflicts with the external identifier lan8720_get_auto_negotiation_expansion_parallel_detection_fault (driver_lan8720.c line 2615).				
487	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_expansion_link_partner_next_page_able()	Low	Justified	(handle == NULL)checked.
488	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_expansion_link_partner_next_page_able()	Low	Justified	(handle == NULL)checked.
154	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_auto_negotiation_expansion_link_partner_next_page_able()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
218	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_auto_negotiation_expansion_link_partner_next_page_able()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
366	5.1	External identifiers shall be distinct. External function lan8720_get_auto_negotiation_expansion_next_page_able conflicts with the external identifier	File Scope	Low	Justified	Distinct.

		lan8720_get_auto_negotiation_expansion_parallel_detection_fault (driver_lan8720.c line 2615).				
489	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_expansion_next_page_able()	Low	Justified	(handle == NULL)checked.
490	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_expansion_next_page_able()	Low	Justified	(handle == NULL)checked.
264	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_auto_negotiation_expansion_next_page_able()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
113	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_auto_negotiation_expansion_next_page_able()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
372	5.1	External identifiers shall be distinct. External function lan8720_get_auto_negotiation_expansion_page_received conflicts with the external identifier lan8720_get_auto_negotiation_expansion_parallel_detection_fault	File Scope	Low	Justified	Distinct.

		(driver_lan8720.c line 2615).				
49 1	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_expansion_page_received()	Low	Justified	(handle == NULL)checked.
49 2	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_expansion_page_received()	Low	Justified	(handle == NULL)checked.
15 1	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_auto_negotiation_expansion_page_received()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
18 8	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_auto_negotiation_expansion_page_received()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
37 1	5.1	External identifiers shall be distinct. External function lan8720_get_auto_negotiation_expansion_link_partner_auto_negotiation_able conflicts with the external identifier lan8720_get_auto_negotiation_expansion_parallel_detection_fault	File Scope	Low	Justified	Distinct.

		(driver_lan8720.c line 2615).				
493	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_expansion_link_partner_auto_negotiation_able()	Low	Justified	(handle == NULL)checked.
494	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_expansion_link_partner_auto_negotiation_able()	Low	Justified	(handle == NULL)checked.
124	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_auto_negotiation_expansion_link_partner_auto_negotiation_able()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
330	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_auto_negotiation_expansion_link_partner_auto_negotiation_able()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
495	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_set_energy_detect_power_down_mode()	Low	Justified	(handle == NULL)checked.
39	10.1	Operands shall not be of an inappropriate essential type.	lan8720_set_energy_detect_power_down_mode()	Low	Not a	Embedded

		The right operand of the &= operator is of an inappropriate essential type category signed.			defect	drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
47	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	lan8720_set_energy_detect_power_down_mode()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
21 6	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	lan8720_set_energy_detect_power_down_mode()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
33	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	lan8720_set_energy_detect_power_down_mode()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
21 3	12.2	The right hand operand of a shift operator shall lie in the range zero to one less than the width in bits of the essential type of the left hand operand.	lan8720_set_energy_detect_power_down_mode()	Low	Justified	Embedded drivers need this method to set or clear

						some bits and drivers guarantee the safety of the operation.
82	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	lan8720_set_energy_detect_power_down_mode()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
21 4	10.1	Operands shall not be of an inappropriate essential type. The right operand of the = operator is of an inappropriate essential type category enum.	lan8720_set_energy_detect_power_down_mode()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
26 2	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the = operator has essentially unsigned type while the right operand has essentially enum type.	lan8720_set_energy_detect_power_down_mode()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
98	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	lan8720_set_energy_detect_power_down_mode()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the

						safety of the operation.
496	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_energy_detect_power_down_mode()	Low	Justified	(handle == NULL)checked.
497	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_energy_detect_power_down_mode()	Low	Justified	(handle == NULL)checked.
219	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_energy_detect_power_down_mode()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
313	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_energy_detect_power_down_mode()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
498	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_set_far_loop_back()	Low	Justified	(handle == NULL)checked.

22 1	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	lan8720_set_far_loop_back()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
35 0	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	lan8720_set_far_loop_back()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
35 5	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	lan8720_set_far_loop_back()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
22 4	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	lan8720_set_far_loop_back()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
34 9	12.2	The right hand operand of a shift operator shall lie in the range zero to one less than the width in bits of the essential type of the left hand operand.	lan8720_set_far_loop_back()	Low	Justified	Embedded drivers need this method

						to set or clear some bits and drivers guarantee the safety of the operation.
18 2	10.1	Operands shall not be of an inappropriate essential type. The right operand of the = operator is of an inappropriate essential type category enum.	lan8720_set_far_loop_back()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
22 6	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the = operator has essentially unsigned type while the right operand has essentially enum type.	lan8720_set_far_loop_back()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
22 7	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	lan8720_set_far_loop_back()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
34 0	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	lan8720_set_far_loop_back()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers

						guarantee the safety of the operation.
499	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_far_loop_back()	Low	Justified	(handle == NULL)checked.
500	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_far_loop_back()	Low	Justified	(handle == NULL)checked.
249	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_far_loop_back()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
173	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_far_loop_back()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
501	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source.	lan8720_set_alternate_interrupt_mode()	Low	Justified	(handle == NULL)checked.

		Pointer may be NULL or may point to unknown memory.				
15 9	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	lan8720_set_alternate_interrupt_mode()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
23 2	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	lan8720_set_alternate_interrupt_mode()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
23 1	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	lan8720_set_alternate_interrupt_mode()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
18 6	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	lan8720_set_alternate_interrupt_mode()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
13	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category.	lan8720_set_alternate_interrupt_mode()	Low	Not a	Embedded drivers need

4		The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)			defect	this method to set or clear some bits and drivers guarantee the safety of the operation.
23 7	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the = operator has essentially unsigned type while the right operand has essentially enum type.	lan8720_set_alternate_interrupt_mode()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
28 3	10.1	Operands shall not be of an inappropriate essential type. The right operand of the = operator is of an inappropriate essential type category enum.	lan8720_set_alternate_interrupt_mode()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
13	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	lan8720_set_alternate_interrupt_mode()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
50 2	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_alternate_interrupt_mode()	Low	Justified	(handle == NULL)checked.

503	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_alternate_interrupt_mode()	Low	Justified	(handle == NULL)checked.
310	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_alternate_interrupt_mode()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
333	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_alternate_interrupt_mode()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
504	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_energy_detected()	Low	Justified	(handle == NULL)checked.
505	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_energy_detected()	Low	Justified	(handle == NULL)checked.
167	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type.	lan8720_get_energy_detected()	Low	Not a defect	We use enumeration

		The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.				to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
259	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_energy_detected()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
506	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_set_mode()	Low	Justified	(handle == NULL)checked.
238	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	lan8720_set_mode()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
241	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	lan8720_set_mode()	Low	Not a defect	Embedded drivers need this method to set or clear

						some bits and drivers guarantee the safety of the operation.
200	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	lan8720_set_mode()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
102	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	lan8720_set_mode()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
251	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	lan8720_set_mode()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
291	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the = operator has essentially unsigned type while the right operand has essentially enum type.	lan8720_set_mode()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the

						safety of the operation.
34 5	10.1	Operands shall not be of an inappropriate essential type. The right operand of the = operator is of an inappropriate essential type category enum.	lan8720_set_mode()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
24 4	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	lan8720_set_mode()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
50 7	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_mode()	Low	Justified	(handle == NULL)checked.
50 8	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_mode()	Low	Justified	(handle == NULL)checked.
28 6	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_mode()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and

						drivers guarantee the safety of the operation.
25 3	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_mode()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
50 9	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_set_phy_address()	Low	Justified	(handle == NULL)checked.
27 5	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	lan8720_set_phy_address()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
28 9	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	lan8720_set_phy_address()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
30 1	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	lan8720_set_phy_address()	Low	Not a defect	Embedded drivers need this method to set or clear

						some bits and drivers guarantee the safety of the operation.
25 4	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	lan8720_set_phy_address()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
26 5	10.6	The value of a composite expression shall not be assigned to an object with wider essential type. The composite expression (of essential type unsigned on 8 bits) is assigned to an object with a wider essential type (unsigned on 16 bits)	lan8720_set_phy_address()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
32 1	10.7	If a composite expression is used as one operand of an operator in which the usual arithmetic conversions are performed then the other operand shall not have wider essential type. The left operand of the = operator shall not have wider essential type (unsigned on 16 bits) than the right operand (unsigned on 8 bits) which is a composite expression	lan8720_set_phy_address()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
51 0	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_phy_address()	Low	Justified	(handle == NULL)checked.
51 1	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source.	lan8720_get_phy_address()	Low	Justified	(handle == NULL)checked

		Pointer may be NULL or may point to unknown memory.				d.
279	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type unsigned on 16 bits) is assigned to an object with a narrower essential type (unsigned on 8 bits)	lan8720_get_phy_address()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
189	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_phy_address()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
512	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_symbol_error_counter()	Low	Justified	(handle == NULL)checked.
513	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_symbol_error_counter()	Low	Justified	(handle == NULL)checked.
514	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_set_auto_mdix()	Low	Justified	(handle == NULL)checked.
67	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	lan8720_set_auto_mdix()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the

						safety of the operation.
25 8	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	lan8720_set_auto_mdix()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
32 9	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	lan8720_set_auto_mdix()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
33 2	12.2	The right hand operand of a shift operator shall lie in the range zero to one less than the width in bits of the essential type of the left hand operand.	lan8720_set_auto_mdix()	Low	Justified	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
14 3	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the = operator has essentially unsigned type while the right operand has essentially enum type.	lan8720_set_auto_mdix()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.

34 6	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	lan8720_set_auto_mdix()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
35 3	10.1	Operands shall not be of an inappropriate essential type. The right operand of the = operator is of an inappropriate essential type category enum.	lan8720_set_auto_mdix()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
84	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	lan8720_set_auto_mdix()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
51 5	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_mdix()	Low	Justified	(handle == NULL)checked.
51 6	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_mdix()	Low	Justified	(handle == NULL)checked.
26 1	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category	lan8720_get_auto_mdix()	Low	Not a defect	We use enumeration to define

		unsigned shall not be cast to the different essential type category enum.				driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
33 6	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_auto_mdix()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
51 7	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_set_manual_channel_select()	Low	Justified	(handle == NULL)checked.
11 8	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	lan8720_set_manual_channel_select()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
25 7	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	lan8720_set_manual_channel_select()	Low	Not a defect	Embedded drivers need this method to set or clear some bits

						and drivers guarantee the safety of the operation.
297	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	lan8720_set_manual_channel_select()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
281	12.2	The right hand operand of a shift operator shall lie in the range zero to one less than the width in bits of the essential type of the left hand operand.	lan8720_set_manual_channel_select()	Low	Justified	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
290	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	lan8720_set_manual_channel_select()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
100	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the = operator has essentially unsigned type while the right operand has essentially enum type.	lan8720_set_manual_channel_select()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the

						operation.
26 7	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	lan8720_set_manual_channel_select()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
32 5	10.1	Operands shall not be of an inappropriate essential type. The right operand of the = operator is of an inappropriate essential type category enum.	lan8720_set_manual_channel_select()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
26 3	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	lan8720_set_manual_channel_select()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
51 8	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_manual_channel_select()	Low	Justified	(handle == NULL)checked.
51 9	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_manual_channel_select()	Low	Justified	(handle == NULL)checked.
30 2	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type.	lan8720_get_manual_channel_select()	Low	Not a defect	We use enumeration

		The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.				to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
220	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_manual_channel_select()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
520	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_set_sqe_test_off()	Low	Justified	(handle == NULL)checked.
207	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	lan8720_set_sqe_test_off()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
284	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	lan8720_set_sqe_test_off()	Low	Not a defect	Embedded drivers need this method to set or clear

						some bits and drivers guarantee the safety of the operation.
34 4	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	lan8720_set_sqe_test_off()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
27 2	12.2	The right hand operand of a shift operator shall lie in the range zero to one less than the width in bits of the essential type of the left hand operand.	lan8720_set_sqe_test_off()	Low	Justified	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
33 7	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	lan8720_set_sqe_test_off()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
29 3	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	lan8720_set_sqe_test_off()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the

						safety of the operation.
318	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the = operator has essentially unsigned type while the right operand has essentially enum type.	lan8720_set_sqe_test_off()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
338	10.1	Operands shall not be of an inappropriate essential type. The right operand of the = operator is of an inappropriate essential type category enum.	lan8720_set_sqe_test_off()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
305	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	lan8720_set_sqe_test_off()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
521	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_sqe_test_off()	Low	Justified	(handle == NULL)checked.
522	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_sqe_test_off()	Low	Justified	(handle == NULL)checked.
46	10.8	The value of a composite expression shall not be cast to a different	lan8720_get_sqe_test_off()	Low	Not a	We use

		essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.			defect	enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
328	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_sqe_test_off()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
523	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_polarity()	Low	Justified	(handle == NULL)checked.
524	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_polarity()	Low	Justified	(handle == NULL)checked.
133	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_polarity()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming

						method and should be accepted and drivers guarantee the safety of the operation.
29 8	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_polarity()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
52 5	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_interrupt_flag()	Low	Justified	(handle == NULL)checked.
52 6	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_interrupt_flag()	Low	Justified	(handle == NULL)checked.
30 7	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_interrupt_flag()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.

303	10.1	Operands shall not be of an inappropriate essential type. The right operand of the >> operator is of an inappropriate essential type category enum.	lan8720_get_interrupt_flag()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
3	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_interrupt_flag()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
527	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_set_interrupt_mask()	Low	Justified	(handle == NULL)checked.
270	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	lan8720_set_interrupt_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
274	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	lan8720_set_interrupt_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the

						operation.
31 2	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the &= operator has essentially unsigned type while the right operand has essentially signed type.	lan8720_set_interrupt_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
33 4	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	lan8720_set_interrupt_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
31 1	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed. The right operand of the << operator is of an inappropriate essential type category enum.	lan8720_set_interrupt_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
16 9	10.1	Operands shall not be of an inappropriate essential type. The right operand of the = operator is of an inappropriate essential type category enum.	lan8720_set_interrupt_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
28	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type	lan8720_set_interrupt_mask()	Low	Not a	Embedded drivers need

5		category. The left operand of the = operator has essentially unsigned type while the right operand has essentially enum type.			defect	this method to set or clear some bits and drivers guarantee the safety of the operation.
323	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	lan8720_set_interrupt_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
316	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum. The right operand of the << operator is of an inappropriate essential type category enum.	lan8720_set_interrupt_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
528	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_interrupt_mask()	Low	Justified	(handle == NULL)checked.
529	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_interrupt_mask()	Low	Justified	(handle == NULL)checked.
331	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_interrupt_mask()	Low	Not a defect	We use enumeration to define driver configuration, which is a

						friendly programming method and should be accepted and drivers guarantee the safety of the operation.
131	10.1	Operands shall not be of an inappropriate essential type. The right operand of the >> operator is of an inappropriate essential type category enum.	lan8720_get_interrupt_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
268	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_interrupt_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
530	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_done()	Low	Justified	(handle == NULL)checked.
531	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_auto_negotiation_done()	Low	Justified	(handle == NULL)checked.
348	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category	lan8720_get_auto_negotiation_done()	Low	Not a defect	We use enumeration to define driver

		enum.				configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
339	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_auto_negotiation_done()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
532	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_speed_indication()	Low	Justified	(handle == NULL)checked.
533	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_speed_indication()	Low	Justified	(handle == NULL)checked.
354	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	lan8720_get_speed_indication()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and

						drivers guarantee the safety of the operation.
15 0	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	lan8720_get_speed_indication()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
53 4	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_set_reg()	Low	Justified	(handle == NULL)checked.
53 5	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_get_reg()	Low	Justified	(handle == NULL)checked.
53 6	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	lan8720_info()	Low	Justified	(handle == NULL)checked.

Chapter 3. Defects

Defects

No defects were found.

Chapter 4. Appendix 1 - Configuration Settings

Polyspace Settings

Option	Value
-author	libdriver
-bug-finder	true
-compiler	generic
-D	__TID__=14, __SIZE_T_TYPE__=unsigned int, __PTRDIFF_T_TYPE__=signed int, __IAR_SYSTEMS_ICC=1
-date	12/08/2023
-dos	true
-I	E:\Github\lan8720\src,E:\Github\lan8720\interface,E:\Github\lan8720\example,E:\Github\lan8720\test
-import-comments	E:\Polyspace\lan8720\Module\BF_Result\comments_bak
-lang	C
-little-endian	true
-logical-signed-right-shift	true
-misra3	mandatory-required
-prog	lan8720
-results-dir	E:\Polyspace\lan8720\Module\BF_Result
-target	mcpu
-verif-version	1.0
-checkers	ALIGNMENT_CHANGE, ASSERT, ATOMIC_VAR_ACCESS_TWICE, ATOMIC_VAR_SEQUENCE_NOT_ATOMIC, BAD_EQUAL_EQUAL_USE, BAD_EQUAL_USE, BAD_FREE, BAD_LOCK, BAD_PTR_SCALING, BAD_UNLOCK, CHARACTER_MISUSE, CHAR_EOF_CONFUSED, CLOSED_RESOURCE_USE, CONSTANT_OBJECT_WRITE, DATA_RACE, DATA_RACE_STD_LIB, DEADLOCK, DEAD_CODE, DECL_MISMATCH, DOUBLE_DEALLOCATION, DOUBLE_LOCK, DOUBLE_RESOURCE_CLOSE, DOUBLE_RESOURCE_OPEN, DOUBLE_UNLOCK, ERRNO_MISUSE, FILE_OBJECT_MISUSE, FLEXIBLE_ARRAY_MEMBER_STRUCT_MISUSE, FLOAT_ABSORPTION, FLOAT_CONV_OVFL, FLOAT_STD_LIB, FLOAT_ZERO_DIV, FREED_PTR, FUNC_CAST, IMPROPER_ARRAY_INIT, INLINE_CONSTRAINT_NOT_RESPECTED, INT_CONV_OVFL, INT_STD_LIB, INT_ZERO_DIV, INVALID_ENV_POINTER, INVALID_MEMORY_ASSUMPTION, INVALID_VA_LIST_ARG, IO_INTERLEAVING, LOCAL_ADDR_ESCAPE, MACRO_USED_AS_OBJECT, MEMCMP_PADDING_DATA, MEMCMP_STRINGS, MEM_STD_LIB,

MISSING_ERRNO_RESET, MISSING_NULL_CHAR, MISSING_RETURN, NON_INIT_PTR, NON_INIT_VAR, NON_POSITIVE_VLA_SIZE, NULL_PTR, OPERATOR_PRECEDENCE, OTHER_STD_LIB, OUT_BOUND_ARRAY, OUT_BOUND_PTR, PARTIALLY_ACCESSED_ARRAY, PRE_DIRECTIVE_MACRO_ARG, PRE_UCNAME_JOIN_TOKENS, PTR_CAST, PTR_SIZEOF_MISMATCH, PTR_TO_DIFF_ARRAY, PUTENV_AUTO_VAR, READ_ONLY_RESOURCE_WRITE, RESOURCE_LEAK, SIDE_EFFECT_IGNORED, SIGN_CHANGE, SIG_HANDLER_CALLING_SIGNAL, SIG_HANDLER_COMP_EXCP_RETURN, SIG_HANDLER_ERRNO_MISUSE, SIG_HANDLER_SHARED_OBJECT, SIZEOF_MISUSE, STD_FUNC_ARG_MISMATCH, STREAM_WITH_SIDE_EFFECT, STRING_FORMAT, STRLIB_BUFFER_OVERFLOW, STRLIB_BUFFER_UNDERFLOW, STR_FORMAT_BUFFER_OVERFLOW, STR_STD_LIB, TEMP_OBJECT_ACCESS, TOO_MANY_VA_ARG_CALLS, TYPEDEF_MISMATCH, UINT_CONV_OVFL, UNPROTOTYPED_FUNC_CALL, UNREACHABLE, USELESS_IF, USELESS_WRITE, VAR_SHADOWING, VA_ARG_INCORRECT_TYPE, VA_START_INCORRECT_TYPE, VA_START_MISUSE

Coding Standard Configuration

Table 4.1. MISRA C:2012 Guidelines Configuration

Guideline	Description	Mode	Comment	Enabled
D1.1	Any implementation-defined behaviour on which the output of the program depends shall be documented and understood.	required	-	yes
D2.1	All source files shall compile without any compilation errors.	required	-	yes
D3.1	All code shall be traceable to documented requirements.	required	Not enforceable	no
D4.1	Run-time failures shall be minimized.	required	-	yes
D4.2	All usage of assembly language should be documented.	advisory	Not enforceable	no
D4.3	Assembly language shall be encapsulated and isolated.	required	-	yes
D4.4	Sections of code should not be "commented out".	advisory	Not implemented	no
D4.5	Identifiers in the same name space with overlapping visibility should be typographically unambiguous.	advisory	-	no
D4.6	typedefs that indicate size and signedness should be used in place of the basic numerical types.	advisory	-	no
D4.7	If a function returns error information, then that error information shall be tested.	required	-	yes
D4.8	If a pointer to a structure or union is never dereferenced within a translation unit, then the implementation of the object should be hidden.	advisory	-	no
D4.9	A function should be used in preference to a function-like macro where they are interchangeable.	advisory	-	no
D4.10	Precautions shall be taken in order to prevent the contents of a header file being included more than once.	required	-	yes
D4.11	The validity of values passed to library functions shall be checked.	required	-	yes

D4.12	Dynamic memory allocation shall not be used.	required	-	yes
D4.13	Functions which are designed to provide operations on a resource should be called in an appropriate sequence.	advisory	-	no
D4.14	The validity of values received from external sources shall be checked.	required	-	yes
1.1	The program shall contain no violations of the standard C syntax and constraints, and shall not exceed the implementation's translation limits.	required	-	yes
1.2	Language extensions should not be used.	advisory	-	no
1.3	There shall be no occurrence of undefined or critical unspecified behaviour.	required	-	yes
2.1	A project shall not contain unreachable code.	required	-	yes
2.2	There shall be no dead code.	required	-	yes
2.3	A project should not contain unused type declarations.	advisory	-	no
2.4	A project should not contain unused tag declarations.	advisory	-	no
2.5	A project should not contain unused macro declarations.	advisory	-	no
2.6	A function should not contain unused label declarations.	advisory	-	no
2.7	There should be no unused parameters in functions.	advisory	-	no
3.1	The character sequences <code>/*</code> and <code>//</code> shall not be used within a comment.	required	-	yes
3.2	Line-splicing shall not be used in <code>//</code> comments.	required	-	yes
4.1	Octal and hexadecimal escape sequences shall be terminated.	required	-	yes
4.2	Trigraphs should not be used.	advisory	-	no
5.1	External identifiers shall be distinct.	required	-	yes
5.2	Identifiers declared in the same scope and name space shall be distinct.	required	-	yes
5.3	An identifier declared in an inner scope shall not hide an identifier declared in an outer scope.	required	-	yes
5.4	Macro identifiers shall be distinct.	required	-	yes
5.5	Identifiers shall be distinct from macro names.	required	-	yes
5.6	A typedef name shall be a unique identifier.	required	-	yes
5.7	A tag name shall be a unique identifier.	required	-	yes
5.8	Identifiers that define objects or functions with external linkage shall be unique.	required	-	yes
5.9	Identifiers that define objects or functions with internal linkage should be unique.	advisory	-	no

6.1	Bit-fields shall only be declared with an appropriate type.	required	-	yes
6.2	Single-bit named bit fields shall not be of a signed type.	required	-	yes
7.1	Octal constants shall not be used.	required	-	yes
7.2	A "u" or "U" suffix shall be applied to all integer constants that are represented in an unsigned type.	required	-	yes
7.3	The lowercase character "l" shall not be used in a literal suffix.	required	-	yes
7.4	A string literal shall not be assigned to an object unless the object's type is "pointer to const-qualified char".	required	-	yes
8.1	Types shall be explicitly specified.	required	-	yes
8.2	Function types shall be in prototype form with named parameters.	required	-	yes
8.3	All declarations of an object or function shall use the same names and type qualifiers.	required	-	yes
8.4	A compatible declaration shall be visible when an object or function with external linkage is defined.	required	-	yes
8.5	An external object or function shall be declared once in one and only one file.	required	-	yes
8.6	An identifier with external linkage shall have exactly one external definition.	required	-	yes
8.7	Functions and objects should not be defined with external linkage if they are referenced in only one translation unit.	advisory	-	no
8.8	The static storage class specifier shall be used in all declarations of objects and functions that have internal linkage.	required	-	yes
8.9	An object should be defined at block scope if its identifier only appears in a single function.	advisory	-	no
8.10	An inline function shall be declared with the static storage class.	required	-	yes
8.11	When an array with external linkage is declared, its size should be explicitly specified.	advisory	-	no
8.12	Within an enumerator list, the value of an implicitly-specified enumeration constant shall be unique.	required	-	yes
8.13	A pointer should point to a const-qualified type whenever possible.	advisory	-	no
8.14	The restrict type qualifier shall not be used.	required	-	yes
9.1	The value of an object with automatic storage duration shall not be read before it has been set.	mandatory	-	yes
9.2	The initializer for an aggregate or union shall be enclosed in braces.	required	-	yes
9.3	Arrays shall not be partially initialized.	required	-	yes
9.4	An element of an object shall not be initialized more than once.	required	-	yes
9.5	Where designated initializers are used to initialize an array object the size of the array shall be specified explicitly.	required	-	yes

10.1	Operands shall not be of an inappropriate essential type.	required	-	yes
10.2	Expressions of essentially character type shall not be used inappropriately in addition and subtraction operations.	required	-	yes
10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category.	required	-	yes
10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category.	required	-	yes
10.5	The value of an expression should not be cast to an inappropriate essential type.	advisory	-	no
10.6	The value of a composite expression shall not be assigned to an object with wider essential type.	required	-	yes
10.7	If a composite expression is used as one operand of an operator in which the usual arithmetic conversions are performed then the other operand shall not have wider essential type.	required	-	yes
10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type.	required	-	yes
11.1	Conversions shall not be performed between a pointer to a function and any other type.	required	-	yes
11.2	Conversions shall not be performed between a pointer to an incomplete type and any other type.	required	-	yes
11.3	A cast shall not be performed between a pointer to object type and a pointer to a different object type.	required	-	yes
11.4	A conversion should not be performed between a pointer to object and an integer type.	advisory	-	no
11.5	A conversion should not be performed from pointer to void into pointer to object.	advisory	-	no
11.6	A cast shall not be performed between pointer to void and an arithmetic type.	required	-	yes
11.7	A cast shall not be performed between pointer to object and a non-integer arithmetic type.	required	-	yes
11.8	A cast shall not remove any const or volatile qualification from the type pointed to by a pointer.	required	-	yes
11.9	The macro NULL shall be the only permitted form of integer null pointer constant.	required	-	yes
12.1	The precedence of operators within expressions should be made explicit.	advisory	-	no
12.2	The right hand operand of a shift operator shall lie in the range zero to one less than the width in bits of the essential type of the left hand operand.	required	-	yes
12.3	The comma operator should not be used	advisory	-	no
12.4	Evaluation of constant expressions should not lead to unsigned integer wrap-around.	advisory	-	no
12.5	The sizeof operator shall not have an operand which is a function parameter declared as "array of type".	mandatory	-	yes
13.1	Initializer lists shall not contain persistent side effects.	required	-	yes

13.2	The value of an expression and its persistent side effects shall be the same under all permitted evaluation orders.	required	-	yes
13.3	A full expression containing an increment (++) or decrement (--) operator should have no other potential side effects other than that caused by the increment or decrement operator.	advisory	-	no
13.4	The result of an assignment operator should not be used.	advisory	-	no
13.5	The right hand operand of a logical && or operator shall not contain persistent side effects.	required	-	yes
13.6	The operand of the sizeof operator shall not contain any expression which has potential side effects.	mandatory	-	yes
14.1	A loop counter shall not have essentially floating type.	required	-	yes
14.2	A for loop shall be well-formed.	required	-	yes
14.3	Controlling expressions shall not be invariant.	required	-	yes
14.4	The controlling expression of an if statement and the controlling expression of an iteration-statement shall have essentially Boolean type.	required	-	yes
15.1	The goto statement should not be used.	advisory	-	no
15.2	The goto statement shall jump to a label declared later in the same function.	required	-	yes
15.3	Any label referenced by a goto statement shall be declared in the same block, or in any block enclosing the goto statement.	required	-	yes
15.4	There should be no more than one break or goto statement used to terminate any iteration statement.	advisory	-	no
15.5	A function should have a single point of exit at the end.	advisory	-	no
15.6	The body of an iteration-statement or a selection-statement shall be a compound-statement.	required	-	yes
15.7	All if ... else if constructs shall be terminated with an else statement.	required	-	yes
16.1	All switch statements shall be well-formed.	required	-	yes
16.2	A switch label shall only be used when the most closely-enclosing compound statement is the body of a switch statement.	required	-	yes
16.3	An unconditional break statement shall terminate every switch-clause.	required	-	yes
16.4	Every switch statement shall have a default label.	required	-	yes
16.5	A default label shall appear as either the first or the last switch label of a switch statement.	required	-	yes
16.6	Every switch statement shall have at least two switch-clauses.	required	-	yes
16.7	A switch-expression shall not have essentially Boolean type.	required	-	yes
17.1	The features of <stdarg.h> shall not be used.	required	-	yes

17.2	Functions shall not call themselves, either directly or indirectly.	required	-	yes
17.3	A function shall not be declared implicitly.	mandatory	-	yes
17.4	All exit paths from a function with non-void return type shall have an explicit return statement with an expression.	mandatory	-	yes
17.5	The function argument corresponding to a parameter declared to have an array type shall have an appropriate number of elements.	advisory	-	no
17.6	The declaration of an array parameter shall not contain the static keyword between the [].	mandatory	-	yes
17.7	The value returned by a function having non-void return type shall be used.	required	-	yes
17.8	A function parameter should not be modified.	advisory	-	no
18.1	A pointer resulting from arithmetic on a pointer operand shall address an element of the same array as that pointer operand.	required	-	yes
18.2	Subtraction between pointers shall only be applied to pointers that address elements of the same array.	required	-	yes
18.3	The relational operators >, >=, < and <= shall not be applied to objects of pointer type except where they point into the same object.	required	-	yes
18.4	The +, -, += and -= operators should not be applied to an expression of pointer type.	advisory	-	no
18.5	Declarations should contain no more than two levels of pointer nesting.	advisory	-	no
18.6	The address of an object with automatic storage shall not be copied to another object that persists after the first object has ceased to exist.	required	-	yes
18.7	Flexible array members shall not be declared.	required	-	yes
18.8	Variable-length array types shall not be used.	required	-	yes
19.1	An object shall not be assigned or copied to an overlapping object.	mandatory	-	yes
19.2	The union keyword should not be used.	advisory	-	no
20.1	#include directives should only be preceded by preprocessor directives or comments.	advisory	-	no
20.2	The ', " or \ characters and the /* or // character sequences shall not occur in a header file name.	required	-	yes
20.3	The #include directive shall be followed by either a <filename> or "filename"sequence.	required	-	yes
20.4	A macro shall not be defined with the same name as a keyword.	required	-	yes
20.5	#undef should not be used.	advisory	-	no
20.6	Tokens that look like a preprocessing directive shall not occur within a macro argument.	required	-	yes

20.7	Expressions resulting from the expansion of macro parameters shall be enclosed in parentheses.	required	-	yes
20.8	The controlling expression of a #if or #elif preprocessing directive shall evaluate to 0 or 1.	required	-	yes
20.9	All identifiers used in the controlling expression of #if or #elif preprocessing directives shall be #define'd before evaluation.	required	-	yes
20.10	The # and ## preprocessor operators should not be used.	advisory	-	no
20.11	A macro parameter immediately following a # operator shall not immediately be followed by a ## operator.	required	-	yes
20.12	A macro parameter used as an operand to the # or ## operators, which is itself subject to further macro replacement, shall only be used as an operand to these operators.	required	-	yes
20.13	A line whose first token is # shall be a valid preprocessing directive.	required	-	yes
20.14	All #else, #elif and #endif preprocessor directives shall reside in the same file as the #if, #ifdef or #ifndef directive to which they are related.	required	-	yes
21.1	#define and #undef shall not be used on a reserved identifier or reserved macro name.	required	-	yes
21.2	A reserved identifier or macro name shall not be declared.	required	-	yes
21.3	The memory allocation and deallocation functions of <stdlib.h> shall not be used.	required	-	yes
21.4	The standard header file <setjmp.h> shall not be used.	required	-	yes
21.5	The standard header file <signal.h> shall not be used.	required	-	yes
21.6	The Standard Library input/output functions shall not be used.	required	-	yes
21.7	The atof, atoi, atol, and atoll functions of <stdlib.h> shall not be used.	required	-	yes
21.8	The library functions abort, exit and system of <stdlib.h> shall not be used.	required	-	yes
21.9	The library functions bsearch and qsort of <stdlib.h> shall not be used.	required	-	yes
21.10	The Standard Library time and date functions shall not be used.	required	-	yes
21.11	The standard header file <tgmath.h> shall not be used.	required	-	yes
21.12	The exception handling features of <fenv.h> should not be used.	advisory	-	no
21.13	Any value passed to a function in <ctype.h> shall be representable as an unsigned char or be the value EOF.	mandatory	-	yes
21.14	The Standard Library function memcmp shall not be used to compare null terminated strings.	required	-	yes
21.15	The pointer arguments to the Standard Library functions memcpy, memmove and memcmp shall be pointers to qualified or unqualified versions of compatible types.	required	-	yes

21.16	The pointer arguments to the Standard Library function memcmp shall point to either a pointer type, an essentially signed type, an essentially unsigned type, an essentially Boolean type or an essentially enum type.	required	-	yes
21.17	Use of the string handling functions from <string.h> shall not result in accesses beyond the bounds of the objects referenced by their pointer parameters.	mandatory	-	yes
21.18	The size_t argument passed to any function in <string.h> shall have an appropriate value.	mandatory	-	yes
21.19	The pointers returned by the Standard Library functions localeconv, getenv, setlocale or, strerror shall only be used as if they have pointer to const-qualified type.	mandatory	-	yes
21.20	The pointer returned by the Standard Library functions asctime, ctime, gmtime, localtime, localeconv, getenv, setlocale or strerror shall not be used following a subsequent call to the same function.	mandatory	-	yes
22.1	All resources obtained dynamically by means of Standard Library functions shall be explicitly released.	required	-	yes
22.2	A block of memory shall only be freed if it was allocated by means of a Standard Library function.	mandatory	-	yes
22.3	The same file shall not be open for read and write access at the same time on different streams.	required	-	yes
22.4	There shall be no attempt to write to a stream which has been opened as read-only.	mandatory	-	yes
22.5	A pointer to a FILE object shall not be dereferenced.	mandatory	-	yes
22.6	The value of a pointer to a FILE shall not be used after the associated stream has been closed.	mandatory	-	yes
22.7	The macro EOF shall only be compared with the unmodified return value from any Standard Library function capable of returning EOF.	required	-	yes
22.8	The value of errno shall be set to zero prior to a call to an errno-setting-function.	required	-	yes
22.9	The value of errno shall be tested against zero after calling an errno-setting-function.	required	-	yes
22.10	The value of errno shall only be tested when the last function to be called was an errno-setting-function.	required	-	yes

Chapter 5. Appendix 2 - Definitions

Table 5.1. Abbreviations

Abbreviation	Definition
NA	Not Available