



GAN - Theory and Applications

Michele de Simoni

Paolo Galeone

Emanuele Ghelfi

Federico di Mattia

March 8, 2019



Generative Adversarial Networks

“Adversarial Training (also called GAN for Generative Adversarial Networks) is the most interesting idea in the last 10 years of ML.”

— Yann LeCun

Generative Adversarial Networks

Two components, the **generator** and the **discriminator**:

- The **generator** G , aim is to capture the data distribution.
- The **discriminator** D , estimates the probability that a sample came from the training data rather than from G .




Figure 1: Credits: Reference

Generative Adversarial Networks

Generator and Discriminator compete against each other, playing the following zero sum min-max game with value function

$V_{GAN}(D, G)$:

$$\min_G \max_D V_{GAN}(D, G) = \mathbb{E}_{x \sim p_{data}(x)} [\log D(x)] + \mathbb{E}_{z \sim p_z(z)} [\log(1 - D(G(z)))] \quad (1)$$

Generative Adversarial Networks

Intuitive explanation:

- Discriminator needs to:
 - Correctly classify real data:

maximize

$$\mathbb{E}_{x \sim p_{data}(x)} [\log D(x)] \quad (2)$$

- Correctly classify wrong data:

maximize

$$\mathbb{E}_{z \sim p_z(z)} [\log(1 - D(G(z)))] \quad (3)$$