

如果您使用的是 **React Router v6** 或更高版本，則不能使用 **withRouter**，因為 **withRouter** 已在 **v6** 中棄用。相反，您可以使用 **useNavigate** hook 來訪問導引物件。下面是使用 **useNavigate** 的範例：

```
npx create-react-app react-nav
```

```
npm install bootstrap
```

```
npm install axios
```

```
npm install react-router-dom
```

EmployeeService.js

```
import axios from 'axios';
```

```
const EMPLOYEE_API_BASE_URL = "http://localhost:8080/api/employees";
```

```
class EmployeeService {
```

```
  getEmployees() {  
    return axios.get(EMPLOYEE_API_BASE_URL);  
  }
```

```
  createEmployee(employee) {  
    return axios.post(EMPLOYEE_API_BASE_URL, employee);  
  }
```

```
  getEmployeeById(employeeId) {  
    return axios.get(EMPLOYEE_API_BASE_URL + '/' + employeeId);  
  }
```

```
  updateEmployee(employee, employeeId) {  
    return axios.put(EMPLOYEE_API_BASE_URL + '/' + employeeId, employee);  
  }
```

```
  deleteEmployee(employeeId) {  
    return axios.delete(EMPLOYEE_API_BASE_URL + '/' + employeeId);  
  }  
}  
export default new EmployeeService();
```

```

import { useState } from 'react';
import { useNavigate } from 'react-router-dom';
import EmployeeService from '../services/EmployeeService';

function AddEmployeeComponent() {
  const navigate = useNavigate();
  const [employee, setEmployee] = useState({
    firstName: "",
    lastName: "",
    emailId: "",
  });

  const handleChange = (e) => {
    const { name, value } = e.target;
    setEmployee((prevEmployee) => ({
      ...prevEmployee,
      [name]: value,
    }));
  };

  const handleSubmit = async (e) => {
    e.preventDefault();
    try {
      await EmployeeService.addEmployee(employee);
      navigate('/');
    } catch (error) {
      console.error(error);
    }
  };

  return (
    <div>
      <h2 className="text-center">Add Employee</h2>
      <div className="row">
        <div className="col-md-6 offset-md-3">
          <form onSubmit={handleSubmit}>
            <div className="form-group">
              <label>First Name:</label>

```

```
        <input
            type="text"
            placeholder="First Name"
            name="firstName"
            className="form-control"
            value={employee.firstName}
            onChange={handleChange}
        />
    </div>
    <div className="form-group">
        <label>Last Name:</label>
        <input
            type="text"
            placeholder="Last Name"
            name="lastName"
            className="form-control"
            value={employee.lastName}
            onChange={handleChange}
        />
    </div>
    <div className="form-group">
        <label>Email Id:</label>
        <input
            type="email"
            placeholder="Email Address"
            name="emailId"
            className="form-control"
            value={employee.emailId}
            onChange={handleChange}
        />
    </div>
    <button type="submit" className="btn btn-primary">
        Save
    </button>
</form>
</div>
</div>
</div>
```

```
    );  
  }  
}
```

```
export default AddEmployeeComponent;
```

```
EmployeeComponent.js
```

```
import { useState, useEffect } from 'react';  
import { BrowserRouter as Router, Route, Routes, useNavigate } from  
'react-router-dom';  
import EmployeeService from '../services/EmployeeService';  
import AddEmployeeComponent from './AddEmployeeComponent';
```

```
function EmployeeComponent() {  
  const navigate = useNavigate();  
  const [employees, setEmployees] = useState([]);  
  
  useEffect(() => {  
    const fetchEmployees = async () => {  
      try {  
        const response = await EmployeeService.getEmployees();  
        setEmployees(response.data);  
      } catch (error) {  
        console.error(error);  
      }  
    };  
    fetchEmployees();  
  }, []);  
  
  const deleteEmployee = async (id) => {  
    try {  
      await EmployeeService.deleteEmployee(id);  
      setEmployees((prevEmployees) => prevEmployees.filter((employee)  
=> employee.id !== id));  
    } catch (error) {  
      console.error(error);  
    }  
  };  
};
```

```
const viewEmployee = (id) => {
  navigate(`/view-employee/${id}`);
};

const editEmployee = (id) => {
  navigate(`/add-employee/${id}`);
};

const addEmployee = () => {
  navigate(`/add-employee/_add`);
};

return (
  <div>
    <h2 className="text-center">Employees List</h2>
    <div className="row">
      <button className="btn btn-primary" onClick={addEmployee}>
        Add Employee
      </button>
    </div>
    <br />
    <div className="row">
      <table className="table table-striped table-bordered">
        <thead>
          <tr>
            <th> Employee First Name</th>
            <th> Employee Last Name</th>
            <th> Employee Email Id</th>
            <th> Actions</th>
          </tr>
        </thead>
        <tbody>
          {employees.map((employee) => (
            <tr key={employee.id}>
              <td> {employee.firstName} </td>
              <td> {employee.lastName}</td>
              <td> {employee.emailId}</td>
              <td>
```

