

lys_instr: A Python Package for Automating Scientific Measurements

- ³ Ziqian Wang ^{1,2¶}, Hidenori Tsuji², Toshiya Shiratori ³, and Asuka
- 4 Nakamura © 2,3
- 5 1 Research Institute for Quantum and Chemical Innovation, Institutes of Innovation for Future Society,
- Nagoya University, Japan ROR 2 RIKEN Center for Emergent Matter Science, Japan ROR 3 Department
- of Applied Physics, The University of Tokyo, Japan ROR ¶ Corresponding author

DOI: 10.xxxxx/draft

Software

- Review 🗗
- Repository 🗗
- Archive ♂

Editor: Open Journals ♂ Reviewers:

@openjournals

Submitted: 01 January 1970 Published: unpublished

License

Authors of papers retain copyrights and release the work under a Creative Commons Attribution 4.Q, International License (CC BY 4.0)0

Summary

Modern experiments increasingly demand automation frameworks capable of coordinating diverse scientific instruments while remaining flexible and easy to customize. Existing solutions, however, often require substantial adaptation or manual handling of low-level communication and threading. We present lys_instr, a Python package that addresses these challenges through an object-oriented, multi-layered architecture for instrument control, workflow coordination, and GUI construction. It enables researchers to rapidly build responsive, asynchronous measurement systems with minimal coding effort. Seamlessly integrated with the lys platform (Nakamura, 2023), lys_instr unifies experiment control, data acquisition, and visualization, offering an efficient foundation for next-generation, automation-driven experimental research.

Statement of need

Modern scientific research increasingly relies on comprehensive measurements across wide parameter spaces to fully understand physical phenomena. As experiments grow in complexity—with longer measurement times and a greater diversity of instruments—efficient automation has become essential. Measurement automation is now evolving beyond simple parameter scans toward informatics-driven, condition-based optimization, paving the way for Al-assisted experimental workflow management. This progress demands robust software infrastructure capable of high integration and flexible logic control.

However, building such a system remains nontrivial for researchers. At the low level, specific instrument methods tightly coupled to diverse communication protocols (e.g., TCP/IP, VISA, serial, etc.) limit interchangeability and flexibility across systems. At the high level, coordinating workflows involving conditional logic, iterative processes, and advanced algorithms from different libraries can lead to redundant implementations of similar functionality across different contexts. Moreover, designing GUIs for these low- and high-level functionalities typically requires complex multithreading, further increasing implementation costs. Existing frameworks such asQCoDeS (Nielsen & others, 2025), PyMeasure (developers, 2025), PyLabControl (Steiner & LISE-B26, 2024), LabVIEW (LabVIEW, 2024), and MATLAB's Instrument Control Toolbox (MATLAB Instrument Control Toolbox, 2024) provide powerful ecosystems for instrument control and measurement scripting, but require users to handle low-level communications and high-level workflow logic themselves. These challenges impose substantial overhead on researchers designing custom measurement systems.

- To address these issues, we introduce lys_instr—an object-oriented framework that abstracts common control patterns from experiment-specific implementations, reducing coding and
- design costs while enabling flexible and efficient automation.



Design Philosophy

- lys_instr adopts a three-layer architecture based on multiple object-oriented design patterns to maximize flexibility, modularity and ease of use.
- 5 1. Base Layer: Instrument Abstraction
- This layer standardizes core instrument functionalities—motors, detectors, and storage—through abstract interfaces. Concrete device implementations are separated from these interfaces, following the *Template Method* design pattern. Independent automatic multi-threading management allows each instrument to operate asynchronously, ensuring responsive operation without blocking other instruments or the GUI.
 - 2. Intermediate Layer: Workflow Coordination
- This layer provides high-level abstractions, including the GUI, to coordinate base instruments for general experimental tasks. It standardizes common operations such as *move-and-detect*, scans, and nested scan sequences without requiring knowledge of concrete instrument implementations, following the *Bridge* design pattern. The GUI interacts with components via signals, adhering to the *Observer* design pattern, ensuring low coupling and high extensibility. Concepts from the *Composite* design pattern are also employed to efficiently manage nested scan configurations.
 - 3. Top Layer: Control System Assembly
- This layer supports flexible assembly of the measurement GUI. Following the *Mediator* design pattern, it manages connections among abstract devices (and, through the Base Layer, the corresponding real hardware) to enable automatic data flow, and organizes the GUI for user control. This grants users maximum freedom to construct tailored control systems without managing complex aspects such as inter-device communication or multi-threading.

Key Functionalities

- lys_instr provides a straightforward user interface—illustrated in the preliminary example in Figure 1—for integrated instrument/data management and declarative workflow control.
 - III lys File Sidebar Python Graph Help lys instr main window template В Name Axes [Status] Waiting 1 filte data3 (2,) List of parameters (right click to edit) 0.6 Add Scan 1 Mode From Step Number of steps ∨ Linear ∨ 0.000 0.100 10 Region (X) ∨ Linear ∨ 0.000 0.100 10 **‡** (1): the first scan param, (2): the second scan pa ٥

Figure 1: Example GUI of *lys_instr*. The main window, embedded in the *lys* window, is organized into three sectors: Storage panel (A), Detector panel (B), and Motor and Scan tabs (C). The Scan tab enables dynamic configuration of mutli-dimensional, nested experimental workflows.



- 67 Integrated Instrument/Data Management: The Base Layer ensures asynchronous operation
- across all instruments (Sector A for storage, Sector B for detector, and the Motor tab in C),
- 69 keeping each GUI component responsive during cooperative measurements.
- 70 Declarative Workflow Management: Users can define multi-dimensional, nested scan sequences
- 71 (MultiScan) via a visual interface (the Scan tab in Sector C). Built on the Intermediate
- ₇₂ Layer abstraction, these workflows hierarchically coordinate motors and detectors, enabling
- sophisticated experiments without any low-level coding.
- 14 In addition, lys_instr supports user-defined GUI layouts through the Top Layer. It further
- enhances extensibility through seamless integration with the lys platform (the outer window
- with tabs), enabling advanced on-the-fly customization of data visualization.

Projects using the software

- 18 lys_instr has been deployed in complex, real-world scientific instruments, supporting multiple
- 79 peer-reviewed publications. It automates Ultrafast Transmission Electron Microscopy (UTEM)
- at RIKEN Center for Emergent Matter Science, coordinating ultrafast laser excitation and
- pulsed electron beam detection in pump-probe experiments (Nakamura et al., 2020, 2021,
- 2022, 2023; Shimojima et al., 2021, 2023a, 2023b), and it controls electromagnetic lenses and
- electron deflectors for advanced microscopy with electron-beam precession (?; ?).

Acknowledgements

- We acknowledge valuable comments from Takahiro Shimojima and Kyoko Ishizaka. This work
- was partially supported by a Grant-in-Aid for Scientific Research (KAKENHI) (Grant No.).
- developers, P. (2025). *PyMeasure*. https://github.com/pymeasure/pymeasure
- LabVIEW. (2024). [Computer software]. National Instruments Corporation. https://www.ni.
- MATLAB instrument control toolbox. (2024). [Computer software]. The MathWorks, Inc. https://www.mathworks.com/products/instrument.html
- Nakamura, A. (2023). lys: Interactive Multi-Dimensional Data Analysis and Visualization
 Platform. *Journal of Open Source Software*, 8(92), 5869. https://doi.org/10.21105/joss.
 05869
- Nakamura, A., Shimojima, T., Chiashi, Y., Kamitani, M., Sakai, H., Ishiwata, S., Li, H., & Ishizaka, K. (2020). Nanoscale Imaging of Unusual Photoacoustic Waves in Thin Flake VTe2. *Nano Letters*, 20(7), 4932–4938. https://doi.org/10.1021/acs.nanolett.0c01006
- Nakamura, A., Shimojima, T., & Ishizaka, K. (2021). Finite-element Simulation of Photoinduced Strain Dynamics in Silicon Thin Plates. *Structural Dynamics*, 8(2), 024103. https://doi.org/10.1063/4.0000059
- Nakamura, A., Shimojima, T., & Ishizaka, K. (2022). Visualizing Optically-Induced Strains by Five-Dimensional Ultrafast Electron Microscopy. *Faraday Discussions*, 237, 27–39. https://doi.org/10.1039/D2FD00062H
- Nakamura, A., Shimojima, T., & Ishizaka, K. (2023). Characterizing an Optically Induced Sub-micrometer Gigahertz Acoustic Wave in a Silicon Thin Plate. *Nano Letters*, *23*(7), 2490–2495. https://doi.org/10.1021/acs.nanolett.2c03938
- Nielsen, J. H., & others. (2025). *QCoDeS* (Version 0.52.0). https://doi.org/10.5281/zenodo. 15144297
- Shimojima, T., Nakamura, A., & Ishizaka, K. (2023a). Development of Five-Dimensional



- Scanning Transmission Electron Microscopy. *Review of Scientific Instruments*, *94*(2), 023705. https://doi.org/10.1063/5.0106517
- Shimojima, T., Nakamura, A., & Ishizaka, K. (2023b). Development and Applications of Ultrafast Transmission Electron Microscopy. *Microscopy*, 72(4), 287–298. https://doi.org/10.1093/jmicro/dfad021
- Shimojima, T., Nakamura, A., Yu, X., Karube, K., Taguchi, Y., Tokura, Y., & Ishizaka, K. (2021). Nano-to-Micro Spatiotemporal Imaging of Magnetic Skyrmion's Life Cycle. *Science Advances*, 7(25), eabg1322. https://doi.org/10.1126/sciadv.abg1322
- Steiner, J. F., & LISE-B26. (2024). *PyLabControl: A scientific instrument control library in python*. https://github.com/LISE-B26/pylabcontrol.

